

Appendix 3

Traffic Impact Assessment

**Proposed Minor Relaxation of Building Height Restriction
for the Permitted Social Welfare Facility
(Redevelopment of The Salvation Army Lai King Home)
at Nos. 200 - 210 Lai King Hill Road, Kwai Chung, New
Territories – S16 Planning Application**

Revised TIA Report

March 2024



CTA Consultants Limited

志達顧問有限公司

LIST OF CONTENTS

1.	INTRODUCTION.....	1
1.1	Background	1
1.2	Study Objectives	2
2.	THE PROPOSED DEVELOPMENT	3
2.1	Site Location	3
2.2	Proposed Development	3
2.3	Vehicular Access	4
2.4	Internal Transport Facilities Provision.....	4
2.5	Public Transport Services in the Vicinity	5
3.	THE EXISTING TRAFFIC CONDITIONS	6
3.1	Critical Junctions	6
4.	TRAFFIC IMPACT ASSESSMENT	9
4.1	Design Year	9
4.2	Traffic Forecast	9
4.3	Traffic Generations of Adjacent New Developments.....	11
4.4	Planned Junction Layout under Development Projects	12
4.5	Reference Traffic Flows	13
4.6	Traffic Generations and Attractions.....	13
4.7	Design Traffic Forecasts	14
5.	TRAFFIC IMPACT ASSESSMENT	15
5.1	Operational Assessment.....	15
6.	PEDESTRIAN IMPACT ASSESSMENT	20
6.1	Survey on Pedestrian Flows.....	20
6.2	Future Pedestrian Condition	21
7.	SUMMARY AND CONCLUSION	24
7.1	Summary	24
7.2	Conclusion	24

LIST OF TABLES

Table 2.1	Development Parameters of the Proposed Development.....	3
Table 2.2	Proposed Parking Provision.....	4
Table 2.3	Road-Based Public Transport Services in the Vicinity.....	5
Table 3.1	Identified Critical Junction	6
Table 3.2	Operational Performance of Identified Critical Junctions in 2023	7
Table 3.3	Volume to Capacity (V/C) Ratio Assessment of Identified Road Links in 2023	7
Table 4.1	Historical Traffic Data from Annual Traffic Census (ATC)	10
Table 4.2	TPEDM Planning Data from 2019 to 2031	11
Table 4.3	Planned Adjacent Developments in the Vicinity and the Estimated Trip Generations and Attractions.....	12
Table 4.4	Adopted Generation and Attraction Trip Rates of Proposed Development Users	13
Table 4.5	Estimated Net Traffic Generation and Attraction of Proposed Development	14
Table 5.1	Junction Performance of Identified Critical Junction in Year 2032 (With and Without Proposed Site).....	15
Table 5.2	Junction Performance of Modified Junction E in Year 2032 (With and Without Proposed Site).....	16
Table 5.3	Volume to Capacity (V/C) Ratio Assessment of Identified Road Links in 2032 (Without Proposed Site).....	17
Table 5.4	Volume to Capacity (V/C) Ratio Assessment of Identified Road Links in 2032 (With Proposed Site).....	18
Table 6.1	Operational Performance of Critical Footpath in Existing Scenario	20
Table 6.2	Operational Performance of Critical Pedestrian Crossing in Existing Scenario.....	21
Table 6.3	Operational Performance of Critical Footpath in Year 2032 Reference Scenario (Without Proposed Development)	21
Table 6.4	Operational Performance of Critical Pedestrian Crossing in Year 2032 Reference Scenario (Without Proposed Development)	22
Table 6.5	Pedestrian Generation and Attraction Rate of Existing Salvation Army Lai King Home.....	22
Table 6.6	Estimated Pedestrian Generation and Attraction of Proposed Development	22
Table 6.7	Operational Performance of Critical Footpath in Year 2032 Design Scenario (With Proposed Development).....	23
Table 6.8	Operational Performance of Critical Pedestrian Crossing in Year 2032 Design Scenario (With Proposed Development)	23

LIST OF FIGURES

Figure 1.1	Site Location Plan
Figure 2.1 (Rev A)	Layout Plan of Proposed Development
Figure 2.2	Proposed Routing for Vehicles of Proposed Development
Figure 3.1 (Rev B)	Area of Influence
Figure 3.2	Existing Junction Layout of Lai King Hill Road / Joint Street / Lai Cho Road (A1 & A2)
Figure 3.3	Existing Junction Layout of Lai King Hill Road / King Cho Road (Near Lai King Estate)(B)
Figure 3.4	Existing Junction Layout of Lai King Hill Road / King Cho Road (Near Lai King Ventilation Building) (C)
Figure 3.5	Existing Junction Layout of Lai King Hill Road / Kwai Chung Hospital Road (D)
Figure 3.6	Existing Junction Layout of Lai King Hill Road / Kwai Chung Interchange (E)
Figure 3.7	Existing Junction Layout of Kwai Fuk Road / Kwai Yi Road / Container Port Road (F)
Figure 3.8 (Rev A)	2023 Observed Traffic Flows
Figure 4.1 (Rev A)	Planned Major Developments in the Vicinity
Figure 4.2	Planned Junction Lai King Hill Road / Kwai Chung Interchange (E)
Figure 4.3 (Rev B)	2032 Reference Traffic Flows
Figure 4.4 (Rev B)	2032 Design Traffic Flows
Figure 4.5 (Rev A)	Proposed Development Traffic Flows
Figure 4.6	Adjacent Development Traffic Flows
Figure 6.1	Pedestrian Connectivity
Figure 6.2	Index Plan of Pedestrian Assessment

Figure 6.3	2023 Existing Pedestrian Flows
Figure 6.4	2032 Reference Pedestrian Flows
Figure 6.5	2032 Design Pedestrian Flows
Figure SP-01 (Rev A)	Swept Path Analysis of HGV at Proposed Vehicular Access
Figure SP-02 (Rev A)	Swept Path Analysis of Light Bus
Figure SP-03 (Rev A)	Swept Path Analysis of Ambulance

APPENDIX

Appendix A Junction Calculation Sheets



1. INTRODUCTION

1.1 Background

- 1.1.1 CTA Consultants Limited was commissioned as the traffic consultant to prepare a Traffic Impact Assessment (TIA) study for Redevelopment of The Salvation Army Lai King Home at Nos. 200-210 Lai King Hill Road (hereafter called “proposed development”).
- 1.1.2 The site currently provides a total of 100 places of Day Activity Centre (DAC), 100 places of Hostel for Severely Mentally Handicapped Persons (HSMHP), 20 places of Extended Care Programme (ECP) and 2 places of Residential Respite Service (RRS). No major renovation or refurbishment works have been carried out since last century, the entire building appears to be dilapidated. Water seepage and spalled concrete are easily found around the buildings.
- 1.1.3 It is planned to demolish the existing three 4-storey main blocks and redevelop into two 7-storey buildings (excluding LG/F) on the site. With the increase in floor areas, more facilities can be provided to serve the community after the redevelopment. The new buildings will provide a total of 178 places of DAC (including 20 places converted ECP) and 20 places of additional ECP, 178 places of Hostel for Severely Mentally Handicapped Persons (HSMH) (including 2 places (casual vacancies) of Residential Respite Service (RRS) and 2 designated places of RRS, 120 places of Integrated Vocational Rehabilitation Services Centre (IVRSC), 80 places of Hostel for Moderately Mentally Handicapped Persons (HMMH), 70 places of Care & Attention Home for Severely Disabled Persons (C&A/SD), and a multi-function hall.
- 1.1.4 The location of the proposed development is shown diagrammatically in **Figure 1.1**.



1.2 Study Objectives

1.2.1 The main objectives of this study are as follows:

- To assess the existing traffic conditions in the vicinity of the proposed development;
- To forecast traffic demands on the adjacent road network in the design year;
- To estimate the likely traffic generated by the proposed development;
- To assess the impacts of traffic generated by the proposed development on the adjacent road network; and
- To recommend improvement measures, if necessary, to alleviate any traffic problems on the road network



2. THE PROPOSED DEVELOPMENT

2.1 Site Location

2.1.1 The proposed development is located at Nos. 200-210 Lai King Hill Road as shown in **Figure 1.1**. The site is the existing three 4-storey main blocks and it is proposed to redevelop into two 7-storey buildings (excluding LG/F).

2.2 Proposed Development

2.2.2 The development schedule for the proposed development is summarized in **Table 2.1**.

Table 2.1 Development Parameters of the Proposed Development

Type of Facilities	Existing Capacity	Proposed Capacity upon Redevelopment
Day Activity Centre (“DAC”) / Hostel for Severely Mentally Handicapped Persons (“HSMH”) ⁽¹⁾	100	178
• Residential Respite Service (“RSS”)	2	2
• Extended Care Programme (“ECP”)	20	20
Integrated Vocational Rehabilitation Services Centre (“IVRSC”)	0	120
Hostel for Moderately Mentally Handicapped Persons (“HMMH”)	0	80
Care & Attention Home for Severely Disabled Persons (“C&A”)	0	70
Total	100	448

Note:

(1) Includes 20 places of converted ECP and 2 places (causal vacancies) of RRS

2.2.1 It is anticipated that the proposed development will be completed by 2029 tentatively. Therefore, design year 2032 (i.e. 3 years after the planned commencement year of the proposed development) is adopted for the Traffic Impact Assessment.



2.3 Vehicular Access

2.3.1 The existing vehicular access will be adopted for the proposed development. Location of the vehicular access is shown diagrammatically in **Figure 2.1 (Rev A)**. Swept path analysis demonstrates it is feasible to maneuver HGV in/out the proposed vehicular access is shown in **Figure SP-01 (Rev A)**.

2.3.2 The proposed routing for vehicles of proposed development is illustrated in **Figure 2.2**.

2.4 Internal Transport Facilities Provision

2.4.1 There is no relevant requirements stipulated in the latest Hong Kong Planning Standards and Guidelines (HKPSG) published by Planning Department for “DAC”, “HSMH”, “ECP”, “RRS”, “IVRSC”, “HMMH” or “C&A/SD”. Comments from SWD on the proposed parking provisions have been and are summarized in **Table 2.2**.

Table 2.2 Proposed Parking Provision

Parking Requirement		Loading/Unloading Requirement		
Private Car Parking Space 5m x 2.5m	Light Bus Parking Space 8m x 3m	LGV 7m x 3.5m	M/HGV 11m x 3.5m	Ambulance 7.5m x 3.5m
5 ⁽¹⁾	6 ⁽²⁾	1 ⁽²⁾	1	1 ⁽²⁾

Notes:

(1) Including 1 accessible car parking space for 1-50 car parking spaces.

(2) As per SWD comments dated 11 October 2023,

Comment (A)(I)(6)(i): 4 parking spaces measuring 8mL* 3mW*3.3mH for the 4 light buses for the 178-p HSMH; 1 parking space measuring 7mL*3.5mW*3.6mH for a 5.5 ton goods vehicle for the 120-p IVRSC and a parking space measuring 8mL*3mW*3.3mH for a light bus for C&A/SD are required.

Comment (A)(I)(6)(ii): A shared loading / unloading area for the private light buses and ambulance for DAC cum HSMH and C&A/SD, a shared loading /unloading area or lay-by for ambulance for HMMH, a shared loading /unloading area for 5.5 ton goods vehicle of IVRSC are required.

2.4.2 Swept path analysis demonstrates it is feasible to maneuver for the proposed critical parking spaces are shown in **Figure SP-01 (Rev A)** to **Figure SP-03 (Rev A)**.



2.5 Public Transport Services in the Vicinity

2.5.1 Numerous road-based public transport services are provided in vicinity of the proposed development. Details of the current services of franchised buses and GMB routes within 500 meters catchment area are listed in **Table 2.3**.

Table 2.3 Road-Based Public Transport Services in the Vicinity

Service	Route	Origin-Destination	Headway (min)
Franchised Buses	269M	Tin Yan Estate - Cho Yiu	12-25
	30	Tsuen Wan (Allway Gardens) - Cheung Sha Wan	25-30
	32H	Cheung Shan - Lai Chi Kok	30-60
	42	Tsing Yi (Cheung Hong Estate) - Shun Lee	15-20
	45	Kwai Chung (Lai Yiu Estate) - Kowloon City Ferry	25-30
	46	Kwai Chung (Lai Yiu Estate) - Jordan (West Kowloon Station)	25-30
	46X	Hin Keng - Mei Foo	5-15
	N241	Tsing Yi (Cheung Wang Estate) - Hung Hom Station	25-30 (00:15 to 06:00 only)
GMB	46M	Lai Kong Street - Lai King Station (Circular)	5-15
	47M	Wonderland Villas - Lai King Station (Circular)	8-15
	87K	Hoi Kwai Road Public Transport Interchange - Kwai Fong Station	6-10
	90M	Mei Foo Station - Lai King Headland (Circular)	4-6
	91A	Kwai Fong Station - Lai Kong Street	9-15
	92M	Mei Foo Station - Wah Yuen Chuen (Circular)	5-10
	93	Wah Yuen Chuen - Tsuen Wan (Ham Tin Street)	6-15
	93A	Wonderland Villas - Tsuen Wan (Ham Tin Street)	15-25
	313	Princess Margaret Hospital - Tsuen Wan (Tso Kung Street)	6-11
	405	Lai King South - Cheung Hang (Circular)	15-20
	407	Cheung Wang - Princess Margaret Hospital	4-10
	407A	Princess Margaret Hospital - Kwai Fong Station (Hing Ning Road)	7-13
	411	Kwai Chung (Lai Kong Street) - Sham Shui Po (Un Chau Street) (Circular)	8-15
	413	Princess Margaret Hospital - Tsing Yi Public Pier	10-20

2.5.2 It is revealed that the proposed development is well-served by the comprehensive public transport services in the vicinity.



3. THE EXISTING TRAFFIC CONDITIONS

3.1 Critical Junctions

3.1.1 As shown in **Figure 3.1 (Rev B)**, 5 junctions were identified to be critical for assessment of traffic impact due to the proposed development. They are listed in below **Table 3.1** and their existing junction layout arrangements are shown in **Figure 3.2** to **Figure 3.7** respectively.

Table 3.1 Identified Critical Junction

Ref.	Junction	Method of Control	Figure No.
A1	Lai King Hill Road / Joint Street	Priority	3.2
A2	Joint Street / Lai Cho Road	Priority	3.2
B	Lai King Hill Road / King Cho Road (Near Lai King Estate)	Priority	3.3
C	Lai King Hill Road / King Cho Road (Near Lai King Ventilation Building)	Priority	3.4
D	Lai King Hill Road / Kwai Chung Hospital Road	Priority	3.5
E	Lai King Hill Road / Kwai Chung Interchange	Signal	3.6
F	Kwai Fuk Road / Kwai Yi Road / Container Port Road	Roundabout	3.7

3.1.2 In order to establish the existing traffic condition in the above-mentioned critical junctions, traffic survey in the form of manual classified count was conducted during AM and PM peak periods during 7:30am to 9:30am and 5:30pm to 7:30pm on a typical weekday on 30 March 2023.

3.1.3 Analysis of the observed traffic data indicates that the AM and PM peak hour flows occurred from 7:45am to 8:45am and 5:45pm to 6:45pm respectively. The existing traffic flows is presented in **Figure 3.8 (Rev A)**.

3.1.4 Existing performance of the identified critical junction and road links are assessed. The results are summarized in **Table 3.2**, **Table 3.3** and the junction calculation sheets are attached in **Appendix A**.



Table 3.2 Operational Performance of Identified Critical Junctions in 2023

Ref.	Junction	Method of Control	Year 2023 RC/DFC ⁽¹⁾	
			AM Peak	PM Peak
A1	Lai King Hill Road / Joint Street	Priority	0.54	0.55
A2	Joint Street / Lai Cho Road	Priority	0.64	0.60
B	Lai King Hill Road / King Cho Road (Near Lai King Estate)	Priority	0.67	0.71
C	Lai King Hill Road / King Cho Road (Near Lai King Ventilation Building)	Priority	0.58	0.36
D	Lai King Hill Road / Kwai Chung Hospital Road	Priority	0.59	0.37
E	Lai King Hill Road / Kwai Chung Interchange	Signal	54%	67%
F	Kwai Fuk Road / Kwai Yi Road / Container Port Road	Roundabout	0.57	0.55

Notes: (1) RC = Reserve Capacity
DFC = Design Flow/Capacity ratio for Priority Junction

3.1.5 The assessment results in **Table 3.2** indicate that all critical junctions are at present operating within their capacities during peak hours.

Table 3.3 Volume to Capacity (V/C) Ratio Assessment of Identified Road Links in 2023

Road Link	Direction	Capacity (pcu/hr) ⁽¹⁾⁽²⁾	Year 2023 Observed Traffic Flow			
			AM Peak Hour		PM Peak Hour	
			Flow (pcu/hr)	V/C	Flow (pcu/hr)	V/C
Lai King Hill Road (Between Joint Street and King Cho Road)	Northeast bound	1,450	540	0.37	520	0.36
	Southwest bound	1,450	610	0.42	550	0.38
Lai King Hill Road (Between King Cho Road near OUHK - Cita Lai King Learning Centre and Proposed Site)	Northeast bound	1,450	460	0.32	370	0.26
	Southwest bound	1,450	610	0.42	560	0.39
Lai King Hill Road (Between Proposed Site and King Cho Road near Cho Yiu Chuen)	Northeast bound	1,450	460	0.32	390	0.27
	Southwest bound	1,450	650	0.45	580	0.40
Lai King Hill Road (Between King Cho Road near Cho Yiu Chuen and Kwai Chung Hospital Road)	Northeast bound	1,450	570	0.39	560	0.39
	Southwest bound	1,450	810	0.56	670	0.46
Lai King Hill Road (Between Kwai Chung	Northeast bound	1,450	710	0.49	540	0.37



Road Link	Direction	Capacity (pcu/hr) (1)(2)	Year 2023 Observed Traffic Flow			
			AM Peak Hour		PM Peak Hour	
			Flow (pcu/hr)	V/C	Flow (pcu/hr)	V/C
Hospital Road and Kwai Chung Interchange)	Southwest bound	1,450	740	0.51	700	0.48
Lai King Hill Road (Between Kwai Chung Interchange and Access Road to FSD New Territories Workshop)	Northeast bound	1,450	620	0.43	510	0.35
	Southwest bound	1,450	720	0.50	690	0.48
Kwai Fuk Road (Between Container Port Road/Kwai Yi Road/Kwai Fuk Road Interchange and Joint Street)	Northeast bound	1,450	580	0.40	670	0.46
	Southwest bound	1,450	520	0.36	430	0.30

Notes:

- (1) Capacity based on Table 2.4.1.1 of Section 2.4, Chapter 2, Volume 2, T.P.D.M.
- (2) PCU factor of 1.32 has been derived from the result of traffic count survey. Lai King Hill Road and Kwai Fuk Road are district distributor of approximately 10m wide, therefore capacity per direction = $2,200 \div 2 \times 1.32 = 1,450$ pcu/hr.
- (3) V/C ratio – volume to capacity ratio for road link. A v/c ratio ≤ 1.0 means that a road has sufficient capacity to cope with the anticipated volume of vehicular traffic. A v/c ratio > 1.0 indicates the onset of congestion. A v/c ratio > 1.2 indicates more serious congestion with traffic speeds deteriorating progressively when there is further increase in traffic.

3.1.6 The assessment results in **Tables 3.3** indicate that all critical links are at present operating with ample capacities.



4. TRAFFIC IMPACT ASSESSMENT

4.1 Design Year

4.1.1 The proposed development is anticipated to be completed by year 2029 tentatively. Year 2032 (i.e. 3 years after completion) is therefore adopted as the design year for this TIA.

4.2 Traffic Forecast

4.2.1 The traffic growth can be estimated by applying growth factor, based on the following information sources:

- I. Historical traffic growth in Annual Traffic Census (ATC) published by the Transport Department (TD).
- II. Territorial planning assumptions prepared by the Planning Department.

Annual Traffic Census

4.2.2 Numerous of traffic count stations are located in the vicinity of the proposed development. The traffic counts reported in the Annual Traffic Census (ATC), which is published by Transport Department, over a period of six years, i.e. 2016 to 2021 are summarized in **Table 4.1**.



Table 4.1 Historical Traffic Data from Annual Traffic Census (ATC)

ATC Stn	Road Name	Annual Average Daily Traffic (AADT)						Avg. Annual Growth Rate
		2016	2017	2018	2019	2020	2021	
5427	Lai King Hill Rd (From Joint St to Kwai Fuk Rd)	16,830*	17,140*	17,400*	19,320	17,720	18,410*	1.81%
5443	Lai King Hill Rd (From Lai Wan Rd to Kwai Chung INT slip rds)	6,600*	6,720*	6,820*	7,590	7,590	7,880*	3.61%
5476	Lai King Hill Rd slip rds C & D (From Lai King Hill RA to Kwai Chung Rd)	10,840*	10,890*	11,190*	11,430	12,210	11,870*	1.83%
5628	Lai King Hill Rd (From King Cho Rd southern junction to Joint St)	15,770	16,060*	16,300*	16,240*	16,590	18,570	3.32%
6204	Lai King Hill Rd (From Kwai Chung INT slip rds to King Cho Rd)	17,020	17,470	16,860	16,450	16,140	16,050	-1.17%
6642	Lai Cho Road (From Joint Street to Lim Cho Street)	3,010	3,220	3,130	2,400	3,000	2,740	-1.86%
Total		70,070	71,500	71,700	73,430	73,250	75,520	1.51%

Note: *AADT estimated by Growth factor

Planning Data

4.2.3 Reference has also been made to the latest 2019-based Territorial Population Employment Data Matrices (TPEDM) planning data published by the Planning Department for years 2019 and 2031 in the study district. The average annual growth rates in terms of population and employment from 2019 to 2031 are tabulated in **Table 4.2**.



Table 4.2 TPEDM Planning Data from 2019 to 2031

Zone	Population			Avg. Annual Growth Rate	Employment			Avg. Annual Growth Rate
	2019	2026	2031		2019	2026	2031	
Kwai Chung	319,150	315,800	319,700	0.01%	195,950	192,350	183,600	-0.54%

4.2.4 It is indicated that the average annual growth rate of population in the study area from 2019 to 2031 under the 2019-based Territorial Planning Data is +0.01% per year while the growth rate of employment is -0.54% per year.

Adopted Growth Rate

4.2.5 A.A.D.T. of ATC indicates that the traffic flow of the local road network has an average annual growth rate of +1.51% from year 2016 to year 2021.

4.2.6 Whilst, the planning data indicates that the population and employment in the area are expected to develop with an average annual growth rate of +0.01% and -0.54% respectively from 2019 to 2031.

4.2.7 As a conservative approach, annual growth rate **+1.51%** p.a. is adopted.

4.3 Traffic Generations of Adjacent New Developments

4.3.1 To fully reflect the growth traffic, trip generation of the future vicinity developments have been taken into consideration. The estimated peak hour trips of the planned adjacent development is detailed in **Figure 4.1 (Rev A)** and **Table 4.3**.



Table 4.3 Planned Adjacent Developments in the Vicinity and the Estimated Trip Generations and Attractions

Approved Planning Application	Description	Development Parameter	AM Peak		PM Peak	
			GEN (pcu/hr)	ATT (pcu/hr)	GEN (pcu/hr)	ATT (pcu/hr)
A/KC/445	Public rental housing development at Lai Cho Road	819 flats	35 ⁽¹⁾	27 ⁽¹⁾	19 ⁽¹⁾	25 ⁽¹⁾
A/KC/447	Proposed Minor Relaxation of Domestic Plot Ratio Restriction for Public Housing Development	540 flats	29 ⁽¹⁾	17 ⁽¹⁾	12 ⁽¹⁾	15 ⁽¹⁾
A/KC/451	Redevelopment of Kwai Chung Hospital	1000 beds + 96 consultation rooms	143 ⁽¹⁾	48 ⁽¹⁾	32 ⁽¹⁾	77 ⁽¹⁾
A/KC/470	Expansion of Lai King Building in Princess Margaret Hospital	~850 beds	76 ⁽¹⁾	54 ⁽¹⁾	54 ⁽¹⁾	54 ⁽¹⁾
A/KC/489	Proposed Comprehensive Development including Flat and Community Facility in “Comprehensive Development Area” Zone at Various Lots in S.D.4 and Adjoining Government Land, Kau Wa Keng, Kwai Chung	5,973 flats + Proposed Feeder Service	513 ⁽¹⁾	302 ⁽¹⁾	222 ⁽¹⁾	287 ⁽¹⁾
-	Lai Kong Street private housing development	410 flats (av. flat size: 60m ²)	0.0718 ⁽²⁾	0.0425 ⁽²⁾	0.0286 ⁽²⁾	0.037 ⁽²⁾
			30	18	12	16

Note:

(1) Extracted from TIA report of the relevant application.

(2) Trip rate as stipulated in TPDM Volume 1 Annex C Table 1.

4.4 Planned Junction Layout under Development Projects

4.4.1 According to the approved TIA report of the adjacent development A/KC/489, Junction Lai King Hill Road / Kwai Chung Interchange (E) will be modified and the detail is presented in **Figure 4.2**. It is intended to be carried out before year 2028.



4.5 Reference Traffic Flows

4.5.1 The reference traffic flow is estimated by applying the adopted growth rate to the observed traffic flow in the current year, and the 2032 reference traffic flows can be computed with the following calculation:

$$\begin{array}{l} \text{2032} \\ \text{Reference Traffic} \\ \text{Flows} \\ \text{(Without Proposed} \\ \text{Development)} \end{array} = \left(\begin{array}{l} \text{2023} \\ \text{Observed} \\ \text{Traffic Flows} \end{array} \times \begin{array}{l} \text{Adopted Growth} \\ \text{Factor} \\ \text{(i.e. +1.51\% p.a.} \\ \text{for 9 year)} \end{array} \right) + \begin{array}{l} \text{Traffic Flows of} \\ \text{Planned} \\ \text{Adjacent} \\ \text{Development} \end{array}$$

4.5.2 The 2032 reference traffic flows are shown in **Figure 4.3 (Rev B)**.

4.6 Traffic Generations and Attractions

4.6.1 To estimate the trip generations of the proposed development users, reference has been made to the trip generation rates of the existing Salvation Army Lai King House and sites of similar nature from in-house database. The adopted trip generation rates and the estimated net generation and attraction due to the proposed development users are summarized in **Table 4.4**.

Table 4.4 Adopted Generation and Attraction Trip Rates of Proposed Development Users

Reference Sites	AM Peak		PM Peak	
	Generation (pcu/hr/bed)	Attraction (pcu/hr/bed)	Generation (pcu/hr/bed)	Attraction (pcu/hr/bed)
Existing Salvation Army Lai King House	0.03	0.06	-	-
Providence Garden for Rehab	0.10	0.08	-	-
Hong Chi Fanling Integrative Rehabilitation Complex	0.07	0.08	-	-
Harmony Manor - Scenic Court (HSMH)	-	0.08	0.08	0.10
Adopted Rate	0.10	0.08	0.08	0.10



4.6.2 Based on **Table 4.4**, the estimated traffic generation and attraction due to the proposed development are summarized in **Table 4.5**.

Table 4.5 Estimated Net Traffic Generation and Attraction of Proposed Development

Additional No. of Places	AM Peak		PM Peak	
	Generation (pcu/hr)	Attraction (pcu/hr)	Generation (pcu/hr)	Attraction (pcu/hr)
448-100 = 348	35	28	28	35

4.6.3 It is anticipated that the proposed development would generate and attract +35 pcu/hr and +28 pcu/hr respectively during AM peak hour, and generate and attract +28 pcu/hr and +35 pcu/hr respectively during PM peak hour.

4.7 Design Traffic Forecasts

4.7.1 The future traffic generations of the proposed development were then assigned onto the road network and superimposed onto the 2032 reference traffic flows (without proposed development) to derive the 2032 design traffic forecasts (with proposed development).

$$\begin{array}{ccc}
 \text{2032 Design} & & \text{2032 Reference} \\
 \text{Traffic Flows} & & \text{Traffic Flows} \\
 \text{(with proposed} & = & \text{(without proposed} & + & \text{Proposed} \\
 \text{development)} & & \text{development)} & & \text{Development} \\
 & & & & \text{Traffic Flows}
 \end{array}$$

4.7.2 Year 2032 design traffic flows (with proposed development) and the development traffic flows are shown in **Figure 4.4 (Rev B)** and **Figure 4.5** respectively.



5. TRAFFIC IMPACT ASSESSMENT

5.1 Operational Assessment

5.1.1 To assess the potential traffic impact due to the proposed development, capacity analysis of the identified critical junctions and road links for both reference and design scenarios in year 2032 were carried out. The results are summarized in **Table 5.1**, **Table 5.3**, **Table 5.4** and the junction calculation sheets are attached in **Appendix A**.

**Table 5.1 Junction Performance of Identified Critical Junction in Year 2032
(With and Without Proposed Site)**

Ref.	Junction	Method of Control		Year 2032 RC/DFC ⁽¹⁾			
				Reference Scenario (Without Proposed Site)		Design Scenario (With Proposed Site)	
				AM Peak	PM Peak	AM Peak	PM Peak
A1	Lai King Hill Road / Joint Street	Priority	With A/KC/489	0.81	0.55	0.82	0.66
A2	Joint Street / Lai Cho Road	Priority	With A/KC/489	0.79	0.69	0.79	0.71
B	Lai King Hill Road / King Cho Road (Near Lai King Estate)	Priority	With A/KC/489	0.81	0.79	0.81	0.79
			Without A/KC/489	0.79	0.78	0.79	0.78
C	Lai King Hill Road / King Cho Road (Near Lai King Ventilation Building)	Priority	With A/KC/489	0.76	0.43	0.77	0.44
D	Lai King Hill Road / Kwai Chung Hospital Road	Priority	With A/KC/489	0.76	0.41	0.77	0.45
E	Lai King Hill Road / Kwai Chung Interchange (Without improvement)	Signal	With A/KC/489	-1%	25%	-1%	24%
			Without A/KC/489	36%	58%	34%	57%
F	Kwai Fuk Road / Kwai Yi Road / Container Port Road	Roundabout	With A/KC/489	0.70	0.61	0.71	0.61

Notes: (1) RC = Reserve Capacity
DFC = Design Flow/Capacity ratio for Priority Junction

5.1.2 The assessment results in **Table 5.1** revealed that all critical junctions would still operate within their capacities in both reference and design year 2032 during the peak hours, except Junction Lai King Hill Road / Kwai Chung Interchange (E).



5.1.3 Without junction modification, it is anticipated that Junction E will have negative reserve capacity during AM peak hour in Year 2032 without and with the proposed development. According to approved TIA report of A/KC/489, junction modification work is intended to be carried out before year 2028, i.e. before the completion of the proposed development in year 2029. Capacity analysis of Junction E with junction modification was carried out for both reference and design scenarios. The results are summarized in **Table 5.2** and the junction calculation sheets are also attached in **Appendix A**.

**Table 5.2 Junction Performance of Modified Junction E in Year 2032
(With and Without Proposed Site)**

Ref.	Junction	Method of Control	Year 2032 RC/DFC ⁽¹⁾			
			Reference Scenario (Without Proposed Site)		Design Scenario (With Proposed Site)	
			AM Peak	PM Peak	AM Peak	PM Peak
E	Lai King Hill Road / Kwai Chung Interchange (With Junction Modification)	Signal	15%	46%	15%	45%

Notes: (1) RC = Reserve Capacity
DFC = Design Flow/Capacity ratio for Priority Junction

5.1.4 The assessment results in **Table 5.2** revealed that Junction E would operate within its capacities during the peak hours in both reference and design year with junction modification.



Table 5.3 Volume to Capacity (V/C) Ratio Assessment of Identified Road Links in 2032 (Without Proposed Site)

Road Link	Direction	Capacity (pcu/hr) (1)(2)	Year 2032 Reference Scenario (Without Proposed Site)			
			AM Peak Hour		PM Peak Hour	
			Flow (pcu/hr)	V/C	Flow (pcu/hr)	V/C
Lai King Hill Road (Between Joint Street and King Cho Road)	Northeast bound	1,450	660	0.46	560	0.39
	Southwest bound	1,450	740	0.51	610	0.42
Lai King Hill Road (Between King Cho Road near OUHK - Cita Lai King Learning Centre and Proposed Site)	Northeast bound	1,450	570	0.39	420	0.29
	Southwest bound	1,450	750	0.52	620	0.43
Lai King Hill Road (Between Proposed Site and King Cho Road near Cho Yiu Chuen)	Northeast bound	1,450	560	0.39	440	0.30
	Southwest bound	1,450	800	0.55	630	0.43
Lai King Hill Road (Between King Cho Road near Cho Yiu Chuen and Kwai Chung Hospital Road)	Northeast bound	1,450	720	0.50	640	0.44
	Southwest bound	1,450	1,020	0.70	760	0.52
Lai King Hill Road (Between Kwai Chung Hospital Road and Kwai Chung Interchange)	Northeast bound	1,450	900	0.62	610	0.42
	Southwest bound	1,450	940	0.65	790	0.54
Lai King Hill Road (Between Kwai Chung Interchange and Access Road to FSD New Territories Workshop)	Northeast bound	1,450	1,070	0.74	690	0.48
	Southwest bound	1,450	1,050	0.72	910	0.63
Kwai Fuk Road (Between Container Port Road/Kwai Yi Road/Kwai Fuk Road Interchange and Joint Street)	Northeast bound	1,450	740	0.51	750	0.52
	Southwest bound	1,450	680	0.47	510	0.35

Notes:

- (1) Capacity based on Table 2.4.1.1 of Section 2.4, Chapter 2, Volume 2, T.P.D.M.
- (2) PCU factor of 1.32 has been derived from the result of traffic count survey. Lai King Hill Road and Kwai Fuk Road are district distributor of approximately 10m wide, therefore capacity per direction = $2,200 \div 2 \times 1.32 = 1,450$ pcu/hr.
- (3) V/C ratio – volume to capacity ratio for road link. A v/c ratio ≤ 1.0 means that a road has sufficient capacity to cope with the anticipated volume of vehicular traffic. A v/c ratio > 1.0 indicates the onset of congestion. A v/c ratio > 1.2 indicates more serious congestion with traffic speeds deteriorating progressively when there is further increase in traffic.



Table 5.4 Volume to Capacity (V/C) Ratio Assessment of Identified Road Links in 2032 (With Proposed Site)

Road Link	Direction	Capacity (pcu/hr) ⁽¹⁾⁽²⁾	Year 2032 Design Scenario (With Proposed Site)			
			AM Peak Hour		PM Peak Hour	
			Flow (pcu/hr)	V/C	Flow (pcu/hr)	V/C
Lai King Hill Road (Between Joint Street and King Cho Road)	Northeast bound	1,450	680	0.47	560	0.39
	Southwest bound	1,450	750	0.52	610	0.42
Lai King Hill Road (Between King Cho Road near OUHK - Cita Lai King Learning Centre and Proposed Site)	Northeast bound	1,450	590	0.41	420	0.29
	Southwest bound	1,450	760	0.52	620	0.43
Lai King Hill Road (Between Proposed Site and King Cho Road near Cho Yiu Chuen)	Northeast bound	1,450	580	0.40	440	0.30
	Southwest bound	1,450	820	0.57	630	0.43
Lai King Hill Road (Between King Cho Road near Cho Yiu Chuen and Kwai Chung Hospital Road)	Northeast bound	1,450	740	0.51	640	0.44
	Southwest bound	1,450	1,040	0.72	760	0.52
Lai King Hill Road (Between Kwai Chung Hospital Road and Kwai Chung Interchange)	Northeast bound	1,450	910	0.63	610	0.42
	Southwest bound	1,450	940	0.65	790	0.54
Lai King Hill Road (Between Kwai Chung Interchange and Access Road to FSD New Territories Workshop)	Northeast bound	1,450	1,080	0.74	690	0.48
	Southwest bound	1,450	1,050	0.72	910	0.63
Kwai Fuk Road (Between Container Port Road/Kwai Yi Road/Kwai Fuk Road Interchange and Joint Street)	Northeast bound	1,450	740	0.51	750	0.52
	Southwest bound	1,450	680	0.47	510	0.35

Notes:

- (1) Capacity based on Table 2.4.1.1 of Section 2.4, Chapter 2, Volume 2, T.P.D.M.
- (2) PCU factor of 1.32 has been derived from the result of traffic count survey. Lai King Hill Road and Kwai Fuk Road are district distributor of approximately 10m wide, therefore capacity per direction = $2,200 \div 2 \times 1.32 = 1,450$ pcu/hr.
- (3) V/C ratio – volume to capacity ratio for road link. A v/c ratio ≤ 1.0 means that a road has sufficient capacity to cope with the anticipated volume of vehicular traffic. A v/c ratio > 1.0 indicates the onset of congestion. A v/c ratio > 1.2 indicates more serious congestion with traffic speeds deteriorating progressively when there is further increase in traffic.



5.1.5 The assessment results in **Table 5.3** and **Table 5.4** revealed that all critical links would still operate within their capacities in both reference scenario (without proposed development) and design scenario (with proposed development) in 2032 during the peak hours.



6. PEDESTRIAN IMPACT ASSESSMENT

6.1 Survey on Pedestrian Flows

6.1.1 The pedestrian connectivity and index plan at footpath sections and pedestrian crossing of access road to the proposed development are shown in **Figure 6.1** and **Figure 6.2** respectively.

6.1.2 In order to establish the existing pedestrian condition of critical footpath in the above-mentioned critical section, pedestrian survey was carried out during AM and PM peak periods during 7:30am to 9:30am and 5:30pm to 7:30pm on a typical weekday, on 9 November 2023.

6.1.3 The existing pedestrian flows is presented in **Figure 6.3**, and the level-of-service (LOS) for existing operational performances of the identified critical section and pedestrian crossing are listed in **Table 6.1** and **Table 6.2** respectively.

Table 6.1 Operational Performance of Critical Footpath in Existing Scenario

Critical Section	Total Footpath Width (m)	Effective Width (m) ⁽¹⁾	Year 2023					
			AM Peak			PM Peak		
			Two-way Pedestrian Flow	Two-way Pedestrian Flow Rate	LOS	Two-way Pedestrian Flow	Two-way Pedestrian Flow Rate	LOS
			(ped/hr) ⁽²⁾	(ped/min/m) ⁽³⁾		(ped/hr) ⁽²⁾	(ped/min/m) ⁽³⁾	
A	2.9	1.9	185	1.6	A	160	1.4	A
B	1.7	0.7	625	14.9	A	420	10.0	A
D	1.5	0.5	465	15.5	A	175	5.8	A

Notes:

(1) Effective Width = Total Footpath Width – Death Width (0.5m from railings).

(2) Two-way Pedestrian Flow Rate (ped/min/m) = Peak Pedestrian Flow / 60 min / Effective Width.

(3) LOS details extracted from the HCM are tabulated in TPDM Volume 6 Chapter 10 Clause 10.4.2.3.



Table 6.2 Operational Performance of Critical Pedestrian Crossing in Existing Scenario

Crossing	Year 2023			
	AM Peak Hour		PM Peak Hour	
	Crossing Demand	Crossing Capacity ⁽¹⁾	Crossing Demand	Crossing Capacity ⁽¹⁾
C	685	3,260	135	3,260

Note:

(1) Crossing capacity according to TPDM Volume 2, Table 3.7.2.1.

6.1.4 The results of assessment shown in **Table 6.1** and **Table 6.2** indicate that the critical section of footpath and pedestrian crossing are operating with ample reserved capacity during AM and PM peak hours.

6.2 Future Pedestrian Condition

6.2.1 Based on the observed flows and the adopted growth rate of +1.51%, future pedestrian reference flows at the critical section (without proposed development) in Year 2032 are estimated and summarized in **Table 6.3**, **Table 6.4** and **Figure 6.4**.

Table 6.3 Operational Performance of Critical Footpath in Year 2032 Reference Scenario (Without Proposed Development)

Critical Section	Total Footpath Width (m)	Effective Width (m) ⁽¹⁾	Year 2032 Reference Scenario (Without Proposed Development)					
			AM Peak			PM Peak		
			Two-way Pedestrian Flow	Two-way Pedestrian Flow Rate	LOS	Two-way Pedestrian Flow	Two-way Pedestrian Flow Rate	LOS
			(ped/hr) ⁽²⁾	(ped/min/m) ⁽³⁾		(ped/hr) ⁽²⁾	(ped/min/m) ⁽³⁾	
A	2.9	1.9	215	1.9	A	180	1.6	A
B	1.7	0.7	715	17.0	B	480	11.4	A
D	1.5	0.5	530	17.7	B	200	6.7	A

Notes:

(1) Effective Width = Total Footpath Width – Death Width (0.5m from railings).

(2) Two-way Pedestrian Flow Rate (ped/min/m) = Peak Pedestrian Flow / 60 min / Effective Width.

(3) LOS details extracted from the HCM are tabulated in TPDM Volume 6 Chapter 10 Clause 10.4.2.3.



Table 6.4 Operational Performance of Critical Pedestrian Crossing in Year 2032 Reference Scenario (Without Proposed Development)

Crossing	Year 2032 Reference Scenario (Without Proposed Development)			
	AM Peak Hour		PM Peak Hour	
	Crossing Demand	Crossing Capacity ⁽¹⁾	Crossing Demand	Crossing Capacity ⁽¹⁾
C	780	3,260	155	3,260

Note:

(1) Crossing capacity according to TPDM Volume 2, Table 3.7.2.1.

6.2.2 In order to estimate the pedestrian generation and attraction of the proposed development, reference has been made to the trip generation rates from the existing Salvation Army Lai King Home as shown in **Table 6.5**.

Table 6.5 Pedestrian Generation and Attraction Rate of Existing Salvation Army Lai King Home

AM Peak		PM Peak	
Generation (ped/hr/place)	Attraction (ped/hr/place)	Generation (ped/hr/place)	Attraction (ped/hr/place)
0.12	0.42	0.17	0.05

6.2.3 Based on the trip rate in **Table 6.5** and the development parameters listed in **Table 2.1**, the estimated pedestrian generation and attraction due to the proposed development are summarized in **Table 6.6**.

Table 6.6 Estimated Pedestrian Generation and Attraction of Proposed Development

Additional No. of Places	AM Peak		PM Peak	
	Generation (ped/hr)	Attraction (ped/hr)	Generation (ped/hr)	Attraction (ped/hr)
348 places	42	147	60	18

6.2.4 The assessment of the design scenario is summarized in **Table 6.7**, **Table 6.8** and **Figure 6.5**.



Table 6.7 Operational Performance of Critical Footpath in Year 2032 Design Scenario (With Proposed Development)

Critical Section	Total Footpath Width (m)	Effective Width (m) ⁽¹⁾	Year 2032 Design Scenario (With Proposed Development)					
			AM Peak			PM Peak		
			Two-way Pedestrian Flow	Two-way Pedestrian Flow Rate	LOS	Two-way Pedestrian Flow	Two-way Pedestrian Flow Rate	LOS
			(ped/hr) ⁽²⁾	(ped/min/m) ⁽³⁾		(ped/hr) ⁽²⁾	(ped/min/m) ⁽³⁾	
A	2.9	1.9	400	3.5	A	260	2.3	A
B	1.7	0.7	905	21.5	B	560	13.3	A
D	1.5	0.5	625	20.8	B	240	8.0	A

Notes:

(1) Effective Width = Total Footpath Width – Death Width (0.5m from railings).

(2) Two-way Pedestrian Flow Rate (ped/min/m) = Peak Pedestrian Flow / 60 min / Effective Width.

(3) LOS details extracted from the HCM are tabulated in TPDM Volume 6 Chapter 10 Clause 10.4.2.3.

Table 6.8 Operational Performance of Critical Pedestrian Crossing in Year 2032 Design Scenario (With Proposed Development)

Crossing	Year 2032 Design Scenario (With Proposed Development)			
	AM Peak Hour		PM Peak Hour	
	Crossing Demand	Crossing Capacity ⁽¹⁾	Crossing Demand	Crossing Capacity ⁽¹⁾
C	875	3,260	195	3,260

Note:

(1) Crossing capacity according to TPDM Volume 2, Table 3.7.2.1.

6.2.5 It is revealed from the assessment results in **Table 6.3** to **Table 6.8** that the critical section of footpath and pedestrian crossing would all operate with ample reserved capacity during AM and PM peak hours in design year 2032.



7. SUMMARY AND CONCLUSION

7.1 Summary

7.1.1 CTA Consultants Limited (CTA) is commissioned as the traffic consultant to prepare the Traffic Impact Assessment (TIA) and provide technical justifications in supporting the planning application from traffic engineering point of view.

7.1.2 To appraise the existing traffic condition, manual-classified counting surveys were conducted at critical junctions in 2023. Current operational performance of the critical junctions has been assessed. The results reveal that all critical junctions are at present operating within its capacities.

7.1.3 Assessment of operational performance of the critical junctions revealed that all critical junctions would still operate within their capacities in both reference scenario (without proposed development) and design scenario (with proposed development) in 2032 during the peak hours, except Junction Lai King Hill Road / Kwai Chung Interchange (E).

7.1.4 Without junction modification, it is anticipated that Junction E will have negative reserve capacity during AM peak hour in Year 2032 without and with the proposed development. According to approved TIA report of A/KC/489, junction modification work is intended to be carried out before year 2028, i.e. before the completion of the proposed development in year 2029. The assessment results revealed that Junction E would operate within its capacities during the peak hours in both reference and design year with junction modification.


7.2 Conclusion


7.2.1 In conclusion, this TIA has demonstrated that the related traffic trips related to the proposed development can be absorbed by the nearby road network and no insurmountable traffic impact will be induced.

7.2.2 Therefore, the proposed development is considered feasible from traffic engineering point of view.



LEGEND :
 DEVELOPMENT SITE

FIGURE NO.: <p style="text-align: center; font-size: 2em;">1.1</p>		PROJECT TITLE: Proposed Minor Relaxation of Building Height Restriction for the Permitted Social Welfare Facility (Redevelopment of The Salvation Army Lai King Home) at Nos. 200 - 210 Lai King Hill Road, Kwai Chung, New Territories – S16 Planning Application	
PROJECT NO.: <p style="text-align: center;">21149HK</p>		DRAWING TITLE: <p style="text-align: center; font-size: 1.2em;">SITE LOCATION PLAN</p>	
SCALE: 1 : 5000 @A4	DATE: 16 SEP 2022	 CTA Consultants Limited 志達顧問有限公司	




LEGEND :
 DEVELOPMENT SITE

FIGURE NO.: **2.1(REV A)** PROJECT TITLE: Proposed Minor Relaxation of Building Height Restriction for the Permitted Social Welfare Facility (Redevelopment of The Salvation Army Lai King Home) at Nos. 200 - 210 Lai King Hill Road, Kwai Chung, New Territories – S16 Planning Application

PROJECT NO.: 21149HK DRAWING TITLE: LAYOUT PLAN OF PROPOSED DEVELOPMENT

SCALE: 1 : 600 @A4 DATE: 13 MAR 2024









LEGEND :	
	DEVELOPMENT SITE
	ROUTING FOR VEHICLE ATTRACTED BY PROPOSED DEVELOPMENT
	ROUTING FOR VEHICLE GENERATED BY PROPOSED DEVELOPMENT

FIGURE NO.: 2.2		PROJECT TITLE: Proposed Minor Relaxation of Building Height Restriction for the Permitted Social Welfare Facility (Redevelopment of The Salvation Army Lai King Home) at Nos. 200 - 210 Lai King Hill Road, Kwai Chung, New Territories - S16 Planning Application
PROJECT NO.: 21149HK		DRAWING TITLE: PROPOSED ROUTING FOR VEHICLES OF PROPOSED DEVELOPMENT
SCALE: 1 : 4500 @A4	DATE: 21 NOV 2023	
		 CTA Consultants Limited 志達顧問有限公司



LEGEND :

- DEVELOPMENT SITE
- CRITICAL JUNCTION
- AREA OF INFLUENCE

FIGURE NO.:
3.1(REV B)

PROJECT TITLE: Proposed Minor Relaxation of Building Height Restriction for the Permitted Social Welfare Facility
(Redevelopment of The Salvation Army Lai King Home)
at Nos. 200 - 210 Lai King Hill Road, Kwai Chung, New Territories - S16 Planning Application

PROJECT NO.:
21149HK

DRAWING TITLE:

SCALE: 1 : 6500 @A4
DATE: 13 MAR 2024

AREA OF INFLUENCE





FIGURE NO.:		PROJECT TITLE:		 CTA Consultants Limited 志達顧問有限公司
3.2		Proposed Minor Relaxation of Building Height Restriction for the Permitted Social Welfare Facility (Redevelopment of The Salvation Army Lai King Home) at Nos. 200 - 210 Lai King Hill Road, Kwai Chung, New Territories – S16 Planning Application		
PROJECT NO.:		DRAWING TITLE:		
21149HK		EXISTING JUNCTION LAYOUT OF LAI KING HILL ROAD / JOINT STREET / LAI CHO ROAD (A1 & A2)		
SCALE:	DATE:			
1 : 500 @A4	16 SEP 2022			





FIGURE NO.: 3.3		PROJECT TITLE: Proposed Minor Relaxation of Building Height Restriction for the Permitted Social Welfare Facility (Redevelopment of The Salvation Army Lai King Home) at Nos. 200 - 210 Lai King Hill Road, Kwai Chung, New Territories - S16 Planning Application	 CTA Consultants Limited 志達顧問有限公司
PROJECT NO.: 21149HK		DRAWING TITLE: EXISTING JUNCTION LAYOUT OF LAI KING HILL ROAD / KING CHO ROAD (NEAR LAI KING ESTATE) (B)	
SCALE: 1 : 500 @A4	DATE: 16 SEP 2022		




FIGURE NO.:		3.4		PROJECT TITLE:		Proposed Minor Relaxation of Building Height Restriction for the Permitted Social Welfare Facility (Redevelopment of The Salvation Army Lai King Home) at Nos. 200 - 210 Lai King Hill Road, Kwai Chung, New Territories – S16 Planning Application	
PROJECT NO.:		21149HK		DRAWING TITLE:		EXISTING JUNCTION LAYOUT OF LAI KING HILL ROAD / KING CHO ROAD (NEAR LAI KING VENTILATION BUILDING) (C)	
SCALE:	DATE:						
1 : 500 @A4	16 SEP 2022						



CTA Consultants Limited
志達顧問有限公司




FIGURE NO.: 3.5		PROJECT TITLE: Proposed Minor Relaxation of Building Height Restriction for the Permitted Social Welfare Facility (Redevelopment of The Salvation Army Lai King Home) at Nos. 200 - 210 Lai King Hill Road, Kwai Chung, New Territories - S16 Planning Application	 CTA Consultants Limited 志達顧問有限公司
PROJECT NO.: 21149HK		DRAWING TITLE: EXISTING JUNCTION LAYOUT OF LAI KING HILL ROAD / KWAI CHUNG HOSPITAL ROAD (D)	
SCALE: 1 : 500 @A4	DATE: 16 SEP 2022		




FIGURE NO.:		3.6		PROJECT TITLE:		Proposed Minor Relaxation of Building Height Restriction for the Permitted Social Welfare Facility (Redevelopment of The Salvation Army Lai King Home) at Nos. 200 - 210 Lai King Hill Road, Kwai Chung, New Territories - S16 Planning Application	
PROJECT NO.:		21149HK		DRAWING TITLE:		EXISTING JUNCTION LAYOUT OF LAI KING HILL ROAD / KWAI CHUNG INTERCHANGE (E)	
SCALE:	DATE:						
1 : 500 @A4	19 SEP 2022						



CTA Consultants Limited
志達顧問有限公司






FIGURE NO.:		PROJECT TITLE:	
3.7(REV A)		Proposed Minor Relaxation of Building Height Restriction for the Permitted Social Welfare Facility (Redevelopment of The Salvation Army Lai King Home) at Nos. 200 - 210 Lai King Hill Road, Kwai Chung, New Territories - S16 Planning Application	
PROJECT NO.:		DRAWING TITLE:	
21149HK		EXISTING JUNCTION LAYOUT OF KWAI FUK ROAD / KWAI YI ROAD / CONTAINER PORT ROAD (F)	
SCALE:	DATE:		
1 : 700 @A4	22 NOV 2023		




安得利
建築有限公司
Ang Kong
Limited



LEGEND :	
	DEVELOPMENT SITE
	AM(PM) PEAK HOUR TRAFFIC FLOW (IN PCU / HR)
	AM(PM) PEAK HOUR TRAFFIC LINK FLOW (IN PCU / HR)

FIGURE NO.: 3.8 (REV A)		PROJECT TITLE: Proposed Minor Relaxation of Building Height Restriction for the Permitted Social Welfare Facility (Redevelopment of The Salvation Army Lai King Home) at Nos. 200 - 210 Lai King Hill Road, Kwai Chung, New Territories – S16 Planning Application	
PROJECT NO.: 21149HK		DRAWING TITLE: 2023 OBSERVED TRAFFIC FLOWS	
SCALE: N. T. S. @A4	DATE: 13 MAR 2024	 CTA Consultants Limited 志達顧問有限公司	



LEGEND :
 DEVELOPMENT SITE

FIGURE NO.:	PROJECT TITLE:
4.1(REV A)	Proposed Minor Relaxation of Building Height Restriction for the Permitted Social Welfare Facility (Redevelopment of The Salvation Army Lai King Home) at Nos. 200 - 210 Lai King Hill Road, Kwai Chung, New Territories – S16 Planning Application

PROJECT NO.:	DRAWING TITLE:
21149HK	PLANNED MAJOR DEVELOPMENT IN THE VICINITY
SCALE:	
1 : 7000 @A4	20 NOV 2023

 **CTA Consultants Limited**
 志達顧問有限公司






FIGURE NO.:		PROJECT TITLE:	
4.2		Proposed Minor Relaxation of Building Height Restriction for the Permitted Social Welfare Facility (Redevelopment of The Salvation Army Lai King Home) at Nos. 200 - 210 Lai King Hill Road, Kwai Chung, New Territories – S16 Planning Application	
PROJECT NO.:		DRAWING TITLE:	
21149HK		PLANNED JUNCTION LAI KING HILL ROAD / KWAI CHUNG INTERCHANGE (K) CARRIED OUT UNDER A/KC/489	
SCALE:	DATE:		
1 : 550 @A4	07 AUG 2023		





CTA Consultants Limited
志達顧問有限公司



LEGEND :	
	DEVELOPMENT SITE
	AM(PM) PEAK HOUR TRAFFIC FLOW (IN PCU / HR)
	AM(PM) PEAK HOUR TRAFFIC LINK FLOW (IN PCU / HR)

FIGURE NO.: <h3 style="text-align: center;">4.3 (REV A)</h3>		PROJECT TITLE: Proposed Minor Relaxation of Building Height Restriction for the Permitted Social Welfare Facility (Redevelopment of The Salvation Army Lai King Home) at Nos. 200 - 210 Lai King Hill Road, Kwai Chung, New Territories – S16 Planning Application	
PROJECT NO.: 21149HK		DRAWING TITLE: <h3 style="text-align: center;">2032 REFERENCE TRAFFIC FLOWS</h3>	
SCALE: N. T. S. @A4	DATE: 13 MAR 2024	CTA Consultants Limited 志達顧問有限公司	









LEGEND :	
	DEVELOPMENT SITE
	AM(PM) PEAK HOUR TRAFFIC FLOW (IN PCU / HR)
	AM(PM) PEAK HOUR TRAFFIC LINK FLOW (IN PCU / HR)

FIGURE NO.: 4.4 (REV A)		PROJECT TITLE: Proposed Minor Relaxation of Building Height Restriction for the Permitted Social Welfare Facility (Redevelopment of The Salvation Army Lai King Home) at Nos. 200 - 210 Lai King Hill Road, Kwai Chung, New Territories – S16 Planning Application	
PROJECT NO.: 21149HK		DRAWING TITLE: 2032 DESIGN TRAFFIC FLOWS	
SCALE: N. T. S. @A4	DATE: 13 MAR 2024	 CTA Consultants Limited 志達顧問有限公司	



LEGEND :



DEVELOPMENT SITE

420(390)

AM(PM) PEAK HOUR
TRAFFIC FLOW (IN PCU / HR)

FIGURE NO.:
4.5 (REV A)



PROJECT TITLE: Proposed Minor Relaxation of Building Height Restriction for the Permitted Social Welfare Facility (Redevelopment of The Salvation Army Lai King Home) at Nos. 200 - 210 Lai King Hill Road, Kwai Chung, New Territories – S16 Planning Application

PROJECT NO.:
21149HK

DRAWING TITLE:
PROPOSED DEVELOPMENT TRAFFIC FLOWS

SCALE: N. T. S. @A4
DATE: 13 MAR 2024





LEGEND :



DEVELOPMENT SITE

420(390)

AM(PM) PEAK HOUR
TRAFFIC FLOW (IN PCU / HR)

FIGURE NO.:
4.6


PROJECT TITLE: Proposed Minor Relaxation of Building Height Restriction for the Permitted Social Welfare Facility (Redevelopment of The Salvation Army Lai King Home) at Nos. 200 - 210 Lai King Hill Road, Kwai Chung, New Territories – S16 Planning Application

PROJECT NO.:
21149HK

DRAWING TITLE:
ADJACENT DEVELOPMENT TRAFFIC FLOWS

SCALE: N. T. S. @A4
DATE: 13 MAR 2024






LEGEND :
 [Grey Box] DEVELOPMENT SITE

FIGURE NO.:		PROJECT TITLE:	
6.1		Proposed Minor Relaxation of Building Height Restriction for the Permitted Social Welfare Facility (Redevelopment of The Salvation Army Lai King Home) at Nos. 200 - 210 Lai King Hill Road, Kwai Chung, New Territories – S16 Planning Application	
PROJECT NO.:		DRAWING TITLE:	
21149HK		PEDESTRIAN CONNECTIVITY	
SCALE:	DATE:		
1 : 2250 @A4	22 NOV 2023		





LEGEND :

- DEVELOPMENT SITE
- PEDESTRIAN FLOW DIRECTION

FIGURE NO.:	6.2	PROJECT TITLE: Proposed Minor Relaxation of Building Height Restriction for the Permitted Social Welfare Facility (Redevelopment of The Salvation Army Lai King Home) at Nos. 200 - 210 Lai King Hill Road, Kwai Chung, New Territories – S16 Planning Application
PROJECT NO.:	21149HK	DRAWING TITLE:
SCALE: 1 : 2250 @A4	DATE: 22 NOV 2023	INDEX PLAN OF PEDESTRIAN ASSESSMENT

CTA Consultants Limited
志達顧問有限公司





FIGURE NO.:	6.3	PROJECT TITLE:	Proposed Minor Relaxation of Building Height Restriction for the Permitted Social Welfare Facility (Redevelopment of The Salvation Army Lai King Home) at Nos. 200 - 210 Lai King Hill Road, Kwai Chung, New Territories - S16 Planning Application
PROJECT NO.:	21149HK	DRAWING TITLE:	2023 EXISTING PEDESTRIAN FLOWS
SCALE:	1 : 2250 @A4	DATE:	22 NOV 2023

CTA Consultants Limited
志達顧問有限公司




LEGEND :	
	DEVELOPMENT SITE
	PEDESTRIAN FLOW DIRECTION
	AM(PM) PEAK TWO-WAY FLOW (IN PED/HR)

FIGURE NO.:		6.4		PROJECT TITLE:		Proposed Minor Relaxation of Building Height Restriction for the Permitted Social Welfare Facility (Redevelopment of The Salvation Army Lai King Home) at Nos. 200 - 210 Lai King Hill Road, Kwai Chung, New Territories – S16 Planning Application	
PROJECT NO.:		21149HK		DRAWING TITLE:		2032 REFERENCE PEDESTRIAN FLOWS	
SCALE:	DATE:						
1 : 2250 @A4	22 NOV 2023						



CTA Consultants Limited
志達顧問有限公司



LEGEND :	
	DEVELOPMENT SITE
	PEDESTRIAN FLOW DIRECTION
	AM(PM) PEAK TWO-WAY FLOW (IN PED/HR)
A	725(905)

FIGURE NO.:		PROJECT TITLE:		2032 DESIGN PEDESTRIAN FLOWS	 CTA Consultants Limited 志達顧問有限公司
6.5		Proposed Minor Relaxation of Building Height Restriction for the Permitted Social Welfare Facility (Redevelopment of The Salvation Army Lai King Home) at Nos. 200 - 210 Lai King Hill Road, Kwai Chung, New Territories – S16 Planning Application			
PROJECT NO.:		DRAWING TITLE:			
21149HK					
SCALE:	DATE:				
1 : 2250 @A4	22 NOV 2023				




FIGURE NO.: SP-01(REV A)		PROJECT TITLE: Proposed Minor Relaxation of Building Height Restriction for the Permitted Social Welfare Facility (Redevelopment of The Salvation Army Lai King Home) at Nos. 200 - 210 Lai King Hill Road, Kwai Chung, New Territories - S16 Planning Application
PROJECT NO.: 21149HK		DRAWING TITLE: SWEPT PATH ANALYSIS FOR HGV (11m x 2.5m)
SCALE: 1 : 600 @A4	DATE: 13 MAR 2024	

LEGEND :

-  SWEEP PATH (IN)
-  SWEEP PATH (OUT)



CTA Consultants Limited
志達顧問有限公司




FIGURE NO.: SP-02(REV A)		PROJECT TITLE: Proposed Minor Relaxation of Building Height Restriction for the Permitted Social Welfare Facility (Redevelopment of The Salvation Army Lai King Home) at Nos. 200 - 210 Lai King Hill Road, Kwai Chung, New Territories - S16 Planning Application
PROJECT NO.: 21149HK		DRAWING TITLE: SWEPT PATH ANALYSIS FOR LIGHT BUS (8m x 2.5m)
SCALE: 1 : 600 @A4	DATE: 13 MAR 2024	

LEGEND :

-  SWEPT PATH (IN)
-  SWEPT PATH (OUT)



CTA Consultants Limited
志達顧問有限公司



LEGEND :

- SWEPT PATH (IN)
- SWEPT PATH (OUT)

FIGURE NO.: SP-03(REV A)		PROJECT TITLE: Proposed Minor Relaxation of Building Height Restriction for the Permitted Social Welfare Facility (Redevelopment of The Salvation Army Lai King Home) at Nos. 200 - 210 Lai King Hill Road, Kwai Chung, New Territories – S16 Planning Application
PROJECT NO.: 21149HK		DRAWING TITLE: SWEPT PATH ANALYSIS FOR AMBULANCE (6.9m x 1.9m)
SCALE: 1 : 600 @A4	DATE: 13 MAR 2024	



CTA Consultants Limited
志達顧問有限公司




APPENDIX A

JUNCTION CALCULATION SHEETS

Priority Junction : Li King Hill Road/ Joint Street (Jn A1)


Scenario : 2023 Observed Traffic Flows



PLT

Priority Junction : Li King Hill Road/ Joint Street (Jn A1)

Scenario : 2032 Reference Traffic Flows



The predictive equations of capacity of movement are:

$$Q-BA = D(627 + 14W-CR - Y(0.364q-AC + 0.144q-AB + 0.229q-CA + 0.52q-CB))$$

$$Q-BC = E(745 - Y(0.364q-AC + 0.144q-AB))$$

$$Q-CB = F(745 - 0.364Y(q-AC + q-AB))$$

The geometric parameters represented by D, E, F are:

$$D = (1 + 0.094(w-BA - 3.65))(1 + 0.0009(V-rBA - 120))(1 + 0.0006(V-IBA - 150))$$

$$E = (1 + 0.094(w-BC - 3.65))(1 + 0.0009(V-rBC - 120))(1 + 0.0006(V-IBA - 150))$$

$$F = (1 + 0.094(w-CB - 3.65))(1 + 0.0009(V-rCB - 120))$$

where

- Y = 1 - 0.0345W
- q-AB, etc = the design flow of movement AB, etc
- W = major road width
- W-CR = central reserve width
- w-BA, etc = lane width to vehicle
- v-rBA, etc = visibility to the right for waiting vehicles in stream BA, etc
- v-IBA = visibility to the left for waiting vehicles in stream BA, etc

Geometry :	<u>Input</u>				<u>Calculated</u>			
	W	13	V-rBA	50	w-BA	3.8	D	0.893
	W-CR	0	V-IBA	50	w-BC	3.6	E	0.877
			V-rBC	50	w-CB	4	F	0.968
			V-rCB	50			Y	0.552


Analysis :	Traffic Flow	AM	PM	Capacity	AM	PM
	pcu/hr			pcu/hr		
	q-CA	470	380	Q-BA	338	398
	q-CB	190	140	Q-BC	535	572
	q-AB	280	210	Q-CB	558	606
	q-AC	560	380	Q-BAC	419	472
	q-BA	200	150			
	q-BC	140	110			
	f	0.412	0.423			

Results :	Ratio of Flow-to-Capacity	AM	PM
	B-A	0.592	0.377
	B-C	0.262	0.192
	C-B	0.341	0.231
	B-AC	0.811	0.551

PLT

Priority Junction : Li King Hill Road/ Joint Street (Jn A1)

Scenario : 2032 Design Traffic Flows



The predictive equations of capacity of movement are:

$$Q-BA = D(627 + 14W-CR - Y(0.364q-AC + 0.144q-AB + 0.229q-CA + 0.52q-CB))$$

$$Q-BC = E(745 - Y(0.364q-AC + 0.144q-AB))$$

$$Q-CB = F(745 - 0.364Y(q-AC + q-AB))$$

The geometric parameters represented by D, E, F are:

$$D = (1 + 0.094(w-BA - 3.65))(1 + 0.0009(V-rBA - 120))(1 + 0.0006(V-IBA - 150))$$

$$E = (1 + 0.094(w-BC - 3.65))(1 + 0.0009(V-rBC - 120))(1 + 0.0006(V-IBA - 150))$$

$$F = (1 + 0.094(w-CB - 3.65))(1 + 0.0009(V-rCB - 120))$$

where

- Y = 1 - 0.0345W
- q-AB, etc = the design flow of movement AB, etc
- W = major road width
- W-CR = central reserve width
- w-BA, etc = lane width to vehicle
- v-rBA, etc = visibility to the right for waiting vehicles in stream BA, etc
- v-IBA = visibility to the left for waiting vehicles in stream BA, etc

Geometry :	<u>Input</u>	<u>Calculated</u>
	W <u>13</u>	V-rBA <u>50</u>
	W-CR <u>0</u>	V-IBA <u>50</u>
		V-rBC <u>50</u>
		V-rCB <u>50</u>
		w-BA <u>3.8</u>
		w-BC <u>3.6</u>
		w-CB <u>4</u>
		D <u>0.893</u>
		E <u>0.877</u>
		F <u>0.968</u>
		Y <u>0.552</u>


Analysis :	Traffic Flow	AM	PM	Capacity	AM	PM
	pcu/hr			pcu/hr		
	q-CA	<u>480</u>	<u>380</u>	Q-BA	<u>333</u>	<u>385</u>
	q-CB	<u>200</u>	<u>140</u>	Q-BC	<u>533</u>	<u>558</u>
	q-AB	<u>280</u>	<u>250</u>	Q-CB	<u>556</u>	<u>587</u>
	q-AC	<u>570</u>	<u>440</u>	Q-BAC	<u>415</u>	<u>454</u>
	q-BA	<u>200</u>	<u>180</u>			
	q-BC	<u>140</u>	<u>120</u>			
	f	<u>0.412</u>	<u>0.400</u>			

Results :	Ratio of Flow-to-Capacity	AM	PM
	B-A	<u>0.601</u>	<u>0.468</u>
	B-C	<u>0.263</u>	<u>0.215</u>
	C-B	<u>0.360</u>	<u>0.239</u>
	B-AC	<u>0.819</u>	<u>0.661</u>

PLT

Priority Junction : Joint Street / Lai Cho Road (Jn A2)

Scenario : 2023 Observed Traffic Flows



The predictive equations of capacity of movement are:

$$Q-BA = D(627 + 14W-CR - Y(0.364q-AC + 0.144q-AB + 0.229q-CA + 0.52q-CB))$$

$$Q-BC = E(745 - Y(0.364q-AC + 0.144q-AB))$$

$$Q-CB = F(745 - 0.364Y(q-AC + q-AB))$$

The geometric parameters represented by D, E, F are:

$$D = (1 + 0.094(w-BA - 3.65))(1 + 0.0009(V-rBA - 120))(1 + 0.0006(V-IBA - 150))$$

$$E = (1 + 0.094(w-BC - 3.65))(1 + 0.0009(V-rBC - 120))(1 + 0.0006(V-IBA - 150))$$

$$F = (1 + 0.094(w-CB - 3.65))(1 + 0.0009(V-rCB - 120))$$

where

- Y = 1 - 0.0345W
- q-AB, etc = the design flow of movement AB, etc
- W = major road width
- W-CR = central reserve width
- w-BA, etc = lane width to vehicle
- v-rBA, etc = visibility to the right for waiting vehicles in stream BA, etc
- v-IBA = visibility to the left for waiting vehicles in stream BA, etc

Geometry :	<u>Input</u>				<u>Calculated</u>			
	W	10	V-rBA	50	w-BA	3.8	D	0.893
	W-CR	0	V-IBA	50	w-BC	3.8	E	0.893
			V-rBC	50	w-CB	3.8	F	0.950
			V-rCB	50			Y	0.655


Analysis :	Traffic Flow	AM	PM	Capacity	AM	PM
	pcu/hr			pcu/hr		
	q-CA	40	30	Q-BA	497	485
	q-CB	160	200	Q-BC	657	655
	q-AB	30	50	Q-CB	694	690
	q-AC	30	30	Q-BAC	621	598
	q-BA	90	120			
	q-BC	310	240			
	f	0.775	0.667			

Results :	Ratio of Flow-to-Capacity	AM	PM
	B-A	0.181	0.248
	B-C	0.472	0.367
	C-B	0.230	0.290
	B-AC	0.644	0.602

PLT

Priority Junction : Joint Street / Lai Cho Road (Jn A2)


Scenario : 2032 Reference Traffic Flows



PLT

Priority Junction : Joint Street / Lai Cho Road (Jn A2)


Scenario : 2032 Design Traffic Flows



PLT

Priority Junction : Lai King Hill Road / King Cho Road (Near Lai King Estate) (Jn B)

Scenario : 2023 Observed Traffic Flows



The predictive equations of capacity of movement are:

$$Q-BA = D(627 + 14W-CR - Y(0.364q-AC + 0.144q-AB + 0.229q-CA + 0.52q-CB))$$

$$Q-BC = E(745 - Y(0.364q-AC + 0.144q-AB))$$

$$Q-CB = F(745 - 0.364Y(q-AC + q-AB))$$

The geometric parameters represented by D, E, F are:

$$D = (1 + 0.094(w-BA - 3.65))(1 + 0.0009(V-rBA - 120))(1 + 0.0006(V-IBA - 150))$$

$$E = (1 + 0.094(w-BC - 3.65))(1 + 0.0009(V-rBC - 120))(1 + 0.0006(V-IBA - 150))$$

$$F = (1 + 0.094(w-CB - 3.65))(1 + 0.0009(V-rCB - 120))$$

where

- Y = 1 - 0.0345W
- q-AB, etc = the design flow of movement AB, etc
- W = major road width
- W-CR = central reserve width
- w-BA, etc = lane width to vehicle
- v-rBA, etc = visibility to the right for waiting vehicles in stream BA, etc
- v-IBA = visibility to the left for waiting vehicles in stream BA, etc

Geometry :	Input	Calculated
W	10	D 0.786
W-CR	0	E 0.786
V-rBA	50	F 1.056
V-IBA	50	Y 0.655
V-rBC	50	
V-rCB	50	
w-BA	2.5	
w-BC	2.5	
w-CB	5	


Analysis :	Traffic Flow	AM	PM	Capacity	AM	PM
	pcu/hr			pcu/hr		
	q-CA	430	330	Q-BA	340	355
	q-CB	30	40	Q-BC	491	497
	q-AB	180	130	Q-CB	633	648
	q-AC	430	420	Q-BAC	434	421
	q-BA	110	160			
	q-BC	180	140			
	f	0.621	0.467			

Results :	Ratio of Flow-to-Capacity	AM	PM
	B-A	0.324	0.451
	B-C	0.366	0.282
	C-B	0.047	0.062
	B-AC	0.668	0.712

PLT

Priority Junction : Lai King Hill Road / King Cho Road (Near Lai King Estate) (Jn B)

Scenario : 2032 Reference Traffic Flows



The predictive equations of capacity of movement are:

$$Q-BA = D(627 + 14W-CR - Y(0.364q-AC + 0.144q-AB + 0.229q-CA + 0.52q-CB))$$

$$Q-BC = E(745 - Y(0.364q-AC + 0.144q-AB))$$

$$Q-CB = F(745 - 0.364Y(q-AC + q-AB))$$

The geometric parameters represented by D, E, F are:

$$D = (1 + 0.094(w-BA - 3.65))(1 + 0.0009(V-rBA - 120))(1 + 0.0006(V-IBA - 150))$$

$$E = (1 + 0.094(w-BC - 3.65))(1 + 0.0009(V-rBC - 120))(1 + 0.0006(V-IBA - 150))$$

$$F = (1 + 0.094(w-CB - 3.65))(1 + 0.0009(V-rCB - 120))$$

where

- Y = 1 - 0.0345W
- q-AB, etc = the design flow of movement AB, etc
- W = major road width
- W-CR = central reserve width
- w-BA, etc = lane width to vehicle
- v-rBA, etc = visibility to the right for waiting vehicles in stream BA, etc
- v-IBA = visibility to the left for waiting vehicles in stream BA, etc


Geometry :	Input	Calculated
W	10	D 0.786
W-CR	0	E 0.786
V-rBA	50	F 1.056
V-IBA	50	Y 0.655
V-rBC	50	
V-rCB	50	
w-BA	2.5	
w-BC	2.5	
w-CB	5	

Analysis :	Traffic Flow	AM	PM	Capacity	AM	PM
	pcu/hr			pcu/hr		
	q-CA	530	370	Q-BA	303	337
	q-CB	40	50	Q-BC	469	487
	q-AB	200	140	Q-CB	600	633
	q-AC	540	470	Q-BAC	409	407
	q-BA	120	170			
	q-BC	210	150			
	f	0.636	0.469			

Results :	Ratio of Flow-to-Capacity	AM	PM
	B-A	0.395	0.504
	B-C	0.447	0.308
	C-B	0.067	0.079
	B-AC	0.807	0.786

Priority Junction : Lai King Hill Road / King Cho Road (Near Lai King Estate) (Jn B)

Scenario : 2032 Design Traffic Flows



The predictive equations of capacity of movement are:

$$Q-BA = D(627 + 14W-CR - Y(0.364q-AC + 0.144q-AB + 0.229q-CA + 0.52q-CB))$$

$$Q-BC = E(745 - Y(0.364q-AC + 0.144q-AB))$$

$$Q-CB = F(745 - 0.364Y(q-AC + q-AB))$$

The geometric parameters represented by D, E, F are:

$$D = (1 + 0.094(w-BA - 3.65))(1 + 0.0009(V-rBA - 120))(1 + 0.0006(V-IBA - 150))$$

$$E = (1 + 0.094(w-BC - 3.65))(1 + 0.0009(V-rBC - 120))(1 + 0.0006(V-IBA - 150))$$

$$F = (1 + 0.094(w-CB - 3.65))(1 + 0.0009(V-rCB - 120))$$

where

- Y = 1 - 0.0345W
- q-AB, etc = the design flow of movement AB, etc
- W = major road width
- W-CR = central reserve width
- w-BA, etc = lane width to vehicle
- v-rBA, etc = visibility to the right for waiting vehicles in stream BA, etc
- v-IBA = visibility to the left for waiting vehicles in stream BA, etc

Geometry :	Input	Calculated
W	10	D 0.786
W-CR	0	E 0.786
V-rBA	50	F 1.056
V-IBA	50	Y 0.655
V-rBC	50	
V-rCB	50	
w-BA	2.5	
w-BC	2.5	
w-CB	5	


Analysis :	Traffic Flow	AM	PM	Capacity	AM	PM
	pcu/hr			pcu/hr		
	q-CA	550	380	Q-BA	299	334
	q-CB	40	50	Q-BC	467	485
	q-AB	200	140	Q-CB	598	631
	q-AC	550	480	Q-BAC	406	405
	q-BA	120	170			
	q-BC	210	150			
	f	0.636	0.469			

Results :	Ratio of Flow-to-Capacity	AM	PM
	B-A	0.401	0.509
	B-C	0.449	0.309
	C-B	0.067	0.079
	B-AC	0.812	0.790

PLT

Priority Junction : Lai King Hill Road / King Cho Road (Near Lai King Ventilation Building) (Jn C)

Scenario : 2023 Observed Traffic Flows



The predictive equations of capacity of movement are:

$$Q-BA = D(627 + 14W-CR - Y(0.364q-AC + 0.144q-AB + 0.229q-CA + 0.52q-CB))$$

$$Q-BC = E(745 - Y(0.364q-AC + 0.144q-AB))$$

$$Q-CB = F(745 - 0.364Y(q-AC + q-AB))$$

The geometric parameters represented by D, E, F are:

$$D = (1 + 0.094(w-BA - 3.65))(1 + 0.0009(V-rBA - 120))(1 + 0.0006(V-IBA - 150))$$

$$E = (1 + 0.094(w-BC - 3.65))(1 + 0.0009(V-rBC - 120))(1 + 0.0006(V-IBA - 150))$$

$$F = (1 + 0.094(w-CB - 3.65))(1 + 0.0009(V-rCB - 120))$$

where

- Y = 1 - 0.0345W
- q-AB, etc = the design flow of movement AB, etc
- W = major road width
- W-CR = central reserve width
- w-BA, etc = lane width to vehicle
- v-rBA, etc = visibility to the right for waiting vehicles in stream BA, etc
- v-IBA = visibility to the left for waiting vehicles in stream BA, etc

Geometry :	Input	Calculated
W	10	D 0.786
W-CR	0	E 0.786
V-rBA	50	F 1.056
V-IBA	50	Y 0.655
V-rBC	50	
V-rCB	50	
w-BA	2.5	
w-BC	2.5	
w-CB	5	


Analysis :	Traffic Flow	AM	PM	Capacity	AM	PM
	pcu/hr			pcu/hr		
	q-CA	410	360	Q-BA	284	293
	q-CB	160	200	Q-BC	468	481
	q-AB	40	40	Q-CB	623	641
	q-AC	610	540	Q-BAC	431	446
	q-BA	50	30			
	q-BC	200	130			
	f	0.800	0.813			

Results :	Ratio of Flow-to-Capacity	AM	PM
	B-A	0.176	0.103
	B-C	0.427	0.270
	C-B	0.257	0.312
	B-AC	0.580	0.359

PLT

Priority Junction : Lai King Hill Road / King Cho Road (Near Lai King Ventilation Building) (Jn C)

Scenario : 2032 Reference Traffic Flows



The predictive equations of capacity of movement are:

$$Q-BA = D(627 + 14W-CR - Y(0.364q-AC + 0.144q-AB + 0.229q-CA + 0.52q-CB))$$

$$Q-BC = E(745 - Y(0.364q-AC + 0.144q-AB))$$

$$Q-CB = F(745 - 0.364Y(q-AC + q-AB))$$

The geometric parameters represented by D, E, F are:

$$D = (1 + 0.094(w-BA - 3.65))(1 + 0.0009(V-rBA - 120))(1 + 0.0006(V-IBA - 150))$$

$$E = (1 + 0.094(w-BC - 3.65))(1 + 0.0009(V-rBC - 120))(1 + 0.0006(V-IBA - 150))$$

$$F = (1 + 0.094(w-CB - 3.65))(1 + 0.0009(V-rCB - 120))$$

where

- Y = 1 - 0.0345W
- q-AB, etc = the design flow of movement AB, etc
- W = major road width
- W-CR = central reserve width
- w-BA, etc = lane width to vehicle
- v-rBA, etc = visibility to the right for waiting vehicles in stream BA, etc
- v-IBA = visibility to the left for waiting vehicles in stream BA, etc

Geometry :	Input	Calculated
W	10	D 0.786
W-CR	0	E 0.786
V-rBA	50	F 1.056
V-IBA	50	Y 0.655
V-rBC	50	
V-rCB	50	
w-BA	2.5	
w-BC	2.5	
w-CB	5	


Analysis :	Traffic Flow	AM	PM	Capacity	AM	PM
	pcu/hr			pcu/hr		
	q-CA	510	410	Q-BA	232	269
	q-CB	210	230	Q-BC	441	472
	q-AB	50	40	Q-CB	585	628
	q-AC	750	590	Q-BAC	407	440
	q-BA	50	30			
	q-BC	260	160			
	f	0.839	0.842			

Results :	Ratio of Flow-to-Capacity	AM	PM
	B-A	0.215	0.111
	B-C	0.589	0.339
	C-B	0.359	0.366
	B-AC	0.761	0.432

PLT

Priority Junction : Lai King Hill Road / King Cho Road (Near Lai King Ventilation Building) (Jn C)

Scenario : 2032 Design Traffic Flows



The predictive equations of capacity of movement are:

$$Q-BA = D(627 + 14W-CR - Y(0.364q-AC + 0.144q-AB + 0.229q-CA + 0.52q-CB))$$

$$Q-BC = E(745 - Y(0.364q-AC + 0.144q-AB))$$

$$Q-CB = F(745 - 0.364Y(q-AC + q-AB))$$

The geometric parameters represented by D, E, F are:

$$D = (1 + 0.094(w-BA - 3.65))(1 + 0.0009(V-rBA - 120))(1 + 0.0006(V-IBA - 150))$$

$$E = (1 + 0.094(w-BC - 3.65))(1 + 0.0009(V-rBC - 120))(1 + 0.0006(V-IBA - 150))$$

$$F = (1 + 0.094(w-CB - 3.65))(1 + 0.0009(V-rCB - 120))$$

where

- $Y = 1 - 0.0345W$
- q-AB, etc = the design flow of movement AB, etc
- W = major road width
- W-CR = central reserve width
- w-BA, etc = lane width to vehicle
- v-rBA, etc = visibility to the right for waiting vehicles in stream BA, etc
- v-IBA = visibility to the left for waiting vehicles in stream BA, etc

Geometry :	Input	Calculated
W	10	D 0.786
W-CR	0	E 0.786
V-rBA	50	F 1.056
V-IBA	50	Y 0.655
V-rBC	50	
V-rCB	50	
w-BA	2.5	
w-BC	2.5	
w-CB	5	


Analysis :	Traffic Flow	AM	PM	Capacity	AM	PM
	pcu/hr			pcu/hr		
	q-CA	530	420	Q-BA	226	264
	q-CB	210	230	Q-BC	437	468
	q-AB	50	40	Q-CB	580	623
	q-AC	770	610	Q-BAC	403	436
	q-BA	50	30			
	q-BC	260	160			
	f	0.839	0.842			

Results :	Ratio of Flow-to-Capacity	AM	PM
	B-A	0.221	0.114
	B-C	0.595	0.342
	C-B	0.362	0.369
	B-AC	0.769	0.436

PLT

Priority Junction : Lai King Hill Road / Kwai Chung Interchange (Jn D)

Scenario : 2023 Observed Traffic Flows



The predictive equations of capacity of movement are:

$$Q-BA = D(627 + 14W-CR - Y(0.364q-AC + 0.144q-AB + 0.229q-CA + 0.52q-CB))$$

$$Q-BC = E(745 - Y(0.364q-AC + 0.144q-AB))$$

$$Q-CB = F(745 - 0.364Y(q-AC + q-AB))$$

The geometric parameters represented by D, E, F are:

$$D = (1 + 0.094(w-BA - 3.65))(1 + 0.0009(V-rBA - 120))(1 + 0.0006(V-IBA - 150))$$

$$E = (1 + 0.094(w-BC - 3.65))(1 + 0.0009(V-rBC - 120))(1 + 0.0006(V-IBA - 150))$$

$$F = (1 + 0.094(w-CB - 3.65))(1 + 0.0009(V-rCB - 120))$$

where

- Y = 1 - 0.0345W
- q-AB, etc = the design flow of movement AB, etc
- W = major road width
- W-CR = central reserve width
- w-BA, etc = lane width to vehicle
- v-rBA, etc = visibility to the right for waiting vehicles in stream BA, etc
- v-IBA = visibility to the left for waiting vehicles in stream BA, etc

Geometry :	Input			Calculated				
	W	10	V-rBA	50	w-BA	2.5	D	0.786
	W-CR	0	V-IBA	50	w-BC	2.5	E	0.786
			V-rBC	50	w-CB	5	F	1.056
			V-rCB	50			Y	0.655


Analysis :	Traffic Flow	AM	PM	Capacity	AM	PM
	pcu/hr			pcu/hr		
	q-CA	470	500	Q-BA	244	304
	q-CB	240	40	Q-BC	456	467
	q-AB	200	60	Q-CB	583	618
	q-AC	610	610	Q-BAC	355	402
	q-BA	100	60			
	q-BC	110	90			
	f	0.524	0.600			

Results :	Ratio of Flow-to-Capacity	AM	PM
	B-A	0.410	0.197
	B-C	0.241	0.193
	C-B	0.412	0.065
	B-AC	0.591	0.373

PLT

Priority Junction : Lai King Hill Road / Kwai Chung Interchange (Jn D)


Scenario : 2032 Reference Traffic Flows



PLT

Priority Junction : Lai King Hill Road / Kwai Chung Interchange (Jn D)

Scenario : 2032 Design Traffic Flows



PLT

TRAFFIC SIGNALS CALCULATION

Job No: 21149HK

CTA Consultants Ltd.

Junction: **Lai King Hill Road / Kwai Chung Interchange (E)**
 Description: **2023 Observed Traffic Flows**

Approach	Direction	Movement notation	Phase	Stage	Width (m)			Radius (m)			Pro. Turning (%)		Saturation Flow (pcu/hr)	Total Saturation Flow (pcu/hr)	Revised Saturation Flow (pcu/hr)		Total Revised Saturation Flow (pcu/hr)		A.M. Peak			P.M. Peak		
					Left	Right	Nearside 0/1	A.M.	P.M.	A.M.	P.M.	A.M.			P.M.	Flow (pcu/hr)	y Value	Critical y	Flow (pcu/hr)	y Value	Critical y			
Kwai Chung Interchange	E		2	B	3.5	18	0	1	100%	100%	1813.8	1813.8	1675	1675	1675	1675	150	0.090		120	0.072			
Kwai Chung Interchange	E		2	B	3.5	0	25	0	100%	100%	1953.8	1953.8	1845	1845	1845	1845	100	0.054	0.054	110	0.060	0.060		
Lai King Hill Road	N		3	C	3.8	0	0	0	0%	0%	2130	0	2130	2130	0	0	325	0.152		268	0.126			
Lai King Hill Road	N		3	C	3.8	15	0	1	27%	37%	1990	4120	1940	1920	4070	4050	295	0.152	0.152	242	0.126	0.126		
Lai King Hill Road	S		1	A	3.3	0	0	1	0%	0%	1945	1945	1945	1945	1945	1945	620	0.319	0.319	580	0.298	0.298		
Lai King Hill Road	S		1	A	3.3	0	20	0	100%	100%	2085	2085	1940	1940	1940	1940	120	0.062		120	0.062			

Notes:	Traffic Flow (pcu / hr)	AM(PM)	A.M. Check Phase	P.M. Check Phase
	620(580) 120(120) 150(120) 100(110)	540(420) 80(90)	E _y 0.525 L (sec) 12 C (sec) 120 y pract. 0.810 R.C. (%) 54%	E _y 0.484 L (sec) 12 C (sec) 120 y pract. 0.810 R.C. (%) 67%







Stage / Phase Diagrams				
I/G = 5s	I/G = 5s	I/G = 5s		






TRAFFIC SIGNALS CALCULATION




Job No: 21149HK

CTA Consultants Ltd.

Junction: **Lai King Hill Road / Kwai Chung Interchange (E)**
 Description: **2032 Reference Traffic Flows**

Approach	Direction	Movement notation	Phase	Stage	Width (m)			Radius (m)			Pro. Turning (%)		Saturation Flow (pcu/hr)	Total Saturation Flow (pcu/hr)	Revised Saturation Flow (pcu/hr)		Total Revised Saturation Flow (pcu/hr)		A.M. Peak			P.M. Peak		
					Left	Right	Nearside 0/1	A.M.	P.M.	A.M.	P.M.	A.M.			P.M.	Flow (pcu/hr)	y Value	Critical y	Flow (pcu/hr)	y Value	Critical y			
Kwai Chung Interchange	E		2	B	3.5	18	0	1	100%	100%	1813.8	1813.8	1675	1675	1675	1675	210	0.125		160	0.096			
Kwai Chung Interchange	E		2	B	3.5	0	25	0	100%	100%	1953.8	1953.8	1845	1845	1845	1845	300	0.163	0.163	280	0.152	0.152		
Lai King Hill Road	N		3	C	3.8	0	0	0	0%	0%	2130	0	2130	2130	0	0	575	0.270		369	0.173			
Lai King Hill Road	N		3	C	3.8	15	0	1	85%	72%	1990	4120	1835	1855	3965	3985	495	0.270	0.270	321	0.173	0.173		
Lai King Hill Road	S		1	A	3.3	0	0	1	0%	0%	1945	1945	1945	1945	1945	1945	750	0.386	0.386	630	0.324	0.324		
Lai King Hill Road	S		1	A	3.3	0	20	0	100%	100%	2085	2085	1940	1940	1940	1940	190	0.098		160	0.082			

Notes:	Traffic Flow (pcu / hr)	AM(PM)	A.M. Check Phase	P.M. Check Phase
	750(630)  190(160)    210(160) 300(280)	← 650(460)  420(230)	εy 0.818 L (sec) 12 C (sec) 120 y pract. 0.810 R.C. (%) -1%	εy 0.649 L (sec) 12 C (sec) 120 y pract. 0.810 R.C. (%) 25%

Stage / Phase Diagrams				
				
I/G = 5s	I/G = 5s	I/G = 5s		

TRAFFIC SIGNALS CALCULATION

Job No: 21149HK

CTA Consultants Ltd.

Junction: **Lai King Hill Road / Kwai Chung Interchange (E)**
 Description: **2032 Reference Traffic Flows (Without A/KC/489)**

Approach	Direction	Movement notation	Phase	Stage	Width (m)			Radius (m)			Pro. Turning (%)		Saturation Flow (pcu/hr)	Total Saturation Flow (pcu/hr)	Revised Saturation Flow (pcu/hr)		Total Revised Saturation Flow (pcu/hr)		A.M. Peak			P.M. Peak		
					Left	Right	Nearside 0/1	A.M.	P.M.	A.M.	P.M.	A.M.			P.M.	Flow (pcu/hr)	y Value	Critical y	Flow (pcu/hr)	y Value	Critical y			
Kwai Chung Interchange	E		2	B	3.5	18	0	1	100%	100%	1813.8	1813.8	1675	1675	1675	1675	210	0.125		160	0.096			
Kwai Chung Interchange	E		2	B	3.5	0	25	0	100%	100%	1953.8	1953.8	1845	1845	1845	1845	120	0.065	0.065	120	0.065	0.065		
Lai King Hill Road	N		3	C	3.8	0	0	0	0%	0%	2130	0	2130	2130	0	0	367	0.172		284	0.133			
Lai King Hill Road	N		3	C	3.8	15	0	1	27%	39%	1990	4120	1940	1915	4070	4045	333	0.172	0.172	256	0.134	0.134		
Lai King Hill Road	S		1	A	3.3	0	0	1	0%	0%	1945	1945	1945	1945	1945	1945	700	0.360	0.360	610	0.314	0.314		
Lai King Hill Road	S		1	A	3.3	0	20	0	100%	100%	2085	2085	1940	1940	1940	1940	190	0.098		160	0.082			

Notes:	Traffic Flow (pcu / hr)	AM(PM)	A.M. Check Phase	P.M. Check Phase
			εy 0.597 L (sec) 12 C (sec) 120 y pract. 0.810 R.C. (%) 36%	εy 0.512 L (sec) 12 C (sec) 120 y pract. 0.810 R.C. (%) 58%

Stage / Phase Diagrams				
I/G = 5s	I/G = 5s	I/G = 5s		

TRAFFIC SIGNALS CALCULATION

Job No: 21149HK

CTA Consultants Ltd.

Junction: **Lai King Hill Road / Kwai Chung Interchange (E)**
 Description: **2032 Design Traffic Flows**

Approach	Direction	Movement notation	Phase	Stage	Width (m)			Radius (m)			Pro. Turning (%)		Saturation Flow (pcu/hr)	Total Saturation Flow (pcu/hr)	Revised Saturation Flow (pcu/hr)		Total Revised Saturation Flow (pcu/hr)		A.M. Peak			P.M. Peak		
					Left	Right	Nearside 0/1	A.M.	P.M.	A.M.	P.M.	A.M.			P.M.	Flow (pcu/hr)	y Value	Critical y	Flow (pcu/hr)	y Value	Critical y			
Kwai Chung Interchange	E		2	B	3.5	18	0	1	100%	100%	1813.8	1813.8	1675	1675	1675	1675	210	0.125		160	0.096			
Kwai Chung Interchange	E		2	B	3.5	0	25	0	100%	100%	1953.8	1953.8	1845	1845	1845	1845	300	0.163	0.163	280	0.152	0.152		
Lai King Hill Road	N		3	C	3.8	0	0	0	0%	0%	2130	0	2130	2130	0	0	580	0.272		374	0.175			
Lai King Hill Road	N		3	C	3.8	15	0	1	84%	71%	1990	4120	1835	1860	3965	3990	500	0.272	0.272	326	0.175	0.175		
Lai King Hill Road	S		1	A	3.3	0	0	1	0%	0%	1945	1945	1945	1945	1945	1945	750	0.386	0.386	630	0.324	0.324		
Lai King Hill Road	S		1	A	3.3	0	20	0	100%	100%	2085	2085	1940	1940	1940	1940	190	0.098		170	0.088			

Notes:	Traffic Flow (pcu / hr)	AM(PM)	A.M. Check Phase	P.M. Check Phase
	750(630) → 190(170) ↓	← 660(470) ↓ 420(230)	εy 0.821 L (sec) 12 C (sec) 120 y pract. 0.810 R.C. (%) -1%	εy 0.651 L (sec) 12 C (sec) 120 y pract. 0.810 R.C. (%) 24%
	210(160)	300(280)		







Stage / Phase Diagrams				
I/G = 5s	I/G = 5s	I/G = 5s		



TRAFFIC SIGNALS CALCULATION




Job No: 21149HK

CTA Consultants Ltd.

Junction: **Lai King Hill Road / Kwai Chung Interchange (E)**
 Description: **2032 Design Traffic Flows (Without A/KC/489)**

Approach	Direction	Movement notation	Phase	Stage	Width (m)			Radius (m)			Pro. Turning (%)		Saturation Flow (pcu/hr)	Total Saturation Flow (pcu/hr)	Revised Saturation Flow (pcu/hr)		Total Revised Saturation Flow (pcu/hr)		A.M. Peak			P.M. Peak		
					Left	Right	Nearside 0/1	A.M.	P.M.	A.M.	P.M.	A.M.			P.M.	Flow (pcu/hr)	y Value	Critical y	Flow (pcu/hr)	y Value	Critical y			
Kwai Chung Interchange	E		2	B	3.5	18	0	1	100%	100%	1813.8	1813.8	1675	1675	1675	1675	210	0.125		160	0.096			
Kwai Chung Interchange	E		2	B	3.5	0	25	0	100%	100%	1953.8	1953.8	1845	1845	1845	1845	120	0.065	0.065	120	0.065	0.065		
Lai King Hill Road	N		3	C	3.8	0	0	0	0%	0%	2130	0	2130	2130	0	0	372	0.175		290	0.136			
Lai King Hill Road	N		3	C	3.8	15	0	1	27%	38%	1990	4120	1940	1915	4070	4045	338	0.174	0.174	260	0.136	0.136		
Lai King Hill Road	S		1	A	3.3	0	0	1	0%	0%	1945	1945	1945	1945	1945	1945	710	0.365	0.365	610	0.314	0.314		
Lai King Hill Road	S		1	A	3.3	0	20	0	100%	100%	2085	2085	1940	1940	1940	1940	190	0.098		170	0.088			

Notes:	Traffic Flow (pcu / hr)	AM(PM)	A.M. Check Phase	P.M. Check Phase
	710(610) → 190(170) ↓	← 620(450) ↓ 90(100)	εy 0.604 L (sec) 12 C (sec) 120 y pract. 0.810 R.C. (%) 34%	εy 0.515 L (sec) 12 C (sec) 120 y pract. 0.810 R.C. (%) 57%
	 			
	210(160)	120(120)		

Stage / Phase Diagrams					
					
I/G = 5s	I/G = 5s	I/G = 5s			

TRAFFIC SIGNALS CALCULATION


Job No: 21149HK

CTA Consultants Ltd.

Junction: **Lai King Hill Road / Kwai Chung Interchange (E)**
 Description: **2032 Reference Traffic Flows (With improvement)**

Approach	Direction	Movement notation	Phase	Stage	Width (m)			Radius (m)			Nearside 0/1	Pro. Turning (%)		Saturation Flow (pcu/hr)	Total Saturation Flow (pcu/hr)	Revised Saturation Flow (pcu/hr)		Total Revised Saturation Flow (pcu/hr)		A.M. Peak			P.M. Peak		
					Left	Right	N/A	A.M.	P.M.	A.M.		P.M.	A.M.			P.M.	Flow (pcu/hr)	y Value	Critical y	Flow (pcu/hr)	y Value	Critical y			
Kwai Chung Interchange	E	↖	1	A	3.5	18	0	1	100%	100%	1813.8	1813.8	1675	1675	1675	1675	210	0.125		160	0.096				
Kwai Chung Interchange	E	↗	1	A	3.5	0	25	0	100%	100%	1953.8	1953.8	1845	1845	1845	1845	300	0.163		280	0.152	0.152			
Lai King Hill Road	N	←	2	B	3.5	0	0	0	0%	0%	2105	2105	2105	2105	2105	2105	650	0.309		460	0.219				
Lai King Hill Road	N	↙	1	A	4.3	15	0	1	100%	100%	2045	2045	1860	1860	1860	1860	420	0.226	0.226	230	0.124				
Lai King Hill Road	S	→	2	B	3.5	0	0	1	0%	0%	1965	1965	1965	1965	1965	1965	750	0.382	0.382	630	0.321	0.321			
Lai King Hill Road	S	↘	3	C	3.5	0	20	0	100%	100%	2105	2105	1960	1960	1960	1960	190	0.097	0.097	160	0.082	0.082			
Pedestrian crossing		↕	D	A	Min. green time = 5Gm + 5 FGm = 10s																				
		↕	E	C	Min. green time = 5Gm + 9 FGm = 14s																				
		↕	F	C	Min. green time = 5Gm + 11 FGm = 16s																				
		↕	G	B	Min. green time = 5Gm + 10 FGm = 15s																				

Notes:	Traffic Flow (pcu / hr)	AM(PM)	A.M. Check Phase	P.M. Check Phase
	750(630) → 190(160) ↓ ↙ ↘ 210(160) 300(280)	← 650(460) ↓ 420(230)	εy 0.704 L (sec) 12 C (sec) 120 y pract. 0.810 R.C. (%) 15%	εy 0.554 L (sec) 12 C (sec) 120 y pract. 0.810 R.C. (%) 46%



TRAFFIC SIGNALS CALCULATION

Job No: 21149HK


CTA Consultants Ltd.

Junction: **Lai King Hill Road / Kwai Chung Interchange (E)**

Description: **2032 Design Traffic Flows (With improvement)**

Approach	Direction	Movement notation	Phase	Stage	Width (m)			Radius (m)			Pro. Turning (%)		Saturation Flow (pcu/hr)	Total Saturation Flow (pcu/hr)	Revised Saturation Flow (pcu/hr)		Total Revised Saturation Flow (pcu/hr)		A.M. Peak			P.M. Peak		
					Left	Right	Nearside 0/1	A.M.	P.M.	A.M.	P.M.	A.M.			P.M.	Flow (pcu/hr)	y Value	Critical y	Flow (pcu/hr)	y Value	Critical y			
Kwai Chung Interchange	E		1	A	3.5	18	0	1	100%	100%	1813.8	1813.8	1675	1675	1675	1675	210	0.125		160	0.096			
Kwai Chung Interchange	E		1	A	3.5	0	25	0	100%	100%	1953.8	1953.8	1845	1845	1845	1845	300	0.163		280	0.152	0.152		
Lai King Hill Road	N		2	B	3.5	0	0	0	0%	0%	2105	2105	2105	2105	2105	2105	660	0.314		470	0.223			
Lai King Hill Road	N		1	A	4.3	15	0	1	100%	100%	2045	2045	1860	1860	1860	1860	420	0.226	0.226	230	0.124			
Lai King Hill Road	S		2	B	3.5	0	0	1	0%	0%	1965	1965	1965	1965	1965	1965	750	0.382	0.382	630	0.321	0.321		
Lai King Hill Road	S		3	C	3.5	0	20	0	100%	100%	2105	2105	1960	1960	1960	1960	190	0.097	0.097	170	0.087	0.087		
Pedestrian crossing			D	A	Min. green time = 5Gm + 5 FGm = 10s																			
			E	C	Min. green time = 5Gm + 9 FGm = 14s																			
			F	C	Min. green time = 5Gm + 11 FGm = 16s																			
			G	B	Min. green time = 5Gm + 10 FGm = 15s																			

Notes:	Traffic Flow (pcu / hr)	AM(PM)	A.M. Check Phase	P.M. Check Phase
	750(630) 190(170)	660(470) 420(230)	εy 0.704 L (sec) 12 C (sec) 120 y pract. 0.810 R.C. (%) 15%	εy 0.559 L (sec) 12 C (sec) 120 y pract. 0.810 R.C. (%) 45%
	210(160) 300(280)			




Roundabout Junction Calculation

Roundabout Junction : Kwai Fuk Road / Kwai Yi Road / Container Port Road

Project No. 22149HK

Design Year : 2023 Observed Traffic Flows



Input Parameters		Arm A - Kwai Yi Road		Arm B - Kwai Fuk Road		Arm C - Container Port Road		Arm D - Kwai Fuk Road	
		AM	PM	AM	PM	AM	PM	AM	PM
V	= Approach half width (m)	5.5	5.5	7.5	7.5	6.7	6.7	7.1	7.1
E	= Entry width (m)	9.6	9.6	7.9	7.9	7	7	7.8	7.8
L	= Effective length of flare (m)	12	12	1	1	17	17	1	1
R	= Entry radius	35	35	29	29	30	30	18.2	18.2
D	= Inscribed circle diameter (m)	85	85	85	85	85	85	85	85
A	= Entry angle (degree)	18	18	38	38	8	8	34	34
Q	= Entry flow (pcu/hr)	640	710	580	670	690	720	1080	1020
Qc	= Circulating flow across entry (pcu/hr)	790	690	910	970	890	1050	510	590

Output Parameters		Arm A		Arm B		Arm C		Arm D	
		AM	PM	AM	PM	AM	PM	AM	PM
S	= Sharpness of flare = 1.6*(E-V)/L	0.55	0.55	0.64	0.64	0.03	0.03	1.12	1.12
K	= 1-0.00347*(A-30)-0.978*(1/R-0.05)	1.06	1.06	0.99	0.99	1.09	1.09	0.98	0.98
X2	= V+((E-V)/(1+2*S))	7.46	7.46	7.68	7.68	6.98	6.98	7.32	7.32
M	= Exp((D-60)/10)	12.18	12.18	12.18	12.18	12.18	12.18	12.18	12.18
F	= 303*X2	2260	2260	2326	2326	2116	2116	2217	2217
Td	= 1+(0.5/(1+M))	1.04	1.04	1.04	1.04	1.04	1.04	1.04	1.04
Fc	= 0.21*Td*(1+0.2*X2)	0.54	0.54	0.55	0.55	0.52	0.52	0.54	0.54
Qe	= Capacity = K*(F-Fc*Qc)	1946	2003	1800	1767	1804	1713	1907	1864
DFC	= Entry Flow/Capacity = Q/Qe	0.33	0.35	0.32	0.38	0.38	0.42	0.57	0.55

DFC of Critical Approach	=	AM	PM
		0.57	0.55


CTA

Roundabout Junction Calculation

Roundabout Junction : Kwai Fuk Road / Kwai Yi Road / Container Port Road

Project No. 22149HK

Design Year : 2032 Reference Traffic Flows



Input Parameters		Arm A - Kwai Yi Road		Arm B - Kwai Fuk Road		Arm C - Container Port Road		Arm D - Kwai Fuk Road		
		AM	PM	AM	PM	AM	PM	AM	PM	
V	=	Approach half width (m)	5.5	5.5	7.5	7.5	6.7	6.7	7.1	7.1
E	=	Entry width (m)	9.6	9.6	7.9	7.9	7	7	7.8	7.8
L	=	Effective length of flare (m)	12	12	1	1	17	17	1	1
R	=	Entry radius	35	35	29	29	30	30	18.2	18.2
D	=	Inscribed circle diameter (m)	85	85	85	85	85	85	85	85
A	=	Entry angle (degree)	18	18	38	38	8	8	34	34
Q	=	Entry flow (pcu/hr)	720	740	740	750	780	750	1320	1130
Qc	=	Circulating flow across entry (pcu/hr)	990	780	1030	1010	1100	1140	570	610

Output Parameters		Arm A		Arm B		Arm C		Arm D		
		AM	PM	AM	PM	AM	PM	AM	PM	
S	=	Sharepness of flare = 1.6*(E-V)/L	0.55	0.55	0.64	0.64	0.03	0.03	1.12	1.12
K	=	1-0.00347*(A-30)-0.978*(1/R-0.05)	1.06	1.06	0.99	0.99	1.09	1.09	0.98	0.98
X2	=	V+((E-V)/(1+2*S))	7.46	7.46	7.68	7.68	6.98	6.98	7.32	7.32
M	=	Exp((D-60)/10)	12.18	12.18	12.18	12.18	12.18	12.18	12.18	12.18
F	=	303*X2	2260	2260	2326	2326	2116	2116	2217	2217
Td	=	1+(0.5/(1+M))	1.04	1.04	1.04	1.04	1.04	1.04	1.04	1.04
Fc	=	0.21*Td*(1+0.2*X2)	0.54	0.54	0.55	0.55	0.52	0.52	0.54	0.54
Qe	=	Capacity = K*(F-Fc*Qc)	1830	1951	1734	1745	1684	1661	1875	1854
DFC	=	Entry Flow/Capacity = Q/Qe	0.39	0.38	0.43	0.43	0.46	0.45	0.70	0.61

DFC of Critical Approach	=	AM	PM
		0.70	0.61

CTA