


**Proposed Filling and Excavation of Land  
for the Permitted “Agricultural Use” in “Conservation Area”  
at Various Lots in DD238 in Clear Water Bay  
S16 Planning Application**

**(Planning Application No: A/SK-CWBN/77)**

**Appendix I**  
Revised Layout Plan

**SOMEWHERE ORGANIC FARM LAYOUT**  
(FOR REFERENCE ONLY, NOT FOR APPROVAL)

- TEMPORARY STRUCTURE
- A SHELTER FOR WORKERS & VISITORS
- B TOILET/CHANGING ROOM/  
STORAGE OF PERSONAL ITEMS/  
EQUIPMENT/ CONSUMABLES
- C STORAGE OF COMPOST
- D STORAGE OF CONSUMABLES  
(E.G. ORGANIC FERTILIZER)
- E SHELTER FOR LARGE/HEAVY EQUIPMENT
- F CONTROL ROOM/STORAGE OF HOE  
AND MATTOCK
- G RESTING AREA
- PLATFORM
- H RESTING AREA
- I RESTING AREA
- AGRICULTURAL LAND
- SUCCULENT GARDEN
- FOOTPATH



Access Leading from Hang Hau Wing Lung Road

HYDROPONICS & RAINWATER HARVESTING

RAINWATER HARVESTING & FISH CULTIVATION

PLANTING OF VARIOUS CROPS  
(DEPENDING ON SEASONS)

- LEGEND**
- SOMEWHERE ORGANIC FARM
  - MAIN ENTRANCE
  - APPLICATION ITEM**
  - LAND EXCAVATION AREA
  - LAND FILLING AREA
  - APPLICATION SITE BOUNDARY FOR IDENTIFICATION PURPOSE ONLY



**PLANNING LIMITED**  
規劃顧問有限公司

**LAYOUT PLAN**

PROPOSED EXCAVATION AND FILLING OF LAND  
IN SUPPORT OF THE EXISTING AGRICULTURAL USE  
VARIOUS LOTS IN D.D. 238, CLEAR WATER BAY,  
SAI KUNG, NEW TERRITORIES

SCALE 1 : 1 000

**PLAN 2**

EXTRACT PLAN BASED ON  
SURVEY SHEETS No. 12-NW-17B

DATE: 26.7.2024

**Proposed Filling and Excavation of Land  
for the Permitted “Agricultural Use” in “Conservation Area”  
at Various Lots in DD238 in Clear Water Bay  
S16 Planning Application**

**(Planning Application No: A/SK-CWBN/77)**

**Appendix II**  
Revised Drainage Impact Assessment

**S16 PLANNING APPLICATION FOR THE  
PROPOSED FILLING AND EXCAVATION OF  
LAND FOR THE PERMITTED “AGRICULTURAL  
USE” IN “CONSERVATION AREA” AT VARIOUS  
LOTS IN D.D.238, CLEAR WATER BAY, SAI  
KUNG, NEW TERRITORIES**

**DRAINAGE IMPACT ASSESSMENT**

5 August 2024

Ref No: RT24120-DIA-01\_r2

**Prepared By:**



**BeeXergy Consulting Limited (BXG)**

Phone: (852) 3568-4701

Address: Unit 2001-05, Apec Plaza  
49 Hoi Yuen Road, Kwun Tong  
Kowloon, Hong Kong

Email: [info@beexergy.com](mailto:info@beexergy.com)


Project:	S16 PLANNING APPLICATION FOR THE PROPOSED FILLING AND EXCAVATION OF LAND FOR THE PERMITTED "AGRICULTURAL USE" IN "CONSERVATION AREA" AT VARIOUS LOTS IN D.D.238, CLEAR WATER BAY, SAI KUNG, NEW TERRITORIES				
	DRAINAGE IMPACT ASSESSMENT				
Report No.:	RT24120-DIA-01_r2				
<b>Revision</b>					
<b>Issue Date</b>		<b>Description</b>		<b>Author</b>	<b>Checker</b>
0		12/06/2024		Issued for Comment	TL
1		13/06/2024		Issued for Comment	YS
2		05/08/2024		Issued for Comment	YS

Prepared By:




**Theo Lai**  
Senior Consultant

Checked by



**Sui Hang Yan**  
Technical Director

Approved by:



**Henry Mak**  
Director

Disclaimer:

- This report is prepared and submitted by Beexergy Consulting Limited with all reasonable skill to the best of our knowledge, incorporating our Terms and Conditions and taking account of the resources devoted to it by agreement with the client.
- We disclaim any responsibility to the client and others in respect of any matters outside the project scope.
- This report is confidential to the client and we accept no responsibility of whatsoever nature to third parties to whom this report, or any part thereof, is made known. Any such party relies upon the report at their own risk.



## TABLE OF CONTENTS

<b>1</b>	<b>INTRODUCTION.....</b>	<b>1</b>
<b>1.1</b>	<b>PROJECT BACKGROUND .....</b>	<b>1</b>
<b>1.2</b>	<b>PROJECT LOCATION .....</b>	<b>1</b>
<b>1.3</b>	<b>DESCRIPTION OF THE PROJECT SITE .....</b>	<b>1</b>
<b>2</b>	<b>DRAINAGE IMPACT ASSESSMENT.....</b>	<b>2</b>
<b>2.1</b>	<b>SCOPE OF WORKS .....</b>	<b>2</b>
<b>2.2</b>	<b>SITE LOCATION AND TOPOGRAPHY .....</b>	<b>2</b>
<b>2.3</b>	<b>EXISTING DRAINAGE FACILITIES.....</b>	<b>2</b>
<b>2.4</b>	<b>DRAINAGE ANALYSIS.....</b>	<b>2</b>
<b>2.5</b>	<b>ASSESSMENT ASSUMPTIONS.....</b>	<b>4</b>
<b>2.6</b>	<b>ESTIMATED EXISTING AND FUTURE RUNOFF .....</b>	<b>5</b>
<b>2.7</b>	<b>DRAINAGE LAYOUT AND RESULTS .....</b>	<b>6</b>
<b>3</b>	<b>CONCLUSION .....</b>	<b>7</b>

## 1 INTRODUCTION

### 1.1 PROJECT BACKGROUND

BeeXergy Consulting Limited was commissioned by the KTA Planning Limited on behalf of Ringlet Global Limited (the Applicant) to prepare a drainage impact assessment (DIA) to support the S16 Planning Application for the Proposed Filling and Excavation of Land for the Permitted "Agricultural Use" in "Conservation Area" at Various Lots in D.D.238, Clear Water Bay, Sai Kung, New Territories (the Application).

Drawings and technical information on the existing agricultural land were provided by the Applicant and the Project Planning Consultant, KTA Planner Limited.

### 1.2 PROJECT LOCATION

The Project Site is located at Various Lots in D.D.238, Clear Water Bay, Sai Kung, New Territories, surrounded by Hang Hau Wing Lung Road. **Figure 1** shows the Project Site location and its surrounding area.



**Figure 1** Location of the Project Site (Source: GeoInfo Map)

### 1.3 DESCRIPTION OF THE PROJECT SITE

The Project Site area is approximately 6,175 m<sup>2</sup>. Minor filling for a bamboo shelter and excavation of site for two ponds is found. The master layout plan is provided in **Appendix A**.

## 2 DRAINAGE IMPACT ASSESSMENT

### 2.1 SCOPE OF WORKS

The objective of this Drainage Impact Assessment (DIA) is to assess whether the Project Site may cause adverse impacts on drainage and flooding or not with the minor filling and excavation of land. These impacts will be identified and mitigation measures will be proposed (when appropriate) in order to demonstrate that the Project Site with the minor filling and excavation of land will not cause an unacceptable increase in the risk of flooding in areas upstream of, adjacent to or downstream of the agricultural land.

### 2.2 SITE LOCATION AND TOPOGRAPHY

The Project Site is sloping downwards from west to east with topographic level from approximately +46.0 mPD to +32.0 mPD according to the topography map from Lands Department (LandsD). The Project site is currently a farmland.

### 2.3 EXISTING DRAINAGE FACILITIES

The existing drainage record from the GeoInfo Map of the LandsD and DSD are obtained for this DIA. According to the record, there are no existing manholes or public drainage pipes around the Project Site. Currently, the runoff from the Project Site is soaked away into the soil or flow through the natural valley according to topography of the surrounding area. The existing drainage record can be found in **Appendix B**.

Surface runoff inducted from the minor filling of the bamboo shelter will be diverted by a 150mm open U-channel towards the excavated ponds. Proposed internal drainage is provided in **Appendix C**.

### 2.4 DRAINAGE ANALYSIS

#### 2.4.1 ASSUMPTIONS AND METHODOLOGY

Peak instantaneous runoff without and with the minor filling and land excavation was calculated based on the Rational Method. The recommended physical parameters, including runoff coefficient (C) and storm constants for different return periods, are as per the *Stormwater Drainage Manual* issued by DSD.

The Rational Method has been adopted for hydraulic analysis and the peak runoff is given by the following expression:

$$Q_p = 0.278 C i A$$



where:

$Q_p$  = peak runoff in  $m^3/s$

$C$  = runoff coefficient

$i$  = rainfall intensity in mm/hr

$A$  = catchment area in  $km^2$

Rainfall intensity is calculated using the following expression:

$$i = \frac{a}{(t_d + b)^c}$$

where:

$i$  = rainfall intensity in mm/hr

$t_d$  = duration in minutes ( $t_d \leq 240$ )

$a, b, c$  = storm constants given in Table 3 of SDM

For a single catchment, duration ( $t_d$ ) can be assumed to be the time of concentration ( $t_c$ ) which is calculated as follows:

$$t_c = t_0 + t_r$$

where:

$t_c$  = time of concentration

$t_0$  = inlet time (time taken for flow from the most remote point to reach the most upstream point of the urban drainage system)

Generally,  $t_0$  is much smaller than  $t_r$ . As shown in Equation 2,  $t_d$  is the divisor. Therefore, larger  $t_d$  will result in smaller rain intensity ( $i$ ) as well as a smaller  $Q_p$ . For the worst-case scenario,  $t_r$  is assumed to be negligible and so:

$$t_d = t_c = t_0$$

$$t_0 = \frac{0.14465 L}{H^{0.2} A^{0.1}}$$

where:

$A$  = catchment area ( $m^2$ )

$H$  = average slope (m per 100m), measure along the line of natural flow, from the summit of

the catchment to the point under consideration

L = distance (on plan) measured on the line of natural flow between the summit and the point under consideration (m)

The capacities of the drainage pipes have been calculated using the Colebrook-White Equation, assuming full bore flow with no surcharge, as follows, incorporate 10% sedimentation in the calculation of drainage flow capacity in accordance with the *Stormwater Drainage Manual*:

$$V = -\sqrt{32gRs} \times \log\left(\frac{k_s}{14.8R} + \frac{1.25\nu}{R\sqrt{32gRs}}\right)$$

where:

V = mean velocity (m/s)

g = gravitation acceleration (m/s<sup>2</sup>)

R = hydraulic radius (m)

k<sub>s</sub> = hydraulic pipeline roughness (m)

ν = kinematic viscosity of fluid (m<sup>2</sup>/s)

S = hydraulic gradient (energy loss per unit length due to friction)

## 2.5 ASSESSMENT ASSUMPTIONS

### 2.5.1 PROJECT SITE

For the Application, minor filling for a bamboo shelter and excavation of site for two ponds is found for the Project Site. The site characteristics of without and with the minor filling and land excavation are summarized in **Table 1**.

**Table 1: Surface Characteristics and Runoff Coefficients of the Site**

Scenario of Project	Area (m <sup>2</sup> )	Surface Characteristics
Without the Minor Filling and Excavation of Site	6,175	95% unpaved + 5% paved <sup>[1]</sup>
With the Minor Filling and Excavation of Site	6,175	90% unpaved + 10% paved <sup>[1][2][3]</sup>

Remark:

[1] The percentage of paved area is assumed to be the amount of land covered by temporary structures, storage and platforms instead of paved with concrete.

[2] The excavation area is assumed as paved area in a conservative approach.

[3] The entire area of the free-standing bamboo shelter including the shaded area, plinths and barrels is assumed as paved area in a conservative approach.

## 2.5.2 CUMULATIVE RUNOFF (SURROUNDING CATCHMENTS)

According to the existing drainage record from the GeoInfo Map of the LandsD and DSD, there are no manholes and public drainage pipes around the Project site. All runoff from the Project site and the surrounding catchments shall be discharged by soak away method into the soil or flow through the natural valley according to topography of the surrounding area.

The existing drainage network collects runoff from the Project Site and that from the surrounding catchments. Runoff from surrounding catchments (Catchment A) shall be taken into account in the estimation. The Project Site catchment that contributed to the cumulative runoff have been identified as Catchment S. According to the topography of the surrounding area, Catchment A is a valley located next to the Project Site. Runoff from Catchment A will soak away into the soil or flow down along the valley from west to east. Runoff from Catchment S will also soak away into the soil or flow down the valley and eventually flow into Catchment A due to topography of the surrounding area. Therefore, Catchment A is taken into account as a surrounding catchment for the flow estimation. The areas of Catchment S and Catchment A are shown in **Appendix D**.

With reference to the *Stormwater Drainage Manual*, the runoff coefficients of paved surface and soft landscape are 0.95 and 0.25 respectively. The paving conditions and runoff coefficients of related catchments are summarized in **Table 2**.

**Table 2: Surface Characteristics and Runoff Coefficients of Surrounding Catchments**

Catchment	Area (m <sup>2</sup> )	Surface Characteristics	Runoff Coefficient for paved area	Runoff Coefficient for unpaved area
Project Site with the Minor Filling and Excavation of Site (Catchment S)	6,175	90% unpaved + 10% paved <sup>[1]</sup>	0.95	0.25
Catchment A	14,331	77% unpaved + 23% paved <sup>[1][2][3]</sup>	0.95	0.25

Remark:

[1] The percentage of paved area is assumed to be the amount of land covered by temporary structures, storage and platforms instead of paved with concrete.

[2] The excavation area is assumed as paved area in a conservative approach.

[3] The entire area of the free-standing bamboo shelter including the shaded area, plinths and barrels is assumed as paved area in a conservative approach.

## 2.6 ESTIMATED EXISTING AND FUTURE RUNOFF

Based on the assumptions described in **Section 2.4**, the runoff from the Project Site without and with the minor filling and land excavation was estimated based on a return period of 50

years.

The estimated peak runoff under a return period of 50 years generated from the Project Site Catchment S without and with the minor filling and land excavation are **0.131 m<sup>3</sup>/s** and **0.149 m<sup>3</sup>/s** respectively, as shown in **Table 3**. There is an increase of 13.9% in the estimated peak runoff under the return period of 50 years. Combining the peak runoff of the Project Site with the surrounding catchments, the estimated peak runoff generated is **0.555 m<sup>3</sup>/s** and **0.573 m<sup>3</sup>/s** respectively. There is a 3.3% increase in estimated peak runoff under the return period of 50 years. **Table 4** shows the peak runoff of the Project Site and surrounding catchments. **Moreover, the peak runoff of the minor filling for bamboo shelter within the Project Site is provided in Table 5. Detailed calculations are provided in Appendix E.**

**Table 3: Estimated Peak Runoff of the Project Site**

Return Period	Estimated Peak Runoff		
	Without the Minor Filling and Excavation of Site	With the Minor Filling and Excavation of Site	% Change
50 Years	0.131	0.149	+ 13.9%

**Table 4: Estimated Peak Runoff of the Project Site and Surrounding Catchments**

Return Period	Estimated Peak Runoff		
	Without the Minor Filling and Excavation of Site	With the Minor Filling and Excavation of Site	% Change
50 Years	0.555	0.573	+ 3.3%

**Table 5: Estimated Peak Runoff of the Minor Filling for bamboo shelter within the Project Site (internal)**

Return Period	Estimated Peak Runoff
	With the Minor Filling and Excavation of Site
50 Years	0.014

## 2.7 DRAINAGE LAYOUT AND RESULTS

Since there are no existing manholes and public drainage pipes around the Project Site, the surface runoff generated from stormwater within the Project Site will be soaked away or flow into surroundings due to topography of the surrounding area. Infiltration takes place and stormwater will be drained into the soil. Despite the fact that there will be a 13.9% increase in peak runoff with the minor filling and land excavation, the amount of increase is small and the soak away method and natural flow currently used in the Project Site and surroundings can

cater such a small increase in peak runoff. Combining the peak runoff from the Project Site and the surrounding catchment, there is only a 3.3% increase. The soak away method and natural flow used can cater such a small increase in peak runoff. The time for the surface runoff to soak into the soil is provided in **Appendix F**. The soak away time for surface runoff increased by 1.65 hours with the minor filling and excavation of Site. Surface runoff is expected to be retained in the Project Site. On the other hand, the internal drainage capacity for the return period of 50 years has been checked. As mentioned in Section 2.3, the surface runoff induced from the minor filling of bamboo shelter will be diverted to a 150mm open U-channel towards the excavated ponds. Calculation of internal drainage capacity from the minor filling can be found in **Appendix G**. The estimated peak runoff will not be higher than 27% capacity of the drainage systems, and it is anticipated that the proposed drainage system will have sufficient capacity to cater to the surface runoff from the Proposed Development. Therefore, no adverse drainage impact from the Project Site with the minor filling and land excavation is anticipated.

### 3 CONCLUSION

BeeXergy Consulting Limited was commissioned by the KTA Planning Limited on behalf of Ringlet Global Limited (the Applicant) to prepare a drainage impact assessment (DIA) to support the S16 Planning Application for the Proposed Filling and Excavation of Land for the Permitted "Agricultural Use" in "Conservation Area" at Various Lots in D.D.238, Clear Water Bay, Sai Kung, New Territories (the Application).

According to the existing drainage records from the GeoInfo Map of the LandsD and DSD, there are no existing manholes, public drainage pipes around the Project Site, runoff from the Project Site is currently soaked away or flew to the surrounding areas to deal with both surface runoff generated from stormwater. Infiltration takes place and stormwater will be drained into the soil. The increased soak away time due to the minor filling and excavation of Site is 1.65 hours. Surface runoff is expected to be retained in the Project Site.

The estimated peak runoff generated from the Project Site (Catchment S) without and with the minor filling and land excavation are  $0.131 \text{ m}^3/\text{s}$  and  $0.149 \text{ m}^3/\text{s}$  respectively. Combining the peak runoff of the Project Site with the surrounding catchments, the estimated peak runoff generated are  $0.555 \text{ m}^3/\text{s}$  and  $0.573 \text{ m}^3/\text{s}$  respectively. The percentage increases are 13.9% and 3.3% respectively. Since the amount of increase is small, the soak away method and natural flow currently used in the Project Site and surroundings can cater such a small increase in peak runoff. Meanwhile, the estimated peak runoff will not be higher than 27% capacity of the proposed internal drainage system. Therefore, no adverse drainage impact



from the Project Site with the minor filling and land excavation is anticipated.


In conclusion, no adverse drainage impact generated from the Project Site with the minor filling and land excavation is anticipated.

**APPENDIX A**

**MASTER LAYOUT PLAN OF THE PROJECT  
SITE**

SOMEWHERE ORGANIC FARM LAYOUT  
(FOR REFERENCE ONLY, NOT FOR APPROVAL)

- TEMPORARY STRUCTURE
- A SHELTER FOR WORKERS & VISITORS
- B TOILET/CHANGING ROOM/  
STORAGE OF PERSONAL ITEMS/  
EQUIPMENT/ CONSUMABLES
- C STORAGE OF COMPOST
- D STORAGE OF CONSUMABLES  
(E.G. ORGANIC FERTILIZER)
- E SHELTER FOR LARGE/HEAVY EQUIPMENT
- F CONTROL ROOM/STORAGE OF HOE  
AND MATTOCK
- G RESTING AREA
- PLATFORM
- H RESTING AREA
- I RESTING AREA
- AGRICULTURAL LAND
- SUCCULENT GARDEN
- FOOTPATH



- LEGEND**
- SOMEWHERE ORGANIC FARM
  - MAIN ENTRANCE
  - APPLICATION ITEM**
  - LAND EXCAVATION AREA
  - LAND FILLING AREA
  - APPLICATION SITE BOUNDARY FOR IDENTIFICATION PURPOSE ONLY



**LAYOUT PLAN**

PROPOSED EXCAVATION AND FILLING OF LAND  
IN SUPPORT OF THE EXISTING AGRICULTURAL USE  
VARIOUS LOTS IN D.D. 238, CLEAR WATER BAY,  
SAI KUNG, NEW TERRITORIES

SCALE 1 : 1 000

**PLAN 2**

EXTRACT PLAN BASED ON  
SURVEY SHEETS No. 12-NW-17B


DATE: 26.7.2024





## **APPENDIX B**


# **EXISTING DRAINAGE SYSTEM**





## APPENDIX C

# PROPOSED DRAINAGE CONNECTION



Legend

- Project Site
- ← Proposed 150mm u-channel
- Minor Filling for Bamboo shelter
- Excavation for ponds

	Prepared	Checked	Approved
Initial	TL	YS	HM
Date	20240801	20240801	20240801

Project Title  
 PLANNING APPLICATION FOR THE PROPOSED FILLING AND EXCAVATION OF LAND FOR THE PERMITTED "AGRICULTURAL USE" IN "CONSERVATION AREA" AT VARIOUS LOTS IN D.D.238, CLEAR WATER BAY, SAI KUNG, NEW TERRITORIES

Drawing Title  
 Proposed internal drainage connection


Drawing No.	Appendix C	Rev.	0
-------------	------------	------	---

Scale: A3



## APPENDIX D

# SURROUNDING CATCHMENTS PLAN



LEGEND:

- PROJECT SITE
- CATCHMENT TAKEN INTO ACCOUNT

	Prepared	Checked	Approved
Initial	HY	CC	YS
Date	09052023	09052023	09052023

Project Title  
 S16 PLANNING APPLICATION FOR THE PROPOSED FILLING AND EXCAVATION OF LAND FOR THE PERMITTED "AGRICULTURAL USE" IN "CONSERVATION AREA" AT VARIOUS LOTS IN D.D.238, CLEAR WATER BAY, SAI KUNG, NEW TERRITORIES

Drawing Title  
 SURROUNDING CATCHMENTS PLAN

Drawing No. DIA- 1001	Rev. 0
--------------------------	-----------

Scale:  
 A4 - 1:2000

## APPENDIX E

# RUNOFF CALCULATION

**Calculation of Runoff for Return Period of 50 Years**

Catchment ID	Unpaved Catchment Area (km <sup>2</sup> )	Paved Catchment Area (km <sup>2</sup> )	Catchment Area (A), km <sup>2</sup>	Average slope (H), m/100m	Flow path length (L), m	Inlet time (t <sub>0</sub> ), min	Duration (t <sub>d</sub> ), min	Storm Constants			Runoff intensity (i) with climate change factor(*), mm/hr	Runoff coefficient for unpaved area (C <sub>up</sub> )	Runoff coefficient for paved area (C <sub>p</sub> )	C x A	Peak runoff (Q <sub>p</sub> ) m <sup>3</sup> /s
								a	b	c					
<b>Without the Minor Filling and Excavation of Site</b>															
Catchment S	0.005891	0.000284	0.0062	11.49	121.9	4.52	4.52	505.5	3.29	0.355	270.74	0.25	0.95	0.00174	0.131
Catchment A	0.011044	0.003287	0.0143	21.64	184.8	5.55	5.55	505.5	3.29	0.355	259.07	0.25	0.95	0.00588	0.424
														<b>Total</b>	<b>0.555</b>
<b>With the Minor Filling and Excavation of Site</b>															
Catchment S	0.005546	0.000629	0.0062	11.49	121.9	4.52	4.52	505.5	3.29	0.355	270.74	0.25	0.95	0.00198	0.149
Catchment A	0.011044	0.003287	0.0143	21.64	184.8	5.55	5.55	505.5	3.29	0.355	259.07	0.25	0.95	0.00588	0.424
														<b>Total</b>	<b>0.573</b>

Remark:

\*Rainfall Increase due to climate change = 111.1% (1.111)

Rainfall increase percentage due to climate change is referenced from Table 28 in DSD Corrigendum No. 1/2022 of the Stormwater Drainage Manual (SDM). 11.1% for Mid of 21st Century is adopted as worst case scenario.

**Calculation of Runoff for Return Period of 50 Years within the Project Site (Internal)**

Catchment ID	Unpaved Catchment Area (km <sup>2</sup> )	Paved Catchment Area (km <sup>2</sup> )	Catchment Area (A), km <sup>2</sup>	Average slope (H), m/100m	Flow path length (L), m	Inlet time (t <sub>0</sub> ), min	Duration (t <sub>d</sub> ), min	Storm Constants			Runoff intensity (i) with climate change factor(*), mm/hr	Runoff coefficient for unpaved area (C <sub>up</sub> )	Runoff coefficient for paved area (C <sub>p</sub> )	C x A	Peak runoff (Q <sub>p</sub> ) m <sup>3</sup> /s
								a	b	c					
<b>With the Minor Filling and Excavation of Site</b>															
Catchment MF	0.000000	0.000155	0.0002	9.70	20.6	1.14	1.14	505.5	3.29	0.355	331.03	0.25	0.95	0.00015	0.014
														<b>Total</b>	<b>0.014</b>





**APPENDIX F**  
**SOAK AWAY TIME**

### Calculation of the soakaway time

Scenarios	Soakaway Area (m2)	Peak runoff (m3/hr)	Infiltration Rate (m/hr)[1]	Soakaway time (hr)
Without the Minor Filling and Excavation of Site	5891.45	472.08	0.01016	7.89
With the Minor Filling and Excavation of Site	5546.25	537.55	0.01016	9.54
			<b>Increase in soakaway time</b>	1.65

Remarks:

[1] Infiltration rate of plant soil is referenced from the Soil Quality Indicators issued by the USDA Natural Resources Conservation Service, '<https://www.nrcs.usda.gov/sites/default/f>  
The infiltration rate for planting soil with gravel is assumed as 0.4 in/hr.

**APPENDIX G**  
**CALCULATION OF INTERNAL DRAINAGE**  
**CAPACITY**

**Calculation of Internal Drainage Capacity for Return Period of 50 Years within the Project Site**

SECTION		Pipe	Catchment	Length	Upstream Invert Level	Downstream Invert Level	d	r	A <sub>w</sub>	P <sub>w</sub>	R	s	k <sub>s</sub>	V	Q <sub>c</sub>	Total Runoff in 50 Years	% of capacity	Remark
From	To																	
S1	S2	1 x 150mm U-channel	MF	25.5	38	36	0.15	0.075	0.018	0.471	0.04	0.078431373	0.6	2.8369	0.050	0.014	27%	OK
S2	S3	1 x 150mm U-channel	MF	17.14	36	34	0.15	0.075	0.018	0.471	0.04	0.116686114	0.6	3.4632	0.061	0.014	22%	OK

**Legend**

d = pipe diameter, m

r = pipe radius (m) = 0.5d

A<sub>w</sub> = wetted area (m<sup>2</sup>) =  $\pi r^2$  (circular) ;  $\pi r^2/2 + 2r^2$  (U-channel)

P<sub>w</sub> = wetted perimeter (m) = 2 $\pi r$  (circular) ; 2 $\pi r/2$  (U-channel)

R = Hydraulic radius (m) = A<sub>w</sub> / P<sub>w</sub>

s = Slope of the total energy line

k<sub>s</sub> = equivalent sand roughness, mm

V = Velocity of flow calculated based on Colebrook White Equation, m/s

Q<sub>c</sub> = Flow Capacity (10% sedimentation incorporated), m<sup>3</sup>/s

Q<sub>p</sub> = Estimated total peak flow from the Site during peak season, m<sup>3</sup>/s