

# Appendix C

## Geotechnical Planning Review Report





**Geotechnical Planning Review Report  
for Proposed Minor Relaxation of Building  
Height Restriction for Permitted House  
Development in “Residential (Group C) 2”  
Zone at Lot No. 214 & the Extension thereto  
in D.D. 219 and Adjoining Government Land,  
Tin Shek Road, Sai Kung, New Territories**

**November 2024**

**Contents Amendment Record**

This report has been issued and amended as follows:

Issue	Revision	Description	Date	Prepared by
1	0	First issue	November 2024	IC

## TABLE OF CONTENTS

1.	INTRODUCTION	1
2.	EXISTING INFORMATION	2
2.1	THE SITE TOPOGRAPHY AND SURROUNDING FACILITIES	2
2.2	EXISTING SLOPE/RETAINING WALL FEATURES	2
2.3	GEOLOGY	3
2.4	NATURAL TERRAIN LANDSLIDE INVENTORY	3
2.5	HISTORICAL LANDSLIDE CATCHMENT INVENTORY	3
2.6	BOULDER INVENTORY	3
2.7	GASP REPORT	3
3.	PROPOSED DEVELOPMENT	5
4.	GEOTECHNICAL CONSIDERATIONS	6
4.1	GENERAL	6
4.2	GROUND INVESTIGATION WORKS	6
4.3	EXISTING SLOPES AND RETAINING WALLS	7
4.4	FOUNDATION AND SUB-STRUCTURE WORKS	8
4.5	EXCAVATION AND LATERAL SUPPORT WORKS	9
5.	CONCLUSION	10
6.	REFERENCES	11

## FIGURES

- Figure 1.1      Location Plan of the Site
- Figure 1.2      Lot Boundary Plan of the Site
- Figure 1.3      Aerial View of the Site
- Figure 2.1      Topographic Survey Plan
- Figure 2.2      Topographic Survey Plan in Map
- Figure 3        Extract of GASP Report Map – Geological Map
- Figure 4        ENTLI – Landslide Record
- Figure 5        Area of QRA of Boulder Fall Hazards No. S7\_U
- Figure 6        Extract of GASP Report Map – Geotechnical Land Use Map
- Figure 7        Extract of GASP Report Map – Physical Constraints Map
- Figure 8        Record from Historical Landslide Catchment Inventory

## APPENDICES

- Appendix 1    Site Photographic Records
- Appendix 2    Conceptual Drawings of the Proposed Re-development
- Appendix 3    Location Plan and Slope Maintenance Responsibility Records
- Appendix 4    Report of Site-specific Ground Investigation

## **1. INTRODUCTION**

A redevelopment of a new 2 storey house plus 1 storey of basement carpark is proposed within Lot No. 214 in D.D. 219 & Extension Thereto and adjoining Government land where an existing building is located (The Site). In support of a S16 planning application for minor relaxation of Building Height restriction for permitted house development, this Geotechnical Planning Review Report (GPRR) is submitted to form part of the submission. Amax Architects and Surveyors Limited has been appointed to be the Consultant responsible for this study and submission. This report contained the desk study summarizing the available information on geological and ground condition. It is anticipated that a detailed design of the development will be submitted to Building Department for approval after the GPRR is accepted by various government departments.

The geotechnical planning review is generally carried out according to the document “GEO Advice Note for Planning Applications under Town Planning Ordinance (Cap.131)”.

## **2. EXISTING INFORMATION**

### **2.1 THE SITE TOPOGRAPHY AND SURROUNDING FACILITIES**

The Site is currently occupied by a building structures which would be demolished. The photographs of the Site are presented in [Appendix 1](#) for information.

The Site is polygonal in shape and comprised of flat grounds at 2 levels of +85.5mPD and +82.9mPD which are demarcated by existing walls within the Site. The total site area is about 681.4m<sup>2</sup>.

Unregistered walls could be observed retaining the western boundary of the Site and the adjacent Tin Shek Road respectively. A sloping ground facing East is observed adjacent to the unregistered walls within the Site. Opposite to the unregistered walls at another side of Tin Shek Road there is a registered retaining wall with No. 7SE-D/R46 which is about 5m away from the Site area. At the northern boundary, the Site is bounded by Tin Shek Road. The eastern and southern boundaries of the Site are bounded by an unregistered slope below 3m high. A registered slope with No. 7SE-D/CR150 which is about 3m from the Site area is observed bounding along the toe of the unregistered slope. The superstructure and the foundation of the existing building would be demolished and cleared out for the subject re-development. The footprint of the proposed main building is approximately 17m long and 8m wide on plan.

[Figures 1.1 and 1.2](#) and [1.3](#) show the location, lot boundary and an aerial view of the Site respectively.

[Figure 2.1](#) shows the topographic survey plan of the Site and [Figure 2.2](#), shows the topographic survey plan with the base map 7-SE-25A.

### **2.2 EXISTING SLOPE/RETAINING WALL FEATURES**

According to Slope Information System (SIS) of Geotechnical Engineering Office (GEO) as presented in [Appendix 3](#), details man-made slopes which would be affected by the re-development works are as follows:

The feature 7SE-D/CR150 is comprised of a soil/rock cut slope and a toe retaining wall. It contains 6 sub-divisions according to land status. The cut slope portion is 6m high at maximum. The average angle of the cut slope is 50 degrees while the 3.5m tall wall is with a face angle of 90 degrees. Both of the cut slope and retaining wall are around 110 long. It is facing towards south-eastern direction. The crest facility of the slope is a road/footpath with low traffic density while the toe facilities is cottage therefore the Consequence-to-life category is 1. A Stage 2 Study (S2R155/2004) report was compiled by C M Wong & Associates Limited in January 2005. No Dangerous Hillside (DH) Order to the private lot owners were required but only a Type 3 Advisory Letter were recommended to one of the owners.

The feature 7SE-D/R46 is a masonry retaining wall which is 4.2m high and 32m long with face angle of 85 degrees. It is supporting the platform surrounding the residential building of Fung Ming Villa which is at the crest area of the wall before 1977. The crest facility is a densely-used sitting out area while the toe facility is the Tin Shek Road with

very low traffic density. Therefore, the Consequence-to-life category is 2. It contains 2 sub-divisions according to land status.

The existing unregistered slope adjacent to the eastern and southern boundary of the Site is at maximum 1.8m high and 45m long with face angle of 27 degrees sloping down towards South-east. It is covered with vegetation surface. The toe found the feature 7SE-D/CR150 while the crest found the Site. No adverse deteriorating of the slope was observed during site inspection.

The existing unregistered retaining wall along the western and northern boundary has the maximum retained height of 2.6m and length of 40m approximately. Its face angle is 90 degrees facing towards East. A 1.4m high fence wall is protruding from the top of the unregistered wall. The crest facility of the wall is the Tin Shek Road and the toe facility of the wall is the Site. No adverse deteriorating of the wall was observed during site inspection.

### **2.3 GEOLOGY**

According to a geological map in Geotechnical Area Studies Program (GASP) – Report 9 “East New Territories” published by Geotechnical Control Office in 1988, the site is underlain by COARSE TUFF. No geological faults is identified at the site. The geological map is reproduced in [Figure 3](#).

### **2.4 NATURAL TERRAIN LANDSLIDE INVENTORY**

According to the Natural Terrain Landslide Inventory (NTIL) shown in Geotechnical Engineering Office’s (GEO) online system Ginfo, five relict landslides were first observed in 1963 within a circular area with radius about 200m from the Site. A graphical NTLI-Landslide Record is shown in [Figure 4](#).

### **2.5 HISTORICAL LANDSLIDE CATCHMENT INVENTORY**

According to the Historical Landslide Catchment Inventory (HLCI) shown in Geotechnical Engineering Office’s online system Ginfo, the catchment No. 7SE-D/DF9 with a plan area of 111745m<sup>2</sup> fell within a circular area with radius about 200m from the Site. Six numbers of relict ENTIL records were located within the catchment. A graphical HLCI-Landslide Record is shown in [Figure 8](#).

### **2.6 BOULDER INVENTORY**

According to the GEO’s Quantitative Risk Assessment (QRA) of Boulder Fall Hazards No. S7\_U, no boulder fall records are found in the study area. The corresponding extract of information is shown in [Figure 5](#).

### **2.7 GASP REPORT**

The GASP – Report 9 contained a layout namely Geotechnical Land Use Map (GLUM)

which indicated the Site belongs to Class II. Any development fall into this Class will possibly require average intensity of site investigation works and normal engineering cost of development. Another map namely Physical Constraints Map indicated that the Site did not have no geological constraints. The extracts of the portions of the two maps are included in *Figures 6 & 7*.

All of the above existing information are based on some observation from site inspections, the plans from the GASP report in year 1988, historical records and current slope information from GEO’s Ginfo. The engineering findings and assessment concluded and included this report forming the desk study basis of the geotechnical suitability for the redevelopment would be subject to future detailed design stage.

### **3. PROPOSED DEVELOPMENT**

The proposed re-development will include a 2-storeys house with a basement, provision of staircases, minor flattening of the sloping ground within the site to form the podium, after the demolition of the existing building.

The proposed building will contain floors from B/F to R/F. Staircases and rooms would be constructed at the G/F and 1/F floor of the building. Flushing and sprinkler water tanks would be provided at the R/F floor. Car-parking area would be provided at the B/F. The floor levels of B/F, G/F, 1/F and R/F would be +82.35mPD, +85.65mPD, +89.65mPD and +93.65mPD respectively.

With reference to the Conceptual Drawing of the Proposed Development, [Appendix 2](#) shows the footprint of the proposed re-development.



## **4. GEOTECHNICAL CONSIDERATION**

### **4.1 GENERAL**

The following geotechnical works related to the proposed re-development would be required:

- a) Ground Investigation Works
- b) Existing Slopes and Retaining Walls
- c) Foundation and Sub-structures Works
- d) Excavation and Lateral Support Works

### **4.2 GROUND INVESTIGATION WORKS**

There is no borehole information available from the Geotechnical Information Unit (GIU) of the Civil Engineering Development Department (CEDD) for the Site area.

To identify the geology of the Site and retrieve the geological information for this development, site-specific ground investigation (GI) works were carried out and completed in July/August 2024. The ground investigation works included 3 boreholes with field tests, groundwater monitoring and soil/rock sampling and 7 trial pits at the boundary of the Site to expose widely the ground conditions at shallow depth from ground surface.

The ground materials samples obtained from the site-specific GI could be used to assess a set of engineering design parameters of each type of soils and bedrock, and to determine the groundwater table based on the groundwater monitoring for the engineering design of the foundation and excavation and lateral support (ELS) works.

A ground slab of around 200mm thick covers the most of the ground surface of the Site. The boreholes logs indicate the Site is underlain by Fill, subsurface Concrete materials, Colluvium then decomposed Tuff. The bedrock head levels vary from about 12m to 16m deep from the existing ground level.

Based on the results of existing site investigation data, the geology of the Site comprises of the following major geological strata:

#### **(a) Fill**

A layer of fill was encountered below 200mm thick ground slab in most of the ground investigation stations. Thickness generally varies from 0.3m (TP3, TP6) to maximum 3m (BH3P). The fill is described as silt/sand/gravel/cobble/concrete with gravel/cobble sized concrete/rock fragments/rootlets/brick fragments.

#### **(b) Colluvium**

A layer of colluvium is encountered below the Fill layer. The thickness of the colluvium is around 6m. The colluvium is described as silt/gravel/cobble/boulder with rock fragments/rootlets.

#### **(c) Completely Decomposed Tuff (CDT)**

CDT is extremely weak, pinkish brown/brownish grey, completely decomposed Tuff (Stiff to very stiff, sandy silt with gravel sized rock fragments / Very dense, sandy gravel sized rock fragments).

#### **(d) Highly Decomposed Tuff (HDT)**

HDT is weak to moderately weak, greyish brown and grey, highly decomposed coarse as Tuff with very closely and closely spaced, rough undulating and planar, narrow, iron stained joints.

**(e) Moderately Decomposed Tuff (MDT)**

MDT is strong/moderately strong, brownish grey/grey/greyish brown, spotted with black and white, moderately/slightly decomposed coarse as Tuff with very closely/closely/medium/locally medium spaced, rough undulating and planar, narrow/very narrow/extremely narrow, iron/chlorite stained joints.

**(f) Slightly Decomposed Tuff (SDT)**

SDT is strong, brownish grey/grey/dark grey/spotted with black and white, slightly decomposed coarse ash Tuff, with closely/medium/widely/very widely spaced, rough undulating and planar, very narrow/extremely narrow, iron/chlorite stained joints.

According to the groundwater monitoring records from 12-08-2024 to 09-09-2024 as a part of the site-specific ground investigation, it could be observed that the highest groundwater level was +81.70mPD (around 3.8m below existing ground level) and the lowest groundwater level was +76.78mPD (around 8.7m below existing ground level). The design groundwater levels and any necessary pumping tests would be investigated from further groundwater monitoring results in the detailed design stage.

A copy of the ground investigation fieldworks report for this Development is enclosed in [Appendix 4](#).

### **4.3 EXISTING SLOPES AND RETAINING WALLS**

**a.) Unregistered Slope Adjacent to the Southern and Eastern Boundaries of the Site and Existing Feature 7SE-D/CR150**

Since the earth excavation works within the Site would be carried out at the crest of the unregistered slope which is at the crest of the existing feature 7SE-D/CR150, overburden loads on the descending sloping grounds of the slopes would be reduced. This would have a beneficial effect on the stability of the sloping grounds. As the loads on the sides of the pipe pile walls of the proposed ELS works would be different, unbalanced stress would result. The resultant unbalanced forces could have a detrimental effect on the sloping grounds. Besides, loads from the permanent foundation within the Site would be founded as deep as possible to ensure no additional loads exerted on the sloping grounds. The details of ensuring no adverse loadings and effects on the sloping grounds would be catered for during the detailed design stages.

**b.) Existing Retaining Wall 7SE-D/R46**

The proposed ELS works at the Site includes excavation of earth to form space for the construction of the permanent foundation works. The retaining wall 7SE-D/R46 is at 5m from the Site and thus fall into the influence zone of settlement due to the earth excavation works. The wall thus would experience ground settlements due to the pipe pile wall deflection and groundwater drawdown. The settlement would be controlled to 25mm at maximum and the effects of settlements on the retaining wall would be maintained at minimal. Regarding the loads from the permanent foundation within the Site, they would be founded as deep as possible to minimize the effects to the existing retaining wall including the sub-surface portion of the wall. The details of controlling

and minimize the effects on the wall would be catered for during the detailed design stages.

#### **4.4 FOUNDATION AND SUB-STRUCTURES WORKS**

The proposed development includes a low-rise building with main loading on its proposed foundation from the superstructure weight, pressure from the groundwater and wind, the lateral earth pressures and the other vertical loads during the service period of the building. Thus, shallow foundation system are appropriate for the facilities. In the followings, the feasibility of some common foundation systems in Hong Kong for this project are discussed.

a. Bored Piles

Bored piling is the common foundation type suitable all types of buildings. The only drawback is its high construction cost.

b. Driven H-piles

According to the Code of Practice for Foundation 2017, the minimum pile length of pile foundation is 10m. As unveiled from the site-specific ground investigation, the bedrock would be around 12m below existing ground level, the bouldery colluvium layer above the bedrock would require pre-boring before driving the H-piles into the ground and hard driving operation would be anticipated. The environmental nuisance caused by the driving action would be a major problem to the existing facilities and residential building surrounding the Site. It will render driven H-piles is not a suitable option for the project.

c. Mini-piles

Mini-piles socketed in Grade III or better rock are considered to be a feasible foundation option since vertical and raking mini-piles can be used together to provide a foundation system that can resist vertical loads and lateral loads.

A mini-pile has a lower design capacity than that of a socketed H-pile therefore mini-pile is suitable for the low-rise building in the project if the rockhead level is deep and the soil stratum is weak.

d. Rock socketed H-piles

Rock socketed H-piles embedded in Grade III or better rock are considered to be a feasible foundation option if the rockhead is not shallow. The rock socketed H-piles can be designed to resist the vertical loads and lateral loads acting on the pile foundations.

Predrilling will be carried out to confirm the rockhead level and adequacy of the founding materials. The locations of the predrill holes will be carefully planned such that all proposed socketed H-piles will be located within a distance of 5m maximum from a completed borehole or a predrill hole.

e. Shallow Foundation

Shallow foundation founding on competent soil stratum is considered to be

feasible foundation system for the development. As the proposed facilities will be short or shallow, and the site area is not congested with proposed facilities therefore the sufficient subsurface space could be allowed, wide shallow foundations can be used to achieve a feasible foundation solution to the project. Nonetheless, the competence of the soil stratum should be verified by plate load tests. If sufficient bearing capacity could not be attained, ground improvement for the incompetent soil stratum or other feasible types of foundation system should be sought.

Based on the above discussions, it is considered that shallow foundation founding on competent soil or mini-pile socketed in rock will be feasible foundation options for the proposed development.

The sub-structure works is mainly the construction of basement. The basement walls and the ground floor slabs would be constructed after the completion of the excavation and lateral support works as mentioned below and the completion foundation works for a proposed bottom-up construction sequence.

#### **4.5 EXCAVATION AND LATERAL SUPPORT WORKS**

Based on the planning submission, works of ELS to provide space for the construction of the sub-structures construction, including foundation and basement, and removal of existing sub-structure would thus be required. The loadings on the ELS system included the lateral earth pressures, groundwater pressure, surcharge and loadings from subsurface structures surrounding the Site. Proposed pipe pile walls as temporary supports against the mentioned loads are the most suitable as the ELS works of the Site. They are preferred because they are viable to be constructed to penetrate hard underground materials within the Site. The pipe pile walls would be either cantilevered with socketed into rock or braced with temporary shorings depending on the calculation in the later detailed design stage. The pipe pile walls would be installed to avoid damaging existing structures especially for those underground. Demolition of the temporary shoring should be carried out at the end of the ELS stage if shorings are required. Grout curtain would be provided to provide a cut-off effect to the groundwater seepage through the steel walls into the Site. As dewatering would be necessary within the Site, the curtain also extend the seepage path underneath the toe of the pile walls to limit excessive groundwater drawdown outside the Site and piping within the site due to the dewatering. The performance of the dewatering would be evaluated by pumping tests if required.

Pipe pile wall retaining the ground with cantilever actions without strutting system as the ELS works option was preferred to provide a non-congested excavation underground.

## **5. CONCLUSIONS**

A geotechnical planning review of the Site for proposed development is concluded as below:

The 2-storeys house with a storey basement carpark would cater shallow earth excavation works feasible at the Site, thus providing a simple scheme of embedded cantilevered wall for the proposed ELS, sub-structures and shallow foundation works.

Therefore, any adverse effects on the existing utilities, buildings and structures adjacent to the Site from all of the proposed ELS, sub-structures works and foundation works for this redevelopment would be reduced as much as possible. Conversely, all the effects of surrounding facilities on the proposed works within the Site would be taken into account in the design of works.

Condition surveys would be carried out before the start of the works and geotechnical and structural monitoring stations would be installed for quantifying the effects of the works on the monitored facilities.

The detailed site-specific ground investigation works that had been carried out and laboratory tests to be carried out will determine the geological information and groundwater of the Site and the design parameters for the proposed ELS, foundation and the sub-structures works of this re-development in detailed design stage.

Moreover, the detailed design of the ELS, foundation and sub-structures works should be submitted accordingly to the Building Authority for approval in next stage.

In conclusion, it is considered that the proposed development at the Site based on the S16 planning application is geotechnically feasible with the schemes opting for pipe piles as the main proposed ELS, sub-structures works and shallow foundation as the proposed foundation works.


**6. CONCLUSIONS**

GCO (1988) – Geotechnical Area Studies Programme, East New Territories, GASP Report IX, Geotechnical Control Office, Civil Engineering Services Department.

GEO (2024) – Natural Terrain Landslide Inventory, Slope Information System, Geotechnical Engineering Office, Civil Engineering and Development Department.

GEO (2024) – QRA of Boulder Fall Hazard, Slope Information System, Geotechnical Engineering Office, Civil Engineering and Development Department.

Appendix 1  
Site Photographic Records



**Location Plan of Photos**





**Photo V1 – General View of the Entrance to the Existing Building**



**Photo V2 – General View of Central Portion of the Existing Building**




**Photo V3 – General View of Northern Portion of the Existing Building**



Appendix 2


Conceptual Drawings of the Proposed Re-  
development





**BASEMENT FLOOR PLAN**  
SCALE = 1:250


Drawing Title  <b>BASEMENT FLOOR PLAN</b>	Project <b>PROPOSED DOMESTIC BLDG. IN LOT NO. 214 IN D.D. 219 &amp; THE EXTENSION THERETO.</b>		Figure no. <b>GP-001</b>		
	 創建坊建築測量及顧問有限公司 AMAX ARCHITECTS AND SURVEYORS LIMITED UNIT 12, 9/F, YUEN FAT INDUSTRIAL BUILDING, 25 WANG CHIU ROAD, KOWLOON BAY. TEL: 3702 1188 FAX: 3702 1181	 IP FOOK CHUEN THOMAS AUTHORIZED PERSON (ARCHITECT)		Prepared <b>AF</b>	Checked <b>JW</b>
		Date <b>NOV. 2024</b>		Scale <b>1:250</b>	






GROUND FLOOR PLAN

SCALE = 1:250


LEGEND:

 CAR RAMP/TWO-WAY DRIVEWAY (MIN. 5000 WIDTH)


Drawing Title  GROUND FLOOR PLAN	Project PROPOSED DOMESTIC BLDG. IN LOT NO. 214 IN D.D. 219 & THE EXTENSION THERETO.	Figure no. GP-002	
	 創建坊建築測量及顧問有限公司 AMAX ARCHITECTS AND SURVEYORS LIMITED UNIT 12, 9/F, YUEN FAT INDUSTRIAL BUILDING, 25 WANG CHU ROAD, KOWLOON BAY. TEL: 3702 1188 FAX: 3702 1181	Prepared AF	Checked JW
 IP FOOK CHUEN THOMAS AUTHORIZED PERSON (ARCHITECT)		Date NOV. 2024	Scale 1:250




FIRST FLOOR PLAN  
SCALE = 1:250

Drawing Title  FIRST FLOOR PLAN	Project PROPOSED DOMESTIC BLDG. IN LOT NO. 214 IN D.D. 219 & THE EXTENSION THERETO.	Figure no. GP-003	
	 創建坊建築測量及顧問有限公司 AMAX ARCHITECTS AND SURVEYORS LIMITED UNIT 12, 9/F, YUEN FAT INDUSTRIAL BUILDING, 25 WANG CHU ROAD, KOWLOON BAY. TEL: 3702 1188 FAX: 3702 1181	Prepared AF	Checked JW
		Date NOV. 2024	Scale 1:250



IP FOOK CHUEN THOMAS  
AUTHORIZED PERSON (ARCHITECT)



SECTION A-A  
SCALE = 1:250



SECTION B-B  
SCALE = 1:250

Drawing Title	Project PROPOSED DOMESTIC BLDG. IN LOT NO. 214 IN D.D. 219 & THE EXTENSION THERETO.		Figure no. GP-004	
	 創建坊建築測量及顧問有限公司 AMAX ARCHITECTS AND SURVEYORS LIMITED UNIT 12, 9/F, YUEN FAT INDUSTRIAL BUILDING, 25 WANG CHU ROAD, KOWLOON BAY. TEL: 3702 1188 FAX: 3702 1181		Prepared AF	Checked JW
DIAGRAMMATIC SECTION	 IP FOOK CHUEN THOMAS AUTHORIZED PERSON (ARCHITECT)		Date NOV. 2024	Scale 1:250

Appendix 3  
Location Plan and Slope Maintenance  
Responsibility Records



7SE-D/CR150

## BASIC INFORMATION

Location: Along Mau Tin Lane, Hing Keng Shek Village, Sai Kung  
Registration Date: 19-12-1997  
Ranking Score (NPRS): 45 (LPMit)  
Date of Formation: pre-1977  
Date of Construction/ Modification: 29-03-2006  
Data Source: Project Office  
Approximate Coordinates: Easting : 843746 Northing : 824970

## CONSEQUENCE-TO-LIFE CATEGORY

Facility at Crest: Road/footpath with low traffic density  
Distance of Facility from Crest (m): 0  
Facility at Toe: Cottage, licensed and squatter area  
Distance of Facility from Toe (m): 2  
Consequence-to-life Category: 1  
Remarks: N/A

## SLOPE PART

(1) Max. Height (m): 6 Length (m): 110 Average Angle (deg): 50

## WALL PART

(1) Max. Height (m): 3.5 Length (m): 110 Face Angle (deg): 90

## MAINTENANCE RESPONSIBILITY

(1) Sub Div.: 1 Mixed Feature Party: DD219 LOT 214 &Ext Thereto Agent: N/A Land Cat.: 5a Reason Code: 43 MR Endorsement Date: 04-01-2021  
(2) Sub Div.: 2 Mixed Feature Party: DD219 LOT 221 Agent: N/A Land Cat.: 5a Reason Code: 43 MR Endorsement Date: 04-01-2021  
(3) Sub Div.: 3 Mixed Feature Party: Lands D Agent: Lands D Land Cat.: 5b(vi) Reason Code: 62 MR Endorsement Date: 04-01-2021  
(4) Sub Div.: 4 Mixed Feature Party: STTSX1945 Agent: N/A Land Cat.: 1,5a Reason Code: 3 MR Endorsement Date: 04-01-2021  
(5) Sub Div.: 4 Mixed Feature Party: DD210 LOT 536 Agent: N/A Land Cat.: 1,5a Reason Code: 43 MR Endorsement Date: 04-01-2021  
(6) Sub Div.: 5 Mixed Feature Party: DD210 LOT 536 Agent: N/A Land Cat.: 1 Reason Code: 1 MR Endorsement Date: 04-01-2021  
(7) Sub Div.: 6 Mixed Feature Party: DD210 LOT 524 Agent: N/A Land Cat.: 1,5a Reason Code: 1,43 MR Endorsement Date: 04-01-2021

## DETAILS OF SLOPE / RETAINING WALL

Date of Inspection: 16-01-2020  
Data Source: Project Office  
Slope Part Drainage: (1) Position: On slope Size(mm): 225  
Wall Part Drainage: (1) Position: Crest Size(mm): 225

## SLOPE PART

### Slope Part (1)

Surface Protection (%): Bare: 0 Vegetated: 60 Chunam: 30 Shotcrete: 10 Other Cover: 0  
Material Description: Material type: Soil & Rock Geology: N/A  
Berm: No. of Berms: N/A Min. Berm Width (m): N/A  
Weepholes: Size (mm): 75 Spacing (m): 1.5

## WALL PART

### Wall Part (1)

Type of Wall: Wall Material: Concrete Wall Location: Wall at toe  
Berm: No. of Berms: N/A Min. Berm Width (m): N/A  
Weepholes: Size (mm): 75 Spacing (m): 1.5

## SERVICES

(1) Utilities Type: Water Main Size(mm): 80 Location: On crest Remark: N/A  
(2) Utilities Type: Water Main Size(mm): 80 Location: On slope Remark: N/A

## CHECKING STATUS INFORMATION

N/A

## BACKGROUND INFORMATION

GIU Cell Ref.: 7SE25A4  
Map Sheet Reference (1:1000): 7SE-25A  
Aerial Photos: CN10978 (1995), CN10979 (1995)  
Nearest Rainguage Station (Station Number): Pak Kong Tsui Hang Special Area Management Centre(N50)  
Data Collected On: 16-01-2020  
Date of Construction, Subsequent Modification and Demolition: Modification: Constructed Before: 1974 After: 1974  
Related Reports/Files or Documents: N/A  
Remarks: N/A  
Follow Up Actions: N/A  
DH-Order (To Be Confirmed with Buildings Department): None  
Advisory Letter (To Be Confirmed with Buildings Department): None

LPMIS: Agreement No.: CE13/2002 Report No.: S2R155/2004

## ENHANCED MAINTENANCE INFORMATION

From Maintenance Department: (Last Updated Date: 01/08/2024)

Upgraded by:

Prescriptive Design Using GEO Report No. 56: N/A

Non-prescriptive Design Including Conventional Design: N/A

Improved by:

Type 1 / Type 2 Prescriptive Measures: Yes

Type 3 Prescriptive Measures (not up to upgrading standard): Yes


Actual Completion Date: 18-07-2006

## STAGE 1 STUDY REPORT

Inspected On: 12-03-1997

Weather: Mainly Fine

District: ME



Section No: 1-1  
 Height(m): H1 : 6 , H2 : 2  
 Type of Toe Facility: Cottage, licensed and squatter area  
 Distance from Toe(m): 2  
 Type of Crest Facility: Road/footpath with low traffic density  
 Distance from Crest(m): 0  
 Consequence Category: 1  
 Engineering Judgement: P  
 Section No: 2-2  
 Type of Toe Facility: Residential  
 Distance from Toe(m): 5  
 Type of Crest Facility: Road with very low traffic  
 Distance from Crest(m): 5  
 Consequence Category: 1  
 Engineering Judgement: P  
 Sign of Seepage: Slope : Signs of seepage  
 Wall : Signs of seepage  
 Criterion A satisfied: N

Sign of Distress:	Slope : Reasonable (near crest, mid-portion) Wall : N/A
Criterion D satisfied:	N
Non-routine maintenance required:	N
Note:	N/A
Masonry wall/Masonry facing:	Y
Note:	Wall B-part squares rubble.
Consequence category (for critical section):	1
Observations:	N/A
Emergency Action Required:	N
Action By:	N/A

### ACTION TO INITIATE PREVENTIVE WORKS

Criterion A/Criterion D:	N/A
Action By:	N/A
Further Study:	Y
Action By:	Mixed

### OTHER EXTERNAL ACTION

Check / repair Services:	N
Action By:	N/A
Non-routine Maintenance:	N
Action By:	N/A

### eLPMIS

#### LPM/LPMit Details Report

LPM Study Feature No.:	7SE-D/CR 150
Location:	ALONG MAU TIN LANE, TIN KENG SHEK VILLAGE, SAI KUNG
District Council:	Sai Kung
Maintenance Responsibility (At the Time of Selection):	Mixed
Responsible Party for Maintenance of Government Portion:	Lands D
Private Lot No.:	DD219 Lot 214 and Ext, DD210 Lot536,DD210 Lot 524, STTSX2270

#### LPM/LPMit Study

Agreement No.:	CE13/2002
Study Type:	Stage 2 Study
Consultant:	C M Wong & Associates Ltd.
GEO Managing Section / Engineer:	SS / SS2
Study Status:	Study completed



Design Approach:	N/A
Option Assessment Accepted:	N/A
Study Report No.:	S2R155/2004
Programme / Actual Commencement:	07-03-2003
Programme / Actual Completion:	06-02-2005
Report Recommendation (For Stage 2 Study):	Advisory Letter
District Check Status:	Checked
Checking Certificate No.:	N/A
GEO Engineer's Remarks:	Advisory Letter for private portion. Further study for Government portion, however, the CNPCS score for the feature does not qualify for action under LPM Programme and it is returned to maintenance Department for follow-up action.

**LPM/LPMit Works**


Works Contract No.:	N/A
GEO Managing Section / Engineer:	N/A / N/A
Contractor:	N/A
Progress Status:	N/A
Reason of Study Termination / Works Deletion (If Necessary):	N/A
Forecast Commencement Date:	N/A
Forecast Completion Date:	N/A
Completion Cert. Issued:	N/A
Site Handed Over to Maintenance Department on:	N/A
Estimated Cost for Upgrading (HK\$M):	N/A
Maintenance Manual No.:	N/A
Actual Works:	N/A
No. of Tree Felled:	N/A
No. of Tree Planted (Incl. Transplant):	N/A
% Bare of Slope Surfacing:	N/A
% Vegetated of Slope Surfacing:	N/A
% Shotcrete of Slope Surfacing:	N/A
Other Hard Surface of Slope Surfacing:	N/A



PHOTO









# Slope Maintenance Responsibility Report

(7SE-D/CR150)



ESTATE MANAGEMENT SECTION  
LANDS DEPARTMENT

## List of Slope Maintenance Responsibility Area(s)

1	7SE-D/CR150		Sub-Division	1
	Location	Partly on DD210 LOT 524 and DD210 LOT 536, partly on STTSX1945 and partly on adjoining unallocated Government land		
	Responsible Lot/Party	DD219 LOT 214 &Ext Thereto	Maintenance Agent	Not Applicable
	Remarks	Not Applicable		
2	7SE-D/CR150		Sub-Division	2
	Location	Partly on DD210 LOT 524 and DD210 LOT 536, partly on STTSX1945 and partly on adjoining unallocated Government land		
	Responsible Lot/Party	DD219 LOT 221	Maintenance Agent	Not Applicable
	Remarks	Not Applicable		
3	7SE-D/CR150		Sub-Division	3
	Location	Partly on DD210 LOT 524 and DD210 LOT 536, partly on STTSX1945 and partly on adjoining unallocated Government land		
	Responsible Lot/Party	Lands Department	Maintenance Agent	Lands Department
	Remarks	For enquiries about the maintenance of this slope / sub-division of the slope, please contact the Maintenance Agent directly.		
4	7SE-D/CR150		Sub-Division	4
	Location	Partly on DD210 LOT 524 and DD210 LOT 536, partly on STTSX1945 and partly on adjoining unallocated Government land		
	Responsible Lot/Party	STTSX1945	Maintenance Agent	Not Applicable
	Remarks	Not Applicable		
5	7SE-D/CR150		Sub-Division	4
	Location	Partly on DD210 LOT 524 and DD210 LOT 536, partly on STTSX1945 and partly on adjoining unallocated Government land		
	Responsible Lot/Party	DD210 LOT 536	Maintenance Agent	Not Applicable
	Remarks	Not Applicable		
6	7SE-D/CR150		Sub-Division	5
	Location	Partly on DD210 LOT 524 and DD210 LOT 536, partly on STTSX1945 and partly on adjoining unallocated Government land		
	Responsible Lot/Party	DD210 LOT 536	Maintenance Agent	Not Applicable
	Remarks	Not Applicable		

The use of this report and plan is subject to the terms and conditions set out under the respective Disclaimers, Copyright Notice and Privacy Policy displayed on the Slope Maintenance Responsibility Information System webpage at <http://www.slope.landsd.gov.hk/smris/disclaimer>. The contents of this report and plan, including but not limited to all text, graphics, drawings, diagrams and compilation of data or other materials are protected by copyright. The users of this report and plan acknowledge that the Government of the Hong Kong Special Administrative Region is the owner of all copyright works contained in this report and plan. Any reproduction, adaptation, distribution, dissemination or making available of any copyright works contained in this report and plan to the public is strictly prohibited unless prior written authorization is obtained from the Lands Department.

<b>7</b>	<b>7SE-D/CR150</b>	<b>Sub-Division</b>	6
<b>Location</b>	Partly on DD210 LOT 524 and DD210 LOT 536, partly on STTSX1945 and partly on adjoining unallocated Government land		
<b>Responsible Lot/Party</b>	DD210 LOT 524	<b>Maintenance Agent</b>	Not Applicable
<b>Remarks</b>	Not Applicable		


- End of Report -

**Notes:**

- (i) The location plan in Annex is for identification purposes of slope(s) only.
- (ii) The slope(s) as listed in the Slope Maintenance Responsibility Report may not be shown on the location plan in Annex.

The use of this report and plan is subject to the terms and conditions set out under the respective Disclaimers, Copyright Notice and Privacy Policy displayed on the Slope Maintenance Responsibility Information System webpage at <http://www.slope.landsd.gov.hk/smr/s/disclaimer>. The contents of this report and plan, including but not limited to all text, graphics, drawings, diagrams and compilation of data or other materials are protected by copyright. The users of this report and plan acknowledge that the Government of the Hong Kong Special Administrative Region is the owner of all copyright works contained in this report and plan. Any reproduction, adaptation, distribution, dissemination or making available of any copyright works contained in this report and plan to the public is strictly prohibited unless prior written authorization is obtained from the Lands Department.

## Location Plan



## Legend

- Slope Area(s)
- Search Location
- Slope(s) Maintained by Government
- Slope(s) Maintained by Private Party/Parties
- Slope(s) Maintained by Government and Private Party/Parties



**ESTATE MANAGEMENT SECTION  
LANDS DEPARTMENT**

This Plan is **NOT TO SCALE** and intended for **IDENTIFICATION** only. All information shown on this plan **MUST** be verified by field survey.

Printed on: 29/10/2024

The use of this report and plan is subject to the terms and conditions set out under the respective Disclaimers, Copyright Notice and Privacy Policy displayed on the Slope Maintenance Responsibility Information System webpage at <http://www.slope.landsd.gov.hk/smris/disclaimer>. The contents of this report and plan, including but not limited to all text, graphics, drawings, diagrams and compilation of data or other materials are protected by copyright. The users of this report and plan acknowledge that the Government of the Hong Kong Special Administrative Region is the owner of all copyright works contained in this report and plan. Any reproduction, adaptation, distribution, dissemination or making available of any copyright works contained in this report and plan to the public is strictly prohibited unless prior written authorization is obtained from the Lands Department.

7SE-D/R46

## BASIC INFORMATION

Location: NO.55 TIN SHEK ROAD, HING KENG SHEK VILLAGE, SAI KUNG  
Registration Date: 19-12-1997  
Ranking Score (NPRS): 2 (Notional)  
Date of Formation: pre-1977  
Date of Construction/ Modification:  
Data Source: SIRST  
Approximate Coordinates: Easting : 843725 Northing : 825010

## CONSEQUENCE-TO-LIFE CATEGORY

Facility at Crest: Densely-used sitting out area  
Distance of Facility from Crest (m): 0  
Facility at Toe: Road/footpath with very low traffic density  
Distance of Facility from Toe (m): 0.5  
Consequence-to-life Category: 2  
Remarks: N/A

## SLOPE PART

N/A

## WALL PART

(1) Max. Height (m): 4.2 Length (m): 32 Face Angle (deg): 85

## MAINTENANCE RESPONSIBILITY

(1) Sub Div.: 1 Private Feature Party: DD219 Lot230 Agent: N/A Land Cat.: 1,5a,7 Reason Code: 1 MR Endorsement Date: 04-08-1998  
(2) Sub Div.: 2 Private Feature Party: STTSX1079 Agent: N/A Land Cat.: 1,5a,7 Reason Code: 49 MR Endorsement Date: 04-08-1998

## DETAILS OF SLOPE / RETAINING WALL

Date of Inspection: 12-03-1997  
Data Source: SIRST  
Slope Part Drainage: N/A  
Wall Part Drainage: (1) Position: Toe Size(mm): 225

## SLOPE PART

N/A

## WALL PART

Wall Part (1)

Type of Wall: Wall Material: Others Wall Location: Retaining wall with level platform  
Berm: No. of Berms: N/A Min. Berm Width (m): N/A  
Weepholes: Size (mm): N/A Spacing (m): N/A

### SERVICES

- (1) Utilities Type: Electricity Size(mm): 20 Location: On crest Remark: N/A
- (2) Utilities Type: Electricity Size(mm): 0 Location: On slope Remark: Size cannot be determined
- (3) Utilities Type: Sewer/Drain Size(mm): 90 Location: On slope Remark: N/A
- (4) Utilities Type: Water Main Size(mm): 30 Location: On crest Remark: N/A
- (5) Utilities Type: Water Main Size(mm): 40 Location: On slope Remark: N/A

### CHECKING STATUS INFORMATION

N/A

### BACKGROUND INFORMATION


GIU Cell Ref.: 7SE25A1  
Map Sheet Reference (1:1000): 7SE-25A  
Aerial Photos: CN10978 (1995), CN10979 (1995)  
Nearest Rainguage Station (Station Number): Pak Kong Tsui Hang Special Area Management Centre(N50)  
Data Collected On: 12-03-1997  
Date of Construction, Subsequent Modification and Demolition: Modification: Constructed Before: 1978 After: N/A  
Related Reports/Files or Documents: File/Report: LA Ref. No.: GCME5/3/8 pt6  
File/Report: LA Ref. No.: GCME5/3/8 pt6  
Remarks: N/A  
Follow Up Actions: N/A  
DH-Order (To Be Confirmed with Buildings Department): None  
Advisory Letter (To Be Confirmed with Buildings Department): None  
LPMIS: None

### ENHANCED MAINTENANCE INFORMATION

From Maintenance Department: (Last Updated Date: 01/08/2024)

## STAGE 1 STUDY REPORT

Inspected On: 12-03-1997  
 Weather: Mainly Fine  
 District: ME



Section No: 1-1  
 Height(m): H1 : 4 , H2 : 4  
 Type of Toe Facility: Road/footpath with very low traffic density  
 Distance from Toe(m): 0.5  
 Type of Crest Facility: Densely-used sitting out area  
 Distance from Crest(m): 0  
 Consequence Category: 2  
 Engineering Judgement: P  
 Section No: 2-2  
 Type of Toe Facility:  
 Distance from Toe(m):  
 Type of Crest Facility:  
 Distance from Crest(m):  
 Consequence Category: 2  
 Engineering Judgement: P  
 Sign of Seepage: Slope : N/A  
 Wall : Signs of seepage  
 Criterion A satisfied: N  
 Sign of Distress: Slope : N/A  
 Wall : Minimal(mid-portion, at toe)  
 Criterion D satisfied: N  
 Non-routine maintenance required: N  
 Note: N/A  
 Masonry wall/Masonry facing: Y  
 Note: Squared rubble and boulders.  
 Consequence category (for critical section): 2  
 Observations: N/A



Emergency Action Required: N  
Action By: N/A

### ACTION TO INITIATE PREVENTIVE WORKS

Criterion A/Criterion D: N/A  
Action By: N/A  
Further Study: Y  
Action By: Mixed

### OTHER EXTERNAL ACTION

Check / repair Services: N  
Action By: N/A  
Non-routine Maintenance: N  
Action By: N/A



**PHOTO**




7SE-D/R46

Close Area.



7SE-D/R46

General View



# Slope Maintenance Responsibility Report

(7SE-D/R46)



ESTATE MANAGEMENT SECTION  
LANDS DEPARTMENT

## List of Slope Maintenance Responsibility Area(s)

1	7SE-D/R46	Sub-Division	1	
	Location	PARTLY IN GL & PARTLY IN STTSX1079 E OF DD219 LOT230		
	Responsible Lot/Party	DD219 Lot230	Maintenance Agent	Not Applicable
	Remarks	Slope information being reviewed.		
2	7SE-D/R46	Sub-Division	2	
	Location	PARTLY IN GL & PARTLY IN STTSX1079 E OF DD219 LOT230		
	Responsible Lot/Party	STTSX1079	Maintenance Agent	Not Applicable
	Remarks	Slope information being reviewed.		

- End of Report -

### Notes:

- (i) The location plan in Annex is for identification purposes of slope(s) only.
- (ii) The slope(s) as listed in the Slope Maintenance Responsibility Report may not be shown on the location plan in Annex.

The use of this report and plan is subject to the terms and conditions set out under the respective Disclaimers, Copyright Notice and Privacy Policy displayed on the Slope Maintenance Responsibility Information System webpage at <http://www.slope.landsd.gov.hk/smris/disclaimer>. The contents of this report and plan, including but not limited to all text, graphics, drawings, diagrams and compilation of data or other materials are protected by copyright. The users of this report and plan acknowledge that the Government of the Hong Kong Special Administrative Region is the owner of all copyright works contained in this report and plan. Any reproduction, adaptation, distribution, dissemination or making available of any copyright works contained in this report and plan to the public is strictly prohibited unless prior written authorization is obtained from the Lands Department.

## Location Plan



## Legend

- Slope Area(s)
- Search Location
- Slope(s) Maintained by Government
- Slope(s) Maintained by Private Party/Parties
- Slope(s) Maintained by Government and Private Party/Parties



**ESTATE MANAGEMENT SECTION  
LANDS DEPARTMENT**

This Plan is **NOT TO SCALE** and intended for **IDENTIFICATION** only. All information shown on this plan **MUST** be verified by field survey.

Printed on: 29/10/2024

The use of this report and plan is subject to the terms and conditions set out under the respective Disclaimers, Copyright Notice and Privacy Policy displayed on the Slope Maintenance Responsibility Information System webpage at <http://www.slope.landsd.gov.hk/smris/disclaimer>. The contents of this report and plan, including but not limited to all text, graphics, drawings, diagrams and compilation of data or other materials are protected by copyright. The users of this report and plan acknowledge that the Government of the Hong Kong Special Administrative Region is the owner of all copyright works contained in this report and plan. Any reproduction, adaptation, distribution, dissemination or making available of any copyright works contained in this report and plan to the public is strictly prohibited unless prior written authorization is obtained from the Lands Department.

Appendix 4  
Report of Site-specific Ground  
Investigation

**WINFIELD ENGINEERING COMPANY**

**GROUND INVESTIGATION  
FIELD WORK REPORT**

**Drillhole Nos. : BH1(P) to BH3(P)**

**Trial Pit Nos. : TP1 To TP7**

**G.I. Works for  
Lot No. 301 in D.D. 219,  
Hing Keng Shek,  
Sai Kung, N.T.**



# ***WINFIELD ENGINEERING COMPANY***

**Ground Investigation Works for  
Lot No. 301 in D.D. 219, Hing Keng Shek,  
Sai Kung, N.T.**

## **Ground Investigation Report**

### **CONTENT**

- 1. Introduction**
- 2. General Site Description**
- 3. Geology**
- 4. Field Work**
  - 4.1 Drillholes & Trial Pits**
  - 4.2 Field Tests**
  - 4.3 Field Installation**
  - 4.4 Groundwater Monitoring**
  - 4.5 Sample Description**
- 5. Reference**

## **FIGURES**

**Figure 1 – S.I. Station Location Plan**

## **TABLES**

**Table 1 – S.I. Station Co-ordinates and Ground Levels**

## **APPENDICES**

**Appendix A – Drillhole Records**

**Appendix B - Drillhole Photographs**

**Appendix C - Trial Pit Records**

**Appendix D - Trial Pit Photographs**

**Appendix E - Installation Details of Piezometer/Standpipe  
and Response Test Record**

**Appendix F - Groundwater Monitoring Records**

**Appendix G - Checklists for Soil and Rock Description**

**Appendix H - Legend for Use on Exploratory Station  
Records**



## **1. Introduction**

Winfield Engineering Company was appointed to carry out the Ground Investigation Works for Lot No. 301 in D.D. 219, Hing Keng Shek, Sai Kung, N.T.

The scopes of works include three vertical drillholes (BH1(P) to BH3(P)) and seven trial pits (TP1 to TP7), carry out standard penetration tests and obtain rock samples and undisturbed soil samples.

The ground investigation in the designated area was generally implemented in accordance with Geoguide 2: (GCO 2017): ‘Guide to Site Investigation’, BS1377: (BSI 1990): ‘Method of test for Soils for civil engineering purposes’ and the Specification for this Contract. References to other standards and publications are given in the individual sections of the report corresponding to the relevant works conducted.

This report details a brief description of the site and the procedures adopted together with the findings of the fieldwork. The fieldwork was carried out between 23<sup>rd</sup> July 2024 and 31<sup>st</sup> August 2024.

## **2. General Site Description**

The site is located at Lot No. 301 in D.D. 219, Hing Keng Shek, Sai Kung, N.T. and at Hong Kong 1980 Grid co-ordinates E843730 and E843755, N824980 and N825020.

The position of the S.I. station is indicated on the Ground Investigation Plan in Figure 1.

Co-ordinates and levels of the S.I. station are shown in Table 1

### **3. Geology**

**Geology is with reference to the 1:20,000 scaled geological map of the area published by the Geotechnical Control Office (Sheet 8: Sai Kung Peninsula HGM20 Series: Edition 1 – 1989).**

**According to the investigation work, the geological strata encountered in this investigation can be summarized as follows:**

- **Fill**
- **Colluvium**
- **Completely decomposed TUFF**
- **Highly decomposed TUFF**
- **Moderately decomposed TUFF or better grade TUFF**

### **4. Field Work**

#### **4.1 Drillholes & Trial Pits**

**Three vertical drillholes (BH1(P) to BH3(P)) were carried out by using conventional of hydraulic feed type rotary drilling rig which equipped with diamond and tungsten carbide bits, using water flushing medium in drilling progress.**

**Rotary coring with 84mm diameter (T2-101) and 61mm (TNW) double tube core barrel were used to retrieve core of rocks.**

**The drillholes records are shown in Appendix A.**

**Photographs were taken for all rotary cored materials at core boxes of drillhole, the photographs were shown in Appendix B.**

**Seven trial pits (TP1 to TP7) were excavated by hand tools to various depths as instructed by the Engineer on site. The trial pit was backfilled with compacted excavated materials.**

**The trial pit records are shown in Appendix C.**

**Photographs were taken of materials for trial pits, the photographs are shown in Appendix D.**

#### **4.2 Field Test**

**Standard Penetration Tests (SPT) were carried out in all drillholes. The tests were carried out in accordance with BS1377 (1990: Part 9) ‘Methods of Test for Soils for Civil Engineering Proposes’, with modifications as suggested in Geoguide 2. The SPT results are recorded in the drillhole records in Appendix A.**

#### **4.3 Field Installation**

**Piezometers and standpipes were installed in all drillholes (BH1(P) to BH3(P)). Response test were carried out in standpipes and piezometers to check the functioning of them. The details of installation of piezometer/standpipe and the response test result are shown in Appendix E.**

#### **4.4 Groundwater monitoring**

**Monitoring of groundwater levels were recorded after installation. The records are shown in Appendix F.**

#### **4.5 Sample Description**

**Soil and rock descriptions are in accordance with the general principles given in Geoguide 3 – Guide to Rock and Soil Descriptions (GEO, 2017). The classification and definitions of the use on the exploratory station records are attached in Appendix G and Appendix H.**

## **5. References**

**Map HGM20( 1989), Sheet 8 , Edition I, Sai Kung Peninsula : Solid and Superficial Geology (1:20,000 Scale)**

**GEO (2000). Geological Map of Hong Kong, Series HGM 100, Hong Kong Geological Survey, Geotechnical Engineering Office, Hong Kong. (1:100,000)**

**GEO (2017). Guide to Site Investigation (Geoguide 2). Geotechnical Engineering Office, Hong Kong.**

**GEO (2017). Guide to Rock and Soil Descriptions (Geoguide 3). Geotechnical Engineering Office, Hong Kong.**

**Figure 1**

**S.I. Station Location Plan**



PROPOSED GI LAYOUT PLAN N.T.S.

**GENERAL NOTES**

- ALL LEVELS ARE IN METRES ABOVE P.D.
- PRIOR TO THE COMMENCEMENT OF ANY WORK, THE CONTRACTOR SHALL CONTACT ALL LIBERTY UNDERGRADERS FOR RECORDS REGARDING THE PRESENCE OF THEIR SERVICES WITHIN AND IN THE VICINITY OF THE SITE.
- ALL SETTING OUT COORDINATES, DIMENSIONS AND LEVELS SHALL BE VERIFIED BY THE CONTRACTOR ON SITE. ANY DISCREPANCY SHALL BE REPORTED TO THE ENGINEER. THE CONTRACTOR SHALL MAINTAIN THE STABILITY OF THE WORKS AT ALL TIMES DURING THE COURSE OF THE INVESTIGATION.
- UNLESS OTHERWISE SPECIFIED ON THE DRAWING, ALL WORKS SHALL BE CARRIED OUT IN ACCORDANCE WITH THE GENERAL SPECIFICATION OF CIVIL ENGINEERING WORKS THAT FORM PART OF THE 1000 HONG KONG SPEC.
- ON COMPLETION OF THE PROPOSED WORKS, THE CONTRACTOR SHALL AT HIS OWN EXPENSE REINSTATE ALL AREAS TO REPAIR ANY DAMAGE CAUSED HERETOBY, TO CLEAN AND TO TEND THE SITE TO THE SATISFACTION OF THE ENGINEER.

**GROUND INVESTIGATION WORKS**

- GROUND INVESTIGATION WORKS SHALL BE CARRIED OUT IN ACCORDANCE WITH GEOTECH 2 (CODE OF BEST PRACTICE) AND GEOTECH 3 (CODE TO ROCK AND SOIL DESCRIPTION) ISSUED BY GEO & PAW (14).
- INSPECTION PIT SHALL BE COMPLETED BEFORE COMMENCEMENT OF THE BORE HOLES.
- BORINGS SHALL BE DRILLED DOWN TO 10m INTO GRADE III OR BETTER WITH TOTAL CORE RECOVERED EXCEEDS 70% OF THE LENGTH.
- WATER SAMPLES FOR DISCONTAMINATED ROOF AND PAVEMENT SAMPLES FOR CLAY MATERIALS SHALL BE TAKEN IN ALL BORINGS AND AT EACH CHANGE IN STRATUM AT 2.0m INTERVALS. COMPOSITE 150mm DEPTH GROUND LEVEL WATER SAMPLES SHALL BE OBTAINED FROM UNDISTURBED SAMPLES SHOULD BE TAKEN INSTANTLY AT 2.0m INTERVALS AND AT EACH CHANGE IN STRATUM AFTER WOODS/PIEZOMETER SAMPLING.
- STANDARD PENETRATION TESTS (SPT) SHALL BE PERFORMED IN ALL BORINGS COMMENCING AT 1.5m AND THEN AT 2.0m INTERVALS AND AT EACH CHANGE IN STRATUM AFTER WOODS/PIEZOMETER SAMPLING.

**STANDPIPE/PIEZOMETERS INSTALLATION AND MONITORING**


- THE CONTRACTOR SHALL INSTALL STANDPIPE/PIEZOMETERS IN ACCORDANCE WITH GEOTECH 2. THE PIPE SHALL BE OF RIGID P.V.C. TUBING NOT LESS THAN 100mm O.D. WITH A WALL THICKNESS NOT LESS THAN 3mm.
- THE TUBE SHALL BE CONNECTED AT ITS LOWER END BY A SUITABLE P.V.C. FITTING TO A PIEZOMETER TIP. THE PIEZOMETER TIP SHALL HAVE A PERMEABILITY IN THE ORDER OF 5x10<sup>-6</sup>cm/sec. THE UPPER END OF THE TUBE SHALL BE SET IN CONCRETE AND FITTED WITH A REMOVABLE RESISTOR CAP.
- THE SAND FILTER IN THE SURROUNDINGS OF THE POROUS ELEMENT SHALL BE CLEAN SAND FALLING BETWEEN THE LIMITS OF GRAVING 10/20 AND 2/10 MESH AND THE VOLUME OF THE SAND FILTER TO BE PLACED SHALL BE RECORDED.
- IN PLACING THE SAND THE CONTRACTOR SHALL ENSURE THAT NO SAND ADHERES TO THE SIDE OF THE SLOTS OF AN UNLINED HOLE. WHERE THERE IS WATER IN A HOLE THE CONTRACTOR SHALL ALLOW SUFFICIENT TIME FOR ALL THE SAND TO SETTLE AND INDICATED TO THE UPPER SURFACE OF THE SAND SHALL BE TAKEN FROM TIME TO TIME.
- THE CONTRACTOR SHALL PROTECT THE STANDPIPE DURING THE INSTALLATION OF PIEZOMETERS.
- THE CONTRACTOR SHALL CARRY OUT GROUND WATER MONITORING DAILY FOR 14 DAYS FOLLOWING PIEZOMETERS INSTALLATION AND MEDICALLY TREATED FOR 3 HOURS. THE CONTRACTOR SHALL SUBMIT THE MONITORING RECORDS TO THE ENGINEER WITHIN ONE WORKING DAY OF MONITORING.
- HATCHCOCK BUCKETS SHALL BE INSTALLED IN ALL PIEZOMETERS IN ACCORDANCE WITH GEOTECH 2.

**METHODS OF DRILLING**

- THE ENGINEER OR ENGINEER'S REPRESENTATIVE SHALL BE INFORMED IMMEDIATELY PRIOR TO THE COMMENCEMENT OF ANY DRILLING.
- HOLES SHALL BE SUNK BY ROTARY METHODS IN FILLED AND COMMON GROUND. ROTARY CORING WILL BE USED IN ROCK OR IN COMMON GROUND WITH SPT 'N' VALUE EXCEEDING 2000. DRILLING BITS FOR ROCK SHALL BE THE HYDRAULIC FEED TYPE CAPABLE IN DRIVING A ROTARY TOOL, TESTED WITH DRAGAGES OR TORQUE CONTROL.
- THE METHOD AND EQUIPMENT TO BE USED AND THE DIMENSION OF THE HOLE SHALL BE SUCH THAT:-
  - (a) THE LEVEL SHALL BE MAINTAINED TO WITHIN 20mm OF THE METRE, WITH 140mm (5.5) O.M. CASING.
  - (b) THE HOLE SHALL NOT DEVIATE FROM THE VERTICAL BY MORE THAN 1%.
  - (c) THE LEVELS OF ALL SAMPLES IN W-SITES TESTS AND FIELD INSTALLATIONS, SHALL BE ACCURATELY DETERMINED.
  - (d) REPRESENTATIVE UNDISTURBED SAMPLES SHALL BE RECORDED FROM AN INSTANT TO THE FIELD.
  - (e) IN-SITU TESTS CAN BE CARRIED OUT AND FIELD OBSERVATIONS (I.E. PIEZOMETER) INSTALLED AT DEPTH IN THE HOLE.
- THE CASING SHALL BE ADVANCED CONCURRENTLY WITH THE REMOVAL OF MATERIAL IN SUCH A MANNER THAT LOSS OF GROUND IS AVOIDED.
- THE METHOD OF ROTARY CORING AND EQUIPMENT USED SHALL BE SUCH THAT:-
  - (a) DRILLING IN ROCK IN 'X' SIZE CAN BE CARRIED OUT TO A DEPTH OF 45 METRES.
  - (b) DOUBLE FLUTE SWELL TYPE CORE BARREL WITH CORE LIFTOR.
- EQUIPMENT TO BE ADOPTED FOR CORE RECOVERY SHALL BE SUBJECT TO THE ENGINEER OR THE ENGINEER'S REPRESENTATIVE APPROVAL AND SHALL EITHER BE:-
  - (a) DOUBLE TUBE SWELL BEARING SWELL TYPE CORE BARREL WITH CORE LIFTOR IN THE LOWER END OF THE INNERMOST TUBING, OR
  - (b) TRIPLE TUBE SWELL TYPE CORE BARREL WITH CORE LIFTOR.
- STANDARD CORING SHALL BE LIMITED TO A MAXIMUM LENGTH OF 1.5m WITHIN 1500mm DIA OF THE HOLE AT INSTALLATION STAGE. THE LENGTH OF THE FOLLOWING HOLES SHALL BE REDUCED BY 50% UNLESS OTHERWISE SPECIFIED BY THE ENGINEER OR THE ENGINEER'S REPRESENTATIVE.
  - (a) CONTRACTOR'S NAME, CONTACT NUMBER, SITE NAME AND HOLE NUMBER.
  - (b) RIG TYPE, RIG NUMBER, OPERATOR, HOURS WORKED AND METHOD OF BORING.
  - (c) DATE OF OPERATION AND WEATHER CONDITIONS.
  - (d) GROUND LEVEL OF HOLE, AND REDUCED LEVEL OF SAMPLES, IN-SITU TEST AND FIELD INSTALLATIONS.
  - (e) DETAILS OF ALL SAMPLES, W-SITE TESTS AND FIELD INSTALLATIONS.
  - (f) DETAILS OF CASING AND LENGTH OF CASING.
  - (g) WATER LEVELS AT START OF WORK, END OF WORK AND RECOMMENDATION.
  - (h) FIELD DESCRIPTION OF EACH STRATUM ENCOUNTERED INCLUDING COLOUR, COSSING USING MANGSELL SOIL COLOUR CHART.
  - (i) WATER RETURN.
  - (j) DETAILS OF ANY GRAY.
  - (k) COORDINATES OF HOLE POSITION RELATED TO THE HONG KONG METRIC GRID.
  - (l) REDUCED LEVEL AT BOREHOLE LOCATION.
  - (m) INCLINATION AND OBSERVATION OF HOLE.
  - (n) S.G.S., FRACTURE MODEL, CORE RECOVERY AND GRADE. THE LOGS AND CLASSIFICATION SHALL BE IN ACCORDANCE WITH GEOTECH 3, 'CODE TO ROCK AND SOIL DESCRIPTION'.


**DRILLING RECORDS**

- THE INFORMATION REQUIRED ON THE DAILY RECORDS AND FINAL LOGS IS LISTED BELOW:
- CONTRACTOR'S NAME, CONTACT NUMBER, SITE NAME AND HOLE NUMBER.
  - RIG TYPE, RIG NUMBER, OPERATOR, HOURS WORKED AND METHOD OF BORING.
  - DATE OF OPERATION AND WEATHER CONDITIONS.
  - GROUND LEVEL OF HOLE, AND REDUCED LEVEL OF SAMPLES, IN-SITU TEST AND FIELD INSTALLATIONS.
  - DETAILS OF ALL SAMPLES, W-SITE TESTS AND FIELD INSTALLATIONS.
  - DETAILS OF CASING AND LENGTH OF CASING.
  - WATER LEVELS AT START OF WORK, END OF WORK AND RECOMMENDATION.
  - FIELD DESCRIPTION OF EACH STRATUM ENCOUNTERED INCLUDING COLOUR, COSSING USING MANGSELL SOIL COLOUR CHART.
  - WATER RETURN.
  - DETAILS OF ANY GRAY.
  - COORDINATES OF HOLE POSITION RELATED TO THE HONG KONG METRIC GRID.
  - REDUCED LEVEL AT BOREHOLE LOCATION.
  - INCLINATION AND OBSERVATION OF HOLE.
  - S.G.S., FRACTURE MODEL, CORE RECOVERY AND GRADE. THE LOGS AND CLASSIFICATION SHALL BE IN ACCORDANCE WITH GEOTECH 3, 'CODE TO ROCK AND SOIL DESCRIPTION'.



DETAILS OF STANDPIPE/PIEZOMETER

NOTES: HATCHCOCK BUCKET SHALL BE INSTALLED AT 500mm INTERVAL THROUGHOUT THE WHOLE DEPTH OF PIEZOMETERS.



TYPICAL DETAIL FOR TEMPORARY SUPPORT FOR EXCAVATION PIT

**LEGEND:**

- BH(P) PROPOSED BOREHOLES WITH PIEZOMETER
- TP TRIAL PITS

**BACKFILLING OF BOREHOLES**

BOREHOLES WITH NO INSTRUMENTATION SHALL BE FILLED WITH CEMENT GROUT. THE CASING SHALL BE GRADUALLY WITHDRAWN AND THE GROUT SHALL BE KEPT ABOVE THE BOTTOM OF THE CASING DURING WITHDRAWAL. ANY SUBSIDENCE OR DEPRESSION OF THE SURFACE SHALL BE FILLED AND COMPACTED BY THE CONTRACTOR TO THE SATISFACTION OF THE ENGINEER. THE HOLE POSITION SHALL BE CLEARLY MARKED WITH A METAL MARKER OR FLAG OR A CONCRETE BLOCK WITH THE HOLE NUMBER INDICATED IN RED PAINT.

**LABORATORY TESTING**

- SAMPLES FOR LABORATORY TESTS SHALL BE TRANSPORTED BY THE CONTRACTOR TO A HONGKONG ACCREDITED TESTING LABORATORY FOR TESTING.
- A PROGRAM OF LABORATORY TESTS SHALL BE CARRIED OUT USING CURRENT STANDARDS ON SELECTED UNDISTURBED SAMPLES INCLUDING:
  - (a) CLASSIFICATION TEST
  - (b) CONSOLIDATED UNDRAINED TRIAXIAL COMPRESSION TEST WITH PORE PRESSURE MEASUREMENT / UNCONSOLIDATED UNDRAINED TEST
  - (c) SOIL DENSITY
  - (d) PARTICLE SIZE DISTRIBUTION - SIEVE AND HYDROMETRIC
  - (e) WATER CONTENT BY OVEN DRYING AT 105°C ± 5°C
  - (f) ATTERBERG LIMITS
  - (g) SHEAR STRENGTH
  - (h) COMBUSTION TEST
  - (i) PROCTOR TEST

**METHODS OF TRIAL PITS**


- TRIAL PITS SHALL BE 1.5m x 1.5m x 3m ON PLAN AND EXCAVATED VERTICALLY BY HAND OR MECHANICAL METHODS TO THE EXISTING FLOORING OR FILL CAP OR ADJACENT STRUCTURES OR AS SPECIFIED BY THE ENGINEER. THE FOUNDATION LEVEL AND THE SHAPE OF THE FOUNDINGS OR FILL CAP SHALL BE DEPICTED IN THE TRIAL PIT RECORDS. TRIAL PITS WHEN DEEPER THAN 1.2M AT THEIR DEEPEST POINT OR WHEN SUSCEPTIBLE TO SPALLING OF THE SURROUNDING SHALL BE ARDUOUSLY SHELVED AT ALL TIMES TO COMPLY WITH THE CONSTRUCTION SITES (SAFETY) REGULATIONS USING A METHOD APPROVED BY THE ENGINEER, AND IN SUCH A MANNER THAT THE STRATA EXPOSED SHALL BE CLEARLY VISIBLE THROUGHOUT THE HEIGHT OF EACH FACE. HANDWORKS SHALL NOT BE USED FOR SHAVING PARALLELISM.
- MATERIALS EXCAVATED FROM TRIAL PITS SHALL BE CAREFULLY STOCKPILED AWAY FROM THE EXCAVATIONS. ALL EXCAVATED MATERIALS SHALL BE PROTECTED FROM WEATHER.
- AN UNDISTURBED SOIL SAMPLES EXCEPT FILL SHALL BE TAKEN AT THE BOTTOM OF ALL TRIAL PITS, AT EACH CHANGE IN STRATUM AND AT 1M INTERVALS IN THE SAME STRATUM.
- GROUND WATER LEVEL SHALL BE RECORDED AT THE BEGINNING OF EACH SHIFT.
- LARGE DISCOURSED SAMPLE AT DEPTH OF IN-SITU DENSITY TESTS FOR FILL SHOULD BE OBTAINED AS INSTRUCTED BY ENGINEER ON SITE.

**TRIAL PITS RECORDS**

- THE INFORMATION REQUIRED ON THE DAILY RECORDS AND FINAL TRIAL PIT LOGS IS LISTED BELOW:
- SITE
  - CONTACT NAME AND NUMBER
  - NUMBER OF TRIAL PIT
  - LEVELS OF THE DATUM MARK RELATIVE TO PRINCIPAL DATUM
  - DATES DURING WHICH TRIAL PIT WAS FORMED
  - TOTALS DEPTH OF TRIAL PIT BELOW DATUM MARK
  - EXCAVATION PLAN OF TRIAL PIT AND OBSERVATION
  - DETAILS OF SHEDDING
  - WATER LEVELS WITH DETAILS OF FLUCTUATION AND LOCATION OF SHEDDING, ALL WITH RESPECT TO THE DATUM MARK
  - DEPTH BELOW DATUM MARK OF ALL SAMPLES AND THE POSITION OF EACH IN PLAN
  - SKETCH AND DETAILED DESCRIPTION OF MATERIAL TYPE DISCOUNTED IN EACH FACE
  - STABILITY CONDITIONS DURING EXCAVATION.

**BACKFILLING OF TRIAL PITS**

UPON THE ENGINEER'S INSTRUCTION, THE CONTRACTOR SHALL BACKFILL THE TRIAL PITS WITH FINE MEDIUM AND COMPACT IN LAYERS NOT EXCEEDING 300mm THICK TO THE DEGREE OF COMPACTOR NOT LESS THAN 90%. FILLING MATERIAL SHALL BE FREE FROM TOP-SOIL, SLURRY, PERVIOUS MATERIALS, ORGANIC MATTER AND OTHER DISTURBED SUBSTANCES. FILLING MATERIAL SHALL CONTAIN NO MATERIAL EXCEEDING 150mm IN SIZE. IT MAY CONTAIN UP TO 20% ROCK DISTRIBUTED EVENLY THROUGHOUT THE WHOLE MASS OF THE MATERIAL.



BLOCK PLAN 1:1000

HOLES NO.	NORTHING	EASTING
TP1	TO BE CONFIRMED	TO BE CONFIRMED
TP2	TO BE CONFIRMED	TO BE CONFIRMED
TP3	TO BE CONFIRMED	TO BE CONFIRMED
TP4	TO BE CONFIRMED	TO BE CONFIRMED
TP5	TO BE CONFIRMED	TO BE CONFIRMED
TP6	TO BE CONFIRMED	TO BE CONFIRMED
TP7	TO BE CONFIRMED	TO BE CONFIRMED
BH1	TO BE CONFIRMED	TO BE CONFIRMED
BH2	TO BE CONFIRMED	TO BE CONFIRMED

COORDINATE FOR REFERENCE ONLY

B.3 REF NO:  
E.S.D. SET NO:  
NOTE:

01/07/2024	FIRST SUBMISSION	C-11	A/N
DATE	REV	REMARK	BY

CLIENT

ARCHITECT

SIGNATURE

PROJECT  
BLDG. IN LOT NO. 301  
IN D.D. 219

TT-1  
SITE INVESTIGATION PLAN

PROJECT NO	DWG NO	REV NO
-	202407-GI-01	-
DRAWN	CHECK	SCALE
CHU	IAN	AS SHOWN
		DATE
		05/07/2024

**Table 1**

**S.I. Station Co-ordinates & Ground Level**

# Winfield Engineering Company

## SURVEY RECORD

Project : Lot No. 301 in D.D. 219, Hing Keng Shek, Sai Kung, N.T.

S.I. Station	Co-ordinates		Ground Level (mPD)	Remarks
	Easting	Northing		
BH1(P)	843743.26	825008.17	+85.58	
BH2(P)	843738.36	824997.16	+85.67	
BH3(P)	843748.26	825000.15	+85.72	
TP1	843738.47	825013.27	+85.42	
TP2	843750.35	825005.08	+85.71	
TP3	843735.19	824997.06	+85.68	
TP4	843746.37	824996.28	+85.74	
TP5	843741.22	824983.53	+85.68	
TP6	843738.05	824990.11	+85.70	
TP7	843738.35	825010.07	+85.52	



## **Appendix A**

### **Drillhole Records**

# WINFIELD ENGINEERING COMPANY

## DRILLHOLE RECORD

CONTRACT NO. : \_\_\_\_\_  
 HOLE NO. : BH1(P)  
 SHEET : 1 OF 3  
 DATE : 29/7/24 TO 10/8/24

PROJECT : Lot No. 301 in D.D. 219, Hing Keng Shek, Sai Kung, N.T.

METHOD : ROTARY

CO-ORDINATES

ROCK COREBIT : T2-101/TNW

MACHINE & NO. : TOHO

E 843743.26

HOLE DIA. : HX/NX

N 825008.17

FLUSHING MEDIUM : WATER

ORIENTATION : VERTICAL

GROUND LEVEL : +85.58 mPD.

Drilling Progress	Casing Depth/Size	Water Level/Time	Water Recovery %	Total Core Recovery %	Solid Core Recovery %	R. Q. D.	Fracture Index	Tests	Samples			Reduced Level	Depth (m)	Legend	Grade	Zone	Description
									No.	Type	Depth						
29/7	Hx											+85.58	0.00				Light greyish brown, slightly clayey silty fine to coarse SAND with gravel sized rock fragments. (FILL)
				38					A ● 0.50			+84.58	1.00				Brownish grey, angular COBBLE sized rock fragments. (COLLUVIUM)
									B ● 1.00			+83.93	1.65				No recovery (inferred as COLLUVIUM)
									T2-101			+83.73	1.85				Brownish grey, angular BOULDER sized rock fragments. (COOLUVIUM)
				69					1.65			+83.15	2.43				
									1.85				2.43				
				0					T2-101			+82.73	2.85				Brownish grey, sandy GRAVEL and COBBLE sized rock fragments. (COLLUVIUM)
									2.43				2.85				Greyish brown and grey, angular COBBLE sized rock fragments. (COLLUVIUM)
									2.50								
				49					2.85								
									T2-101			+81.40	4.18				Brownish grey, sandy GRAVEL and COBBLE sized rock fragments. (COLLUVIUM)
									4.18				4.18				
				0					4.50			+80.68	4.90				Grey, angular BOULDER and COBBLE sized rock fragments. (COLLUVIUM)
									4.80				4.90				
				92					4.90			+80.08	5.50				Very dense, sandy GRAVEL and COBBLE sized rock fragments. (COLLUVIUM)
									TNW				5.50				
									5.50								
									6.00								
									6.08			+78.88	6.70		IV		Moderately weak, greyish brown, highly decomposed coarse ash TUFF with very closely and closely spaced, rough undulating and planar, narrow, iron stained joints.
				90	70	0	>20		6.70				6.70				
									TNW			+78.38	7.20		III		Strong, brownish grey and grey, slightly decomposed coarse ash TUFF with closely and medium spaced, rough undulating and planar, very narrow to extremely narrow, iron stained joints, dipping at 0°-10°, 20°-30°, 40°-50° & subvertical.
				95	89	89			7.20								
									TNW								
									8.20								
				97	94	83	4.8		8.20								
									TNW			+75.88	9.70				From 9.70m to 9.92m, moderately decomposed TUFF.
									9.70			+75.66	9.92				
				95	89	80	>20		9.70				9.92				
							5.9		TNW								
									9.92								

- Small disturbed sample
- ▲ Water sample
- ⬆ Large disturbed sample
- ▼ Water table
- SPT liner sample
- ↓ Standard penetration test
- U76 undisturbed sample
- Permeability test
- U100 undisturbed sample
- ▲ Piezometer tip
- ▨ Mazier sample
- ⊠ Standpipe
- P/S Piston sample

LOGGED Poon Leung  
 DATE 30/8/24  
 CHECKED W.P. Chun  
 DATE 31/8/24

REMARKS  
 1. Inspection pit was excavated to 1.00m.  
 2. Standpipe was installed at 8.00m.  
 3. Piezometer was installed at 11.20m.

# WINFIELD ENGINEERING COMPANY

## DRILLHOLE RECORD

CONTRACT NO. : \_\_\_\_\_  
 HOLE NO. : BH1(P)  
 SHEET : 2 OF 3  
 DATE : 29/7/24 TO 10/8/24

PROJECT : Lot No. 301 in D.D. 219, Hing Keng Shek, Sai Kung, N.T.

METHOD : ROTARY

CO-ORDINATES

ROCK COREBIT : T2-101/TNW

MACHINE & NO. : TOHO

E 843743.26

HOLE DIA. : HX/NX

N 825008.17

FLUSHING MEDIUM : WATER

ORIENTATION : VERTICAL

GROUND LEVEL : +85.58 mPD.

Drilling Progress	Casing Depth/Size	Water Level/Time	Water Recovery %	Total Core Recovery %	Solid Core Recovery %	R. Q. D.	Fracture Index	Tests	Samples			Depth (m)	Legend	Grade	Zone	Description
									No.	Type	Depth					
				95	89	80	5.9		TNW	+74.98	10.60	✓	II		As sheet 1 of 3	
							>20			+74.73	10.85	✓	III		From 10.60m to 10.85m, moderately decomposed TUFF.	
				82	76	0	9.1	▲	✗ 11.20	+74.18	11.40	✓	II		From 11.40m to 11.70m, highly decomposed TUFF.	
							>20		TNW	+73.88	11.70	✓	III			
				98	95	81	6.7		TNW			✓	II			
							>20		✗ 12.60	+72.98	12.60	✓				
				98	88	39	11.8		TNW			✓	III		Moderately strong, greyish brown and grey, moderately decomposed coarse ash TUFF with closely spaced, rough undulating and planar, very narrow to extremely narrow, iron stained joints, dipping at 0°-10°, 20°-30°, 40°-50°, 60°-70° & subvertical.	
									✗ 13.40			✓				
				100	97	59	6.5		TNW			✓				
									✗ 14.85			✓				
				96	91	63			TNW			✓				
									✗ 15.88			✓				
				100	95	69	>20		TNW			✓				
									✗ 16.70	+68.98	16.60	✓				
				97	94	85	12.5		TNW			✓	II		Strong, grey to dark grey, slightly decomposed coarse ash TUFF with closely and medium spaced, rough undulating and planar, very narrow to extremely narrow, iron and chlorite stained joints, dipping at 0°-10°, 30°-40° & 50°-60°.	
									✗ 17.70			✓				
				92	88	88	9.7		TNW			✓				
							>20		✗ 19.10	+66.48	19.10	✓				
				90	77	64	6.2		TNW	+66.18	19.40	✓	III		From 19.10m to 19.40m, moderately decomposed TUFF.	
												✓	II			

- Small disturbed sample    ▲ Water sample
- ⬆ Large disturbed sample    ▼ Water table
- SPT liner sample            ↓ Standard penetration test
- U76 undisturbed sample    ● Permeability test
- U100 undisturbed sample   ▲ Piezometer tip
- ⊠ Mazier sample                ⏏ Standpipe
- P/S Piston sample

LOGGED Poon Leung  
 DATE 30/8/24  
 CHECKED W.P. Chun  
 DATE 31/8/24

REMARKS

# WINFIELD ENGINEERING COMPANY

## DRILLHOLE RECORD

CONTRACT NO. : \_\_\_\_\_  
 HOLE NO. : BH1(P)  
 SHEET : 3 OF 3  
 DATE : 29/7/24 TO 10/8/24

PROJECT : Lot No. 301 in D.D. 219, Hing Keng Shek, Sai Kung, N.T.

METHOD : ROTARY

CO-ORDINATES

ROCK COREBIT : T2-101/TNW

MACHINE & NO. : TOHO

E 843743.26

HOLE DIA. : HX/NX

N 825008.17

FLUSHING MEDIUM : WATER

ORIENTATION : VERTICAL

GROUND LEVEL : +85.58 mPD.

Drilling Progress	Casing Depth/Size	Water Level/Time	Water Recovery %	Total Core Recovery %	Solid Core Recovery %	R. Q. D.	Fracture Index	Tests	Samples		Reduced Level	Depth (m)	Legend	Grade	Zone	Description
									No.	Type Depth						
10/8				90	77	64	6.2			TNW		20	v v v	II		As sheet 2 of 3
									20.50	+65.08	20.50	v v v	III		Moderately strong, brownish grey and grey, moderately decomposed coarse ash TUFF with very closely and closely spaced, rough undulating and planar, narrow to very narrow, iron stained joints, dipping at 0°-10°, 30°-40°, 50°-60° & 70°-80°.	
				90	62	26	>20			TNW		21.70	v v v			
						12.5						21.70	v v v			End of hole at 21.70m.

- Small disturbed sample    ▲ Water sample
- ⬆ Large disturbed sample    ▼ Water table
- SPT liner sample          ↓ Standard penetration test
- U76 undisturbed sample    ● Permeability test
- U100 undisturbed sample   ▲ Piezometer tip
- ☒ Mazier sample              ⏏ Standpipe
- P/S Piston sample

LOGGED Poon Leung  
 DATE 30/8/24  
 CHECKED W.P. Chun  
 DATE 31/8/24

REMARKS

# WINFIELD ENGINEERING COMPANY

## DRILLHOLE RECORD

CONTRACT NO. : \_\_\_\_\_  
 HOLE NO. : BH2(P)  
 SHEET : 1 OF 3  
 DATE : 23/8/24 TO 31/8/24

PROJECT : Lot No. 301 in D.D. 219, Hing Keng Shek, Sai Kung, N.T.

METHOD : ROTARY

CO-ORDINATES

ROCK COREBIT : T2-101/TNW

MACHINE & NO. : TOHO

E 843738.36

HOLE DIA. : HX/NX

N 824997.16

FLUSHING MEDIUM : WATER

ORIENTATION : VERTICAL

GROUND LEVEL : +85.67 mPD.

Drilling Progress	Casing Depth/Size	Water Level/Time	Water Recovery %	Total Core Recovery %	Solid Core Recovery %	R. Q. D.	Fracture Index	Tests	Samples			Reduced Level	Depth (m)	Legend	Grade	Zone	Description
									No.	Type	Depth						
23/8	Hx											+85.67	0.00				Light greyish brown, silty fine to coarse SAND with gravel sized rock fragments. (FILL)
				56					A ● 0.50			+84.82	0.85				Grey and greyish brown, angular and subangular COBBLE sized rock fragments. (COLLUVIUM)
									B ● 0.85								
				57					T2-101								Brownish grey, COBBLE sized rock fragments. (COLLUVIUM)
									1.30								
				45					TNW								Grey and greyish brown, angular and subangular COBBLE sized rock fragments. (COLLUVIUM)
									2.80								
				0					TNW								Extremely weak, pinkish brown, completely decomposed TUFF. (Stiff to very stiff, sandy SILT with gravel sized rock fragments.)
									3.90			+81.77	3.90				
									4.10								Very dense, brownish grey, sandy GRAVEL sized rock fragments. (COLLUVIUM)
									4.30			+81.17	4.50				
												+80.85	4.82				Extremely weak, pinkish brown, completely decomposed TUFF. (Stiff to very stiff, sandy SILT with gravel sized rock fragments.)
									5.00								
									5.03								Extremely weak, pinkish brown, completely decomposed TUFF. (Stiff to very stiff, sandy SILT with gravel sized rock fragments.)
									6.00			+79.67	6.00		V		
				85					6.00								Extremely weak, pinkish brown, completely decomposed TUFF. (Stiff to very stiff, sandy SILT with gravel sized rock fragments.)
									7.10								
									7.10								Extremely weak, pinkish brown, completely decomposed TUFF. (Stiff to very stiff, sandy SILT with gravel sized rock fragments.)
									7.55								
									8.00								Extremely weak, pinkish brown, completely decomposed TUFF. (Stiff to very stiff, sandy SILT with gravel sized rock fragments.)
									9.10								
									9.10								Extremely weak, pinkish brown, completely decomposed TUFF. (Stiff to very stiff, sandy SILT with gravel sized rock fragments.)
									9.55								
									10								

- Small disturbed sample
- ▲ Water sample
- ⬆ Large disturbed sample
- ▼ Water table
- SPT liner sample
- ↓ Standard penetration test
- U76 undisturbed sample
- Permeability test
- U100 undisturbed sample
- ▲ Piezometer tip
- ▨ Mazier sample
- ⊕ Standpipe
- P/S Piston sample

LOGGED Poon Leung  
 DATE 30/8/24  
 CHECKED W.P. Chun  
 DATE 31/8/24

REMARKS

1. Inspection pit was excavated to 0.85m.
2. Standpipe was installed at 10.00m.
3. Piezometer was installed at 15.40m.

# WINFIELD ENGINEERING COMPANY

## DRILLHOLE RECORD

CONTRACT NO. : \_\_\_\_\_  
 HOLE NO. : BH2(P)  
 SHEET : 2 OF 3  
 DATE : 23/8/24 TO 31/8/24

PROJECT : Lot No. 301 in D.D. 219, Hing Keng Shek, Sai Kung, N.T.

METHOD : ROTARY

CO-ORDINATES

ROCK COREBIT : T2-101/TNW

MACHINE & NO. : TOHO

E 843738.36

HOLE DIA. : HX/NX

N 824997.16

FLUSHING MEDIUM : WATER

ORIENTATION : VERTICAL

GROUND LEVEL : +85.67 mPD.

Drilling Progress	Casing Depth/Size	Water Level/Time	Water Recovery %	Total Core Recovery %	Solid Core Recovery %	R. Q. D.	Fracture Index	Tests	Samples			Reduced Level	Depth (m)	Legend	Grade	Zone	Description
									No.	Type	Depth						
	Hx										10.00	10		V		As sheet 1 of 3	
	11.30 Hx			85				50/0.06 200/0.06	11	U76	11.10	+74.57	11.10				
									12	U100	11.22	+74.37	11.30		V	Extremely weak, brownish grey, completely decomposed TUFF. (Very dense, sandy GRAVEL sized rock fragments.)	
				62	45	0	NI		TNW					IV	Moderately weak, greyish brown and grey, highly decomposed coarse ash TUFF with very closely spaced, rough undulating and planar, narrow, iron stained joints.		
				80	76	69	4.6		TNW		12.80	+72.57	13.10		II	Strong, grey, spotted with black and white, slightly decomposed coarse ash TUFF with closely and medium spaced, rough undulating and planar, very narrow to extremely narrow, iron stained joints, dipping at 0°-10° & 20°-30°.	
				71	60	42	NI		TNW		14.00	+71.27	14.40		IV	Moderately weak, greyish brown and grey, highly decomposed coarse ash TUFF with very closely spaced, rough undulating and planar, narrow, iron stained joints.	
				65	43	19			TNW		15.20	+71.27	15.75				
				95	89	85			TNW		15.90				III	Moderately strong, grey, spotted with black and white, slightly decomposed coarse ash TUFF with closely and medium spaced, rough undulating and planar, very narrow to extremely narrow, iron and chlorite stained joints, dipping at 0°-10°, 20°-30° & 40°-50°.	
				100	87	60	9.0		TNW		16.70						
				95	89	60			TNW		17.45						
				98	94	88	4.8		TNW		18.00	+67.37	18.30		II	From 18.30m to 18.72m, slightly decomposed TUFF.	
				98	87	44	16.1		TNW		18.78	+66.95	18.72		III		
				100	90	52	8.6		TNW		19.65						

- Small disturbed sample    ▲ Water sample
- ⬆ Large disturbed sample    ▼ Water table
- SPT liner sample          ↓ Standard penetration test
- U76 undisturbed sample    ● Permeability test
- U100 undisturbed sample    ▲ Piezometer tip
- ▨ Mazier sample              ⏏ Standpipe
- P/S Piston sample

LOGGED Poon Leung  
 DATE 30/8/24  
 CHECKED W.P. Chun  
 DATE 31/8/24

REMARKS

# WINFIELD ENGINEERING COMPANY

## DRILLHOLE RECORD

CONTRACT NO. : \_\_\_\_\_  
 HOLE NO. : BH2(P)  
 SHEET : 3 OF 3  
 DATE : 23/8/24 TO 31/8/24

PROJECT : Lot No. 301 in D.D. 219, Hing Keng Shek, Sai Kung, N.T.

METHOD : ROTARY

CO-ORDINATES

ROCK COREBIT : T2-101/TNW

MACHINE & NO. : TOHO

E 843738.36

HOLE DIA. : HX/NX

N 824997.16

FLUSHING MEDIUM : WATER

ORIENTATION : VERTICAL

GROUND LEVEL : +85.67 mPD.

Drilling Progress	Casing Depth/Size	Water Level/Time	Water Recovery %	Total Core Recovery %	Solid Core Recovery %	R. Q. D.	Fracture Index	Tests	Samples			Reduced Level	Depth (m)	Legend	Grade	Zone	Description
									No.	Type	Depth						
31/8				100	90	52	8.6			TNW	20.10	20	▼	III		As sheet 2 of 3	
				94	84	52	>20			TNW	+64.92	20.75	▼	II		From 20.75m to 21.32m, slightly decomposed TUFF.	
							7.0			✕	21.10	+64.35	21.32	▼	III		
				95	86	44	>20			TNW				▼			
							12.8			✕	22.45	+63.19	22.48	▼	II		From 22.48m to 22.88m, slightly decomposed TUFF.
				95	80	80	4.0			TNW	+62.79	22.88		▼	III		
							>20			✕	23.03			▼			
				98	90	50	14.5			TNW	+62.02	23.65		▼	II		From 23.65m to 24.16m, slightly decomposed TUFF.
							3.9			✕	24.00	+61.51	24.16	▼	III		
				98	90	55	10.9			TNW		+60.87	24.80	▼	II		Strong, grey to dark grey, slightly decomposed coarse ash TUFF with closely to medium spaced, rough planar, very narrow to extremely narrow, iron stained joints, dipping at 0°-10°.
			100	100	100	3.3			TNW				▼				
									✕	25.00			▼				
									TNW				▼			End of hole at 26.00m.	
									✕	26.00	+59.67	26.00	▼				

- Small disturbed sample    ▲ Water sample
- ⬆ Large disturbed sample    ▼ Water table
- SPT liner sample          ↓ Standard penetration test
- U76 undisturbed sample    ● Permeability test
- U100 undisturbed sample   ▲ Piezometer tip
- ⊠ Mazier sample              ⏏ Standpipe
- P/S Piston sample

LOGGED Poon Leung  
 DATE 30/8/24  
 CHECKED W.P. Chun  
 DATE 31/8/24

REMARKS

# WINFIELD ENGINEERING COMPANY

CONTRACT NO. : \_\_\_\_\_  
 HOLE NO. : BH3(P)  
 SHEET : 1 OF 3  
 DATE : 14/8/24 TO 21/8/24

## DRILLHOLE RECORD

PROJECT : Lot No. 301 in D.D. 219, Hing Keng Shek, Sai Kung, N.T.

METHOD : ROTARY	CO-ORDINATES	ROCK COREBIT : T2-101/TNW
MACHINE & NO. : TOHO	E 843748.28 N 825000.15	HOLE DIA. : HX/NX
FLUSHING MEDIUM : WATER	ORIENTATION : VERTICAL	GROUND LEVEL : +85.72 mPD.

Drilling Progress	Casing Depth/Size	Water Level/Time	Water Recovery %	Total Core Recovery %	Solid Core Recovery %	R. Q. D.	Fracture Index	Tests	Samples			Reduced Level	Depth (m)	Legend	Grade	Zone	Description
									No.	Type	Depth						
14/8	HX										+85.72	0.00				Greyish brown, silty fine to coarse SAND with gravel sized rock fragments.	
									A ● 0.50								
									B ● 1.00								
									C ● 1.50								
									↕ 2.00		+83.72	2.00				Grey, angular COBBLE sized rock fragments. (FILL)	
				25					T2-101								
									↕ 3.00		+82.72	3.00				Concrete	
				40					TNW								
									↕ 3.50		+82.22	3.50				Greyish brown, angular COBBLE sized rock fragments. (COLLUVIUM)	
				36					TNW								
									↕ 4.25		+81.47	4.25				Very dense, greyish brown, sandy GRAVEL sized rock fragments. (COLLUVIUM)	
									1 ● 5.10								
								50/0.04 ↓ 200/0.06	● 5.20								
									↕ 5.90		+79.82	5.90				Light greyish brown, angular COBBLE and BOULDER sized rock fragments. (COLLUVIUM)	
				43					TNW								
									↕ 6.90								
				50					TNW								
									↕ 7.90		+77.82	7.90				Brownish grey, sandy GRAVEL and COBBLE sized rock fragments. (COLLUVIUM)	
				0					2 ▨ 8.40		+77.32	8.40		III		Moderately strong, greyish brown and grey, moderately decomposed coarse ash TUFF with closely and very closely spaced, rough undulating and planar, narrow to very narrow, iron stained joints, dipping at 0°-10°, 20°-30°, 40°-50° & subvertical.	
									↕ 8.40		+76.77	8.95		IV		From 8.95m to 9.70m, highly decomposed TUFF.	
									↕ 9.70		+76.02	9.70		III			
	Hx			67	60	37	7.7		TNW			10					

● Small disturbed sample	▲ Water sample	LOGGED <u>Poon Leung</u>
⬆ Large disturbed sample	▼ Water table	DATE <u>30/8/24</u>
□ SPT liner sample	↓ Standard penetration test	CHECKED <u>W.P. Chun</u>
■ U76 undisturbed sample	● Permeability test	DATE <u>31/8/24</u>
■ U100 undisturbed sample	▲ Piezometer tip	
▨ Mazier sample	⊕ Standpipe	
P/S Piston sample		

REMARKS

- Inspection pit was excavated to 1.50m.
- Standpipe was installed at 10.00m.
- Piezometer was installed at 11.50m.



# WINFIELD ENGINEERING COMPANY

## DRILLHOLE RECORD

CONTRACT NO. : \_\_\_\_\_  
 HOLE NO. : BH3(P)  
 SHEET : 2 OF 3  
 DATE : 14/8/24 TO 21/8/24

PROJECT : Lot No. 301 in D.D. 219, Hing Keng Shek, Sai Kung, N.T.

METHOD : ROTARY

CO-ORDINATES

ROCK COREBIT : T2-101/TNW

MACHINE & NO. : TOHO

E 843748.28

HOLE DIA. : HX/NX

N 825000.15

FLUSHING MEDIUM : WATER

ORIENTATION : VERTICAL

GROUND LEVEL : +85.72 mPD.

Drilling Progress	Casing Depth/Size	Water Level/Time	Water Recovery %	Total Core Recovery %	Solid Core Recovery %	R. Q. D.	Fracture Index	Tests	Samples			Reduced Level	Depth (m)	Legend	Grade	Zone	Description
									No.	Type	Depth						
	Hx						7.7										As sheet 1 of 3
				67	60	37	NI	▲	TNW			+75.37	10.35	v	III		Weak to moderately weak, greyish brown and grey, highly decomposed coarse ash TUFF with very closely and closely spaced, rough undulating and planar, narrow, iron stained joints.
	12.00 Hx			23	18	0			TNW		11.20				v	IV	
				95	88	48	10.0		TNW			+73.72	12.00	v	III		Moderately strong, greyish brown and grey, moderately decomposed coarse ash TUFF with closely and locally medium spaced, rough undulating and planar, very narrow, iron stained joints, dipping at 0°-10°, 30°-40°, 50°-60° & 70°-80°.
				95	83	76	>20		TNW			+72.42	13.30	v	III		Strong, brownish grey and grey, slightly decomposed coarse ash TUFF with closely and medium to widely, locally widely to very widely spaced, rough undulating and planar, very narrow to extremely narrow, iron and chlorite stained joints, dipping at 0°-10°, 20°-30°, 40°-50° & occasional subvertical.  From 17.85m to 18.05m, moderately decomposed TUFF.  From 19.32m to 19.55m, moderately decomposed TUFF.
				97	97	97	7.5		TNW					v	II		
				100	100	100	1.9		TNW					v			
				96	96	96			TNW					v			
				100	100	93			TNW			+67.87	17.85	v			
							15.0		TNW			+67.67	18.05	v	III		
				96	96	96	2.4		TNW					v	II		
				100	97	62			TNW			+66.40	19.32	v	III		
							10.9		TNW			+66.17	19.55	v	III		
				100	100	85	5.4		TNW				19.85	v	II		

- Small disturbed sample    ▲ Water sample
- ⬆ Large disturbed sample    ▼ Water table
- SPT liner sample            ↓ Standard penetration test
- U76 undisturbed sample    ● Permeability test
- U100 undisturbed sample   ▲ Piezometer tip
- ⊠ Mazier sample                ⏏ Standpipe
- P/S Piston sample

LOGGED Poon Leung  
 DATE 30/8/24  
 CHECKED W.P. Chun  
 DATE 31/8/24

REMARKS

# WINFIELD ENGINEERING COMPANY

## DRILLHOLE RECORD

CONTRACT NO. : \_\_\_\_\_  
 HOLE NO. : BH3(P)  
 SHEET : 3 OF 3  
 DATE : 14/8/24 TO 21/8/24

PROJECT : Lot No. 301 in D.D. 219, Hing Keng Shek, Sai Kung, N.T.

METHOD : ROTARY

CO-ORDINATES

ROCK COREBIT : T2-101/TNW

MACHINE & NO. : TOHO

E 843748.28

HOLE DIA. : HX/NX

N 825000.15

FLUSHING MEDIUM : WATER

ORIENTATION : VERTICAL

GROUND LEVEL : +85.72 mPD.

Drilling Progress	Casing Depth/Size	Water Level/Time	Water Recovery %	Total Core Recovery %	Solid Core Recovery %	R. Q. D.	Fracture Index	Tests	Samples		Reduced Level	Depth (m)	Legend	Grade	Zone	Description
									No.	Type Depth						
21/8				100	100	85			TNW			20	v	II		As sheet 2 of 3
							5.4		± 20.85				v			
				100	96	77			TNW	+64.17	+63.87	21.55 21.85	v	III		From 21.55m to 21.85m, moderately decomposed TUFF.
									↓ 22.08	+63.64	+63.64	22.08	v	II		End of hole at 22.08m.


- Small disturbed sample    ▲ Water sample
- ⬆ Large disturbed sample    ▼ Water table
- SPT liner sample            ↓ Standard penetration test
- U76 undisturbed sample    ● Permeability test
- U100 undisturbed sample   ▲ Piezometer tip
- ☒ Mazier sample                ⏏ Standpipe
- P/S Piston sample

LOGGED Poon Leung  
 DATE 30/8/24  
 CHECKED W.P. Chun  
 DATE 31/8/24


REMARKS

## **Appendix B**

### **Drillhole Photographs**



DRILLHOLE NO. ABH1(P)      BOX 1 FO 4




DRILLHOLE NO. ABH1(P)      BOX 2 OF 4







DRILLHOLE NO. ABH1(P)      BOX 3 FO 4



DRILLHOLE NO. ABH1(P)      BOX 4 OF 4




DRILLHOLE NO. ABH2(P)      BOX 1 FO 4




DRILLHOLE NO. ABH2(P)      BOX 2 OF 4







DRILLHOLE NO. ABH2(P)      BOX 3 FO 4



DRILLHOLE NO. ABH2(P)      BOX 4 OF 4




DRILLHOLE NO. ABH3(P)      BOX 1 FO 3



DRILLHOLE NO. ABH3(P)      BOX 2 OF 3





DRILLHOLE NO. ABH3(P)      BOX 3 FO 3

## **Appendix C**

### **Trial Pit Records**

# WINFIELD ENGINEERING COMPANY

<b>Location:</b> Lot No. 301 in D.D. 219, Hing Keng Shek, Sau Kung, N.T.	<b>Trial Pit No.:</b> TP1	<b>Sheet</b> 1 <b>of</b> 1
--	---------------------------	----------------------------

<b>Logged by:</b> Poon Leung	<b>Excavation method:</b> Hand Dug	<b>Excavated:</b> 23-7-2024
<b>Date:</b> 27-7-2024	<b>Coordinates:</b> E 843738.47 N 825013.27	<b>Backfill:</b> 29-7-2024

Samples & Test	Depth (m)	Face A: width: 1.50 m	Face B: width: 1.50 m	Face C: width: 1.50 m	Face D: width: 1.50 m
U76	0.00	Datum line +85.42 mPD			
	0.50				
	1.00				
	1.50				
	2.00				
	2.50				
	3.00				
	3.50				
	4.00				
	4.50				
5.00	End of Pit at 0.80m.				


**Remarks:**

Legend	Description	Grade	Plan (not to scale)																								
	Concrete slab																										
	Firm to stiff, yellowish brown, sandy SILT with gravel and cobble sized rock fragments. (COLLUVIUM)																										
	Light greyish and yellowish brown, angular and subangular BOULDER and COBBLE sized rock fragments. (COLLUVIUM)																										
			<table style="width:100%; font-size: small;"> <tr> <td>⊥</td> <td>Plate bearing test</td> <td>●</td> <td>Small disturbed sample</td> </tr> <tr> <td>U</td> <td>Insitu density test</td> <td>◆</td> <td>Large disturbed sample</td> </tr> <tr> <td>m</td> <td>Moisture content test</td> <td>◀</td> <td>Water sample</td> </tr> <tr> <td>☐</td> <td>Photograph</td> <td>⊙</td> <td>Seepage</td> </tr> <tr> <td>■</td> <td>Undisturbed sample hor.</td> <td>⊠</td> <td>Bulk sample</td> </tr> <tr> <td>■</td> <td>Undisturbed sample ver.</td> <td>■</td> <td>Block sample</td> </tr> </table>	⊥	Plate bearing test	●	Small disturbed sample	U	Insitu density test	◆	Large disturbed sample	m	Moisture content test	◀	Water sample	☐	Photograph	⊙	Seepage	■	Undisturbed sample hor.	⊠	Bulk sample	■	Undisturbed sample ver.	■	Block sample
⊥	Plate bearing test	●	Small disturbed sample																								
U	Insitu density test	◆	Large disturbed sample																								
m	Moisture content test	◀	Water sample																								
☐	Photograph	⊙	Seepage																								
■	Undisturbed sample hor.	⊠	Bulk sample																								
■	Undisturbed sample ver.	■	Block sample																								

# WINFIELD ENGINEERING COMPANY

<b>Location:</b> Lot No. 301 in D.D. 219, Hing Keng Shek, Sai Kung, N.T.	<b>Trial Pit No.:</b> TP2	<b>Sheet</b> 1 <b>of</b> 1
--	---------------------------	----------------------------

<b>Logged by:</b> Poon Leung	<b>Excavation method:</b> Hand Dug	<b>Excavated:</b> 24-7-2024
<b>Date:</b> 27-7-2024	<b>Coordinates:</b> E 843750.35 N 825005.08	<b>Backfill:</b> 29-7-2024



**Remarks:**

Legend	Description	Grade	Plan (not to scale)												
	Surface channel														
	Concrete slab														
	Concrete														
	Loose to medium dense, grey and greyish brown, sandy GRAVEL and COBBLE sized concrete and rock fragments. (FILL)														
	Medium dense, light greyish brown, slightly silty fine to coarse SAND with gravel sized rock fragments. (FILL)														
			<table style="width:100%; font-size: small;"> <tr> <td> Plate bearing test</td> <td> Small disturbed sample</td> </tr> <tr> <td> Insitu density test</td> <td> Large disturbed sample</td> </tr> <tr> <td> Moisture content test</td> <td> Water sample</td> </tr> <tr> <td> Photograph</td> <td> Seepage</td> </tr> <tr> <td> Undisturbed sample hor.</td> <td> Bulk sample</td> </tr> <tr> <td> Undisturbed sample ver.</td> <td> Block sample</td> </tr> </table>	Plate bearing test	Small disturbed sample	Insitu density test	Large disturbed sample	Moisture content test	Water sample	Photograph	Seepage	Undisturbed sample hor.	Bulk sample	Undisturbed sample ver.	Block sample
Plate bearing test	Small disturbed sample														
Insitu density test	Large disturbed sample														
Moisture content test	Water sample														
Photograph	Seepage														
Undisturbed sample hor.	Bulk sample														
Undisturbed sample ver.	Block sample														





# WINFIELD ENGINEERING COMPANY

<b>Location:</b> Lot No. 301 in D.D. 219, Hing Keng Shek, Sai Kung, N.T.	<b>Trial Pit No.:</b> TP3	<b>Sheet</b> 1 <b>of</b> 1
--	---------------------------	----------------------------

<b>Logged by:</b> Poon Leung	<b>Excavation method:</b> Hand Dug	<b>Excavated:</b> 21-8-2024
<b>Date:</b> 23-8-2024	<b>Coordinates:</b> E 843735.19 N 824997.06	<b>Backfill:</b> 2-9-2024

Samples & Test	Depth (m)	Face A: width: 1.50 m	Face B: width: 1.50 m	Face C: width: 1.50 m	Face D: width: 1.50 m
U76 ■	0.00	Datum line +85.68 mPD			
	0.50	End of Pit at 0.50m.			
	1.00				
	1.50				
	2.00				
	2.50				
	3.00				
	3.50				
	4.00				
	4.50				
5.00					


**Remarks:**

Legend	Description	Grade	Plan (not to scale)																								
	Concrete slab																										
	Medium dense, reddish pink, slightly clayey silty fine to medium SAND with gravel and occasional cobble sized rock fragments and rootlets. (FILL)																										
	Light greyish brown and pink, angular and subangular BOULDER and COBBLE sized rock fragments. (COLLUVIUM)																										
			<table style="width:100%; font-size: small;"> <tr> <td>⊥</td><td>Plate bearing test</td> <td>●</td><td>Small disturbed sample</td> </tr> <tr> <td>U</td><td>In situ density test</td> <td>◆</td><td>Large disturbed sample</td> </tr> <tr> <td>m</td><td>Moisture content test</td> <td>W</td><td>Water sample</td> </tr> <tr> <td>☐</td><td>Photograph</td> <td>⦿</td><td>Seepage</td> </tr> <tr> <td>■</td><td>Undisturbed sample hor.</td> <td>▣</td><td>Bulk sample</td> </tr> <tr> <td>■</td><td>Undisturbed sample ver.</td> <td>■</td><td>Block sample</td> </tr> </table>	⊥	Plate bearing test	●	Small disturbed sample	U	In situ density test	◆	Large disturbed sample	m	Moisture content test	W	Water sample	☐	Photograph	⦿	Seepage	■	Undisturbed sample hor.	▣	Bulk sample	■	Undisturbed sample ver.	■	Block sample
⊥	Plate bearing test	●	Small disturbed sample																								
U	In situ density test	◆	Large disturbed sample																								
m	Moisture content test	W	Water sample																								
☐	Photograph	⦿	Seepage																								
■	Undisturbed sample hor.	▣	Bulk sample																								
■	Undisturbed sample ver.	■	Block sample																								

# WINFIELD ENGINEERING COMPANY

<b>Location:</b> Lot No. 301 in D.D. 219, Hing Keng Shek, Sai Kung, N.T.	<b>Trial Pit No.:</b> TP4	<b>Sheet</b> 1 <b>of</b> 1
--	---------------------------	----------------------------

<b>Logged by:</b> Poon Leung	<b>Excavation method:</b> Hand Dug	<b>Excavated:</b> 24-7-2024
<b>Date:</b> 27-7-2024	<b>Coordinates:</b> E 843746.37 N 824996.28	<b>Backfill:</b> 29-7-2024



**Remarks:**

Legend	Description	Grade	Plan (not to scale)																								
	Surface channel																										
	Concrete slab																										
	Concrete																										
	Medium dense, grey, sandy GRAVEL and COBBLE sized rock and concrete fragments. (FILL)																										
	Medium dense, yellowish brown, slightly clayey silty fine to coarse SAND with gravel sized rock fragments. (FILL)																										
	Loose to medium dense, light greyish brown, sandy GRAVEL and COBBLE sized rock fragments. (FILL)																										
			<table style="width:100%; font-size: small;"> <tr> <td></td> <td>Plate bearing test</td> <td></td> <td>Small disturbed sample</td> </tr> <tr> <td></td> <td>Insitu density test</td> <td></td> <td>Large disturbed sample</td> </tr> <tr> <td></td> <td>Moisture content test</td> <td></td> <td>Water sample</td> </tr> <tr> <td></td> <td>Photograph</td> <td></td> <td>Seepage</td> </tr> <tr> <td></td> <td>Undisturbed sample hor.</td> <td></td> <td>Bulk sample</td> </tr> <tr> <td></td> <td>Undisturbed sample ver.</td> <td></td> <td>Block sample</td> </tr> </table>		Plate bearing test		Small disturbed sample		Insitu density test		Large disturbed sample		Moisture content test		Water sample		Photograph		Seepage		Undisturbed sample hor.		Bulk sample		Undisturbed sample ver.		Block sample
	Plate bearing test		Small disturbed sample																								
	Insitu density test		Large disturbed sample																								
	Moisture content test		Water sample																								
	Photograph		Seepage																								
	Undisturbed sample hor.		Bulk sample																								
	Undisturbed sample ver.		Block sample																								

# WINFIELD ENGINEERING COMPANY

<b>Location:</b> Lot No. 301 in D.D. 219, Hing Keng Shek, Sai Kung, N.T.	<b>Trial Pit No.:</b> TP5	<b>Sheet</b> 1 <b>of</b> 1
--	---------------------------	----------------------------

<b>Logged by:</b> Poon Leung	<b>Excavation method:</b> Hand Dug	<b>Excavated:</b> 21-8-2024
<b>Date:</b> 23-8-2024	<b>Coordinates:</b> E 843741.22 N 824983.53	<b>Backfill:</b> 2-9-2024

Samples & Test	Depth (m)	Face A: width: 1.50 m	Face B: width: 1.50 m	Face C: width: 1.50 m	Face D: width: 1.50 m
U76	0.00	Datum line +85.68 mPD			
	0.50				
	1.00	End of Pit at 0.80m.			
	1.50				
	2.00				
	2.50				
	3.00				
	3.50				
	4.00				
	4.50				
5.00					

**Remarks:**

Legend	Description	Grade	Plan (not to scale)		
	① Medium dense, light greyish brown, slightly clayey silty fine to medium SAND with gravel sized rock fragments and rootlets. (FILL)				
	② Firm, yellowish brown and pink, slightly clayey sandy SILT with gravel sized rock fragments. (FILL)				
	③ Loose to medium dense, brownish grey, slightly silty sandy GRAVEL and COBBLE sized rock and brick fragments. (FILL)				
	Firm, yellowish brown and pink, slightly clayey sandy SILT with gravel sized rock fragments and rootlets. (COLLUVIUM)				
			<table style="width:100%; font-size: small;"> <tr> <td style="width:50%; vertical-align: top;"> <ul style="list-style-type: none"> <li> Plate bearing test</li> <li> Insitu density test</li> <li> Moisture content test</li> <li> Photograph</li> <li> Undisturbed sample hor.</li> <li> Undisturbed sample ver.</li> </ul> </td> <td style="width:50%; vertical-align: top;"> <ul style="list-style-type: none"> <li> Small disturbed sample</li> <li> Large disturbed sample</li> <li> Water sample</li> <li> Seepage</li> <li> Bulk sample</li> <li> Block sample</li> </ul> </td> </tr> </table>	<ul style="list-style-type: none"> <li> Plate bearing test</li> <li> Insitu density test</li> <li> Moisture content test</li> <li> Photograph</li> <li> Undisturbed sample hor.</li> <li> Undisturbed sample ver.</li> </ul>	<ul style="list-style-type: none"> <li> Small disturbed sample</li> <li> Large disturbed sample</li> <li> Water sample</li> <li> Seepage</li> <li> Bulk sample</li> <li> Block sample</li> </ul>
<ul style="list-style-type: none"> <li> Plate bearing test</li> <li> Insitu density test</li> <li> Moisture content test</li> <li> Photograph</li> <li> Undisturbed sample hor.</li> <li> Undisturbed sample ver.</li> </ul>	<ul style="list-style-type: none"> <li> Small disturbed sample</li> <li> Large disturbed sample</li> <li> Water sample</li> <li> Seepage</li> <li> Bulk sample</li> <li> Block sample</li> </ul>				

# WINFIELD ENGINEERING COMPANY

<b>Location:</b> Lot No. 301 in D.D. 219, Hing Keng Shek, Sai Kung, N.T.	<b>Trial Pit No.:</b> TP6	<b>Sheet</b> 1 <b>of</b> 1
--	---------------------------	----------------------------

<b>Logged by:</b> Poon Leung	<b>Excavation method:</b> Hand Dug	<b>Excavated:</b> 21-8-2024
<b>Date:</b> 23-8-2024	<b>Coordinates:</b> E 843738.05 N 824990.11	<b>Backfill:</b> 2-9-2024

Samples & Test	Depth (m)	Face A: width: 1.50 m	Face B: width: 1.50 m	Face C: width: 1.50 m	Face D: width: 1.50 m
U76	0.00	Datum line +85.70 mPD			
	0.50				
	1.00				
	1.50				
	2.00				
	2.50				
	3.00				
	3.50				
	4.00				
	4.50				
5.00					

**Remarks:**


Legend	Description	Grade	Plan (not to scale)																								
	Concrete slab																										
	Medium dense, reddish brown and pink, silty fine to coarse SAND with gravel and occasional cobble sized rock fragments and rootlets. (FILL)																										
	Firm, reddish brown and pink, slightly clayey sandy SILT with gravel sized rock fragments. (COLLUVIUM)																										
	Light greyish brown and pink, angular BOULDER sized rock fragments. (COLLUVIUM)																										
			<table style="width:100%; font-size: small;"> <tr> <td>⊥</td><td>Plate bearing test</td> <td>●</td><td>Small disturbed sample</td> </tr> <tr> <td>U</td><td>In situ density test</td> <td>◆</td><td>Large disturbed sample</td> </tr> <tr> <td>m</td><td>Moisture content test</td> <td>◀</td><td>Water sample</td> </tr> <tr> <td>☐</td><td>Photograph</td> <td>↕</td><td>Seepage</td> </tr> <tr> <td>■</td><td>Undisturbed sample hor.</td> <td>▣</td><td>Bulk sample</td> </tr> <tr> <td>■</td><td>Undisturbed sample ver.</td> <td>■</td><td>Block sample</td> </tr> </table>	⊥	Plate bearing test	●	Small disturbed sample	U	In situ density test	◆	Large disturbed sample	m	Moisture content test	◀	Water sample	☐	Photograph	↕	Seepage	■	Undisturbed sample hor.	▣	Bulk sample	■	Undisturbed sample ver.	■	Block sample
⊥	Plate bearing test	●	Small disturbed sample																								
U	In situ density test	◆	Large disturbed sample																								
m	Moisture content test	◀	Water sample																								
☐	Photograph	↕	Seepage																								
■	Undisturbed sample hor.	▣	Bulk sample																								
■	Undisturbed sample ver.	■	Block sample																								



# WINFIELD ENGINEERING COMPANY

<b>Location:</b> Lot No. 301 in D.D. 219, Hing Keng Shek, Sai Kung, N.T.	<b>Trial Pit No.:</b> TP7	<b>Sheet</b> 1 <b>of</b> 1
--	---------------------------	----------------------------

<b>Logged by:</b> Poon Leung	<b>Excavation method:</b> Hand Dug	<b>Excavated:</b> 23-7-2024
<b>Date:</b> 27-7-2024	<b>Coordinates:</b> E 843738.35 N 825010.07	<b>Backfill:</b> 29-7-2024



**Remarks:**

Legend	Description	Grade	Plan (not to scale)																								
	Concrete slab																										
	Medium dense to dense, yellowish brown and pink, slightly silty, sandy GRAVEL and COBBLE sized rock fragments. (COLLUVIUM)																										
	Light greyish and yellowish brown, angular and subangular BOULDER and COBBLE sized rock fragments. (COLLUVIUM)																										
			<table style="width:100%; font-size: small;"> <tr> <td>⊥</td> <td>Plate bearing test</td> <td>●</td> <td>Small disturbed sample</td> </tr> <tr> <td>U</td> <td>In situ density test</td> <td>◆</td> <td>Large disturbed sample</td> </tr> <tr> <td>m</td> <td>Moisture content test</td> <td>W</td> <td>Water sample</td> </tr> <tr> <td>☐</td> <td>Photograph</td> <td>~</td> <td>Seepage</td> </tr> <tr> <td>■</td> <td>Undisturbed sample hor.</td> <td>□</td> <td>Bulk sample</td> </tr> <tr> <td>■</td> <td>Undisturbed sample ver.</td> <td>■</td> <td>Block sample</td> </tr> </table>	⊥	Plate bearing test	●	Small disturbed sample	U	In situ density test	◆	Large disturbed sample	m	Moisture content test	W	Water sample	☐	Photograph	~	Seepage	■	Undisturbed sample hor.	□	Bulk sample	■	Undisturbed sample ver.	■	Block sample
⊥	Plate bearing test	●	Small disturbed sample																								
U	In situ density test	◆	Large disturbed sample																								
m	Moisture content test	W	Water sample																								
☐	Photograph	~	Seepage																								
■	Undisturbed sample hor.	□	Bulk sample																								
■	Undisturbed sample ver.	■	Block sample																								

## **Appendix D**

### **Trial Pit Photographs**



TRIAL PIT NO. TP1      FACE A



TRIAL PIT NO. TP1      FACE B





TRIAL PIT NO. TP1      FACE C



TRIAL PIT NO. TP1      FACE D



TRIAL PIT NO. TP1      FACE BOTTOM





TRIAL PIT NO. TP2      FACE A



TRIAL PIT NO. TP2      FACE B





TRIAL PIT NO. TP2      FACE C



TRIAL PIT NO. TP2      FACE D



TRIAL PIT NO. TP2      FACE BOTTOM





TRIAL PIT NO. TP3      FACE A




TRIAL PIT NO. TP3      FACE B





TRIAL PIT NO. TP3      FACE C



TRIAL PIT NO. TP3      FACE D





TRIAL PIT NO. TP3      FACE BOTTOM



TRIAL PIT NO. TP4      FACE A



TRIAL PIT NO. TP4      FACE B






TRIAL PIT NO. TP4      FACE C



TRIAL PIT NO. TP4      FACE D



TRIAL PIT NO. TP4      FACE BOTTOM





TRIAL PIT NO. TP5      FACE A



TRIAL PIT NO. TP5      FACE B





TRIAL PIT NO. TP5      FACE C



TRIAL PIT NO. TP5      FACE D





TRIAL PIT NO. TP5      FACE BOTTOM





TRIAL PIT NO. TP6      FACE A



TRIAL PIT NO. TP6      FACE B





TRIAL PIT NO. TP6      FACE C



TRIAL PIT NO. TP6      FACE D



TRIAL PIT NO. TP6      FACE BOTTOM





TRIAL PIT NO. TP7      FACE A



TRIAL PIT NO. TP7      FACE B





TRIAL PIT NO. TP7      FACE C



TRIAL PIT NO. TP7      FACE D



TRIAL PIT NO. TP7      FACE BOTTOM

## **Appendix E**

### **Installation Details of Piezometer/Standpipe**

### **& Response Test Records**



# PIEZOMETER/STANDPIPE DETAIL AND RESPONSE TEST RECORD SHEET

Project : Lot No. 301 in D.D. 219, Hing Keng Shek, Sai Kung, N.T.

Drillhole No. BH1(P)

Date of Test : 12-8-2024

Ground Level : +85.58 mPD.

Initial Water Level : 3.88 m. (Piezometer)

Depth of Piezometer : 11.20 m.

Initial Water Level : 3.92 m. (Standpipe)

Depth of Standpipe : 8.00 m.

Tested By : Ma

Time Elapsed (minutes)	Depth of Water From Top of Pipe (m.)		Depth Below Ground Level	
	Piezometer	Standpipe		
0.00	0.00	0.00	0.00 m.	
0.25	0.32	0.62		
0.50	0.55	1.18		
0.75	0.81	1.68		
1.00	0.98	2.05	1.00 m.	
2.00	1.41	3.25		
3.00	1.73	3.92		
4.00	2.02			
5.00	2.33			
6.00	2.58		8.00 m.	
7.00	2.79		8.50 m.	
8.00	3.05		9.00 m.	
9.00	3.33			
10.00	3.52			
15.00	3.88		9.70 m.	
			10.20 m.	
			11.20 m.	
			11.70 m.	
			12.20 m.	
			21.70 m. (Bottom of Hole)	

REMARKS :

# PIEZOMETER/STANDPIPE DETAIL AND RESPONSE TEST RECORD SHEET

Project : Lot No. 301 in D.D. 219, Hing Keng Shek, Sai Kung, N.T.

Drillhole No. BH2(P)	Date of Test : 2-9-2024
Ground Level : +85.67 mPD.	Initial Water Level : 8.58 m. (Piezometer)
Depth of Piezometer : 15.40 m.	Initial Water Level : 8.53 m. (Standpipe)
Depth of Standpipe : 10.00 m.	Tested By : Ma

Time Elapsed (minutes)	Depth of Water From Top of Pipe (m.)		Depth Below Ground Level	
	Piezometer	Standpipe		
0.00	0.00	0.00	0.00 m.	
0.25	0.31	0.69		
0.50	0.57	1.22		
0.75	0.79	1.78		
1.00	1.05	2.26	1.00 m.	
2.00	1.87	3.33		
3.00	2.46	4.02		
4.00	3.00	4.87		
5.00	3.48	5.36		
6.00	3.91	5.87	10.00 m.	
7.00	4.30	6.26	10.50 m.	
8.00	4.73	6.68	11.00 m.	
9.00	4.98	7.01		
10.00	5.19	7.38		
15.00	5.98	8.14	13.90 m.	
20.00	6.71	8.53	14.40 m.	
25.00	7.44			
30.00	8.02			
45.00	8.58			
			15.40 m.	
			15.90 m.	
			16.40 m.	
			22.08 m. (Bottom of Hole)	

REMARKS :

# PIEZOMETER/STANDPIPE DETAIL AND RESPONSE TEST RECORD SHEET

Project : Lot No. 301 in D.D. 219, Hing Keng Shek, Sai Kung, N.T.

Drillhole No. BH3(P)	Date of Test : 22-8-2024
Ground Level : +85.72 mPD.	Initial Water Level : 8.90 m. (Piezometer)
Depth of Piezometer : 11.50 m.	Initial Water Level : 8.88 m. (Standpipe)
Depth of Standpipe : 10.00 m.	Tested By : Ma

Time Elapsed (minutes)	Depth of Water From Top of Pipe (m.)		Depth Below Ground Level	
	Piezometer	Standpipe		
0.00	0.00	0.00	0.00 m.	
0.25	0.29	0.58		
0.50	0.58	0.92		
0.75	0.72	1.47		
1.00	0.93	1.86	1.00 m.	
2.00	1.75	3.01		
3.00	2.60	3.92		
4.00	3.42	4.79		
5.00	4.03	5.55		
6.00	4.68	6.28		
7.00	5.17	6.89		
8.00	5.55	7.50		
9.00	5.90	8.12		
10.00	6.28	8.61		
15.00	7.34	8.88	10.00 m.	
20.00	7.82		10.50 m.	
25.00	8.34			
30.00	8.70			
45.00	8.90			
			11.50 m.	
			12.00 m.	
			12.50 m.	
			22.08 m. (Bottom of Hole)	

REMARKS :

## **Appendix F**

### **Groundwater Monitoring Records**

# RECORD OF WATER LEVEL READING

Project : Lot No. 301 in D.D. 219, Hing Keng Shek, Sai Kung, N.T.

Drillhole No.	BH1(P)			BH2(P)			BH3(P)			
	Date of Installation	Standpipe	Piezometer	Date of Installation	Standpipe	Piezometer	Date of Installation	Standpipe	Piezometer	
Ground Level (mPD)	10-8-2024	8.00	11.20	31-8-2024	10.00	15.40	21-8-2024	10.00	11.50	
Type of Installation	+85.58			+85.67			+85.72			
Installation Depth (m)										
Date	Water Level Below G.L.	Elevation of Water Level	Water Level Below G.L.	Elevation of Water Level	Water Level Below G.L.	Elevation of Water Level	Water Level Below G.L.	Elevation of Water Level	Water Level Below G.L.	Elevation of Water Level
12-8-2024	3.92	+81.66	3.88	+81.70	-	-	-	-	-	-
13-8-2024	3.98	+81.60	3.95	+81.63	-	-	-	-	-	-
14-8-2024	4.00	+81.58	3.99	+81.59	-	-	-	-	-	-
15-8-2024	4.02	+81.56	4.00	+81.58	-	-	-	-	-	-
16-8-2024	4.04	+81.54	4.02	+81.56	-	-	-	-	-	-
17-8-2024	4.03	+81.55	4.00	+81.58	-	-	-	-	-	-
19-8-2024	4.01	+81.57	3.97	+81.61	-	-	-	-	-	-
20-8-2024	4.00	+81.58	3.95	+81.63	-	-	-	-	-	-
21-8-2024	4.00	+81.58	3.97	+81.61	-	-	-	-	-	-
22-8-2024	3.99	+81.59	3.98	+81.60	-	-	8.88	+76.84	8.90	+76.82
23-8-2024	3.98	+81.60	3.97	+81.61	-	-	8.89	+76.83	8.91	+76.81
24-8-2024	4.03	+81.55	4.01	+81.57	-	-	8.90	+76.82	8.94	+76.78
26-8-2024	4.03	+81.55	4.02	+81.56	-	-	8.91	+76.81	8.93	+76.79
27-8-2024	4.02	+81.56	4.00	+81.58	-	-	8.91	+76.81	8.92	+76.80
28-8-2024	4.00	+81.58	3.97	+81.61	-	-	8.89	+76.83	8.90	+76.82
29-8-2024	3.98	+81.60	3.95	+81.63	-	-	8.87	+76.85	8.89	+76.83
30-8-2024	4.00	+81.58	3.98	+81.60	-	-	8.88	+76.84	8.87	+76.85
31-8-2024	3.99	+81.59	3.96	+81.62	-	-	8.88	+76.84	8.89	+76.83
2-9-2024	4.03	+81.55	4.02	+81.56	8.53	+77.14	8.90	+76.82	8.91	+76.81
3-9-2024	4.05	+81.53	4.03	+81.55	8.55	+77.12	8.92	+76.80	8.93	+76.79
4-9-2024	4.03	+81.55	4.00	+81.58	8.57	+77.10	8.91	+76.81	8.90	+76.82
5-9-2024	4.02	+81.56	4.01	+81.57	8.56	+77.11	8.90	+76.82	8.88	+76.84
6-9-2024	3.98	+81.60	3.95	+81.63	8.55	+77.12	8.86	+76.86	8.87	+76.85
7-9-2024	3.99	+81.59	3.92	+81.66	8.51	+77.16	8.83	+76.89	8.85	+76.87
9-9-2024	4.00	+81.58	3.96	+81.62	8.54	+77.13	8.87	+76.85	8.89	+76.83

## **Appendix G**

### **Checklists for Soil and Rock Description**

## SOIL DESCRIPTION

For the preparation of drillhole logs, the soil description may report the following information as appropriate in the order indicated:

Soil Strength (Compactness & consistency)

Colour

Weathering

Soil Name

Other qualifying remarks

Additional Geological Information

The following descriptions were achieved from **GUIDE TO ROCK AND SOIL DESCRIPTIONS (GEOGUIDE 3)**

### I) Soil Strength (Compactness & Consistency)

Soil Type	Term	Identification
Very Coarse (COBBLES & BOULDERS)	Loose	By Inspection of voids & particle packing in the field (from trial pits only)
	Dense	
Coarse (SANDS & GRAVELS)	Very loose	SPT 'N' value 0-4
	Loose	SPT 4-10; can be excavated with spade;
	Medium dense	SPT 10-30
	Dense	SPT 30-50; requires pick for excavation;
	Very dense	SPT > 50
Fine (CLAYS & SILTS)	Very soft	Undrained shear strength (USS) < 20kPa; exudes between fingers when squeezed in hand.
	Soft	USS 20-40 kPa; moulded by light finger pressure.
	Firm	USS 40-75 kPa; can be moulded by strong finger pressure.
	Stiff	USS 75-150 kPa; cannot be moulded by finger, can be indented by thumb.
	Very stiff or hard	USS > 150 kPa; can be indented by thumbnail.

Terms applicable only to TRANSPORTED SOILS. For soils derived from insitu rock weathering, record actual values of quantitative tests as part of the description, where appropriate.

### II) Colour

Parameter	Terms
Value	Light Dark
Chroma	Pinkish, Reddish, Yellowish, Orangish, Brownish, Greenish, Bluish, Purplish, Greyish
Hue	Pink, Red, Yellow, Orange, Brown, Green, Blue, Purple, White, Grey, Black.

For uniform colour distribution, choose a hue, supplemented by a value and / or chroma if necessary.

For non-uniform distribution, repeat this procedure using one of the following descriptors: spotted, mottled, dappled, streaked, striped (e.g. light yellowish brown mottled with red)

State whether sample was wet or dry when described.



### III) Weathering

#### Soils Derived from In-situ Weathering of Rocks

There are two main types: saprolites (rock texture/structure retained) and residual soils (rock texture/structure completely destroyed).

Describe state of weathering in accordance with item 4 for rock description (see Rock Description).

#### Sedimentary (Transported) Soils

Coarse soils: Describe overall discolouration of soil and degree of decomposition of gravel and larger particles. Also note any signs of disintegration of large particles where apparent.

### IV) Soil Name

#### A) Basic Soil Types

Soil Type	Particle Sizes (mm)	Identification	
BOULDERS	-	> 200	Only seen complete in pits or exposures. Often difficult to recover from boreholes
COBBLES	-	60–200	
GRAVELS	Coarse	20–60	Easily visible to naked eye; particle shape and grading can be described.
	Medium	6–20	Well-graded: wide range of grain sizes.
	Fine	2–6	Poorly graded: not well-graded (split further into uniform or gap-graded).
SANDS	Coarse	0.6–2	Visible to naked eye: very little or no cohesion: grading can be described. Maybe well graded or poorly-graded (uniform or gap-graded) as for gravel.
	Medium	0.2–0.5	
	Fine	0.06–0.2	
SILTS	Coarse	0.02–0.06	Only coarse silt barely visible to naked eye: exhibits little plasticity and marked dilatancy: slightly granular or silky to the touch. Disintegrates in water, lumps dry quickly possesses cohesion but can be powdered easily between fingers.
	Medium	0.006–0.02	
	Fine	0.002–0.006	
CLAYS	-	< 0.002	Dry lumps can be broken by hand but not powdered between fingers. Disintegrates in water more slowly than silts: smooth to the touch: exhibits plasticity but no dilatancy: sticks to the fingers and dries slowly: shrinks appreciably on drying, usually showing cracks. These properties more noticeable with increasing plasticity.
ORGANIC CLAYS, SILTS OR SANDS	-	Varies	Contains much organic vegetable matter. Often has a noticeable smell and changes colour on oxidation.
PEATS	-	Varies	Predominantly plant remains: usually dark brown or black in colour, often with distinctive smell: low bulk density.

## B) Composite Soil Types (Mixtures of Basic Types)

Principal Soil Type	Terminology Sequence	Term for Secondary Constituent	% of Secondary Constituent
Very Coarse (BOULDERS & COBBLES)	Secondary Constituents (finer material) ▲	With occasional	< 5
(> 50% of soil > 60mm)	After principal	With some	5-20
		With much	20-50
Coarse (GRAVELS & SANDS)	Secondary constituents before principal (excluding gravel, cobbles & boulders) +	Slight (silty, clayey or silty/clayey)	☉ < 5
		- (silty, clayey or silty/clayey)	☉ 5-15
		Very (silty, clayey or silty/clayey)	☉ 15-35
		AND/OR	
		Slightly (sandy)	☉ < 5
		- (sandy)	☉ 5-20
		Very (sandy)	☉ 20-50
Fine (SILTS & CLAYS)	Secondary constituents before principal (excluding gravel, cobbles & boulders) ▲	Slightly (sandy) ☉	< 35
(< 35% silt & clay sizes)		- (sandy) ☉	35-65

+ Full name of finer material should be given.

▲ Secondary soil type as appropriate; use 'silty/clayey' when a distinction cannot be made between the two.

☉ If cobbles or boulders are also present in a coarse or fine soil, this can be indicated by using one of the following terms relating to the very coarse fraction after the principal: 'with occasional' (<5), 'with many' (20-50), where figures in brackets are % very coarse material expressed as a fraction of the whole soil.

For fine soils, plasticity terms should also be described where possible, viz.: 'non-plastic' (generally silts), 'intermediate plasticity' (lean clays), 'high plasticity' (fat clays).

## V) Other Qualifying Remarks (If requested)

Here any additional relevant information may be added

- e.g.
- Particle shape & Composition
  - Structure
  - Discontinuities

Notes: For full description of soils derived from insitu rock weathering:

- Saprolites (rock texture/structure retained) – described as rocks, supplemented by soil strength (but not relative density) and soil name terms in brackets.
- Residual Soils (rock texture/structure completely destroyed) – describe as soils, supplemented by name of parent rock where apparent from field evidence.

## VI) Additional Geological Information

Record geological name, which indicates geological origin or soil type (e.g. Alluvium, Debris Flow Deposit, Marine Deposit etc.). Refer to HKGS maps & memoirs for further information.

### ROCK DESCRIPTION

For the preparation of drillhole logs the rock description may report the following information as appropriate in the order indicated:

Strength

Colour

Material Weathering/Alteration

Grain Size

Rock Name

Discontinuities

Additional Geological Information

Other qualifying remarks

The following descriptions were achieved from **GUIDE TO ROCK AND SOIL DESCRIPTIONS (GEOGUIDE 3)**

#### I) Strength

<b>Term</b>	<b>Identification</b>
Extremely weak	Easily crumbled by hand: indented deeply by thumbnail.
Very weak	Crumbled with difficulty: scratched easily by thumbnail: peeled by pocketknife.
Weak	Broken into pieces by hand: scratched by thumbnail: peeled by pocketknife: deep indentations (to 5mm) by point of geological pick: hand-held specimen easily broken by single light hammer blow.
Moderately weak	Broken with difficulty in two hands: scratched with difficulty by thumbnail: difficult to peel but easily scratched by pocketknife: shallow indentations easily made by point of pick: hand-held specimen usually broken by single light hammer blow.
Moderately strong	Scratched by pocketknife: shallow indentations made by firm blow with point of pick: hand-held specimen usually broken by single firm hammer blow.
Strong	Firm blows with point of pick cause only superficial surface damage: hand-held specimen requires more than one firm hammer blow to break.
Very strong	Many hammer blows required to break specimen.
Extremely strong	Specimen only chipped by hammer blows.

## II) Colour

Parameter	Terms
Value	Light, Dark
Chroma	Pinkish, Reddish, Yellowish, Orangish, Brownish, Greenish, Bluish, Purplish, Greyish
Hue	Pink, Red, Yellow, Orange, Brown, Green, Blue, Purple, White, Grey, Black.

For uniform colour distribution, choose a hue supplemented by a value and / or chroma if necessary.

For non-uniform distribution, repeat this procedure using one of the following descriptors: spotted, mottled, dappled, streaked and striped (e.g. light pinkish grey spotted with black).

## III) Grain Size

Term	Size of Component Particles	Equivalent Soil Grade
Fine grained	2-60 microns (grains larger than 10 microns visible using X10 hand lens)	Silt
Medium grained	60 microns–2 mm (just visible to naked eyes)	Sand size
Coarse grained	2-60 mm	Gravel size

## IV) Material Weathering / Alteration

Decomposition Term	Grade Symbol	Typical Characteristics
Residual Soil	VI	Original rock textures completely destroyed; can be crumbled by hand and finger pressure into constituent grains.
Completely Decomposed	V	Original rock texture preserved; can be crumbled by hand & finger pressure into constituent grains; easily indented by point of geological pick; slakes in water; completely discoloured compared with fresh rock.
Highly Decomposed	IV	Can be broken by hand into smaller pieces; makes a dull sound when struck by hammer; not easily indented by point of pick; does not slake in water; completely discoloured compared with fresh rock.
Moderately Decomposed	III	Cannot usually be broken by hand; easily broken by hammer; makes a dull or slight ringing sound when struck by hammer; completely stained throughout.
Slightly Decomposed	II	Not broken easily by hammer; makes a ringing sound when struck by hammer; fresh rock colours generally retained but stained neat joint surfaces.
Fresh Rock	I	Not broken easily by hammer; makes a ringing sound when struck by hammer; no visible signs of decomposition (i.e. no discolouration).

This classification is applicable to igneous and volcanic rocks and other rocks of equivalent strength in fresh state.

### Disintegration

Describe small-scale cracking and fracturing caused by mechanical weathering, where apparent.

### Alteration

Describe state of alteration (e.g. mineralised, kaolinised) where apparent.



**V) Rock Name (Including Grain Size)**

Igneous	Coarse - (6–20mm), Medium - (2–6mm) & Fine - (0.06–2mm) grained GRANITE, GRANODIORITE, Very Fine - grained (< 0.06mm) RHYOLITE, BASALT. (Common types only, see GEOGUIDE 3 for others).
Pyroclastic	PYROCLASTIC BRECCIA (> 60mm), Lapilli TUFF (2–60mm), Coarse ash TUFF (0.06–2mm), Fine ash TUFF (< 0.06mm).
Metamorphic	Foliated – SCHIST (> 0.06mm), PHYLLITE (> 0.06mm), Non – foliated –MARBLE, QUARTZITE and FAULT BRECCIA.
Sedimentary	CONGLOMERATE, BRECCIA (>2mm), SANDSTONE (0.06–2mm), MUDSTONE (< 0.06mm) = SILTSTONE (0.002–0.06mm) + CLAYSTONE (< 0.002mm). (Common types only).

If rock name cannot be identified, describe grain size quantitatively, including textural term where appropriate.

**VI) Discontinuities Spacing**

Term	Spacing
Extremely widely spaced	> 6m
Very widely spaced	2–6mm
Widely spaced	0.6–2mm
Medium spaced	200–600mm
Closely spaced	60–200mm
Very closely spaced	20–60mm
Extremely closely spaced	< 20mm

**Aperture Size**

Wide (>200mm), Moderately wide (60–200mm), Moderately narrow (20–60mm), Narrow (6–20mm), Very narrow (2–6mm), Extremely narrow (>0–2mm), Tight (zero).

**Infilling (Nature)**

Clean	Surface staining	Decomposed/Disintegrated rock	Quartz
Non-cohesive soil	Cohesive soil	Calcite	Manganese
Kaolin	Other (Specify)		

Give full description of infill materials/minerals where appropriate.

**Fracture State**

In drillhole cores, measure the following:

- 1) TOTAL CORE RECOVERY (TCR)      Defined as summed length of all pieces of recovered core expressed as a percentage of length drilled (core run). When the core is highly fragmented, the length of such core is estimated by assembling the fragments and estimating the length of core that the fragments appear to represent.
  
- 2) SOLID CORE RECOVERY (SCR)      Defined as the length of material, which is recovered as solid core pieces at full diameter expressed as a percentage of the length of core (drill) run.

3) ROCK QUALITY DESIGNATION (RQD) Defined as the length of solid core recovered in lengths greater than 100mm expressed as a percentage of the length of core (drill) run. Measurements are made along the core axis and core pieces must possess a full diameter to be included in the RQD value.

4) FRACTURED INDEX (FI) Defined as the number of fractures per metre run, measured over any length of reasonably uniform character, which is not necessarily the core run length. If there is a marked change in fracture frequently during a run the fracture index should be calculated for each part of the run separately. Where core is too highly fractured for fracture index to be measured the term N.I. meaning NOT INTACT is inserted.  
NR – NO RECOVERY  
NA – NOT APPLICABLE

NOTE : Artificial fractures caused by core handling or by the drilling process are ignored when measuring the above values.

#### **VII) Additional Geological Information**

Record geological formation name if known. Avoid conjecture. Refer to HKGS maps & memoirs for further information.

#### **VIII) Other Qualifying Remarks**

At the end of the description comments can be made on the nature of joints and discontinuities, mineralisation and other factors that may be engineering or descriptive importance.

Examples:

Very strong, light greyish pink, slightly decomposed fine-grained GRANITE, with closely to medium spaced, iron stained joints dipping at subhorizontal to 10°, 40° and 85°. (One subvertical joint)

Extremely weak, light yellowish brown spotted with grey, dark brown and white, completely decomposed, medium-grained GRANITE, with occasional relict joints. (Slightly silty/clayey, fine SAND with some subangular fine to coarse gravel).

## **Appendix H**

### **Legend for use on Exploratory Station Records**

Legend Code (field GEOL LEG)

AGGLOM	Agglomerate
ASPHALT	Asphalt
BASALT	Basalt
BIOCLAST	Shells
BLANK	Material not recovered
BLDR	Boulders
BLDRCBBL	Boulders and Cobbles
BRECCIA	Sedimentary Breccia
CBBL	Cobbles
CLAY	Clay
CLAYSTON	Claystone
CONCRETE	Concrete
CONGLOM	Conglomerate
DOLOMITE	Dolomitic Limestone
FILL	Artificial Fill
FISSIN	Fissure Infill
GABBRO	Gabbro, Lamprophyre
GNEISS	Gneiss
GRACBBZS	Silty Sandy GRAVEL and COBBLES
GRANITE	Granite
GRAV	Gravel
GRAVCBBL	Gravel and Cobbles
LST	Limestone
LSTSLT	Interbedded Limestone and Siltstone
MARBLE	Marble
METACON	Metamorphic Rock - contact
METAREG	Metamorphic Rock - regional
MUDSTONE	Mudstone
ORGANICS	Organic, Peat
PEGMTITE	Pegmatite
PHYLLITE	Phyllite, Mylonite
QUARTZIT	Quartzite
RHYOLITE	Rhyolites
SAND	Sand
SANDSTON	Sandstone
SCHIST	Schist
SHALE	Shale
SILT	Silt
SILTSTON	Siltstone
SYENITE	Granodiorite, Syenite, Monzonite
TRACHYTE	Trachyte
TUFF	Coarse Ash Tuff, Lapilli Tuff
TUFFFINE	Fine Ash Tuff

Notes :

In common ground the following codes are added to the main descriptor in the order stated below to denote secondary constituents :

- |                 |                  |
|-----------------|------------------|
| (i) C - Clay    | (v) K - Cobbles  |
| (ii) Z - Silt   | (vi) O - Organic |
| (iii) S - Sand  | (vii) B - Shells |
| (iv) G - Gravel |                  |

e.g. a silty CLAY with occasional shells and organic material is coded as CLAYZOB






Figure 1.1  
Location Plan of the Site





石芽山  
SHEK NGA SHAN

黃竹山  
Wong Chuk Shan

水牛山  
BUFFALO HILL

打邊油坳  
BUFFALO PASS  
(TA SHE YAU AU)

芙蓉別  
FU YUNG PIT

黃牛山  
WEST BUFFALO HILL

石芽背  
SHEK NGA PUI

尖尾峰  
TSIM MEI FUNG

大灘上洋  
Tai No Sheung Yeung

大灘  
Tai No

**SITE**

屋嶺  
UK Cheung

北港  
Pak Kong

瓦寮  
Wu Lei Tau

金鐘  
Kei Pik Shan

三堆田  
Sam Fai Tin

象寮石  
Hing Keng Shek

西貢  
SAI KUNG

青石小築  
Rubi Chai

大灘村  
Kau Sai San Tsuen

沙灣  
Pak Sha Wan

橫瀾  
Wang Che

田寮  
Tin Liu

葵成  
Kai Ham

翠濠庭  
Greenview  
Villas

綠村  
Luk Mei Tsuen


松濤軒  
Venice Villa

綠濠  
Ho Chung

翠濠灣  
Marina Cove

沙灣  
Pak Sha Wan






— Site Boundary

**Division**

**Scale** 1:1000

**Date** 2/10/2024




The Government of the Hong Kong SAR





Figure 1.2

Lot Boundary Plan of the Site



### LandLot

- BuildingLicence
- ConditionPolygon
- DepositAreaAndVestingO
- GLA
- LAOPropertyManagemen
- LicenceAndPermitLine
- LicenceAndPermitPoly
- Lot
- MICA
- TenancyLine
- TenancyPoly
- Waiver

**Division**


**Scale** 1:500

**Date** 2/10/2024



Figure 1.3  
Aerial View of the Site






● BlankOrtho

**The Site**


<b>Division</b>	
<b>Scale</b>	1:5000
<b>Date</b>	2/10/2024



The Government of the Hong Kong SAR



Figure 2.1  
Topographic Survey Plan



**Notes:**

- All levels are in metres above HK Principal Datum
- Grid lines are in H.K. Metric Grid 1980.
- Elevations of kerb are referred to the bottom of kerb

- Legend:**
- Foul Water Manhole
  - 0.30m CC Covered Channel and Invert Level
  - 0.30m UC U-Channel and Invert Level
  - Gully
  - Catch Pit
  - Valve Water
  - Telecom Manhole
  - Slope
  - T1 Tree & Tree Number
  - Lamp Post
  - Telephone Pole / Manhole
  - Gate
  - Fence & Railing
  - Retaining Wall
  - lot Boundary Line

**Tree Table**

Tree No.	Girth (m)	Height (m)	Spread (m)
T1	0.72	6	5
T2	0.43	6	4
T3	0.41	6	3
T4	0.42	5	2
T5	0.67	6	4
T6	0.46	6	4
T7	0.61	5	3
T8	0.56	6	4
T9	0.53	6	4
T10	0.72	6	6
T11	0.70	3	2
T12	0.44	3	4
T13	0.83	5	4
T14	0.40	5	3
T13A	1.53	7	5
T14A	1.22	8	6
T15	0.74	5	4
T16	1.09	9	6
T17	0.51	4	3
T18	0.40	5	5
T19	0.30	4	4
T20	0.30	4	6
T21	0.40	6	6
T22	0.83	7	6
T23	1.02	9	6
T24	1.03	9	6
T25	0.79	9	5
T26	0.70	7	7
T27	1.32	9	7
T28	0.37	3	2
T29	0.57	4	3
T30	0.53	5	2
T31	0.35	4	1
T32	0.52	5	2
T33	0.33	4	1
T34	0.62	5	5
T35	0.46	5	4
T36	0.58	4	5
T37	0.64	6	4

**Extension to Lot No. 214**  
Boundary Dimensions (Area = 15581-97.51 sqm)

From To	Bearing	Dist. (m)	Pt.	N	E
A B	104°44'40"	5.210	A	825 016.016	843 738.168
B C	211°32'30"	1.634	B	825 014.650	843 743.296
C D	111°13'30"	11.186	C	825 016.400	843 743.870
D E	197°35'40"	17.070	D	825 012.350	843 754.257
E F	201°00'00"	8.533	E	824 996.110	843 749.038
F G	196°16'10"	7.667	F	824 988.160	843 745.965
G H	289°45'10"	7.354	G	824 980.800	843 743.817
H J	331°54'50"	12.817	H	824 982.797	843 736.739
J K	Ch. 00°18'10"	9.884	J	824 994.105	843 730.705
K L	29°41'40"	10.838	K	825 003.989	843 730.757
L A	Ch. 41°10'30"	3.349	L	825 013.495	843 735.963

Arc Len. Incl. Angle Radius N (Centre) E  
 J-K 10.301 56°46'30" 10.394 824 998.998 843 739.875  
 L-A 3.376 24°58'00" 7.748 825 009.775 843 742.759

**Lot No. 214**  
Boundary Dimensions (Area = 97.5 sqm)

From To	Bearing	Dist. (m)	Pt.	N	E
M N	115°20'10"	7.620	M	825 010.638	843 742.300
N P	205°20'10"	12.802	N	825 007.397	843 749.187
P Q	295°00'10"	7.650	P	824 995.626	843 743.709
Q M	25°20'10"	12.802	Q	824 999.087	843 736.822

**Drawing title**  
Topographical Survey Plan of No. 214 and the Extension Thereto in D.D. 219, No. 50 Tin Shek Road, Sai Kung


Drawing no.	Date	Scale
HC-15840/01	13/04/2023	1 : 100 (A1)
	Checked by	Drawn by
	H. So	H.Y. Poon

**Surveyor**  
HENRY CHAN SURVEYORS LTD.  
Authorized Land & Hydrographic Survey  
Shop 7, Mei Hing Mansion, Tel : 2638-1313 Fax : 2638-1328  
1-17 Yan Hing Street, Tai Po, N.H.K. Email : hcsurvey@netvigator.com

DRAFT 2023-04-14

Figure 2.2

Topographic Survey Plan in Map



- Notes:**
- All levels are in metres above HK Principal Datum
  - Grid lines are in H.K. Metric Grid 1980.
  - Elevations of kerb are referred to the bottom of kerb.

- Legend:**
- Foul Water Manhole
  - Covered Channel and Invert Level
  - U-Channel and Invert Level
  - Gully
  - Catch Pit
  - Valve Water
  - Telecom Manhole
  - Slope
  - Tree & Tree Number
  - Lamp Post
  - Telephone Pole / Manhole
  - Gate
  - Fence & Railing
  - Retaining Wall
  - Lot Boundary Line

**Tree Table**

Tree No.	Girth (m)	Height (m)	Spread (m)
T1	0.72	6	5
T2	0.43	6	4
T3	0.41	5	3
T4	0.42	5	2
T5	0.67	6	4
T6	0.46	6	4
T7	0.61	5	3
T8	0.55	6	4
T9	0.53	6	4
T10	0.72	6	4
T11	0.70	3	2
T12	0.44	5	4
T13	0.83	5	4
T14	0.40	5	3
T15	0.53	5	4
T16	1.22	8	6
T17	0.74	7	5
T18	1.09	9	6
T19	0.51	5	3
T20	0.40	4	3
T21	0.30	4	2
T22	0.80	6	5
T23	1.02	9	6
T24	1.03	9	6
T25	0.79	7	5
T26	0.70	7	5
T27	1.32	9	7
T28	0.37	3	2
T29	0.57	4	3
T30	0.53	5	2
T31	0.36	4	1
T32	0.52	5	2
T33	0.33	4	1
T34	0.62	5	5
T35	0.46	5	4
T36	0.58	4	5
T37	0.64	6	4

**Extension to Lot No. 214**  
Boundary Dimensions: (Area = [558.1-97.5] sqm)

From: T13	Bearing	Dist. (m)	P1	N	E		
A	104°44'40"	5.210	A 825	016.016	843	738.168	
B	21°13'30"	1.834	B 825	014.650	843	743.206	
C	111°13'30"	11.186	C 825	016.400	843	743.870	
D	197°56'50"	17.970	D 825	013.350	843	754.297	
E	201°08'00"	8.523	E 824	098.110	843	749.038	
F	190°19'10"	7.667	F 824	080.180	843	745.960	
G	289°45'10"	7.354	G 824	060.800	843	743.817	
H	331°54'50"	12.817	H 824	062.977	843	756.758	
J	00°18'10"	9.884	J 824	064.105	843	730.705	
K	281°41'00"	10.838	K 825	003.989	843	730.957	
L	411°01'30"	3.349	L 825	013.435	843	735.963	
Arc. A-L							
J/K	10.301	56°46'00"	10.304	824	068.959	843	739.875
L/A	3.376	24°58'00"	7.748	825	009.775	843	742.759

**Lot No. 214**  
Boundary Dimensions: (Area = 97.5 sqm)

From: T5	Bearing	Dist. (m)	P1	N	E	
M	115°20'10"	7.620	M 825	010.658	843	742.300
N	295°20'10"	12.802	N 825	007.397	843	748.187
P	295°20'10"	7.620	P 824	095.525	843	743.709
Q	25°20'10"	12.802	Q 824	099.087	843	736.622

**Drawing title**

**Topographical Survey Plan of No. 214 and the Extension Thereto in D.D. 219, No. 50 Tin Shek Road, Sai Kung**

**Drawing no.** 13/04/2023

**Date** 1:100 (A1)

**Scale**

**Checked by** H. So

**Drawn by** H.Y. Poon

**Surveyor**

**HENRY CHAN SURVEYORS LTD.**  
Authorized Land & Hydrographic Surveyors

Shop 7, Mei Hing Mansion, Tel: 2638-1313 Fax: 2638-1528  
117 Yan Hing Street, Tai Po, N.T. e-mail: hcsurvey@inetigator.com

Henry H K Chan  
BSc (Hons) RPS(LS)  
Authorized Land Surveyor

DRAFT 2023-04-14




## Figure 3

Extract of GASP Report Map – Geological  
Map

LEGEND

- Geological boundary, position certain
- - - - Geological boundary, position approximate
- · · · · Geological boundary (superficial)
- +—+—+ Geological cross-section line
- Strike and dip of beds
- Vertical bedding
- Horizontal bedding
- Strike and dip of flow-banding in lavas
- Vertical flow banding in lavas
- Fault
- Geological photolineament (from Allen & Stephens, 1971)
- Geological photolineament (approximate)
- ⊗ Catchment boundary with order shown
- Main drainage divide, low order catchment
- Depth in fathoms
- ▨ General instability
- 730 Universal Transverse Mercator (UTM) Grid Reference
- 721 Hong Kong Metric Grid Reference




The Site

白沙灣  
PAK SHA WAN  
(HEBE HAVEN)

Map Unit	Weathering and Soil Development	Engineering Comment (Stability, Foundation, Hydrogeology)	Material Uses and Excavation Characteristics
(Pattern: horizontal lines)	Soils are in relatively good condition. See notes on page 21 for a detailed assessment with long-term weathering data.	The rockmass is highly fractured and weathered, and is generally of low strength. Excavation should be carried out with care.	Can be excavated and used after weathering. Fresh rock and soil should be used for concrete. In situ weathering should be avoided. See notes on page 21 for a detailed assessment with long-term weathering data.
(Pattern: vertical lines)	Soils are in relatively good condition. See notes on page 21 for a detailed assessment with long-term weathering data.	The rockmass is highly fractured and weathered, and is generally of low strength. Excavation should be carried out with care.	Can be excavated and used after weathering. Fresh rock and soil should be used for concrete. In situ weathering should be avoided. See notes on page 21 for a detailed assessment with long-term weathering data.
(Pattern: diagonal lines)	Soils are in relatively good condition. See notes on page 21 for a detailed assessment with long-term weathering data.	The rockmass is highly fractured and weathered, and is generally of low strength. Excavation should be carried out with care.	Can be excavated and used after weathering. Fresh rock and soil should be used for concrete. In situ weathering should be avoided. See notes on page 21 for a detailed assessment with long-term weathering data.
(Pattern: dotted)	Soils are in relatively good condition. See notes on page 21 for a detailed assessment with long-term weathering data.	The rockmass is highly fractured and weathered, and is generally of low strength. Excavation should be carried out with care.	Can be excavated and used after weathering. Fresh rock and soil should be used for concrete. In situ weathering should be avoided. See notes on page 21 for a detailed assessment with long-term weathering data.

Figure 4

ENTLI – Landslide Record



**ENTLI Crown (2019)**

- + Recent
- + Relict

**ENTLI Trail (2019)**

- Recent
- Relict

**Division**

**Scale** 1:3000

**Date** 28/10/2024






Figure 5

Area of QRA of Boulder Fall Hazards No.  
S7\_U



Back

Boulder No. S7\_U

Map Sheet 7

Boulder Type

% of area covered by boulders No data

% of boulder < 1 m

% of boulder 1-2 m

% of boulder 2-5 m


% of boulder > 5 m

SITE



Hebe Haven  
白沙灣


0.6km



## Figure 6

Extract of GASP Report Map –  
Geotechnical Land Use Map





LEGEND

CLASS	CODE	GEOTECHNICAL LIMITATIONS	SUITABILITY FOR DEVELOPMENT	ENGINEERING COST FOR DEVELOPMENT	INTENSITY OF SITE INVESTIGATION REQUIRED
I	[Blank]	Low	High	Low	Normal
II	[Dotted]	Moderate	Moderate	Normal	Normal
III	[Cross-hatched]	Moderate	Moderate - Low	Normal - High	Normal
IV	[Diagonal lines]	High	Low	High	Intensive
V	[Diagonal lines]	Extreme	Probably Unsuitable	Very High	Very Intensive

General Features - terrain which is not classified within the GLUM system

- [Dotted pattern] Waterbodies (streams, man-made channels, storage dams)
- [Blank pattern] Ponds
- [Wavy line pattern] Littoral Zone (generally subject to tidal action)
- [Cross-hatched pattern] Wave cut platform

<sup>2</sup>30 Universal Transverse Mercator (UTM) Grid Reference

<sup>2</sup>24 Hong Kong Metric Grid Reference




## Figure 7

Extract of GASP Report Map – Physical  
Constraints Map

**LEGEND**


- Colluvium
- Zones of colluvium which are subject to overland flow and periodic inundation. Evidence of unusual groundwater regime (delineated as drainage plain on Landform Map).
- Floodplain - subject to overland flow and regular inundation. Evidence of unusual groundwater regime (delineated as floodplain on Landform Map).
- Zones of general instability associated with predominantly colluvial terrain
- Zones of general instability associated with predominantly insitu terrain
- Slopes on insitu terrain which are generally steeper than 30° (other than those delineated as colluvial or unstable)
- Disturbed terrain - extensive cut and fill batters which generally exceed 30°
- Instability on disturbed terrain
- Waterbodies (streams, man-made channels, storage dams)
- Ponds
- Moderate or severe gully erosion (may be superimposed upon other constraints)
- Littoral zone (generally subject to tidal action)
- Wave cut platform
- 30 Universal Transverse Mercator (UTM) Grid Reference
- 24 Hong Kong Metric Grid Reference



## Figure 8

Record from Historical Landslide  
Catchment Inventory





Historical Landslide Catchment (2016)

Division

Scale 1:5000

Date 28/10/2024



The Government of the Hong Kong SAR