

Proposed Development of Hong Kong Sheng Kung Hui St. Christopher's Complex at the Remaining Portion of Taxlord Lot No. T77 In D.D.34. Tai Po

Sewerage Impact Assessment Report

Reference: P060/01 Issue 6

Date: January 2025

Confidential





Proposed Development of Hong Kong Sheng Kung Hui St. Christopher's Complex at the Remaining Portion of Taxlord Lot No. T77 In D.D.34. Tai Po

Sewerage Impact Assessment Report

Reference: P060/01 Issue 6

Date: January 2025

Issue	Status	Prepared By	Date	Checked by	Date	Approved By	Date
1	Final	AIC	26-May-22	EMT	26-May-22	JOC	26-May-22
2	Draft	AIC	7-Feb-24	EMT	7-Feb-24	JOC	7-Feb-24
3	Final	Various	9-Jul-24	EMT	9-Jul-24	JOC	9-Jul-24
4	Final	Various	13-Dec-24	EMT	13-Dec-24	JOC	13-Dec-24

23/F, Wui Tat Centre, No. 55 Connaught Road West, Hong Kong

Tel: (852) 3114 1144

Urban Green Consultants Ltd. assumes no responsibility and shall not be liable for any loss, damage or expense caused by reliance on the information or advice in this document to any third parties. Urban Green Consultants Ltd. also assumes no responsibility and shall not be liable for any loss, damage or expense caused by reliance on the information or advice in this document to the client unless the same is proved to have arisen solely from the negligence or wilful default of Urban Green Consultants Ltd in which case our contractual limit of liability shall apply.

Contents

1	Introduction	1
1.1	Background	1
1.2	Objective of the SIA	1
1.3	Report Structure	1
2	Site Context	2
2.1	Site Location and Its Environs	2
2.2	Proposed Development Scheme	2
2.3	Existing Sewerage Condition	2
3	Evaluation of Sewerage Impact	3
3.1	Assumptions and Methodology	3
3.2	Proposed Sewerage Treatment Plant	4
3.3	Emergency Measures	6
3.4	Recommendation	6
4	Environmental Considerations	7
5	Conclusion	8

List of Figures

- Figure 2.1 Site Location and Its Environs
- Figure 3.1 Location of the Proposed Sewerage Treatment Plant
- Figure 3.2 Proposed Discharge Location
- Figure 3.3 Location of the Downstream Receiving Water Bodies

List of Tables

- Table 3.1 Estimated Population of the Proposed Development
- Table 3.2 Key Parameters of Discharge Standards

List of Appendices

- Appendix A Development Plan
- Appendix B Calculation of Peak Flow
- Appendix C Sewerage Treatment Plant Design Calculation (Tentative)
- Appendix D Relevant Effluent Quality Standards
- Appendix E Existing Drainage System Capacity Calculation
- Appendix F Comment from the Regional Officer

1 Introduction

1.1 Background

- 1.1.1 The Applicant intends to develop a community service complex (hereafter as “the proposed development”) for providing childcare and elderly care services at the remaining portion of Taxlord Lot No. T77 in D.D.34, Tai Po (hereafter as “the Site”).
- 1.1.2 According to the **Approved** Tai Po Outline Zoning Plan (OZP) (**OZP No.: S/TP/30**) published by Town Planning Board in **July 2022**, the Site is in the “Government, Institution or Community” Zone.
- 1.1.3 Urban Green Consultants Limited (UGC) was commissioned by the Applicant to conduct a Sewerage Impact Assessment (SIA) to assess the potential sewerage impacts arising from the change of sewerage generation due to the Proposed Development.

1.2 Objective of the SIA

- 1.2.1 The objectives of this SIA are to assess the potential sewerage impacts arising from the proposed development and recommend the mitigation measures, if necessary, to alleviate the impacts.

1.3 Report Structure

- 1.3.1 The remaining chapters of this report are shown below:

Chapter 2 – Site Context

Chapter 3 – Evaluation of Sewerage Impact

Chapter 4 – Environmental Considerations

2 Site Context

2.1 Site Location and Its Environs

- 2.1.1 The Site is bounded by Tai Po Road – Tai Po Kau to its South. The Japanese International School is located at the West of the Site, while Po Leung Kuk Tin Ka Ping Millennium Primary School is at the Northeast of the Site. The site area is approximately 2,210.2m².
- 2.1.2 [Figure 2.1](#) shows the Site location and its environs.

2.2 Proposed Development Scheme

- 2.2.1 The proposed development is a 10-storey building which consists of seven department units, i.e. Special Child Care Centre (SCCC), Care and Attention Home Providing Continuum of Care (CoC Home), Small Group Home (SGH), Foster Care Service and Agency-based Enhancement of Professional Staff Support Services (FCS), Staff Training Unit (STU), and Child Care Centre (CCC). There will also be residential places for the elderly, a basement carpark, and a localized sewerage treatment plant on B2/F. The anticipated commissioning year of the proposed development is 2030.
- 2.2.2 The development plans are shown in [Appendix A](#).

2.3 Existing Sewerage Condition

- 2.3.1 Based on the review of drainage plans (reference no.: 7-NE-11C-4, 7-NE-11D-3, 7-NE-16A-2 and 7-NE-16B-1) from Drainage Services Department (DSD) in November 2015, it has revealed that the Site is not served by any form of DSD's sewerage facility currently.

3 Evaluation of Sewerage Impact

3.1 Assumptions and Methodology

- 3.1.1 For the sewerage flow estimation from the proposed development, the ceiling unit flow rates as recommended in the “Guidelines for Estimating Sewerage Flows for Sewerage Infrastructure Planning” (hereafter as “GESF”) published by the Environmental Protection Department (EPD) in 2005 have been adopted in the assessment.
- 3.1.2 The sewerage generation from the proposed development includes the flow contribution from the staffs, visitors and residents in the proposed development. The population for the proposed development is summarised in Table 3.1.
- 3.1.3 The estimation of pollution loadings from the Proposed Development is based on the basic design parameters of Biochemical Oxygen Demand (BOD) and Suspended Solid (SS) loads for commercial populations as stipulated in “Guidelines for the Design of Small Sewerage Treatment Plants”.
- 3.1.4 In the calculation of sewerage generation from both **overnight and non-overnight staff**, the unit flow factor of 0.28m³/person/day was adopted. And the unit flow factor of 0.19m³/person/day was adopted for residents. As for visitors, the unit flow factor adopted is 0.015m³/person/day. For kitchen staff, the unit flow factor adopted is 1.58m³/person/day

Table 3.1 Estimated Population of the Proposed Development

Type of People	No. of persons	Unit Flow Factor (m ³ /person/day)	Category
Staff (non-overnight)	235	0.28	Commercial Employee + Commercial activities – J11 Community, Social & Personal Services in Table T-2 of GESF ^[1]
Staff (overnight)	20	0.28	“Services” in Appendix 2 of GDSSTP ^[2]
Residents	454	0.19	Domestic – Institutional and special class in Table T-1 of GESF ^[1]
Visitors	190	0.015	“Visitor” of Table 3-4 of “Wastewater Engineering Treatment and Reuse” published by Metcalf & Eddy
Staff (Kitchen)	5	1.58	Commercial Employee + Commercial Activities J10 - Restaurants & Hotels in Table T-2 of GESF(b) ^[1]

Notes:

- [1] Environmental Protection Department, HKSARG [EPD] (2005). Guidelines for estimating sewerage flows for sewerage infrastructure planning (EPD/TP 1/05).
- [2] Environmental Protection Department, HKSARG [EPD] (2006). Guidelines for the Design of Small Sewage Treatment Plants

- 3.1.5 The estimated daily flow and hourly flow from the proposed development will be 168.41m³/day and 42.10m³/hr, respectively. The calculations have been provided in [Appendix B](#) for reference.

3.2 Proposed Sewerage Treatment Plant

- 3.2.1 As the Site is not served by public sewer, it is required to provide their own sewerage treatment or disposal facilities to ensure sewerage can be discharged in a proper manner and hence to achieve the best protection to the public and the environment. The use of small Sewerage Treatment Plant (STP) with tertiary wastewater treatment technology is recommended to ensure the sewerage generated from the proposed development will be treated to acceptable level before discharge. The location of the proposed underground sewerage treatment plant is shown in [Figure 3.1](#).
- 3.2.2 The "Guidelines for the Design of Small Sewerage Treatment Plants" published by the EPD for the design, construction, operation, and maintenance of STP should be followed. The effluent quality should comply with the "Standards for effluents discharged into Group D inland waters" and the "Standards for effluents discharged into the coastal waters of Tolo and Port Shelter Water Control Zones" as specified in the "Technical Memorandum on Standards for Effluents Discharged into Drainage and Sewerage Systems, Inland and Coastal Waters (TM-DSS)". The discharge standards of the proposed STP shall adopt the higher standards of the above standards. The key parameters are summarised in Table 3.2.

Table 3.2 Key Parameters of Discharge Standards

Key Parameters	Standards for effluents discharged into Group D inland waters (for flow ≤ 200 m ³ /d)	Standards for effluents discharged into coastal waters of Tolo and Port Shelter Water Control Zones (for flow >10 and ≤ 200 m ³ /d)	Standards for effluents discharged into Group D inland waters (for flow >600 and ≤ 800 m ³ /d)	Standards for effluents discharged into coastal waters of Tolo and Port Shelter Water Control Zones (for flow >600 and ≤ 800 m ³ /d)	Discharge Standard for the Proposed Development
Biochemical Oxygen Demand BOD (mg/L)	20	20	20	20	20
Suspended Solids TSS (mg/L)	30	30	30	30	30
Ammonia Nitrogen NH ₃ -N (mg/L)	20	-	20	-	20
E.coli (count/100mL)	1000	1000	1000	1000	1000
Total Phosphorus TP (mg/L)	10	8	8	5	5
COD	80	80	80	80	80
Surfactants	15	15	15	15	15
Oil & grease	10	20	10	20	10
Total Nitrogen	-	20	-	15	15
Nitrate + Nitrite Nitrogen	50	-	30	-	30

Notes:

[i] All units in mg/L

[ii] All figures are upper limits

- 3.2.3 In order to fulfil the required discharge standards, the proposed STP will provide tertiary treatment and nitrogen, phosphorus removal treatment. The proposed STP will be equipped with biological treatment by Contact Aeration Process, Ultra Filtration System and Ultra Violet (UV) Sterilization. Furthermore, the treated sewerage from the Site will be discharged in accordance with the Water Pollution Control (General) Regulation. Therefore, no adverse water quality impact due to sewerage generation from the proposed development will be anticipated.
- 3.2.4 The treated sewerage and the drainage discharge from the site boundary will be discharged into the existing drainage system through DSD catchpit SCH1003542. Peak runoff is estimated to be 0.113m³/s, which exceeds the capacity of the drainage pipes, as shown in [Appendix E](#). Upgrading works of the drainage system will be required to cater the treated sewerage and drainage discharge.
- 3.2.5 The treated sewage and drainage discharge from the site boundary will be directed into the existing drainage system via DSD catchpit SCH1003542, which connects to box culvert SBP1001645 and subsequently discharges into Tolo Harbour through box culvert SBP100293. These two box culverts are linked by a channelized culvert passing through Villa Castell. No other beneficial uses of inland water were identified

in the downstream receiving waters. The location of the downstream receiving water bodies is shown in [Figure 3.3](#).

3.3 Emergency Measures

- 3.3.1 Submersible pump, air blower, chemical dosing pump and submersible ejector will be provided with standby unit. An emergency generator will be provided in case electric power supply for whole system **fails**. As such, suspension of whole STP operation is **rare** under normal operation.
- 3.3.2 Regular preventive maintenance service will be provided to check operation condition of equipment and plan the repairing and replacement scheme for equipment and material of treatment system. An operation and maintenance manual will be prepared by the contractor and then the future operator should appoint competent technician(s) to operate the STP. The operator should be fully conversant with the recommended operating procedures as stipulated in the operation and maintenance manual.
- 3.3.3 In case of STP failure, raw sewerage will be temporarily stored in the equalization tank with volume to 2.19 hours retention time on peak flow, a 30.80m³ effective tank volume of equalization tank will be provided. The detailed design calculation as shown in [Appendix C](#). Real-time monitor will be provided to monitoring the sewerage flow. In the event of any emergency overflow, on-call crews will follow the overflow emergency response plan and proceed with the best response to correct the problem at once. For example, the alarm system will be activated once overflow occurs. The on-call crews will provide instant response by acknowledging the alarm, to investigate the cause of overflow and correct the problem. The alarm system will be repeated until it is acknowledged. In addition, the on-call crews will ensure the standby pump is switched on and contains the overflow sewage using temporary weirs or vacuum trucks, where applicable. Furthermore, tanker away service will be arranged immediately to draw away the sewerage from equalization tank to avoid flooding from treatment system.

3.4 Recommendation

- 3.4.1 Upon detailed design stage of the Project, the project proponent will appoint authorized Persons and consultant to design the STP. Detailed information of the proposed STP will be prepared and submitted to EPD and DSD during the detailed design stage.


4 Environmental Considerations

- 4.1.1 The proposed on-site STP will be fully enclosed and integrated with ventilation system equipped. Odour treatment facilities shall be installed with the ventilation system to remove any odour from the STP.
- 4.1.2 To be prudent, the STP should also implement good housekeeping practices to ensure that the continuous operation of the on-site STP will not generate any unacceptable odour impact on the surrounding environment. These should include the regular inspection of treatment components where odour could be produced, regular cleaning and flushing of screens and other sewerage handling equipment to remove odorous sources, proper handling, and disposal of collected grit and sludge, regular inspections and maintenance of the deodorisation and ventilation systems.
- 4.1.3 As the proposed on-site STP will be fully enclosed by the building structure of the proposed development, the potential breakout noise from the STP upon the surroundings should be minimal.
- 4.1.4 After the implementation of the above measures, the potential odour and noise impact due to the operation of the on-site STP would be minimal or negligible.

5 Conclusion

- 5.1.1 A Sewerage Impact Assessment (SIA) has been conducted to evaluate the potential impacts due to the sewerage generation from the proposed development.
- 5.1.2 The proposed development will serve approximately 904 people and the estimated sewerage generation from the proposed development will be approximately 168.41m³/day.
- 5.1.3 As there is no existing public sewerage in the vicinity of the Site and, to fulfil the required discharge standards, an underground Sewerage Treatment Plant (STP) will be provided by the Applicant.
- 5.1.4 The proposed STP will be designed, constructed, operated and maintained in accordance with the "Guidelines for the Design of Small Sewerage Treatment Plants" published by the EPD to ensure the sewerage generated from the proposed development will be treated to acceptable standards before discharge to the receiving water. Effluent discharge location from the proposed underground STP will be discharged into the existing drainage system to the west of the Site. No adverse water quality impact due to sewerage generation from the proposed development is anticipated.
- 5.1.5 With the implementation of mitigation measures including the emergency generator, spare pumps, emergency storage and control system etc, no emergency sewage discharge during the operation of STP is anticipated.
- 5.1.6 The flow of the sewerage generated and stormwater runoff from the Site will, however, exceed the capacity of the existing drainage system. Upgrading works of the drainage pipes will be required to cater the treated sewerage and drainage discharge.
- 5.1.7 With the proposed upgrading works, it is concluded that there shall be no sewerage impact arising from the proposed development.

Figures



LEGEND
 Project Site

0 50m



Proposed Development of Hong Kong Sheng Kung Hui St. Christopher's Complex at the Remaining Portion of Taxlord Lot No. T77 In D.D.34. Tai Po

The Site and Its Environs

Figure 2.1

Rev. 0



LEGEND

- Project Site
- Proposed Sewage Treatment Plant




Proposed Development of Hong Kong Sheng Kung Hui St. Christopher's Complex at the Remaining Portion of Taxlord Lot No. T77 In D.D.34. Tai Po

Location of the Proposed Sewage Treatment Plant

Figure 3.1

Rev. 1




Proposed Development of Hong Kong Sheng Kung Hui St. Christopher's Complex at the Remaining Portion of Taxlord Lot No. T77 In D.D.34. Tai Po

Proposed Discharge Location

Figure 3.2

Rev. 1



LEGEND

- Project Site
- Existing Drainage System
- Proposed Discharge Point
- Down Stream Water Bodies



Proposed Development of Hong Kong Sheng Kung Hui St. Christopher's Complex at the Remaining Portion of Taxlord Lot No. T77 in D.D.34 Tai Po

Location of the Downstream Receiving Water Bodies

Figure 3.3
Rev. 0

Appendix A


Development Plan



Department Legend

- (A) 289 place CoC Home
- (C) 100 place Special Child Care Centre (SCCC)
- (D) 65 place Child Care Center (CCC)
- BOH
- BOH Circulation
- Common Connection
- Outdoor Space
- Vehicular Circulation

BD REF -		
BIM REF -		
FSD REF -		
Rev.	Date	Amendment Purpose
PROJECT NO.: HKA-P-01757		
<ul style="list-style-type: none"> • This drawing and the contents herein are the copyright of LWK & Partners(HK) Ltd. • No part of the drawing and the design contained herein may be reproduced without the prior written consent of a director of LWK & Partners (HK) Ltd. • Do not take measurements directly from this drawing. • Check and verify all dimensions on site. • Read this drawing in conjunction with the specifications and all other related drawings. • Notify the Architect immediately of any discrepancy found herein. 		
CLIENT Hong Kong Sheng Kung Hui Welfare Council Limited		
PROJECT TFS for The Proposed Hong Kong Sheng Kung Hui St. Christopher's Complex		
DRAWING TITLE GF Plan		
SCALE 1 : 200 @A3		
DRAWING NO. A001	ISSUE DATE 07/03/24	
LEAD CONSULTANT & ARCHITECT		
LWK + PARTNERS		
BUILDING SERVICES ENGINEER WSP Hong Kong Limited		
STRUCTURAL, CIVIL & GEOTECHNICAL ENGINEER JMK Consulting Engineers Limited		
TRAFFIC ENGINEER Ho Wang SPB Limited		
ENVIRONMENTAL CONSULTANT Urban Green Consultants Limited		
QUANTITY SURVEYOR Rider Levett Bucknall Ltd		
LANDSCAPE ARCHITECT Otherland Limited		




Department Legend

- (A) 289 place CoC Home
- (C) 100 place Special Child Care Centre (SCCC)
- (D) 65 place Child Care Center (CCC)
- BOH Circulation
- Common Connection
- Outdoor Space


BD REF -		
BIM REF -		
FSD REF -		
Rev.	Date	Amendment Purpose
PROJECT NO.: HKA-P-01757		
<ul style="list-style-type: none"> • This drawing and the contents herein are the copyright of LWK & Partners(HK) Ltd. • No part of the drawing and the design contained herein may be reproduced without the prior written consent of a director of LWK & Partners (HK) Ltd. • Do not take measurements directly from this drawing. • Check and verify all dimensions on site. • Read this drawing in conjunction with the specifications and all other related drawings. • Notify the Architect immediately of any discrepancy found herein. 		
CLIENT Hong Kong Sheng Kung Hui Welfare Council Limited		
PROJECT TFS for The Proposed Hong Kong Sheng Kung Hui St. Christopher's Complex		
DRAWING TITLE 1F Plan		
SCALE 1 : 200 @A3		
DRAWING NO. A002	ISSUE DATE 16/02/24	
LEAD CONSULTANT & ARCHITECT		
LWK + PARTNERS		
BUILDING SERVICES ENGINEER WSP Hong Kong Limited		
STRUCTURAL, CIVIL & GEOTECHNICAL ENGINEER JMK Consulting Engineers Limited		
TRAFFIC ENGINEER Ho Wang SPB Limited		
ENVIRONMENTAL CONSULTANT Urban Green Consultants Limited		
QUANTITY SURVEYOR Rider Levett Bucknall Ltd		
LANDSCAPE ARCHITECT Otherland Limited		



BD REF -		
BIM REF -		
FSD REF -		
Rev.	Date	Amendment Purpose
PROJECT NO.: HKA-P-01757		
<ul style="list-style-type: none"> This drawing and the contents herein are the copyright of LWK & Partners(HK) Ltd. No part of the drawing and the design contained herein may be reproduced without the prior written consent of a director of LWK & Partners (HK) Ltd. Do not take measurements directly from this drawing. Check and verify all dimensions on site. Read this drawing in conjunction with the specifications and all other related drawings. Notify the Architect immediately of any discrepancy found herein. 		
CLIENT Hong Kong Sheng Kung Hui Welfare Council Limited		
PROJECT TFS for The Proposed Hong Kong Sheng Kung Hui St. Christopher's Complex		
DRAWING TITLE 2F Plan		
SCALE 1 : 200 @A3		
DRAWING NO. A003	ISSUE DATE 15/01/24	
LEAD CONSULTANT & ARCHITECT		
LWK + PARTNERS		
BUILDING SERVICES ENGINEER WSP Hong Kong Limited		
STRUCTURAL, CIVIL & GEOTECHNICAL ENGINEER JMK Consulting Engineers Limited		
TRAFFIC ENGINEER Ho Wang SPB Limited		
ENVIRONMENTAL CONSULTANT Urban Green Consultants Limited		
QUANTITY SURVEYOR Rider Levett Bucknall Ltd		
LANDSCAPE ARCHITECT Otherland Limited		



BD REF -
BIM REF -
FSD REF -
Rev. Date Amendment Purpose
PROJECT NO.: HKA-P-01757
This drawing and the contents herein are the copyright of LWK & Partners (HK) Ltd. No part of the drawing and the design contained herein may be reproduced without the prior written consent of a director of LWK & Partners (HK) Ltd. Do not take measurements directly from this drawing. Check and verify all dimensions on site. Read this drawing in conjunction with the specifications and all other related drawings. Notify the Architect immediately of any discrepancy found herein.
CLIENT Hong Kong Sheng Kung Hui Welfare Council Limited
PROJECT TFS for The Proposed Hong Kong Sheng Kung Hui St. Christopher's Complex
DRAWING TITLE 3F Plan
SCALE 1 : 200 @A3
DRAWING NO. A004 ISSUE DATE 28/02/24
LEAD CONSULTANT & ARCHITECT
LWK + PARTNERS
BUILDING SERVICES ENGINEER WSP Hong Kong Limited
wsp
STRUCTURAL, CIVIL & GEOTECHNICAL ENGINEER JMK Consulting Engineers Limited
JMK
TRAFFIC ENGINEER Ho Wang SPB Limited
HWSPB Traffic & Transportation Consultants Ho Wang SPB Limited
ENVIRONMENTAL CONSULTANT Urban Green Consultants Limited
UG URBAN GREEN
QUANTITY SURVEYOR Rider Levett Bucknall Ltd
RLB Rider Levett Bucknall
LANDSCAPE ARCHITECT Otherland Limited
L otherland



Department Legend

- (A) 289 place CoC Home
- (F) Foster Care Services and Agency based Enhancement of Professional Staff Support Services (FSC & APBSS)
- (G) Staff Training Unit (STU)
- BOH Circulation
- Common Connection
- Outdoor Space

BD REF -		
BIM REF -		
FSD REF -		
Rev.	Date	Amendment Purpose
PROJECT NO.: HKA-P-01757		
<ul style="list-style-type: none"> • This drawing and the contents herein are the copyright of LWK & Partners (HK) Ltd. • No part of the drawing and the design contained herein may be reproduced without the prior written consent of a director of LWK & Partners (HK) Ltd. • Do not take measurements directly from this drawing. • Check and verify all dimensions on site. • Read this drawing in conjunction with the specifications and all other related drawings. • Notify the Architect immediately of any discrepancy found herein. 		
CLIENT Hong Kong Sheng Kung Hui Welfare Council Limited		
PROJECT	1	E005
TFS for The Proposed Hong Kong Sheng Kung Hui St. Christopher's Complex		
DRAWING TITLE 7F Plan		
SCALE 1 : 200 @A3		
DRAWING NO.	ISSUE DATE	
A005	15/01/24	
LEAD CONSULTANT & ARCHITECT		
LWK + PARTNERS		
BUILDING SERVICES ENGINEER WSP Hong Kong Limited		
STRUCTURAL, CIVIL & GEOTECHNICAL ENGINEER JMK Consulting Engineers Limited		
TRAFFIC ENGINEER Ho Wang SPB Limited		
ENVIRONMENTAL CONSULTANT Urban Green Consultants Limited		
QUANTITY SURVEYOR Rider Levett Bucknall Ltd		
LANDSCAPE ARCHITECT Otherland Limited		



Department Legend

- (Ea) Three 8-place SGH
- (Eb) One 6-place SGH
- BOH
- BOH Circulation
- Common Connection
- Outdoor Space


BD REF -		
BIM REF -		
FSD REF -		
Rev.	Date	Amendment Purpose
PROJECT NO.: HKA-P-01757		
<ul style="list-style-type: none"> • This drawing and the contents herein are the copyright of LWK & Partners (HK) Ltd. • No part of the drawing and the design contained herein may be reproduced without the prior written consent of a director of LWK & Partners (HK) Ltd. • Do not take measurements directly from this drawing. • Check and verify all dimensions on site. • Read this drawing in conjunction with the specifications and all other related drawings. • Notify the Architect immediately of any discrepancy found herein. 		
CLIENT Hong Kong Sheng Kung Hui Welfare Council Limited		
PROJECT TFS for The Proposed Hong Kong Sheng Kung Hui St. Christopher's Complex		
DRAWING TITLE 8F Plan		
SCALE 1 : 200 @A3		
DRAWING NO. A006	ISSUE DATE 15/01/24	
LEAD CONSULTANT & ARCHITECT		
LWK + PARTNERS		
BUILDING SERVICES ENGINEER WSP Hong Kong Limited		
STRUCTURAL, CIVIL & GEOTECHNICAL ENGINEER JMK Consulting Engineers Limited		
TRAFFIC ENGINEER Ho Wang SPB Limited		
ENVIRONMENTAL CONSULTANT Urban Green Consultants Limited		
QUANTITY SURVEYOR Rider Levett Bucknall Ltd		
LANDSCAPE ARCHITECT Otherland Limited		




Department Legend

- (Ec) Three 8-place SGH
- (Ed) Three 8-place SGH
- BOH
- BOH Circulation
- Common Connection
- Outdoor Space

BD REF -		
BIM REF -		
FSD REF -		
Rev.	Date	Amendment Purpose
PROJECT NO.: HKA-P-01757		
<ul style="list-style-type: none"> • This drawing and the contents herein are the copyright of LWK & Partners (HK) Ltd. • No part of the drawing and the design contained herein may be reproduced without the prior written consent of a director of LWK & Partners (HK) Ltd. • Do not take measurements directly from this drawing. • Check and verify all dimensions on site. • Revisit this drawing in conjunction with the specifications and all other related drawings. • Notify the Architect immediately of any discrepancy found herein. 		
CLIENT Hong Kong Sheng Kung Hui Welfare Council Limited		
PROJECT TFS for The Proposed Hong Kong Sheng Kung Hui St. Christopher's Complex		
DRAWING TITLE 9F Plan		
SCALE 1 : 200 @A3		
DRAWING NO. A007	ISSUE DATE 15/01/24	
LEAD CONSULTANT & ARCHITECT		
LWK + PARTNERS		
BUILDING SERVICES ENGINEER WSP Hong Kong Limited		
STRUCTURAL, CIVIL & GEOTECHNICAL ENGINEER JMK Consulting Engineers Limited		
TRAFFIC ENGINEER Ho Wang SPB Limited		
ENVIRONMENTAL CONSULTANT Urban Green Consultants Limited		
QUANTITY SURVEYOR Rider Levett Bucknall Ltd		
LANDSCAPE ARCHITECT Otherland Limited		











BD REF -
BIM REF -
FSD REF -
Rev. Date Amendment Purpose
PROJECT NO.: HKA-P-01757
<ul style="list-style-type: none"> This drawing and the contents herein are the copyright of LWK & Partners (HK) Ltd. No part of the drawing and the design contained herein may be reproduced without the prior written consent of a director of LWK & Partners (HK) Ltd. Do not take measurements directly from this drawing. Check and verify all dimensions on site. Read this drawing in conjunction with the specifications and all other related drawings. Notify the Architect immediately of any discrepancy found herein.
CLIENT Hong Kong Sheng Kung Hui Welfare Council Limited
PROJECT TFS for The Proposed Hong Kong Sheng Kung Hui St. Christopher's Complex
DRAWING TITLE RF Plan
SCALE 1 : 200 @A3
DRAWING NO. A008 ISSUE DATE 15/01/24
LEAD CONSULTANT & ARCHITECT
LWK + PARTNERS
BUILDING SERVICES ENGINEER WSP Hong Kong Limited
STRUCTURAL, CIVIL & GEOTECHNICAL ENGINEER JMK Consulting Engineers Limited
TRAFFIC ENGINEER Ho Wang SPB Limited
ENVIRONMENTAL CONSULTANT Urban Green Consultants Limited
QUANTITY SURVEYOR Rider Levett Bucknall Ltd
LANDSCAPE ARCHITECT Otherland Limited









Department Legend


- (A) 289 place CoC Home
- (C) 100 place Special Child Care Centre (SCCC)
- (D) 65 place Child Care Center (CCC)
- BOH
- BOH Circulation
- Common Connection
- Vehicular Circulation

BD REF -	
BIM REF -	
FSD REF -	
Rev.	Date Amendment Purpose
PROJECT NO.: HKA-P-01757	
<ul style="list-style-type: none"> • This drawing and the contents herein are the copyright of LWK & Partners (HK) Ltd. • No part of the drawing and the design contained herein may be reproduced without the prior written consent of a director of LWK & Partners (HK) Ltd. • Do not take measurements directly from this drawing. • Check and verify all dimensions on site. • Read this drawing in conjunction with the specifications and all other related drawings. • Notify the Architect immediately of any discrepancy found herein. 	
CLIENT Hong Kong Sheng Kung Hui Welfare Council Limited	
PROJECT TFS for The Proposed Hong Kong Sheng Kung Hui St. Christopher's Complex	
DRAWING TITLE B1F Plan	
SCALE 1 : 200 @A3	
DRAWING NO. A009	ISSUE DATE 15/01/24
LEAD CONSULTANT & ARCHITECT	
	
BUILDING SERVICES ENGINEER WSP Hong Kong Limited 	
STRUCTURAL, CIVIL & GEOTECHNICAL ENGINEER JMK Consulting Engineers Limited 	
TRAFFIC ENGINEER Ho Wang SPB Limited 	
ENVIRONMENTAL CONSULTANT Urban Green Consultants Limited 	
QUANTITY SURVEYOR Rider Levett Bucknall Ltd 	
LANDSCAPE ARCHITECT Otherland Limited 	



BD REF -
BIM REF -
FSD REF -
Rev. Date Amendment Purpose
PROJECT NO.: HKA-P-01757
<ul style="list-style-type: none"> This drawing and the contents herein are the copyright of LWK & Partners(HK) Ltd. No part of the drawing and the design contained herein may be reproduced without the prior written consent of a director of LWK & Partners (HK) Ltd. Do not take measurements directly from this drawing. Check and verify all dimensions on site. Read this drawing in conjunction with the specifications and all other related drawings. Notify the Architect immediately of any discrepancy found herein.
CLIENT Hong Kong Sheng Kung Hui Welfare Council Limited
PROJECT TFS for The Proposed Hong Kong Sheng Kung Hui St. Christopher's Complex
DRAWING TITLE B2F Plan
SCALE 1 : 200 @A3
DRAWING NO. ISSUE DATE A010 15/01/24
LEAD CONSULTANT & ARCHITECT
LWK + PARTNERS
BUILDING SERVICES ENGINEER WSP Hong Kong Limited

STRUCTURAL, CIVIL & GEOTECHNICAL ENGINEER JMK Consulting Engineers Limited

TRAFFIC ENGINEER Ho Wang SPB Limited

ENVIRONMENTAL CONSULTANT Urban Green Consultants Limited

QUANTITY SURVEYOR Rider Levett Bucknall Ltd

LANDSCAPE ARCHITECT Otherland Limited


B7 B6 B5 B4 B3 B2 B1



Structural Beam = 600
E&M Zone = 300
False ceiling = 50
Clear headroom = 3000
Finished Floor = 50

Structural Beam = 600
E&M Zone = 300
False ceiling = 50
Clear headroom = 4500
Finished Floor = 50

UR/F 118600
R/F 115000
9/F 112000
8/F 109000
7/F 105700
6/F 102300
5/F 98900
4/F 95500
3/F 92100
2/F 88700
1/F 84700
G/F 79200
B1/F 73900
B2/F 69900

35955
23100

Mean Street Level +79.045

BD REF -
BIM REF -
FSD REF -

Rev.	Date	Amendment	Purpose

PROJECT NO.: HKA-P-01757

This drawing and the contents herein are the copyright of LWK & Partners (HK) Ltd.
No part of the drawing and the design contained herein may be reproduced without the prior written consent of a director of LWK & Partners (HK) Ltd.
Do not take measurements directly from this drawing.
Check and verify all dimensions on site.
Revisit this drawing in conjunction with the specifications and all other related drawings.
Notify the Architect immediately of any discrepancy found herein.

CLIENT
Hong Kong Sheng Kung Hui Welfare Council Limited

PROJECT
TFS for The Proposed Hong Kong Sheng Kung Hui St. Christopher's Complex

DRAWING TITLE
Section

SCALE 1 : 200 @A3
DRAWING NO. S001
ISSUE DATE 03/07/24
LEAD CONSULTANT & ARCHITECT

LWK + PARTNERS
BUILDING SERVICES ENGINEER
WSP Hong Kong Limited

WSP

STRUCTURAL, CIVIL & GEOTECHNICAL ENGINEER
JMK Consulting Engineers Limited

JMK

TRAFFIC ENGINEER
Ho Wang SPB Limited

HWSPB
Traffic & Transportation Consultants
Ho Wang SPB Limited

ENVIRONMENTAL CONSULTANT
Urban Green Consultants Limited

UG
URBAN GREEN

QUANTITY SURVEYOR
Rider Levett Bucknall Ltd

RLB Rider Levett Bucknall

LANDSCAPE ARCHITECT
Otherland Limited

otherland

Appendix B

Calculation of Peak Flow

Sewage Impact Assessment

Proposed Development of Hong Kong Sheng Kung Hui St. Christopher's Complex at the Remaining Portion of Taxlot Lot No. T77 In D.D.34. Tai Po

A	Estimation of Daily Flow from the Proposed Development	Remark
Daily Flow		
1 Generation from Staff		
	Number of staff (non-overnight) 235 persons	Provided by client.
	Unit flow 0.280 m ³ /person/day	Referred to the planning unit flow for Commercial Employee + Commercial activities - J11 Community, Social & Personal Services in Table T-2 of GESF ^(a) .
	Number of staff (overnight) 20 persons	Provided by client.
	Unit flow 0.280 m ³ /person/day	Referred to the planning unit flow for "Services" in Appendix 2 of GDSSTP ^(b) .
	Estimated daily flow <u>71.40</u> m ³ /dav	
2 Generation from Dormitory		
	Number of residents 454 persons	Provided by client.
	Unit flow 0.190 m ³ /person/day	Referred to the planning unit flow for Domestic - Institutional and special class in Table T-1 of GESF ^(a) .
	Estimated daily flow <u>86.26</u> m ³ /dav	
3 Generation from Visitors		
	Number of persons 190 persons	Provided by client.
	Unit flow 0.015 m ³ /person/day	Referred to the unit flow factor for "Visitor" of Table 3-4 of "Wastewater Engineering Treatment and Reuse" published by Metcalf & Eddy.
	Estimated peak daily flow <u>2.85</u> m ³ /dav	
4 Generation from Proposed Kitchen		
	Total Gross Floor Area 83.70 m ²	Provided by client.
	Worker density 5.10 persons/ 100m ² GFA	Referred to worker density for Restaurants + All Types in Table 8 of CIFSUS(a)
	Total number of persons 5 persons	
	Unit flow 1.58 m ³ /person/day	Referred to the planning unit flow for Commercial Employee + Commercial Activities J10 - Restaurants & Hotels in Table T-2 of GESF(b)
	Estimated daily flow <u>7.90</u> m ³ /dav	
	Total estimated daily flow <u>168.41</u> m ³ /dav	


Notes:

- (a) GESF - "Guidelines for Estimating Sewage Flows for Sewage Infrastructure Planning" published by Environmental Protection Department (EPD) in 2005.
- (b) GDSSTP - "Guidelines for the Design of Small Sewage Treatment Plants" published by Environmental Protection Department (EPD) in 2006.

Appendix C

Sewerage Treatment Plant Design Calculation
(Tentative)

		Remark
A Estimation of Peak Flow from Proposed Development		
1 Generation from Staff		
Number of staff (non-overnight)	235 persons	Provided by client.
Unit flow	0.280 m ³ /person/day	Referred to the planning unit flow for Commercial Employee + Commercial activities - J11 Community, Social & Personal Services in Table T-2 of GESF ^(a) .
Number of staff (overnight)	20 persons	Provided by client.
Unit flow	0.280 m ³ /person/day	Referred to the planning unit flow for "Services" in Appendix 2 of GDSSTP ^(b) .
Estimated daily flow	71.40 m ³ /day	
2 Generation from Dormitory		
Number of bed spaces	454 beds	Provided by client.
Unit flow	0.190 m ³ /person/day	Referred to the planning unit flow for Domestic - Institutional and special class in Table T-1 of GESF ^(a) .
Estimated peak daily flow	86.26 m ³ /day	
3 Generation from Visitors		
Number of persons	190 persons	Provided by client.
Unit flow	0.015 m ³ /person/day	Referred to the unit flow factor for "Visitor" of Table 3-4 of "Wastewater Engineering Treatment and Reuse" published by Metcalf & Eddy.
Estimated daily flow	2.85 m ³ /day	
4 Generation from Kitchen		
Number of persons	5.0 persons	Provided by client.
Unit flow	1.8 m ³ /person/day	Referred to the planning unit flow for Commercial Employee + Commercial Activities J10 - Restaurants & Hotels in Table T-2 of GESFib)
Estimated daily flow	7.9 m ³ /day	
Total estimated daily flow	168.41 m ³ /day	
Average hourly flow (DWF)	7.02 m ³ /hour	Dry Weather Flow
Total estimated peak hourly flow	42.10 m ³ /hour	6 DWF
B BOD loading		
Generation from Proposed Development		
Total Number of population	904 persons	
Unit flow	0.055 kg/h/day	Referred to Guidelines for the Design of Small Sewage Treatment Plants by EPD.
Total BOD loading	49.72 kg/day	
C Design Flow for STP		
Design Flow	28.07 m ³ /hour	Design flow = average hourly flow * 4 DWF
D Design Calculation		
1 Equalization tank		
Minimum flow capacity	28.07 m ³	
Tank length	4 m	
Tank Width	3.5 m	
Tank depth	3 m	
Design water depth	2.6 m	
Effective water level	2.2 m	
Effective tank volume	30.80 m ³	
Retention time	2.19 hr	Minimum retention time of 2 hours at peak flow. Retention time = Tank Volume/(Estimated Peak Hourly Flow - Design Flow)
2 Contact aeration tank		
Tank length	5 m	
Tank width	4 m	
Tank depth	3.5 m	
Design water depth	3.1 m	
Effective tank volume	62 m ³	
Contact media bed		
Length	5 m	
Width	4 m	
Depth	3 m	
Volume	60 m ³	
Detention time	2.21 hr	Detention time = Tank Volume/ Design Flow
3 Final settling tank		
No. of hopper	2	
Hopper length (L)	2.5	
Hopper base width (B)	1.8	
Top water level	+2.5	
Tank bottom level	+0.9	
Water depth	3 m	
h ₂	0.61 m	h ₂ = ((L-B)/2)tan60
h ₁	2.39 m	h ₁ = Water depth - h ₂
V ₁	14.96 m ³	Lx Lx h ₁
V ₂	2.83 m ³	(1/3) x h ₂ x (L ² + L x B + B ²)
Total volume	35.58 m ³	V ₁ +V ₂
Retention time	2.53 hr	Retention time = Tank Volume/(Estimated Peak Hourly Flow - Design Flow)
4 Filtration pump sump		
Tank length	4 m	
Tank width	3 m	
Design water depth	3 m	
Effective tank volume	36 m ³	
5 Ultra filtration system		
No. of module	1 module	
Effective area	33 m ² /module	According to the Manual-Ultrafiltration Technical
Effective area in all module	33 m ²	
Design filtration rate	0.5 m/h	According to the Manual-Ultrafiltration Technical
Flow capacity	16.5 m ³ /hour	
6 Sludge holding tank		
Tank length	5.5 m	
Tank width	5 m	
Design water depth	5 m	
Effective tank volume	137.5 m ³	
BOD loading for biological treatment	45.99 kg/day	7.5% BOD removed after fine bar screen =BOD loading/ Total estimated daily flow x 1000
Effluent BOD concentration	273.09 mg/l	BOD discharge standard
BOD removal rate	20 mg/l	=Total estimated daily flow x 1000 x (BOD loading for biological treatment - Effluent BOD concentration) x 10 ⁻⁵
BOD removal rate	42.62 kg/day	
Sludge production rate	42.62 kg/day	1.0 kg/kg BOD removal
	2.110 m ³ /day	= sludge production rate (kg/day) / 0.02 / 1.01 / 1000
		Assuming that the wet sludge solid content is 2% and specific gravity of 1.01.
Storage time	65.16 days	=Effective tank volume/ Sludge production rate at least 60 days



Notes:
(a) GESF - "Guidelines for Estimating Sewage Flows for Sewage Infrastructure Planning" published by Environmental Protection Department (EPD) in 2005.
(b) GDSSTP - "Guidelines for the Design of Small Sewage Treatment Plants" published by Environmental Protection Department (EPD) in 2006.

Proposed Hong Kong Sheng Kung Hui St. Christopher's Complex at Tai Po
Sewage Treatment Plant Design

STP size

	length,m	width,m	depth,m	
Equalization tank	4	3.5	3	
Contact aeration tank	5	4	3.5	
Final settling tank	4.5	3.5	3	
Filtration pump sum	4	3	3	
Sludge holding tank	5.5	5	5	
Side wall	0.5			
Seperation wall	0.3			
	length,m	width,m	depth,m	
STP	15.1	9.8	6	147.98 m2

Appendix D

Relevant Effluent Quality Standards

Table 6 Standards for effluents discharged into Group D inland waters
(All units in mg/L unless otherwise stated; all figures are upper limits
unless otherwise indicated)

Determinand	Flow rate								
	(m ³ /day)	≤ 200	> 200	> 400	> 600	> 800	> 1000	> 1500	> 2000
			and	and	and	and	and	and	and
			≤ 400	≤ 600	≤ 800	≤ 1000	≤ 1500	≤ 2000	≤ 3000
pH (pH units)		6-10	6-10	6-10	6-10	6-10	6-10	6-10	6-10
Temperature (°C)		30	30	30	30	30	30	30	30
Colour (lovibond units) (25mm cell length)		1	1	1	1	1	1	1	1
Suspended solids		30	30	30	30	30	30	30	30
BOD		20	20	20	20	20	20	20	20
COD		80	80	80	80	80	80	80	80
Oil & Grease		10	10	10	10	10	10	10	10
Iron		10	8	7	5	4	2.7	2	1.3
Boron		5	4	3.5	2.5	2	1.5	1	0.7
Barium		5	4	3.5	2.5	2	1.5	1	0.7
Mercury		0.1	0.05	0.001	0.001	0.001	0.001	0.001	0.001
Cadmium		0.1	0.05	0.001	0.001	0.001	0.001	0.001	0.001
Other toxic metals individually		1	1	0.8	0.8	0.5	0.5	0.2	0.2
Total Toxic metals		2	2	1.6	1.6	1	1	0.5	0.4
Cyanide		0.4	0.4	0.3	0.3	0.2	0.1	0.1	0.05
Phenols		0.4	0.3	0.2	0.1	0.1	0.1	0.1	0.1
Sulphide		1	1	1	1	1	1	1	1
Sulphate		800	600	600	600	600	400	400	400
Chloride		1000	800	800	800	600	600	400	400
Fluoride		10	8	8	8	5	5	3	3
Total phosphorus		10	10	10	8	8	8	5	5
Ammonia nitrogen		20	20	20	20	20	20	20	10
Nitrate + nitrite nitrogen		50	50	50	30	30	30	30	20
Surfactants (total)		15	15	15	15	15	15	15	15
E. coli (count/100ml)		1000	1000	1000	1000	1000	1000	1000	1000

Table 7 Standards for effluents discharged into the coastal waters of Tolo and Port Shelter Water Control Zones
(All units in mg/L unless otherwise stated; all figures are upper limits unless otherwise indicated)

Determinand	Flow rate (m ³ /day)											
	≤ 10	> 10 and ≤ 200	> 200 and ≤ 400	> 400 and ≤ 600	> 600 and ≤ 800	> 800 and ≤ 1000	> 1000 and ≤ 1500	> 1500 and ≤ 2000	> 2000 and ≤ 3000	> 3000 and ≤ 4000	> 4000 and ≤ 5000	> 5000 and ≤ 6000
pH (pH units)	6-9	6-9	6-9	6-9	6-9	6-9	6-9	6-9	6-9	6-9	6-9	6-9
Temperature (°C)	45	45	45	45	45	45	45	45	45	45	45	45
Colour (lovibond units) (25mm cell length)	1	1	1	1	1	1	1	1	1	1	1	1
Suspended solids	30	30	30	30	30	30	15	15	15	15	15	15
BOD	20	20	20	20	20	20	10	10	10	10	10	10
COD	80	80	80	80	80	80	50	50	50	50	50	50
Oil & Grease	20	20	20	20	20	20	10	10	10	10	10	10
Iron	10	10	10	7	5	4	2.7	2	1.3	1	0.8	0.6
Boron	5	4	3	2.5	2	1.6	1.1	0.8	0.5	0.4	0.3	0.2
Barium	5	4	3	2.5	2	1.6	1.1	0.8	0.5	0.4	0.3	0.2
Mercury	0.1	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.001
Cadmium	0.1	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.001	0.001
Other toxic metals individually	1	1	0.8	0.5	0.5	0.4	0.1	0.1	0.1	0.1	0.1	0.1
Total toxic metals	2	2	1.6	1	1	0.8	0.2	0.2	0.2	0.2	0.14	0.1
Cyanide	0.1	0.1	0.1	0.1	0.1	0.1	0.05	0.05	0.03	0.02	0.02	0.01
Phenols	0.5	0.5	0.5	0.25	0.25	0.25	0.1	0.1	0.1	0.1	0.1	0.1
Sulphide	5	5	5	5	5	5	2.5	2.5	1.5	1	1	0.5
Total residual chlorine	1	1	1	1	1	1	1	1	1	1	1	1
Total nitrogen	20	20	20	15	15	15	15	15	10	10	10	10
Total phosphorus	8	8	5	5	5	5	5	5	5	5	5	5
Surfactants (total)	15	15	15	15	15	15	10	10	10	10	10	10
E. coli (count/100ml)	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000

Appendix E

Existing Drainage System Capacity Calculation

Proposed Development of Hong Kong Sheng Kung Hui St. Christopher's Complex at the Remaining Portion of Taxlord Lot No. T77 In D.D.34. Tai Po
Existing Drainage System Capacity Calculation

Calculation of Runoff from Site into Storm Drainage Network

Catchment ID	Surface Type	Catchment Area (A), m ²	Catchment Area (A), km ²	Average Slope (H), m/100m	Flow path length (L), m	Inlet time (t ₀), min	Time of Concentration (t _c), min	Duration (t _d), min	a (50 year return period)	b (50 year return period)	c (50 year return period)	Runoff intensity (i) mm/hr	Runoff coefficient (C)	C × A	Peak runoff (Q _p), m ³ /s
Site Boundary	80% Concrete +20% Grassland (heavysoil), flat	2,208	0.002208	-	-	-	-	5.00	451.3	2.5	0.34	227	0.81	0.001788	0.113

Capacity Flow Estimation and Adequacy Check for Existing Drainage System

Point (channel no.)	Shape	Diameter, m	Depth, m	Slope	Length, m	Manning's roughness coefficient	Cross Section Area, m ²	Wetted perimeter, m	Hydraulic radius, m	Mean velocity, m/s	Capacity flow, m ³ /s	Sewage Treatment Plant and Stormwater Catchment Peak Flow, m ³ /s	% of capacity flow	Sufficient Capacity? (Y/N)
SMD1000600	Circular Pipe × 2 nos.	0.150	--	0.216	3.0	0.015	0.018	0.471	0.04	3.48	0.123	0.125	102%	N
SWD1011379	Circular Pipe	0.300	--	0.007	18.5	0.015	0.071	0.942	0.08	0.99	0.070	0.125	178%	N
SWD1011376	Circular Pipe	0.300	--	0.011	26.6	0.015	0.071	0.942	0.08	1.22	0.086	0.125	145%	N
SWD1011377	Circular Pipe	0.300	--	0.020	10.7	0.015	0.071	0.942	0.08	1.66	0.117	0.125	106%	N
SWD1011381	Circular Pipe	0.300	--	0.009	8.8	0.015	0.071	0.942	0.08	1.13	0.080	0.125	156%	N
SWD1011383	Circular Pipe	0.300	--	0.018	20.0	0.015	0.071	0.942	0.08	1.59	0.113	0.125	111%	N
SWD1014090	Circular Pipe	0.375	--	0.018	17.4	0.015	0.110	1.178	0.09	1.85	0.204	0.125	61%	Y

Appendix F

Comment from Regional Officer

From: maverickckau@epd.gov.hk
To: [Emily Tang](#)
Cc: "[SI\[RN\]13](#)"@Not For Reply From Internet.hksarg.hk; "[E\[RN\]41](#)"@Not For Reply From Internet.hksarg.hk
Subject: Re: Request the Information Advice on District Discharge Standard at Taxlord Lot No. T77 In D.D.34. Tai Po
Date: Tuesday, August 27, 2024 4:40:41 PM

Dear Emily,

Refer to your SIA report for Taxlord Lot No. T77 in D.D.34, please find our comment below:

- "1. In Table 3.2, it is suggested to also include Nitrate + nitrite nitrogen.
2. In part 5 "Ultra filtration system" under Appendix C, the flow capacity (ie. 6m³/hour) is not enough for design capacity (ie. 168.41m³/day). Please review."

If you have further enquiry please contact me at anytime, thank you.

Regards,
Maverick C.K. AU / E(RN)13
Regional Office (North) / EPD
2158 5801 / 9189 0112

From: Emily Tang <emily.tang@urbangreen.hk>
To: "maverickckau@epd.gov.hk" <maverickckau@epd.gov.hk>
Date: 23/08/2024 10:09
Subject: Request the Information Advice on District Discharge Standard at Taxlord Lot No. T77 In D.D.34. Tai Po

Dear Mr. Au,

We are the environmental consultant undertake the Sewerage Impact Assessment for a service complex development at the Remaining Portion of Taxlord Lot No. T77 In D.D.34. Tai Po. We have received a comment from the EPD-Water Quality Mgt team regarding the discharge standard of the proposed sewerage treatment plant. It would be appreciated if you could advise if the discharge standard listed in Table 3.2 of our SIA report could comply with the district discharge requirements.

Attached the comment below and full set SIA report for your kind reference. We would be grateful if you could provide us the relevant advice at your earliest convenience. Thank you.

