



GRANDMAX SURVEYORS LIMITED
俊滙測量師行有限公司

Date : 8th January, 2025
Our Ref. : ADCL/PLG-10289/L012

The Secretary
Town Planning Board
15/F., North Point Government Offices
333 Java Road, North Point, Hong Kong

By Email


Dear Sir/Madam,

**Re: Section 16 Planning Application for Proposed Temporary Open Storage of Construction Materials and Construction Equipment for a Period of 3 Years at Lot Nos. 1809 (Part), 1813, 1814, 1815 (Part), 1816, 1817 (Part), 1819, 1820, 1824, 1825, 1826, 1827, 1828, 1829, 1830, 1831 S.A, 1831 S.B, 1832, 1833, 1834, 1835, 1837, 1838, 1839 (Part), 1840, 1841, 1842 and 1843 in D.D. 129, Lau Fau Shan, Yuen Long, New Territories
(Planning Application No. A/YL-LFS/522)**

We refer to the latest comments from Transport Department (dated 2.1.2025) and would like to enclose herewith our Responses-to-Comments with Revised Traffic Impact Assessment to address the abovementioned departmental comments for their consideration.


Thank you for your kind attention and should you have any queries, please do not hesitate to contact our Mr. Thomas LUK at

Yours faithfully,
For and on behalf of
Grandmax Surveyors Limited



Thomas Luk
Planning Consultant

Encl.
c.c. Client
DPO/TM&YLW, PlanD (Attn: Mr. Wilfred CHU)

No.	Comments	Responses
Comments from Transport Department		
1	As claimed by the Applicant, the Applicant will provide a LGV with load capacity of 2.5 tons. The Applicant shall provide photos and the vehicle registration number of the proposed LGV for checking.	<p>At current stage, there is no operation at the development, only reference photo of the proposed LGV can be provided:</p>  <p>五十鈴皇牌輕型貨車</p> <p>www.isuzu.com.hk</p> <p>探索更多 Explore More</p> <p>合眾汽車有限公司 TRANSMILE MOTORS LTD. 大馬行 廣 德 街</p> <p>九龍陳列室：九龍旺角砵磠街402-406號東匯大廈地下 電話：2397 2323 新田陳列室：新界元朗新田村路地庫744RP 電話：2476 6276</p> <p>ISUZU EURO 6</p>
2	By making reference to the lower limit trip rates of industrial buildings under TPDM (relevant part extracted), the am trip generation rate and am attraction rate are 0.0698 and 0.1044 (pcu/hr/100 sqm GFA) respectively. On this basis, the two-way traffic of the application site is about 27	Noted. The suggested trip rates has been adopted for traffic estimation, please see Section 4 in the updated TIA report for more details.

	pcu/hr at am peak hour. In this regard, the Applicant's estimated traffic flow of 6 LGV round trips per day is significantly differed from the traffic flow figure estimated on the basis of TPDM. TD has reservation on Applicant's statement that only 6 LGV round trips would be involved per day.	
3	In connection with the additional traffic arising from the development, the Applicant shall consider proposing improvement works along the proposed traffic route.	Improvement works are proposed. Please see Section 5.7 in the updated TIA report for more details.
4	Tin Yuet Road shall be unnamed road (see markup), please amend related drawings accordingly.	Noted, all related drawings have been revised from "Tin Yuet Road" to "Unnamed Road 3".

**S.16 Planning Application for Proposed
Temporary Open Storage of Construction Materials and
Construction Equipment for a Period of 3 Years at
Various Lots in D.D.129 Lau Fau Shan,
Yuen Long, New Territories**

TRAFFIC IMPACT ASSESSMENT

Reference: 80108-R01-03

Date: January 2025

Prepared by: 8FM Consultancy Limited

Content

1	INTRODUCTION	1
1.1	Background	1
1.2	Study Objectives	1
1.3	Report Structure	1
2	PROPOSED DEVELOPMENT	3
2.1	The Site Location	3
2.2	The Development Schedule	3
2.3	Vehicle Access Arrangement	3
2.4	Internal Transport Facilities	4
3	EXISTING TRAFFIC SITUATION	5
3.1	Existing Road Network	5
3.2	Public Transport Facilities	5
3.3	Traffic Survey	5
3.4	Existing Traffic Condition	6
3.5	Delivery Route	9
4	DEVELOPMENT TRAFFIC GENERATION	10
4.1	Estimated Development Flows	10
5	FUTURE TRAFFIC SITUATION	12
5.1	Design Year	12
5.2	Traffic Forecast Methodology	12

5.3	Regional Traffic Growth	12
5.4	Planned and Committed Development	13
5.5	2027 Traffic Flows	13
5.6	Future Traffic Impact Assessment	14
5.7	Proposed Improvement Measures	15
6	Summary and Conclusion	16
6.1	Summary	16
6.2	Conclusion	16

Appendix A – Junction Calculation Sheets

List of Table

Table 2.1	Key Development Parameters
Table 2.2	Internal Transport Facilities
Table 3.1	Franchised Bus and GMB Services Close to Project Site
Table 3.2	Existing Road Link Capacity Assessment
Table 3.3	Existing Junction Capacity Assessment
Table 4.1	Traffic Rates for Industrial Building
Table 4.2	Estimated Traffic Generation & Attraction Arising from Storage Area
Table 4.3	Traffic Rates for Office Development
Table 4.4	Estimated Traffic Generation & Attraction Arising from Office
Table 4.5	Estimated Development Flow
Table 5.1	AADT Extracted from Annual Traffic Census
Table 5.2	2019-Based TPDEM Data for Yuen Long District
Table 5.3	Future Year Link Capacity Assessment
Table 5.4	Future Year Junction Capacity Assessment

List of Figure

Figure 1	Site Location
Figure 2.1	Layout of Project Site
Figure 2.2	Vehicle Access Arrangement
Figure 2.3	Swept Path Analysis
Figure 3.1	Public Transport Facilities
Figure 3.2	Key Junctions and Road Links
Figure 3.3	2024 Observed Traffic Flows during Peak Hours
Figure 3.4	Existing Condition of Deep Bay Road (L1)
Figure 3.5	Existing Condition of Unnamed Road 3 (L4)
Figure 3.6	2024 Observed Link Flows during Peak Hours
Figure 3.7	Proposed Routing
Figure 3.8	Swept Path Analysis along Delivery Route
Figure 5.1	2027 Reference Traffic Flows during Peak Hours
Figure 5.2	2027 Design Traffic Flows during Peak Hours
Figure 5.3	Provision of Laybys at Deep Bay Road
Figure 5.4	Typical Layout of Laybys

1 INTRODUCTION

1.1 Background

The Applicant intends to seek planning permission for the Section 16 Planning Application for Proposed Temporary Open Storage of Construction Materials and Construction Equipment for a Period of 3 Years at Lot Nos. 1809 (Part), 1813, 1814, 1815 (Part), 1816, 1817 (Part), 1819, 1820, 1824, 1825, 1826, 1827, 1828, 1829, 1830, 1831 S.A, 1831 S.B, 1832, 1833, 1834, 1835, 1837, 1838, 1839 (Part), 1840, 1841, 1842 and 1843 in D.D. 129, Lau Fau Shan, Yuen Long, New Territories (“Project Site”).

The location of the Project Site is shown in **Figure 1**.

8FM Consultancy Limited was commissioned as the traffic consultant to carry out a Traffic Impact Assessment (TIA) Study in support of this planning application.

1.2 Study Objectives

The objectives of this TIA are listed as follows:

- To review the existing traffic conditions in the vicinity of the Project Site;
- To present and evaluate the internal transport facilities;
- To estimate the traffic forecasts of the adopted design year and assess the future traffic situation in the surrounding network;
- To evaluate the potential traffic impact of the proposed development; and
- To suggest traffic improvement proposals, if necessary.

1.3 Report Structure

The report is structured as follows:

- Chapter 2 - Proposed Development
Describing the project site, vehicular access arrangement, development schedule and the proposed internal transport facilities;
- Chapter 3 - Existing Traffic Situation
Presenting the existing traffic context, the traffic survey, and the traffic assessment of the existing traffic conditions; Proposing control measures based on assessment results.
- Chapter 4 - Development Traffic Generation
Estimating the traffic flows arising from the proposed development;
- Chapter 5 – Future Traffic Situation

Describing the traffic forecast methodology and presenting the traffic assessment results under reference and design scenarios;

- Chapter 6 - Summary and Conclusion

Summarizing the findings and conclusion of this traffic impact assessment study.

2 PROPOSED DEVELOPMENT

2.1 The Site Location

The Project Site is located in the Lau Fau Shan and Mong Tseng area, and it can be accessible from Deep Bay Road via a local track. The location of the Project Site is shown in **Figure 1**.

2.2 The Development Schedule

The project site is proposed to be utilised as the open storage for construction materials and equipment on a temporary basis of 3 years. Based on the planning statement, the operation hour of the proposed use is from 8:00a.m. to 6:00p.m. from Mondays to Saturdays and there will be no operation on Sundays and public holidays.

The project site has a total area of about 15,500m², including open storage area, two one-storey storerooms (36m² x 2) and a one-storey site office (36m²). The layout of the project site is shown in **Figure 2.1**. Key development parameters of the proposed use are tabulated in **Table 2.1**.

Table 2.1 Key Development Parameters

Proposed Use	Temporary Open Storage of Construction Materials and Construction Equipment
Operation Hours	8:00am-6:00pm (Monday – Sunday, Except Public Holiday)
Total Site Area	15,500m ²
Open Storage Area	About 14,055m ²
Storeroom	72m ²
Site Office	36m ²

2.3 Vehicle Access Arrangement

At present, there is an existing local access road to the project site. Access to the project site will be provided through an 12m-wide ingress/egress point located at the southwestern boundary, which is connected to a local track leading to Deep Bay Road. The vehicle access arrangement is presented in **Figure 2.2** for reference.

Swept path analysis is also conducted for the access point and the access road. **Figure 2.3** indicates the sufficient turning spaces for the 7m LGV.

2.4 Internal Transport Facilities

The internal transport facilities to be provided in the project site are summarized in **Table 2.2**. As there are no specific parking and loading/unloading requirements for temporary open storage development in accordance to HKPSG, ancillary transport facilities are provided based on the Applicant's requirements to meet operational needs.

Table 2.2 Internal Transport Facilities

Type of Ancillary Transport Facilities	Size	Provision based on Applicant's Operational Needs
Private Car Parking Spaces	5m(L) x 2.5m(W)	3
L/UL Bays	7m(L) x 3.5m(W)	6

3 EXISTING TRAFFIC SITUATION

3.1 Existing Road Network

As indicated in **Figure 1**, the project site is located at the east of Deep Bay Road, and it can be accessible from Deep Bay Road via a local unnamed road. The existing condition of the connecting carriageways are summarized as follows:

- Unnamed Road 2 is a single track access road connecting Deep Bay Road in the west to an unnamed road near Lam Hang Shan in the east. Acting as single carriageway with 1-lane-2 way operation, passing bays are generally identified along the carriageway.
- Deep Bay Road is served as a rural road connecting Lau Fau Shan in the northeast and Pak Nai in the southwest. Acting as single carriageway with 1-lane-2 way operation, passing bays are generally identified along the carriageway.
- Unnamed Road 3 is as a rural road connecting Deep Bay Road in the east and Tin Yuet Road in the west. Acting as single carriageway with 1-lane-2 way operation, passing bays are generally identified along the carriageway.
- Lau Fau Shan Road is served as a rural road which is mainly a single-two carriageway, connecting Deep Bay Road in the west and Tin Wah Road in the east.

3.2 Public Transport Facilities

The project site cannot be immediately accessible by taking the public transportation. The nearest franchised bus and GMB services are around 850m away from the site, operating along Lau Fau Shan Road. Details of these public transport services are presented in **Table 3.1** and **Figure 3.1**.

Table 3.1 Franchised Bus and GMB Services Close to Project Site

Route	Routing	Peak Frequency (minutes)
MTR K65	Lau Fau Shan ↔ Yuen Long Station	9-16
MTR K65A	Lau Fau Shan ↔ Tin Shui Wai Station	12-15
GMB 33	Yuen Long (Tai Fung St) ↔ Ha Pak Nai	20
GMB 34A	Ha Tsuen ↔ Lau Fau Shan	15-30
GMB 35	Hong Lee Court ↔ Cai Ha Village	6-7

3.3 Traffic Survey

In order to evaluate the existing traffic conditions in the vicinity, the classified traffic surveys were conducted on 10 September 2024 (Tuesday) from 7:30 to 10:30 in the morning and from 16:00 to 19:00 in the evening. The key junctions and road links of the study area are indicated **Figure 3.2**.

The traffic flows collected during the traffic surveys have been converted to passenger car unit (PCU) based on the PCU factors as indicated in Volume 2 of Transport Planning and Design Manual (TPDM).

The results of traffic survey identified that the AM and PM peak hours occur during 7:45am to 8:45am and 16:30pm to 17:30pm, respectively. The 2024 observed peak hours traffic flows in the study area are presented in **Figure 3.3**.

3.4 Existing Traffic Condition

Based on the observed traffic flows, the performance of the key junctions and traffic links in the vicinity of the project site during the AM and PM peak hours was assessed.

3.4.1 Determination of Link Capacity

The link capacity of single track access road is referenced from Chapter 3.11, Volume 2 of TPDM. It is noted that the provision of passing places and laybys should be 1 at intervals of approximately 60m (measured from the end of one to the start of next), where each passing place / layby is around 30m long (with tapers length included), i.e. 1 passing bay is equivalent to around 90m in length. Hence, for a 500m-long single track access road, there should be about 5 passing places / laybys, the expected capacity is 100 vehicles per hour (“veh/hr”).

The link capacity of Deep Bay Road (L1) is assumed to have 2-way design flows of 100 veh/hr as outlined in Volume 2 of TPDM.

Whereas, the critical section of Deep Bay Road (L2) identified is to the immediate north of Lau Fau Shan Roundabout. **Figure 3.4** shows the existing condition for this section of Deep Bay Road within 500m from Lau Fau Shan Roundabout.

As shown in **Figure 3.4**, although the section of Deep Bay Road (L2) is mainly a single track access road, there are about 10 passing places or laybys, i.e. 2 times more than the design requirement in TPDM, which allows vehicles travelling in opposite direction to pass by. Therefore, it can be implied that the capacity of this section of Deep Bay Road(L2) is about 2 times more than the expected capacity, i.e. $2 \times 100=200$ veh/hr.

Similarly, as shown in **Figure 3.5**, there are about 9 passing places or laybys in Unnamed Rd 3(L4), it can be implied that the capacity is expected to be 180 veh/hr.

3.4.2 Validation of Link Capacity

A traffic survey with observation was also conducted on 10 September 2024 to determine the validation of the assumed capacity of Deep Bay Road and Unnamed Rd 3.

Figure 3.6 refers, the survey recorded the 2-way traffic flow at Deep Bay Road (L2) and Unnamed Rd 3 (L4) during AM(PM) peak hour was 154(115) veh/hr and 137(120) veh/hr respectively. Observation found that traffic flow during peak hour was generally smooth with stream of multiple vehicles passing through at the same time in one direction. Minor disruptions with traffic queues of about 4-5 vehicles were observed when vehicles stopped within passing places or laybys to allow vehicles in opposite direction to pass by. However, disruptions were short and traffic queue dispersed quickly.

General description on the operation characteristic for different ranges of ratio of flow to capacity area referenced from Table 2.4.2.1 of Chapter 2.4 Volume 2 of TPDM. For range 0.5-0.75, the general description is as follow:

- 1) Generally easy flow conditions.
- 2) Travel speeds begin to be restricted by traffic conditions.
- 3) Ability to manoeuvre within traffic stream is noticeably restricted.
- 4) Minor disruptions may cause local congestion with short traffic queues

The observed traffic flow conditions at Deep Bay Road(L2) and Unnamed Rd 3 (L4) are found to be similar to the description above, which suggests that the observed traffic flow of 154(115) veh/hr at Deep Bay Road and traffic flow of 137(120) veh/hr at Unnamed Rd 3 would have a ratio of flow to capacity within the range of 0.5-0.75. In light of this, the actual capacity of Deep Bay Road in the immediate north of Lau Fau Shan Roundabout is more than 200veh/hr, and the actual capacity of Unnamed Rd 3 is more than 180veh/hr. Hence, it can be concluded that the traffic analysis which adopted the link capacity of 200 veh/hr for the same section of Deep Bay Road(L2) and of 180veh/hr for Unnamed Rd 3 (L4) are considered conservative.

3.4.3 Existing Road Link Capacity Assessment

The results of existing road link capacity are shown in **Table 3.2**.

Table 3.2 Existing Road Link Capacity Assessment

Link No.	Link Location	Peak	Design Capacity ⁽ⁱ⁾ (veh/hr)	Traffic Flow (veh/hr)	V/C Ratio ⁽ⁱⁱ⁾
L1	Deep Bay Road (two-way)	AM	100	59	0.59
		PM	100	61	0.61
L2	Deep Bay Road (two-way)	AM	200	154	0.77
		PM	200	115	0.58
L3	Lau Fau Shan Road (EB)	AM	800	287	0.36
		PM	800	293	0.37
	Lau Fau Shan Road (WB)	AM	800	309	0.39
		PM	800	222	0.28
L4	Unnamed Rd 3 (two-way)	AM	180	137	0.78
		PM	180	120	0.67

Notes:

- (i) Design capacity can be referred to TPDM Vol2 chapter 2.4.1.1 and chapter 3.11.3.1.
- (ii) V/C Ratio = Volume/ Design Capacity. A peak hour v/c ratio of 1.0 or less indicates a satisfactory level of traffic. A V/C ratio between 1.0 and 1.2 indicates a manageable degree of congestion. A V/C ratio above 1.2 indicates more serious congestion.

The results reveal that the key traffic links operate within capacity during peak hours.

3.4.4 Existing Junction Capacity Assessment

The results of junction performance are indicated in **Table 3.3** and detailed junction calculation sheets are given in **Appendix A**.

Table 3.3 Existing Junction Capacity Assessment

Jn No.	Junction Location	Type/ Capacity Index	AM Peak	PM Peak
A	Tin Ying Rd / Tin Wah Rd	Signal / RC ⁽ⁱ⁾	26.6%	43.4%
B	Lau Fau Shan Rd / Tin Wah Rd / Ping Ha Rd	Priority / DFC ⁽ⁱⁱ⁾	1.18	1.25
C	Lau Fau Shan Roundabout	Roundabout / DFC	0.45	0.40
D	Deep Bay Rd / Unnamed Rd A	Priority / DFC	0.02	0.02
E	Unnamed Rd A / Unnamed Rd B	Priority / DFC	0.05	0.11
F	Deep Bay Rd / Unnamed Rd 3	Priority / DFC	0.17	0.16

*Notes:

- (i) DFC - Design Flow / Capacity Ratio. The performance of a priority junction or roundabout is normally measured by its Design Flow / Capacity (DFC) ratio. A DFC ratio less than 1.0 indicates that the junction is operating within design capacity. A DFC ratio greater than 1.0 indicates that the junction is overloaded, resulting in traffic queues and longer delay time to the minor arm traffic.
- (ii) RC = reserve capacity. The performance of a traffic signalised junction is indicated by its reserve capacity (RC). A positive RC (RC>0) indicates that the junction is operating with spare capacity. A negative RC (RC<0) indicates that the junction is overloaded; resulting in traffic queues and longer delay time.

As shown in Table 3.3, it can be seen that the surveyed junctions perform satisfactorily during peak hours with adequate reserve capacities, except for Jn B, i.e. junction of Lau Fau Shan Rd/Tin Wah Rd/Ping Ha Rd, which is currently having inadequate junction capacity during the AM and PM peak hours.

3.5 Delivery Route

Based on the assessment results of the existing traffic condition in the vicinity of project site, control measure is suggested to avoid aggravating the existing condition of concerned traffic junction.

In light of this, the Applicant is committed to the designate a delivery route so as to ensure the efficient delivery. The project-related vehicles will travel to/from the project site via the designated Route 1 only (**Figure 3.7** refers), which will not pass through Junction B of Lau Fau Shan Rd/Tin Wah Rd/Ping Ha Rd, minimizing the traffic impact brought from project site.

Swept path analysis is conducted at the critical junctions along the delivery route and is shown in **Figure 3.8**, which demonstrate adequate maneuvering at the concerned sections when turning to Tin Ying Road.

4 DEVELOPMENT TRAFFIC GENERATION

4.1 Estimated Development Flows

With reference to the Planning Statement, the proposed development will only make use of light goods vehicle (LGV) and private cars to travel to/from the application site.

As the proposed development will be operated as the storage area and a build-up site office, the trip generation & attraction arising from the operational needs will be estimated respectively based on the different land use.

4.1.1 Storage Area

The trip generation & attraction of the storage area is estimated with reference to the the trip rates of industrial buildings under the TPDM Vol 1., which are tabulated in **Table 4.1**. Considering the actual operational needs and the reference made with approved applications of similar use within the same outline zoning plan (OZP) in recent years, the level of lower limit is adopted for trip assessment.

Table 4.1 Traffic Rates for Industrial Building

Land Use	Unit	Upper Limit/ Mean/ Lower Limit	AM		PM	
			Generation Rate	Attraction Rate	Generation Rate	Attraction Rate
Industrial Building	(pcu/hr/100 sqm GFA)	Upper Limit	0.1153	0.1727	0.1648	0.1260
		Mean	0.0926	0.1386	0.1350	0.1049
		Lower Limit	0.0698	0.1044	0.1053	0.0808

The calculated traffic generation & attraction arising from the operation of storage area during the identified peak hours are estimated in **Table 4.2**.

Table 4.2 Estimated Traffic Generation & Attraction Arising from Storage Area

Land Use	Area	Unit	AM Peak		PM Peak	
			Generation	Attraction	Generation	Attraction
Storage Area	14,127m ²	pcu/hr	10	15	15	12
		veh/hr*	7	10	10	8

*Notes: Traffic generation/attraction for LGV is calculated with pcu factor 1.5 based on the PCU factors as indicated in Table 2.3.1.1 of TPDM Vol2.

4.1.2 Site Office

The trip generation & attraction of the build-up development is estimated with reference to the the trip rate tabulated in the TPDM Vol 1. **Table 4.3** shows the trip

rates for office development, and the level of upper limit is adopted for conservative assessment.

Table 4.3 Traffic Rates for Office Development

Land Use	Unit	Upper Limit/ Mean/ Lower Limit	AM		PM	
			Generation Rate	Attraction Rate	Generation Rate	Attraction Rate
Office	(pcu/hr/100sqm GFA)	Upper Limit	0.2361	0.3257	0.1928	0.1510
		Mean	0.1703	0.2452	0.1573	0.1175
		Lower Limit	0.1045	0.1646	0.1217	0.084

The calculated traffic generation & attraction arising from the operation of site office during the identified peak hours are estimated in **Table 4.4**.

Table 4.4 Estimated Traffic Generation & Attraction Arising from Office

Land Use	Area	Unit	AM Peak		PM Peak	
			Generation	Attraction	Generation	Attraction
Storage Area	36m ²	pcu/hr	1	1	1	1
		veh/hr	1	1	1	1

4.1.3 Estimated Development Flow

With the trip generation & attraction estimated for different land use, the development flow is summarized in **Table 4.5**.

Table 4.5 Estimated Development Flow

Unit	AM Peak		PM Peak	
	Generation	Attraction	Generation	Attraction
pcu/hr	11	16	16	13
Total	27 pcu/hr		29 pcu/hr	
veh/hr	8	11	11	9
Total	19 veh/hr		20 veh/hr	

5 FUTURE TRAFFIC SITUATION

5.1 Design Year

The planning application for the Proposed Temporary Open Storage development involves a period of 3 years, it is assumed that the end year for the Project Site would be year 2027. Therefore, year 2027 is adopted as the design year of this study.

5.2 Traffic Forecast Methodology

To conduct the traffic forecast on the road networks in the vicinity of the project site, the existing traffic flows will be adjusted with the following factors considered:

- Historical traffic data from Annual Traffic Census (ATC) by Transport Department;
- The forecast population and employment from the 2019-based Territorial Population and Employment Data Matrices (TPEDM) planning data by Planning Department;
- Committed and planned developments adjacent the project site.

5.3 Regional Traffic Growth

5.3.1 Annual Traffic Census (ATC)

Reference has been made to the ATC reports from year 2018 to 2022. The historical traffic data of the surrounding road links are based on the Annual Average Daily Traffic (AADT) extracted from ATC issued by Transport Department. The relevant AADT data from year 2018 to 2022 are summarized in **Table 5.1**.

Table 5.1 AADT Extracted from Annual Traffic Census

Station	Road	From	To	2018	2019	2020	2021	2022	Growth Rate p.a.
5858	Ping Ha Rd & Lau Fau Shan Rd	Tin Ha Rd	Deep Bay Rd	12,680	12,590	12,070	10,310	8,390	-9.81%
					-0.7%	-4.1%	-14.6	-18.7%	
6603	Deep Bay Rd	Lau Fau Shan Rd	Nam Sha Po	2,920	2,320	2,380	2,570	2,760	-1.40%
					-20.3%	2.3%	7.9%	7.7%	
5284	Tin Ying Rd	Tin Wah Rd	Ping Ha Rd	32,180	31,060	29,780	30,970	30,030	-1.71%
					-3.5%	-4.1%	4.0%	-3.0%	
Total				47,780	45,970	44,230	43,850	41,180	-3.65%

Table 5.1 indicates that the overall average annual growth rate of the adjacent road network is -3.65%.

5.3.2 Projected Population Data

Reference has been made to the 2019-based Territorial Population and Employment Data Matrices (TPEDM) planning data provided by Planning Department. The population and employment data in Yuen Long District for year 2019, 2024 and 2031 are presented in **Table 5.2**.

Table 5.2 2019-Based TPDEM Data for Yuen Long District

Item	TPDEM Estimation/Projection			Annual Growth Rate		
	2019	2026	2031	2019 to 2026	2026 to 2031	2019 to 2031
Population	175,150	172,350	159,850	-0.2% ³	-1.49%	-0.76%
Employment	68,100	70,700	70,250	0.54%	-0.13%	0.26%
total	243,250	243,050	230,100	-0.01%	-1.09%	-0.46%

Source: 2019-based TPEDM by Planning Department

Table 5.2 indicates that the highest annual growth rate for population and employment is 0.54%.

Based on the findings of the above two tables, a conservative growth rate of 0.54% per annum was adopted to estimate the background traffic growth from 2024 to 2027.

5.4 Planned and Committed Development

Based on the published information from Town Planning Board, no planned/committed developments in the site vicinity are identified in design year 2027 in the vicinity of project site.

5.5 2027 Traffic Flows

The growth factor will be applied to the 2024 observed peak hours traffic flows to estimate the 2027 reference flows.

The reference and design flows of the design year 2027 are calculated from the following formula:

$$2027 \text{ Reference Flows (Fig. 5.1)} = 2024 \text{ Observed Flows (Fig 3.3)} \times (1+0.54\%)^3$$

$$2027 \text{ Design Flows (Fig. 5.2)} = 2027 \text{ Reference Flows (Fig. 5.1)} + \text{Net Change in Development Traffic Flows}$$

Figure 5.1 shows the 2027 Reference Peak Hours Flows in the area. By adding the net development traffic, **Figure 5.2** shows the 2027 Design Peak Hours Traffic Flows.

5.6 Future Traffic Impact Assessment

With the delivery route designated by the Applicant, the development traffic will travel via the Route 1 as indicated in **Figure 3.7**.

The traffic impact assessments for design year 2027 were conducted for the key junctions and road links identified along Route 1 for both Reference and Design scenarios.

5.6.1 Future Year Link Capacity Assessment

Based on the Reference Flows and Design Flows, link capacity assessments for design year 2027 are carried out and the results are presented in **Table 5.3**.

Table 5.3 Future Year Link Capacity Assessment

Link No.	Link Location	Design Capacity (veh/hr)	2027 Reference Scenario				2027 Design Scenario			
			Traffic Flow (veh/hr)		Volume to Capacity Ratio (V/C)		Traffic Flow (veh/hr)		Volume to Capacity Ratio (V/C)	
			AM	PM	AM	PM	AM	PM	AM	PM
L1	Deep Bay Road (two-way)	100	60	62	0.60	0.62	79	82	0.79	0.82
L4	Unnamed Rd 3 (two-way)	180	140	122	0.78	0.68	159	142	0.88	0.79

Notes: $V/C \text{ Ratio} = \text{Volume} / \text{Design Capacity}$

- (i) A peak hour v/c ratio of 1.0 or less indicates a satisfactory level of traffic. A V/C ratio between 1.0 and 1.2 indicates a manageable degree of congestion. A V/C ratio above 1.2 indicates more serious congestion.
- (ii) Refer to Figure 3.2 for link location.

Table 5.3 reveals that the key road links identified along the delivery Route 1 will operate within capacity during peak hours for both Reference and Design Scenarios.

5.6.2 Future Year Junction Capacity Assessment

Based on the Reference Flows and Design Flows, junction capacity assessments for design year 2027 are carried out and the results are presented in **Table 5.4**, with detailed calculation sheets given in **Appendix A**.

Table 5.4 Future Year Junction Capacity Assessment

Jun No.	Junction Location	Type/ Capacity Index	2027 Reference Scenario		2027 Design Scenario	
			AM	PM	AM	PM
D	Deep Bay Rd / Unnamed Rd 2	Priority / DFC	0.02	0.02	0.02	0.04
E	Unnamed Rd 1 / Unnamed Rd 2	Priority / DFC	0.05	0.11	0.05	0.11
F	Deep Bay Rd / Unnamed Rd 3	Priority / DFC	0.17	0.16	0.21	0.19

*Notes: RC = reserve capacity; DFC - Design Flow / Capacity Ratio

- (i) The performance of a priority junction or roundabout is normally measured by its Design Flow / Capacity (DFC) ratio. A DFC ratio less than 1.0 indicates that the junction is operating within design capacity. A DFC ratio greater than 1.0 indicates that the junction is overloaded, resulting in traffic queues and longer delay time to the minor arm traffic.
- (ii) The performance of a traffic signalised junction is indicated by its reserve capacity (RC). A positive RC ($RC > 0$) indicates that the junction is operating with spare capacity. A negative RC ($RC < 0$) indicates that the junction is overloaded; resulting in traffic queues and longer delay time.
- (iii) Refer to Figure 3.2 for junction location.

Table 5.4 reveals that all the key junctions identified along the delivery Route 1 will operate satisfactorily with ample junction capacity in both 2027 reference and 2027 design scenarios during peak hours.

5.7 Proposed Improvement Measures

The traffic assessment indicates that the proposed development will not generate significant traffic impact, and the existing road network is sufficient to accommodate the anticipated demand. Nevertheless, to mitigate the potential traffic impact arising from the development, the following traffic improvement measures will be proposed:

5.7.1 Provision of laybys

Laybys will be provided along the delivery route to improve the link capacity, particularly, in the northern section of Deep Bay Road where the lane width is less than 7m. Therefore, three laybys will be provided at intervals of approximately 60m, as indicated in **Figure 5.3**. The dimension of the proposed laybys is around 3m(W) x 30m(L), the typical layout of layby is demonstrated in **Figure 5.4**.

The location and details of laybys to be provided will be subject to the on-site condition, and comments from relevant departments will be sought prior to the laybys construction, ensuring the engineering feasibility of the proposed road improvement works.

5.7.2 Enhanced Traffic Signage

Install temporary signage along the route to guide traffic effectively. Examples include:

- Directional signs to the development and nearby parking areas.
- "No Stopping" or "No Parking" signs at critical points to prevent bottlenecks.

6 Summary and Conclusion

6.1 Summary

The Applicant intends to seek the Town Planning Board permission to utilise the Project Site as the open storage for construction materials and equipment on a temporary basis of 3 years.

In order to appraise the existing traffic conditions, classified turning movement count surveys have been carried out at the key junctions and road links in the vicinity of project site on 10 September 2024 from 7:30 to 10:30 in the morning and 16:00 to 19:00 in the evening. The morning and evening peak hours of the road network have been identified as 7:45am to 8:45am and 16:30pm to 17:30pm, respectively.

Year 2027 is used as the design year for the traffic impact assessment. Based on the historical data, an annual growth rate of 0.54% was adopted for this study. This growth factor has been applied to the observed traffic flows in 2024 to determine the anticipated traffic flows in design year 2027.

Based on the assessment results of existing traffic conditions in the vicinity of project site, control measures will be undertaken by Applicant to minimize the traffic impact. Specifically, a delivery Route 1 will be designated for the development operation, ensuring the delivery efficiency. The future traffic situation will be assessed based on the delivery route committed by the Applicant.

The assessment results reveal that the key junctions and road links identified along Route 1 will operate satisfactorily with sufficient capacity in both 2027 reference and 2027 design scenarios during peak hours.

Improvement works are also proposed to mitigate the potential traffic impact arising from the development, such as provision of laybys and enhanced traffic signage along the delivery route. With the traffic management undertaken by the Applicant, it is believed that the proposed development would not generate significant impact to the adjacent road network.

6.2 Conclusion

The findings of this study show that the development traffic will not cause adverse traffic impact onto the local road network. The proposed development is therefore supported from the traffic engineering point of view at this stage.

Figures



2000m

1000m

800m

600m

400m

200m

100m

100m 200m 400m 600m 800m 1000m 1200m 1400m 1600m 1800m



Proposal - S.16 Planning Application For Proposed Temporary Open Storage of Construction Materials and Construction Equipment for a Period of 3 Years at Various Lots in D.D.129 Lau Fau Shan, Yuen Long, New Territories

Drawing Title - Site Location

Dwg. No. - Figure 1 Rev. - C


Scale - 1:10000@A4 Date - Jan 2025






F:\8FM\8FM PROJECT\p80108 LOT NOS. 1809 (PART),1843 IN D.D. 129, LAU FAU SHAN\DATA\DRAWING\FIGURE 2.1C.DWG

Proposal - S.16 Planning Application For Proposed Temporary Open Storage of Construction Materials and Construction Equipment for a Period of 3 Years at Various Lots in D.D.129 Lau Fau Shan, Yuen Long, New Territories			
Drawing Title -		Layout of Project Site	
Dwg. No. - Figure 2.1	Rev. - C	Legend: Application Site Site Office/ Storeroom (12m x 3m) Private Car Parking Spaces (5m x 2.5m) Ingress/Egress (About 12m wide) LUL Bay for LGV (m x 3.5m) Maneuvering Circle About 20m(D)	
Scale - 1:1000@A4	Date - Jan 2025		



F:\8FM\8FM PROJECT\880108 LOT NOS. 1809 (PART),1843 IN D.D. 129, LAU FAU SHAN\DATA\DRAWING\FIGURE 2.2C.DWG

Proposal - S.16 Planning Application For Proposed Temporary Open Storage of Construction Materials and Construction Equipment for a Period of 3 Years at Various Lots in D.D.129 Lau Fau Shan, Yuen Long, New Territories			
Drawing Title -		Vehicle Access Arrangement	
Dwg. No. -	Figure 2.2	Rev. -	C
Scale -	1:500@A4	Date -	Jan 2025
		Legend: Application Site Ingress/Egress (About 12m wide)	



F:\8FM\8FM PROJECT\p80108 LOT NOS. 1809 (PART),1843 IN D.D. 129, LAU FAU SHAN\DATA\DRAWING\FIGURE 2.3C.DWG

Proposal - S.16 Planning Application For Proposed Temporary Open Storage of Construction Materials and Construction Equipment for a Period of 3 Years at Various Lots in D.D.129 Lau Fau Shan, Yuen Long, New Territories

Drawing Title - Swept Path Analysis for 12m Large Fire Appliance

Dwg. No. - Figure 2.3	Rev. - C
Scale - 1:500@A4	Date - Jan 2025

Legend:
 Application Site
 Ingress/Egress (About 12m wide)





2000m

1000m

800m

600m

400m

200m

100m

100m 200m

400m

600m

800m

1000m

1200m

1400m

1600m

1800m

Proposal - S.16 Planning Application For Proposed Temporary Open Storage of Construction Materials and Construction Equipment for a Period of 3 Years at Various Lots in D.D.129 Lau Fau Shan, Yuen Long, New Territories

Drawing Title - Public Transport Facilities

Dwg. No. - Figure 3.1

Rev. - C

Legend:

Scale - 1:10000@A4

Date - Jan 2025

 BUS STOP  GMB STOP





2000m

1000m

800m


600m

400m

200m

100m

100m 200m 400m 600m 800m 1000m 1200m 1400m 1600m 1800m





Proposal - S.16 Planning Application For Proposed Temporary Open Storage of Construction Materials and Construction Equipment for a Period of 3 Years at Various Lots in D.D.129 Lau Fau Shan, Yuen Long, New Territories


Drawing Title - Key Road Links and Junctions


Dwg. No. - Figure 3.2 Rev. - C

Scale - 1:10000@A4 Date - Jan 2025

Legend:
 Key Junction
 Key Road Link






Proposal - S.16 Planning Application For Proposed Temporary Open Storage of Construction Materials and Construction Equipment for a Period of 3 Years at Various Lots in D.D.129 Lau Fau Shan, Yuen Long, New Territories			
Drawing Title -		2024 Observed Flows During AM & PM Peak Hours	
Dwg. No. -	Figure 3.3	Rev. -	C
Scale -	--	Date -	Jan 2025
		Legend: Traffic Flows at AM Peak Hr (PCU/HR) _____100 Traffic Flows at PM Peak Hr (PCU/HR) _____(100)	
			



Lau Fau Shan Roundabout

Deep Bay Road



Proposal - S.16 Planning Application For Proposed Temporary Open Storage of Construction Materials and Construction Equipment for a Period of 3 Years at Various Lots in D.D.129 Lau Fau Shan, Yuen Long, New Territories

Drawing Title - Existing Condition of Deep Bay Road within 500m Northeast of the Junction of the Lau Fau Shan Roundabout






Dwg. No. - Figure 3.4

Rev. - C

Scale - 1:1600 @ A3

Date - Jan 2025

Legend -

-  2-Lane Road Section
-  1-Lane Road Section
-  Road Section with Passing Place / Layby
-  Road Section with Passing Place on Adjacent Concrete Pavement
-  Concrete Pavement Accessible by Vehicles



Proposal -
 S.16 Planning Application
 For Proposed Temporary
 Open Storage of
 Construction Materials and
 Construction Equipment for
 a Period of 3 Years at
 Various Lots in D.D.129 Lau
 Fau Shan, Yuen Long, New
 Territories


Drawing Title -
 Existing Condition of Tin
 Yuet Road within 500m
 East of the Junction of
 Deep Bay Road, Unnamed
 Road 3

Dwg. No. - Figure 3.5

Rev. - C

Scale - 1:1700 @ A3


Date - Jan 2025




Legend -

- 2-Lane Road Section
- 1-Lane Road Section
- Road Section with Passing Place / Layby
- Road Section with Passing Place on Adjacent Concrete Pavement
- Concrete Pavement Accessible by Vehicles





Proposal - S.16 Planning Application For Proposed Temporary Open Storage of Construction Materials and Construction Equipment for a Period of 3 Years at Various Lots in D.D.129 Lau Fau Shan, Yuen Long, New Territories			
Drawing Title - 2024 Observed Link Flow (Veh/hr) During AM & PM Peak Hours			
Dwg. No. - Figure 3.6	Rev. - C	Legend:	
Scale - --	Date - Jan 2025	Traffic Flows at AM Peak Hr (VEH/HR) _____100 Traffic Flows at PM Peak Hr (VEH/HR) _____(100)	



2000m

1000m

800m

600m

400m

200m

100m

100m 200m

400m

600m

800m


1000m

1200m

1400m

1600m

1800m



Proposal - S.16 Planning Application For Proposed Temporary Open Storage of Construction Materials and Construction Equipment for a Period of 3 Years at Various Lots in D.D.129 Lau Fau Shan, Yuen Long, New Territories

Drawing Title - Proposed Routing



Dwg. No. - Figure 3.7

Rev. - C

Scale - 1:10000@A4

Date - Jan 2025





F:\8FM\8FM PROJECT\PROJECT\1809 (PART)1843 IN D.D. 129, LAU FAU SHAN\DATA\DRAWING\FIGURE 3.8-1C.DWG



Proposal - S.16 Planning Application For Proposed Temporary Open Storage of Construction Materials and Construction Equipment for a Period of 3 Years at Various Lots in D.D.129 Lau Fau Shan, Yuen Long, New Territories

Drawing Title - Swept Path Analysis for 7m LGV at Junction on Deep Bay Road and unnamed road 2

Dwg. No. - Figure 3.8-1 Rev. - C

Scale - 1:500@A4 Date - Jan 2025







F:\8FM\8FM PROJECT\PS0108 LOT NOS. 1809 (PART),1843 IN D.D. 129, LAU FAU SHAN\DATA\DRAWING\FIGURE 3.8-2C.DWG

Proposal - S.16 Planning Application For Proposed Temporary Open Storage of Construction Materials and Construction Equipment for a Period of 3 Years at Various Lots in D.D.129 Lau Fau Shan, Yuen Long, New Territories	
Drawing Title - Swept Path Analysis for 7m LGV at Junction on Deep Bay Road and Unnamed Road 3	
Dwg. No. - Figure 3.8-2	Rev. - C
Scale - 1:500@A4	Date - Jan 2025





F:\8FM\8FM PROJECT\P80108 LOT NOS. 1809 (PART),1843 IN D.D. 129, LAU FAU SHAN\DATA\DRAWING\FIGURE 3.8-3C.DWG


Proposal - S.16 Planning Application For Proposed Temporary Open Storage of Construction Materials and Construction Equipment for a Period of 3 Years at Various Lots in D.D.129 Lau Fau Shan, Yuen Long, New Territories


Drawing Title - Swept Path Analysis for 7m LGV at Junction on Unnamed Road 3 and Tin Yuet Road


Dwg. No. - Figure 3.8-3 Rev. - C

Scale - 1:500@A4 Date - Jan 2025





Proposal - S.16 Planning Application For Proposed Temporary Open Storage of Construction Materials and Construction Equipment for a Period of 3 Years at Various Lots in D.D.129 Lau Fau Shan, Yuen Long, New Territories			
Drawing Title - 2027 Reference Traffic Flows during Peak Hours			
Dwg. No. - Figure 5.1	Rev. - C	Legend:	
Scale - --	Date - Jan 2025	Traffic Flows at AM Peak Hr (PCU/HR) _____ 100	
		Traffic Flows at PM Peak Hr (PCU/HR) _____ (100)	



Proposal - S.16 Planning Application For Proposed Temporary Open Storage of Construction Materials and Construction Equipment for a Period of 3 Years at Various Lots in D.D.129 Lau Fau Shan, Yuen Long, New Territories			
Drawing Title -		2027 Design Traffic Flows during Peak Hours	
Dwg. No. -	Figure 5.2	Rev. -	C
Scale -	--	Date -	Jan 2025
Legend:			
Traffic Flows at AM Peak Hr (PCU/HR) _____ 100		Traffic Flows at PM Peak Hr (PCU/HR) _____ (100)	



Added 3m(W) x 30m(L) Layby

2000m

1000m

600m

200m

100m

100m 200m

400m

600m

800m

1000m

1200m

1400m

1600m

1800m

Deep Bay Road

Unnamed Road 3

Unnamed Road 2

Road 1

Site

60m
60m
60m
60m

48m

6.7m

7.17m

8.1

4.8

12.4

26.8

16.1

32.4

19.0

25.0

35.8

30.1

5.3

露天貨倉

雲浮仙觀

Wan Fau Sin Koon

骨灰龕

墓地

Graves

墓地

墓地

6.8

13.5

F:\8FM\8FM PROJECT\PS0108 LOT NOS. 1809 (PART),1843 IN D.D. 129, LAU FAU SHAN\DATA\DRAWING\FIGURE 5.3C.DWG

Proposal - S.16 Planning Application For Proposed Temporary Open Storage of Construction Materials and Construction Equipment for a Period of 3 Years at Various Lots in D.D.129 Lau Fau Shan, Yuen Long, New Territories

Drawing Title - Provision of Laybys at Deep Bay Road

Dwg. No. - Figure 5.3

Rev. - C

Scale - 1:10000@A4

Date - Jan 2025





2000m

1000m

800m

600m

400m

200m

100m

100m 200m

400m

600m

800m

1000m

1200m

1400m

1600m

1800m

Existing Road

8m

8m

RM1107

30m

3m



TS620
150mmx520mm



TS620
150mmx520mm

Proposal - S.16 Planning Application For Proposed Temporary Open Storage of Construction Materials and Construction Equipment for a Period of 3 Years at Various Lots in D.D.129 Lau Fau Shan, Yuen Long, New Territories

Drawing Title - Typical Layout of Layby

Dwg. No. - Figure 5.4

Rev. - C

Scale - 1:10000@A4

Date - Jan 2025



F:\8FM\8FM PROJECT\p80108 LOT NOS. 1809 (PART),1843 IN D.D. 129, LAU FAU SHAN\DATA\DRAWING\FIGURE 5.4C.DWG



Appendix A

Junction Calculation Sheets

8FM CONSULTANCY LIMITED

TRAFFIC SIGNAL CALCULATION

INITIALS

DATE

Various Lots in DD129, Lau Fau Shan

Project No.: 80108

Prepared By: FF

FF

Sep-24

Tin Wah Road / Tin Ying Road

2024 Observed - AM Peak

Checked By: MM


MM

Sep-24


Reviewed By: FM

FM

Sep-24



No. of stages per cycle	N = 4
Intergreen Period	I = 31 sec
Cycle time	C = 120 sec
Sum(y)	Y = 0.444
Loss time	L = 45 sec
Total Flow	= 4877.6 pcu
Co = (1.5*L+5)/(1-Y)	= 130.4 sec
Cm = L/(1-Y)	= 81.0 sec
Yult	= 0.563
R.C.ult = (Yult-Y)/Y*100%	= 26.6 %
Cp = 0.9*L/(0.9-Y)	= 88.9 sec
Ymax = 1-L/C	= 0.625
R.C.(C) = (0.9*Ymax-Y)/Y*100%	= 26.6 %



Pedestrian Phase	Width (m)	Stage	Green Time Required		Green Time Provided (s)		Check
			SG	FG	SG	FG	

Movement	Stage	Lane Width m.	Phase	No. of lane	Radius m.	O	N	Straight-Ahead Sat. Flow	m			Total Flow pcu/h	Proportion of Turning Vehicles	Sat. Flow pcu/h	Flare lan Length m.	Flare lane Effect	Revised Sat. Flow pcu/h	y	Greater y	L sec	g (required) sec	g (input) sec	Degree of Saturation X	Queue Length (m/lane)	Average Delay (sec)
									Left pcu/h	Straight pcu/h	Right pcu/h														
3	1,2,3,4	3.40		1	20		N	1955	890			890	1.00	1819			1819	0.489		27	83	19	3.126	890	2018
2	3	3.40		2				4190		390		390	0.00	4190			4190	0.093			16	19	0.594	55	48
1	3	3.40		1	25			2095			33	33	1.00	1976			1976	0.016	0.016	9	3	12	0.168	5	51
								0																	
6	1,2	4.80		1	25		N	2095	637			637	1.00	1976			1976	0.322			54	42	0.911	84	56
5	2	3.40		1				2095		281		281	0.00	2095			2095	0.134	0.134		23	23	0.711	39	50
4,5	2	3.40		1	35			2095		0	329	329	1.00	2009			2009	0.164			28				
4	2	3.40		1	30			2095			327	327	1.00	1995			1995	0.164			28	23	0.868	53	68
8,9	1	3.40		1	25		N	1955	89	334		423	0.21	1931			1931	0.219	0.219		37	45	0.584	44	32
7,8	1	3.30		1	28			2085		40	417	457	0.91	1988			1988	0.230			39	45	0.613	48	32
7	1	3.30		1	25			2085			431	431	1.00	1967			1967	0.219			37	37	0.711	50	40
12	3,4	3.30		1	25		N	1945	43			43	1.00	1835			1835	0.024			4	22	0.131	6	42
11	4	3.30		2				4170		486		486	0.00	4170			4170	0.117			20	22	0.650	67	47
10	4	3.30		1	40			2085			149	149	1.00	2010			2010	0.074	0.074	9	13	22	0.414	20	45
																					0	0			

8FM CONSULTANCY LIMITED

PRIORITY JUNCTION CALCULATION

INITIALS

DATE

Traffic Impact Assessment for Proposed Temporary Open Storage of Construction Material and Equipment of 3 Years at Various Lots in D.D.129, Lau Fau Shan

Prepared By: FF

Jan-2025

Jn B - Lau Fau Shan Rd / Tin Wah Rd / Ping Ha Rd

2024 Observed - AM Peak


Project No.: 80108

Checked By: MM

Jan-2025

Reviewed By: FM

Jan-2025



NOTES : (GEOMETRIC INPUT DATA)

- W = MAJOR ROAD WIDTH
- W_{cr} = CENTRAL RESERVE WIDTH
- W_{b-a} = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-a
- W_{b-c} = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-c
- W_{c-b} = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM c-b
- Vi_{b-a} = VISIBILITY TO THE LEFT FOR VEHICLES WAITING IN STREAM b-a
- Vr_{b-a} = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-a
- Vr_{b-c} = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-c
- Vr_{c-b} = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM c-b
- D = STREAM-SPECIFIC B-A
- E = STREAM-SPECIFIC B-C
- F = STREAM-SPECIFIC C-B
- Y = (1-0.0345W)

GEOMETRIC DETAILS:

MAJOR ROAD (ARM A)

W = 8.9 (metres)
 W_{cr} = 0 (metres)
 q_{a-b} = 560 (pcu/hr)
 q_{a-c} = 136 (pcu/hr)

MAJOR ROAD (ARM C)

W_{c-b} = 3.5 (metres)
 Vr_{c-b} = 150 (metres)
 q_{c-a} = 170 (pcu/hr)
 q_{c-b} = 352 (pcu/hr)

MINOR ROAD (ARM B)

W_{b-a} = 4.2 (metres)
 W_{b-c} = 4.2 (metres)
 Vi_{b-a} = 200 (metres)
 Vr_{b-a} = 200 (metres)
 Vr_{b-c} = 50 (metres)
 q_{b-a} = 527 (pcu/hr)
 q_{b-c} = 505 (pcu/hr)

GEOMETRIC FACTORS :

D = 1.161
 E = 0.985
 F = 1.013
 Y = 0.693

THE CAPACITY OF MOVEMENT :

Q_{b-a} = 445 (pcu/hr)
 Q_{b-c} = 645 (pcu/hr)
 Q_{c-b} = 577 (pcu/hr)
 Q_{c-a} = 701 (pcu/hr)

TOTAL FLOW = 2250 (pcu/hr)

COMPARISON OF DESIGN FLOW TO CAPACITY:

DFC_{b-a} = 1.1843
 DFC_{b-c} = 0.7829
 DFC_{c-b} = 0.6107
 DFC_{c-a} = 0.2426

CRITICAL DFC = 1.18

8FM CONSULTANCY LIMITED

ROUNDBABOUT JUNCTION ANALYSIS

INITIALS

DATE

Traffic Impact Assessment for Proposed Temporary Open Storage of Construction Material and Equipment of 3 Years at Various Lots in D.D.129, Lau Fau Shan

Prepared By: FF

Jan-2025

Jn C - Lau Fau Shan Rd / Deep Bay Rd / Shan Tung Str / Lau Fau Shan Main Str 2024 Observed - AM Peak


Project No.: 80108

Checked By: MM

Jan-2025

Reviewed By: FM

Jan-2025



GEOMETRIC DETAILS:

	ARM	A	B	C	D	
V	=	Approach half width (m)	1.9	1.5	3.2	1.9
E	=	Entry width (m)	1.9	4.1	4.2	3.7
L	=	Effective length of flare (m)	1.0	2.3	1.5	1.8
R	=	Entry radius (m)	14.0	46.0	7.4	7.5
D	=	Inscribed circle diameter (m)	38.0	38.0	38.0	38.0
A	=	Entry angle (degree)	42.0	52.0	20.0	51.0
Q	=	Entry flow (pcu/h)	23	204	457	192
Qc	=	Circulating flow across entry (pcu/h)	412	302	18	241

OUTPUT PARAMETERS:

S	=	Sharpness of flare = $1.6(E-V)/L$	0.00	1.81	1.07	1.60
K	=	$1-0.00347(A-30)-0.978(1/R-0.05)$	0.94	0.95	0.95	0.85
X2	=	$V + ((E-V)/(1+2S))$	1.90	2.06	3.52	2.33
M	=	$EXP((D-60)/10)$	0.11	0.11	0.11	0.11
F	=	$303 \times X2$	576	625	1066	706
Td	=	$1+(0.5/(1+M))$	1.45	1.45	1.45	1.45
Fc	=	$0.21 \times Td(1+0.2 \times X2)$	0.42	0.43	0.52	0.45
Qe	=	$K(F-Fc \times Qc)$	377	471	1006	506
DFC	=	Design flow/Capacity = Q/Qe	0.06	0.43	0.45	0.38

TOTAL FLOW = 1847 (pcu/hr)
CRITICAL DFC = 0.45

8FM CONSULTANCY LIMITED

PRIORITY JUNCTION CALCULATION

INITIALS

DATE

Traffic Impact Assessment for Proposed Temporary Open Storage of Construction Material and Equipment of 3 Years at Various Lots in D.D.129, Lau Fau Shan

Prepared By: FF

Jan-2025

Jn D - Deep Bay Rd / Unnamed Rd 2

2024 Observed - AM Peak


Project No.: 80108

Checked By: MM

Jan-2025

Reviewed By: FM

Jan-2025



NOTES : (GEOMETRIC INPUT DATA)

- W = MAJOR ROAD WIDTH
- W cr = CENTRAL RESERVE WIDTH
- W b-a = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-a
- W b-c = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-c
- W c-b = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM c-b
- VI b-a = VISIBILITY TO THE LEFT FOR VEHICLES WAITING IN STREAM b-a
- Vr b-a = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-a
- Vr b-c = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-c
- Vr c-b = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM c-b
- D = STREAM-SPECIFIC B-A
- E = STREAM-SPECIFIC B-C
- F = STREAM-SPECIFIC C-B
- Y = (1-0.0345W)

GEOMETRIC DETAILS:

GENERAL

W = 3.90 (metres)
W cr = 0 (metres)

Y = 0.865

MAJOR ROAD (ARM A)

W a-d = 2.0 (metres)
Vr a-d = 120 (metres)
q a-b = 3 (pcu/hr)
q a-c = 49 (pcu/hr)
q a-d = 1 (pcu/hr)

MAJOR ROAD (ARM C)

W c-b = 2.0 (metres)
Vr c-b = 60 (metres)
q c-a = 39 (pcu/hr)
q c-b = 9 (pcu/hr)
q c-d = 1 (pcu/hr)

MINOR ROAD (ARM B)

W b-a = 3.3 (metres)
W b-c = 3.3 (metres)
VI b-a = 28 (metres)
Vr b-a = 28 (metres)
Vr b-c = 80 (metres)
q b-a = 0 (pcu/hr)
q b-c = 10 (pcu/hr)
q b-d = 3 (pcu/hr)

MINOR ROAD (ARM D)

W d-c = 6.0 (metres)
W d-a = 6.0 (metres)
VI d-c = 22 (metres)
Vr d-c = 60 (metres)
Vr d-a = 90 (metres)
q d-c = 4 (pcu/hr)
q d-a = 2 (pcu/hr)
q d-b = 2 (pcu/hr)

GEOMETRIC FACTORS :

X b = 0.818
X c = 0.799
Z b = 0.928
M b = 0.860

X a = 0.845
X d = 1.066
Z d = 1.188
M d = 1.097

PROPORTION OF MINOR STRAIGHT AHEAD TRAFFIC :

r b-a = 0
ql b-d = 1.5 (pcu/hr)
qr b-d = 1.5 (pcu/hr)

r d-c = 0.007
ql d-b = 0.7550628 (pcu/hr)
qr d-b = 0.7449372 (pcu/hr)

CAPACITY OF MOVEMENT :

Q b-a = 489 (pcu/hr)
Q b-c = 677 (pcu/hr)
Q c-b = 582 (pcu/hr)
Ql b-d = 515 (pcu/hr)
Qr b-d = 490 (pcu/hr)

Q d-c = 637 (pcu/hr)
Q d-a = 869 (pcu/hr)
Q a-d = 615 (pcu/hr)
Ql d-b = 659 (pcu/hr)
Qr d-b = 641 (pcu/hr)

TOTAL FLOW = 122.7 (PCU/HR)

COMPARISON OF DESIGN FLOW TO CAPACITY :

DFC b-a = 0.0000
DFC b-c = 0.0154
DFC c-b = 0.0160
DFCI b-d = 0.0029
DFCr b-d = 0.0031
DFC d-c = 0.0068
DFC d-a = 0.0017
DFC a-d = 0.0016
DFCI d-b = 0.0011
DFCr d-b = 0.0012

CRITICAL DFC = 0.02

8FM CONSULTANCY LIMITED

PRIORITY JUNCTION CALCULATION

INITIALS

DATE

Traffic Impact Assessment for Proposed Temporary Open Storage of Construction Material and Equipment of 3 Years at Various Lots in D.D.129, Lau Fau Shan

Prepared By: FF

Jan-2025

Jn E - Unnamed Rd 1 / Unnamed Rd 2

2024 Observed - AM Peak


Project No.: 80108

Checked By: MM

Jan-2025

Reviewed By: FM

Jan-2025



NOTES : (GEOMETRIC INPUT DATA)

- W = MAJOR ROAD WIDTH
- W_{cr} = CENTRAL RESERVE WIDTH
- W_{b-a} = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-a
- W_{b-c} = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-c
- W_{c-b} = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM c-b
- V_{l b-a} = VISIBILITY TO THE LEFT FOR VEHICLES WAITING IN STREAM b-a
- V_{r b-a} = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-a
- V_{r b-c} = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-c
- V_{r c-b} = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM c-b
- D = STREAM-SPECIFIC B-A
- E = STREAM-SPECIFIC B-C
- F = STREAM-SPECIFIC C-B
- Y = (1-0.0345W)

GEOMETRIC DETAILS:

MAJOR ROAD (ARM A)

W = 5.2 (metres)
W_{cr} = 0 (metres)
q_{a-b} = 0 (pcu/hr)
q_{a-c} = 41 (pcu/hr)

MAJOR ROAD (ARM C)

W_{c-b} = 2.5 (metres)
V_{r c-b} = 22 (metres)
q_{c-a} = 49 (pcu/hr)
q_{c-b} = 11 (pcu/hr)

MINOR ROAD (ARM B)

W_{b-a} = 2.5 (metres)
W_{b-c} = 2.5 (metres)
V_{l b-a} = 22 (metres)
V_{r b-a} = 24 (metres)
V_{r b-c} = 22 (metres)
q_{b-a} = 17 (pcu/hr)
q_{b-c} = 6 (pcu/hr)

GEOMETRIC FACTORS :

D = 0.752
E = 0.813
F = 0.813
Y = 0.821

F for (Q_{b-ac}) = 0.263

THE CAPACITY OF MOVEMENT :

Q_{b-a} = 452 (pcu/hr)
Q_{b-c} = 596 (pcu/hr)
Q_{c-b} = 596 (pcu/hr)
Q_{b-ac} = 483 (pcu/hr)
Q_{c-a} = 1768 (pcu/hr)
TOTAL FLOW = 59.1 (pcu/hr)

COMPARISON OF DESIGN FLOW TO CAPACITY:

DFC_{b-a} = 0.0372
DFC_{b-c} = 0.0101
DFC_{c-b} = 0.0178
DFC_{b-ac} = 0.0472
(Share Lane)
DFC_{c-a} = 0.0274

CRITICAL DFC = 0.05

8FM CONSULTANCY LIMITED

PRIORITY JUNCTION CALCULATION

INITIALS

DATE

Traffic Impact Assessment for Proposed Temporary Open Storage of Construction Material and Equipment of 3 Years at Various Lots in D.D.129, Lau Fau Shan

Prepared By: FF

Jan-2025

Jn F - Deep Bay Rd / Unnamed Rd 3

2024 Observed - AM Peak

Project No.: 80108


Checked By: MM

Jan-2025

Reviewed By: FM

FM

Jan-2025



NOTES : (GEOMETRIC INPUT DATA)

- W = MAJOR ROAD WIDTH
- W_{cr} = CENTRAL RESERVE WIDTH
- W_{b-a} = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-a
- W_{b-c} = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-c
- W_{c-b} = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM c-b
- V_l b-a = VISIBILITY TO THE LEFT FOR VEHICLES WAITING IN STREAM b-a
- V_r b-a = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-a
- V_r b-c = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-c
- V_r c-b = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM c-b
- D = STREAM-SPECIFIC B-A
- E = STREAM-SPECIFIC B-C
- F = STREAM-SPECIFIC C-B
- Y = (1-0.0345W)

GEOMETRIC DETAILS:

MAJOR ROAD (ARM A)

W = 4.8 (metres)
W_{cr} = 0 (metres)
q_{a-b} = 4 (pcu/hr)
q_{a-c} = 24 (pcu/hr)

MAJOR ROAD (ARM C)

W_{c-b} = 2.1 (metres)
V_r c-b = 38 (metres)
q_{c-a} = 34 (pcu/hr)
q_{c-b} = 82 (pcu/hr)

MINOR ROAD (ARM B)

W_{b-a} = 2.5 (metres)
W_{b-c} = 2.5 (metres)
V_l b-a = 22 (metres)
V_r b-a = 24 (metres)
V_r b-c = 38 (metres)
q_{b-a} = 22 (pcu/hr)
q_{b-c} = 72 (pcu/hr)

GEOMETRIC FACTORS :

D = 0.752
E = 0.826
F = 0.791
Y = 0.834

F for (Q_{b-ac}) = 0.766

THE CAPACITY OF MOVEMENT :

Q_{b-a} = 434 (pcu/hr)
Q_{b-c} = 609 (pcu/hr)
Q_{c-b} = 583 (pcu/hr)
Q_{b-ac} = 556 (pcu/hr)
Q_{c-a} = 1547 (pcu/hr)

TOTAL FLOW = 82 (pcu/hr)

COMPARISON OF DESIGN FLOW TO CAPACITY:

DFC_{b-a} = 0.0509
DFC_{b-c} = 0.1186
DFC_{c-b} = 0.1407
DFC_{b-ac} = 0.1695
(Share Lane)
DFC_{c-a} = 0.0222

CRITICAL DFC = 0.17

8FM CONSULTANCY LIMITED

TRAFFIC SIGNAL CALCULATION

INITIALS

DATE

Various Lots in DD129, Lau Fau Shan

Project No.: 80108

Prepared By: FF

FF

Sep-24

Tin Wah Road / Tin Ying Road

2024 Observed - PM Peak

Checked By: MM


MM

Sep-24


Reviewed By: FM

FM

Sep-24



No. of stages per cycle	N = 4
Intergreen Period	I = 31 sec
Cycle time	C = 120 sec
Sum(y)	Y = 0.392
Loss time	L = 45 sec
Total Flow	= 4223 pcu
Co = (1.5*L+5)/(1-Y)	= 119.3 sec
Cm = L/(1-Y)	= 74.1 sec
Yult	= 0.563
R.C.ult = (Yult-Y)/Y*100%	= 43.4 %
Cp = 0.9*L/(0.9-Y)	= 79.8 sec
Ymax = 1-L/C	= 0.625
R.C.(C) = (0.9*Ymax-Y)/Y*100%	= 43.4 %



Pedestrian Phase	Width (m)	Stage	Green Time Required		Green Time Provided (s)		Check
			SG	FG	SG	FG	

Movement	Stage	Lane Width m.	Phase	No. of lane	Radius m.	O	N	Straight-Ahead Sat. Flow	m			Total Flow pcu/h	Proportion of Turning Vehicles	Sat. Flow pcu/h	Flare lan Length m.	Flare lane Effect	Revised Sat. Flow pcu/h	y	Greater y	L sec	g (required) sec	g (input) sec	Degree of Saturation X	Queue Length (m/lane)	Average Delay (sec)
									Left pcu/h	Straight pcu/h	Right pcu/h														
3	1,2,3,4	3.40		1	20		N	1955	543			543	1.00	1819			1819	0.298		27	57	18	1.955	418	946
2	3	3.40		2				4190		238		238	0.00	4190			4190	0.057			11	18	0.372	34	46
1	3	3.40		1	25			2095			24	24	1.00	1976			1976	0.012	0.012	9	2	11	0.129	4	51
6	1,2	4.80		1	25		N	2095	983			983	1.00	1976			1976	0.498			95	45	1.314	409	342
5	2	3.40		1				2095		286		286	0.00	2095			2095	0.137	0.137		26	26	0.628	37	45
4,5	2	3.40		1	35			2095		0	287	287	1.00	2009			2009	0.143			27				
4	2	3.40		1	30			2095			285	285	1.00	1995			1995	0.143			27	26	0.658	37	46
8,9	1	3.40		1	25		N	1955	106	280		386	0.28	1923			1923	0.201	0.201		38	47	0.510	39	29
7,8	1	3.30		1	28			2085		0	428	428	1.00	1979			1979	0.216			41	47	0.549	43	30
7	1	3.30		1	25			2085			404	404	1.00	1967			1967	0.205			39	39	0.628	45	36
12	3,4	3.30		1	25		N	1945	39			39	1.00	1835			1835	0.021			4	17	0.149	6	46
11	4	3.30		2				4170		233		233	0.00	4170			4170	0.056			11	17	0.391	33	47
10	4	3.30		1	40			2085			86	86	1.00	2010			2010	0.043	0.043	9	8	17	0.299	12	47

8FM CONSULTANCY LIMITED

PRIORITY JUNCTION CALCULATION

INITIALS

DATE

Traffic Impact Assessment for Proposed Temporary Open Storage of Construction Material and Equipment of 3 Years at Various Lots in D.D.129, Lau Fau Shan

Prepared By: FF

Jan-2025

Jn B - Lau Fau Shan Rd / Tin Wah Rd / Ping Ha Rd

2024 Observed - PM Peak


Project No.: 80108

Checked By: MM

Jan-2025

Reviewed By: FM

Jan-2025



NOTES : (GEOMETRIC INPUT DATA)

- W = MAJOR ROAD WIDTH
- W cr = CENTRAL RESERVE WIDTH
- W b-a = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-a
- W b-c = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-c
- W c-b = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM c-b
- Vi b-a = VISIBILITY TO THE LEFT FOR VEHICLES WAITING IN STREAM b-a
- Vr b-a = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-a
- Vr b-c = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-c
- Vr c-b = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM c-b
- D = STREAM-SPECIFIC B-A
- E = STREAM-SPECIFIC B-C
- F = STREAM-SPECIFIC C-B
- Y = (1-0.0345W)

GEOMETRIC DETAILS:

MAJOR ROAD (ARM A)

W = 8.9 (metres)
 W cr = 0 (metres)
 q a-b = 516 (pcu/hr)
 q a-c = 173 (pcu/hr)

MAJOR ROAD (ARM C)

W c-b = 3.5 (metres)
 Vr c-b = 150 (metres)
 q c-a = 142 (pcu/hr)
 q c-b = 499 (pcu/hr)

MINOR ROAD (ARM B)

W b-a = 4.2 (metres)
 W b-c = 4.2 (metres)
 Vi b-a = 200 (metres)
 Vr b-a = 200 (metres)
 Vr b-c = 50 (metres)
 q b-a = 480 (pcu/hr)
 q b-c = 662 (pcu/hr)

GEOMETRIC FACTORS :

D = 1.161
 E = 0.985
 F = 1.013
 Y = 0.693

THE CAPACITY OF MOVEMENT :

Q b-a = 383 (pcu/hr)
 Q b-c = 640 (pcu/hr)
 Q c-b = 578 (pcu/hr)
 Q c-a = 246 (pcu/hr)

TOTAL FLOW = 2471 (pcu/hr)

COMPARISON OF DESIGN FLOW TO CAPACITY:

DFC b-a = 1.2533
 DFC b-c = 1.0336
 DFC c-b = 0.8633
 DFC c-a = 0.5772

CRITICAL DFC = 1.25

8FM CONSULTANCY LIMITED

ROUNDBABOUT JUNCTION ANALYSIS

INITIALS

DATE

Traffic Impact Assessment for Proposed Temporary Open Storage of Construction Material and Equipment of 3 Years at Various Lots in D.D.129, Lau Fau Shan

Prepared By: FF

Jan-2025

Jn C - Lau Fau Shan Roundabout

2024 Observed - PM Peak


Project No.: 80108

Checked By: MM

Jan-2025

Reviewed By: FM

Jan-2025



GEOMETRIC DETAILS:

	ARM	A	B	C	D	
V	=	Approach half width (m)	1.9	1.5	3.2	1.9
E	=	Entry width (m)	1.9	4.1	4.2	3.7
L	=	Effective length of flare (m)	1.0	2.3	1.5	1.8
R	=	Entry radius (m)	14.0	46.0	7.4	7.5
D	=	Inscribed circle diameter (m)	38.0	38.0	38.0	38.0
A	=	Entry angle (degree)	42.0	52.0	20.0	51.0
Q	=	Entry flow (pcu/h)	19	178	359	200
Qc	=	Circulating flow across entry (pcu/h)	411	308	34	247

OUTPUT PARAMETERS:

S	=	Sharpness of flare = $1.6(E-V)/L$	0.00	1.81	1.07	1.60
K	=	$1-0.00347(A-30)-0.978(1/R-0.05)$	0.94	0.95	0.95	0.85
X2	=	$V + ((E-V)/(1+2S))$	1.90	2.06	3.52	2.33
M	=	$EXP((D-60)/10)$	0.11	0.11	0.11	0.11
F	=	$303 \times X2$	576	625	1066	706
Td	=	$1+(0.5/(1+M))$	1.45	1.45	1.45	1.45
Fc	=	$0.21 \times Td(1+0.2 \times X2)$	0.42	0.43	0.52	0.45
Qe	=	$K(F-Fc \times Qc)$	378	469	998	504
DFC	=	Design flow/Capacity = Q/Qe	0.05	0.38	0.36	0.40

TOTAL FLOW = 1757 (pcu/hr)
CRITICAL DFC = 0.40

8FM CONSULTANCY LIMITED

PRIORITY JUNCTION CALCULATION

INITIALS

DATE

Traffic Impact Assessment for Proposed Temporary Open Storage of Construction Material and Equipment of 3 Years at Various Lots in D.D.129, Lau Fau Shan

Prepared By: FF

Jan-2025

Jn D - Deep Bay Rd / Unnamed Rd 2

2024 Observed - PM Peak


Project No.: 80108

Checked By: MM

Jan-2025

Reviewed By: FM

Jan-2025



NOTES : (GEOMETRIC INPUT DATA)

- W = MAJOR ROAD WIDTH
- W cr = CENTRAL RESERVE WIDTH
- W b-a = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-a
- W b-c = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-c
- W c-b = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM c-b
- Vi b-a = VISIBILITY TO THE LEFT FOR VEHICLES WAITING IN STREAM b-a
- Vr b-a = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-a
- Vr b-c = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-c
- Vr c-b = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM c-b
- D = STREAM-SPECIFIC B-A
- E = STREAM-SPECIFIC B-C
- F = STREAM-SPECIFIC C-B
- Y = (1-0.0345W)

GEOMETRIC DETAILS:

GENERAL

W = 3.90 (metres)
W cr = 0 (metres)

Y = 0.865

MAJOR ROAD (ARM A)

W a-d = 2.0 (metres)
Vr a-d = 120 (metres)
q a-b = 0 (pcu/hr)
q a-c = 61 (pcu/hr)
q a-d = 0 (pcu/hr)

MAJOR ROAD (ARM C)

W c-b = 2.0 (metres)
Vr c-b = 60 (metres)
q c-a = 29 (pcu/hr)
q c-b = 11 (pcu/hr)
q c-d = 3 (pcu/hr)

MINOR ROAD (ARM B)

W b-a = 3.3 (metres)
W b-c = 3.3 (metres)
Vi b-a = 28 (metres)
Vr b-a = 28 (metres)
Vr b-c = 80 (metres)
q b-a = 1 (pcu/hr)
q b-c = 11 (pcu/hr)
q b-d = 0 (pcu/hr)

MINOR ROAD (ARM D)

W d-c = 6.0 (metres)
W d-a = 6.0 (metres)
Vi d-c = 22 (metres)
Vr d-c = 60 (metres)
Vr d-a = 90 (metres)
q d-c = 0 (pcu/hr)
q d-a = 0 (pcu/hr)
q d-b = 0 (pcu/hr)

GEOMETRIC FACTORS :

X b = 0.818
X c = 0.799
Z b = 0.928
M b = 0.860

X a = 0.845
X d = 1.066
Z d = 1.188
M d = 1.097

PROPORTION OF MINOR STRAIGHT AHEAD TRAFFIC :

r b-a = 0.001567
ql b-d = 0 (pcu/hr)
qr b-d = 0 (pcu/hr)

r d-c = 0.000
ql d-b = 0 (pcu/hr)
qr d-b = 0 (pcu/hr)

CAPACITY OF MOVEMENT :

Q b-a = 488 (pcu/hr)
Q b-c = 673 (pcu/hr)
Q c-b = 580 (pcu/hr)
Ql b-d = 513 (pcu/hr)
Qr b-d = 488 (pcu/hr)

Q d-c = 638 (pcu/hr)
Q d-a = 874 (pcu/hr)
Q a-d = 617 (pcu/hr)
Ql d-b = 660 (pcu/hr)
Qr d-b = 642 (pcu/hr)

TOTAL FLOW = 115.5 (PCU/HR)

COMPARISON OF DESIGN FLOW TO CAPACITY :

DFC b-a = 0.0020
DFC b-c = 0.0160
DFC c-b = 0.0195
DFCI b-d = 0.0000
DFCr b-d = 0.0000
DFC d-c = 0.0000
DFC d-a = 0.0000
DFC a-d = 0.0000
DFCI d-b = 0.0000
DFCr d-b = 0.0000

CRITICAL DFC = 0.02

8FM CONSULTANCY LIMITED

PRIORITY JUNCTION CALCULATION

INITIALS

DATE

Traffic Impact Assessment for Proposed Temporary Open Storage of Construction Material and Equipment of 3 Years at Various Lots in D.D.129, Lau Fau Shan

Prepared By: FF

Jan-2025

Jn E - Unnamed Rd 1 / Unnamed Rd 2

2024 Observed - PM Peak


Project No.: 80108

Checked By: MM

Jan-2025

Reviewed By: FM

Jan-2025



NOTES : (GEOMETRIC INPUT DATA)

- W = MAJOR ROAD WIDTH
- W_{cr} = CENTRAL RESERVE WIDTH
- W_{b-a} = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-a
- W_{b-c} = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-c
- W_{c-b} = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM c-b
- V_{l b-a} = VISIBILITY TO THE LEFT FOR VEHICLES WAITING IN STREAM b-a
- V_{r b-a} = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-a
- V_{r b-c} = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-c
- V_{r c-b} = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM c-b
- D = STREAM-SPECIFIC B-A
- E = STREAM-SPECIFIC B-C
- F = STREAM-SPECIFIC C-B
- Y = (1-0.0345W)

GEOMETRIC DETAILS:

MAJOR ROAD (ARM A)

W = 5.2 (metres)
W_{cr} = 0 (metres)
q_{a-b} = 0 (pcu/hr)
q_{a-c} = 35 (pcu/hr)

MAJOR ROAD (ARM C)

W_{c-b} = 2.5 (metres)
V_{r c-b} = 22 (metres)
q_{c-a} = 50 (pcu/hr)
q_{c-b} = 22 (pcu/hr)

MINOR ROAD (ARM B)

W_{b-a} = 2.5 (metres)
W_{b-c} = 2.5 (metres)
V_{l b-a} = 22 (metres)
V_{r b-a} = 24 (metres)
V_{r b-c} = 22 (metres)
q_{b-a} = 45 (pcu/hr)
q_{b-c} = 4 (pcu/hr)

GEOMETRIC FACTORS :

D = 0.752
E = 0.813
F = 0.813
Y = 0.821

F for (Q_{b-ac}) = 0.072

THE CAPACITY OF MOVEMENT :

Q_{b-a} = 450 (pcu/hr)
Q_{b-c} = 597 (pcu/hr)
Q_{c-b} = 597 (pcu/hr)
Q_{b-ac} = 458 (pcu/hr)
Q_{c-a} = 1735 (pcu/hr)
TOTAL FLOW = 71.8 (pcu/hr)

COMPARISON OF DESIGN FLOW TO CAPACITY:

DFC_{b-a} = 0.0996
DFC_{b-c} = 0.0059
DFC_{c-b} = 0.0363
DFC_{b-ac} = 0.1054
(Share Lane)
DFC_{c-a} = 0.0289

CRITICAL DFC = 0.11

8FM CONSULTANCY LIMITED

PRIORITY JUNCTION CALCULATION

INITIALS

DATE

Traffic Impact Assessment for Proposed Temporary Open Storage of Construction Material and Equipment of 3 Years at Various Lots in D.D.129, Lau Fau Shan

Prepared By: FF

Jan-2025

Jn F - Deep Bay Rd / Unnamed Rd 3

2024 Observed - PM Peak


Project No.: 80108

Checked By: MM

Jan-2025

Reviewed By: FM

Jan-2025



NOTES : (GEOMETRIC INPUT DATA)

- W = MAJOR ROAD WIDTH
- W_{cr} = CENTRAL RESERVE WIDTH
- W_{b-a} = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-a
- W_{b-c} = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-c
- W_{c-b} = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM c-b
- V_l b-a = VISIBILITY TO THE LEFT FOR VEHICLES WAITING IN STREAM b-a
- V_r b-a = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-a
- V_r b-c = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-c
- V_r c-b = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM c-b
- D = STREAM-SPECIFIC B-A
- E = STREAM-SPECIFIC B-C
- F = STREAM-SPECIFIC C-B
- Y = (1-0.0345W)

GEOMETRIC DETAILS:

MAJOR ROAD (ARM A)

W = 4.8 (metres)
W_{cr} = 0 (metres)
q_{a-b} = 8 (pcu/hr)
q_{a-c} = 13 (pcu/hr)

MAJOR ROAD (ARM C)

W_{c-b} = 2.1 (metres)
V_r c-b = 38 (metres)
q_{c-a} = 29 (pcu/hr)
q_{c-b} = 50.3 (pcu/hr)

MINOR ROAD (ARM B)

W_{b-a} = 2.5 (metres)
W_{b-c} = 2.5 (metres)
V_l b-a = 22 (metres)
V_r b-a = 24 (metres)
V_r b-c = 38 (metres)
q_{b-a} = 13 (pcu/hr)
q_{b-c} = 78 (pcu/hr)

GEOMETRIC FACTORS :

D = 0.752
E = 0.826
F = 0.791
Y = 0.834

F for (Q_{b-ac}) = 0.857

THE CAPACITY OF MOVEMENT :

Q_{b-a} = 447 (pcu/hr)
Q_{b-c} = 611 (pcu/hr)
Q_{c-b} = 584 (pcu/hr)
Q_{b-ac} = 580 (pcu/hr)
Q_{c-a} = 1645 (pcu/hr)
TOTAL FLOW = 50.3 (pcu/hr)

COMPARISON OF DESIGN FLOW TO CAPACITY:

DFC_{b-a} = 0.0293
DFC_{b-c} = 0.1282
DFC_{c-b} = 0.0861
DFC_{b-ac} = 0.1575
(Share Lane)
DFC_{c-a} = 0.0174

CRITICAL DFC = 0.16

8FM CONSULTANCY LIMITED

PRIORITY JUNCTION CALCULATION

INITIALS

DATE

Traffic Impact Assessment for Proposed Temporary Open Storage of Construction Material and Equipment of 3 Years at Various Lots in D.D.129, Lau Fau Shan

Prepared By: FF

Jan-2025

Jn D - Deep Bay Rd / Unnamed Rd 2

2027 Reference - AM Peak


Project No.: 80108

Checked By: MM

Jan-2025

Reviewed By: FM

Jan-2025



NOTES : (GEOMETRIC INPUT DATA)

- W = MAJOR ROAD WIDTH
- W cr = CENTRAL RESERVE WIDTH
- W b-a = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-a
- W b-c = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-c
- W c-b = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM c-b
- VI b-a = VISIBILITY TO THE LEFT FOR VEHICLES WAITING IN STREAM b-a
- Vr b-a = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-a
- Vr b-c = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-c
- Vr c-b = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM c-b
- D = STREAM-SPECIFIC B-A
- E = STREAM-SPECIFIC B-C
- F = STREAM-SPECIFIC C-B
- Y = (1-0.0345W)

GEOMETRIC DETAILS:

GENERAL

W = 3.90 (metres)
W cr = 0 (metres)

MAJOR ROAD (ARM A)

W a-d = 2.0 (metres)
Vr a-d = 120 (metres)
q a-b = 4 (pcu/hr)
q a-c = 50 (pcu/hr)
q a-d = 2 (pcu/hr)

MINOR ROAD (ARM B)

W b-a = 3.3 (metres)
W b-c = 3.3 (metres)
VI b-a = 28 (metres)
Vr b-a = 28 (metres)
Vr b-c = 80 (metres)
q b-a = 0 (pcu/hr)
q b-c = 11 (pcu/hr)
q b-d = 4 (pcu/hr)

MAJOR ROAD (ARM C)

W c-b = 2.0 (metres)
Vr c-b = 60 (metres)
q c-a = 40 (pcu/hr)
q c-b = 10 (pcu/hr)
q c-d = 2 (pcu/hr)

MINOR ROAD (ARM D)

W d-c = 6.0 (metres)
W d-a = 6.0 (metres)
VI d-c = 22 (metres)
Vr d-c = 60 (metres)
Vr d-a = 90 (metres)
q d-c = 5 (pcu/hr)
q d-a = 2 (pcu/hr)
q d-b = 2 (pcu/hr)

GEOMETRIC FACTORS :

X b = 0.818
X c = 0.799
Z b = 0.928
M b = 0.860

PROPORTION OF MINOR STRAIGHT AHEAD TRAFFIC :

r b-a = 0
ql b-d = 2 (pcu/hr)
qr b-d = 2 (pcu/hr)

CAPACITY OF MOVEMENT :

Q b-a = 487 (pcu/hr)
Q b-c = 676 (pcu/hr)
Q c-b = 581 (pcu/hr)
Ql b-d = 514 (pcu/hr)
Qr b-d = 489 (pcu/hr)

X a = 0.845
X d = 1.066
Z d = 1.188
M d = 1.097

r d-c = 0.008
ql d-b = 1.007874 (pcu/hr)
qr d-b = 0.992126 (pcu/hr)

Q d-c = 635 (pcu/hr)
Q d-a = 868 (pcu/hr)
Q a-d = 614 (pcu/hr)
Ql d-b = 657 (pcu/hr)
Qr d-b = 639 (pcu/hr)

COMPARISON OF DESIGN FLOW TO CAPACITY :

DFC b-a = 0.0000
DFC b-c = 0.0163
DFC c-b = 0.0172
DFCI b-d = 0.0039
DFCr b-d = 0.0041
DFC d-c = 0.0079
DFC d-a = 0.0023
DFC a-d = 0.0033
DFCI d-b = 0.0015
DFCr d-b = 0.0016

CRITICAL DFC = 0.02

TOTAL FLOW = 132 (PCU/HR)

8FM CONSULTANCY LIMITED

PRIORITY JUNCTION CALCULATION

INITIALS

DATE

Traffic Impact Assessment for Proposed Temporary Open Storage of Construction Material and Equipment of 3 Years at Various Lots in D.D.129, Lau Fau Shan

Prepared By: FF

Jan-2025

Jn E - Unnamed Rd 1 / Unnamed Rd 2

2027 Reference - AM Peak


Project No.: 80108

Checked By: MM

Jan-2025

Reviewed By: FM

Jan-2025



NOTES : (GEOMETRIC INPUT DATA)

- W = MAJOR ROAD WIDTH
- W_{cr} = CENTRAL RESERVE WIDTH
- W_{b-a} = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-a
- W_{b-c} = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-c
- W_{c-b} = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM c-b
- V_l b-a = VISIBILITY TO THE LEFT FOR VEHICLES WAITING IN STREAM b-a
- V_r b-a = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-a
- V_r b-c = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-c
- V_r c-b = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM c-b
- D = STREAM-SPECIFIC B-A
- E = STREAM-SPECIFIC B-C
- F = STREAM-SPECIFIC C-B
- Y = (1-0.0345W)

GEOMETRIC DETAILS:

MAJOR ROAD (ARM A)

W = 5.2 (metres)
 W_{cr} = 0 (metres)
 q_{a-b} = 0 (pcu/hr)
 q_{a-c} = 42 (pcu/hr)

MAJOR ROAD (ARM C)

W_{c-b} = 2.5 (metres)
 V_r c-b = 22 (metres)
 q_{c-a} = 50 (pcu/hr)
 q_{c-b} = 11 (pcu/hr)

MINOR ROAD (ARM B)

W_{b-a} = 2.5 (metres)
 W_{b-c} = 2.5 (metres)
 V_l b-a = 22 (metres)
 V_r b-a = 24 (metres)
 V_r b-c = 22 (metres)
 q_{b-a} = 18 (pcu/hr)
 q_{b-c} = 7 (pcu/hr)

GEOMETRIC FACTORS :

D = 0.752
 E = 0.813
 F = 0.813
 Y = 0.821

F for (Q_{b-ac}) = 0.28

THE CAPACITY OF MOVEMENT :

Q_{b-a} = 452 (pcu/hr)
 Q_{b-c} = 596 (pcu/hr)
 Q_{c-b} = 596 (pcu/hr)
 Q_{b-ac} = 485 (pcu/hr)
 Q_{c-a} = 1767 (pcu/hr)
 TOTAL FLOW = 61 (pcu/hr)

COMPARISON OF DESIGN FLOW TO CAPACITY:

DFC_{b-a} = 0.0398
 DFC_{b-c} = 0.0117
 DFC_{c-b} = 0.0185
 DFC_{b-ac} = 0.0516
 (Share Lane)
 DFC_{c-a} = 0.0283

CRITICAL DFC = 0.05

8FM CONSULTANCY LIMITED

PRIORITY JUNCTION CALCULATION

INITIALS

DATE

Traffic Impact Assessment for Proposed Temporary Open Storage of Construction Material and Equipment of 3 Years at Various Lots in D.D.129, Lau Fau Shan

Prepared By: FF

Jan-2025

Jn F - Deep Bay Rd / Unnamed Rd 3

2027 Reference - AM Peak


Project No.: 80108

Checked By: MM

Jan-2025

Reviewed By: FM

Jan-2025



NOTES : (GEOMETRIC INPUT DATA)

- W = MAJOR ROAD WIDTH
- W_{cr} = CENTRAL RESERVE WIDTH
- W_{b-a} = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-a
- W_{b-c} = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-c
- W_{c-b} = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM c-b
- V_l b-a = VISIBILITY TO THE LEFT FOR VEHICLES WAITING IN STREAM b-a
- V_r b-a = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-a
- V_r b-c = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-c
- V_r c-b = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM c-b
- D = STREAM-SPECIFIC B-A
- E = STREAM-SPECIFIC B-C
- F = STREAM-SPECIFIC C-B
- Y = (1-0.0345W)

GEOMETRIC DETAILS:

MAJOR ROAD (ARM A)

W = 4.8 (metres)
W_{cr} = 0 (metres)
q_{a-b} = 5 (pcu/hr)
q_{a-c} = 25 (pcu/hr)

MAJOR ROAD (ARM C)

W_{c-b} = 2.1 (metres)
V_r c-b = 38 (metres)
q_{c-a} = 35 (pcu/hr)
q_{c-b} = 84 (pcu/hr)

MINOR ROAD (ARM B)

W_{b-a} = 2.5 (metres)
W_{b-c} = 2.5 (metres)
V_l b-a = 22 (metres)
V_r b-a = 24 (metres)
V_r b-c = 38 (metres)
q_{b-a} = 23 (pcu/hr)
q_{b-c} = 74 (pcu/hr)

GEOMETRIC FACTORS :

D = 0.752
E = 0.826
F = 0.791
Y = 0.834

F for (Q_{b-ac}) = 0.763

THE CAPACITY OF MOVEMENT :

Q_{b-a} = 433 (pcu/hr)
Q_{b-c} = 609 (pcu/hr)
Q_{c-b} = 582 (pcu/hr)
Q_{b-ac} = 555 (pcu/hr)
Q_{c-a} = 1540 (pcu/hr)
TOTAL FLOW = 84 (pcu/hr)

COMPARISON OF DESIGN FLOW TO CAPACITY:

DFC_{b-a} = 0.0531
DFC_{b-c} = 0.1215
DFC_{c-b} = 0.1443
DFC_{b-ac} = 0.1746
(Share Lane)
DFC_{c-a} = 0.0227

CRITICAL DFC = 0.17

8FM CONSULTANCY LIMITED

PRIORITY JUNCTION CALCULATION

INITIALS

DATE

Traffic Impact Assessment for Proposed Temporary Open Storage of Construction Material and Equipment of 3 Years at Various Lots in D.D.129, Lau Fau Shan

Prepared By: FF

Jan-2025

Jn D - Deep Bay Rd / Unnamed Rd 2

2027 Reference - PM Peak


Project No.: 80108

Checked By: MM

Jan-2025

Reviewed By: FM

Jan-2025



NOTES : (GEOMETRIC INPUT DATA)

- W = MAJOR ROAD WIDTH
- W cr = CENTRAL RESERVE WIDTH
- W b-a = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-a
- W b-c = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-c
- W c-b = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM c-b
- VI b-a = VISIBILITY TO THE LEFT FOR VEHICLES WAITING IN STREAM b-a
- Vr b-a = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-a
- Vr b-c = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-c
- Vr c-b = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM c-b
- D = STREAM-SPECIFIC B-A
- E = STREAM-SPECIFIC B-C
- F = STREAM-SPECIFIC C-B
- Y = (1-0.0345W)

GEOMETRIC DETAILS:

GENERAL

W = 3.90 (metres)
W cr = 0 (metres)

Y = 0.865

MAJOR ROAD (ARM A)

W a-d = 2.0 (metres)
Vr a-d = 120 (metres)
q a-b = 0 (pcu/hr)
q a-c = 62 (pcu/hr)
q a-d = 0 (pcu/hr)

MAJOR ROAD (ARM C)

W c-b = 2.0 (metres)
Vr c-b = 60 (metres)
q c-a = 30 (pcu/hr)
q c-b = 12 (pcu/hr)
q c-d = 3 (pcu/hr)

MINOR ROAD (ARM B)

W b-a = 3.3 (metres)
W b-c = 3.3 (metres)
VI b-a = 28 (metres)
Vr b-a = 28 (metres)
Vr b-c = 80 (metres)
q b-a = 2 (pcu/hr)
q b-c = 11 (pcu/hr)
q b-d = 0 (pcu/hr)

MINOR ROAD (ARM D)

W d-c = 6.0 (metres)
W d-a = 6.0 (metres)
VI d-c = 22 (metres)
Vr d-c = 60 (metres)
Vr d-a = 90 (metres)
q d-c = 0 (pcu/hr)
q d-a = 0 (pcu/hr)
q d-b = 0 (pcu/hr)

GEOMETRIC FACTORS :

X b = 0.818
X c = 0.799
Z b = 0.928
M b = 0.860

X a = 0.845
X d = 1.066
Z d = 1.188
M d = 1.097

PROPORTION OF MINOR STRAIGHT AHEAD TRAFFIC :

r b-a = 0.00314
ql b-d = 0 (pcu/hr)
qr b-d = 0 (pcu/hr)

r d-c = 0.000
ql d-b = 0 (pcu/hr)
qr d-b = 0 (pcu/hr)

CAPACITY OF MOVEMENT :

Q b-a = 488 (pcu/hr)
Q b-c = 673 (pcu/hr)
Q c-b = 580 (pcu/hr)
Ql b-d = 512 (pcu/hr)
Qr b-d = 487 (pcu/hr)

Q d-c = 637 (pcu/hr)
Q d-a = 873 (pcu/hr)
Q a-d = 616 (pcu/hr)
Ql d-b = 659 (pcu/hr)
Qr d-b = 641 (pcu/hr)

TOTAL FLOW = 120 (PCU/HR)

COMPARISON OF DESIGN FLOW TO CAPACITY :

DFC b-a = 0.0041
DFC b-c = 0.0163
DFC c-b = 0.0207
DFCI b-d = 0.0000
DFCr b-d = 0.0000
DFC d-c = 0.0000
DFC d-a = 0.0000
DFC a-d = 0.0000
DFCI d-b = 0.0000
DFCr d-b = 0.0000

CRITICAL DFC = 0.02

8FM CONSULTANCY LIMITED

PRIORITY JUNCTION CALCULATION

INITIALS

DATE

Traffic Impact Assessment for Proposed Temporary Open Storage of Construction Material and Equipment of 3 Years at Various Lots in D.D.129, Lau Fau Shan

Prepared By: FF

Jan-2025

Jn E - Unnamed Rd 1 / Unnamed Rd 2

2027 Reference - PM Peak


Project No.: 80108

Checked By: MM

Jan-2025

Reviewed By: FM

Jan-2025



NOTES : (GEOMETRIC INPUT DATA)

- W = MAJOR ROAD WIDTH
- W cr = CENTRAL RESERVE WIDTH
- W b-a = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-a
- W b-c = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-c
- W c-b = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM c-b
- Vl b-a = VISIBILITY TO THE LEFT FOR VEHICLES WAITING IN STREAM b-a
- Vr b-a = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-a
- Vr b-c = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-c
- Vr c-b = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM c-b
- D = STREAM-SPECIFIC B-A
- E = STREAM-SPECIFIC B-C
- F = STREAM-SPECIFIC C-B
- Y = (1-0.0345W)

GEOMETRIC DETAILS:

MAJOR ROAD (ARM A)

W = 5.2 (metres)
 W cr = 0 (metres)
 q a-b = 0 (pcu/hr)
 q a-c = 36 (pcu/hr)

MAJOR ROAD (ARM C)

W c-b = 2.5 (metres)
 Vr c-b = 22 (metres)
 q c-a = 51 (pcu/hr)
 q c-b = 23 (pcu/hr)

MINOR ROAD (ARM B)

W b-a = 2.5 (metres)
 W b-c = 2.5 (metres)
 Vl b-a = 22 (metres)
 Vr b-a = 24 (metres)
 Vr b-c = 22 (metres)
 q b-a = 46 (pcu/hr)
 q b-c = 4 (pcu/hr)

GEOMETRIC FACTORS :

D = 0.752
 E = 0.813
 F = 0.813
 Y = 0.821

F for (Qb-ac) = 0.08

THE CAPACITY OF MOVEMENT :

Q b-a = 449 (pcu/hr)
 Q b-c = 597 (pcu/hr)
 Q c-b = 597 (pcu/hr)
 Q b-ac = 458 (pcu/hr)
 Q c-a = 1731 (pcu/hr)

TOTAL FLOW = 74 (pcu/hr)

COMPARISON OF DESIGN FLOW TO CAPACITY:

DFC b-a = 0.1024
 DFC b-c = 0.0067
 DFC c-b = 0.0385
 DFC b-ac = 0.1092
 (Share Lane)
 DFC c-a = 0.0295

CRITICAL DFC = 0.11

8FM CONSULTANCY LIMITED

PRIORITY JUNCTION CALCULATION

INITIALS

DATE

Traffic Impact Assessment for Proposed Temporary Open Storage of Construction Material and Equipment of 3 Years at Various Lots in D.D.129, Lau Fau Shan

Prepared By: FF

Jan-2025

Jn F - Deep Bay Rd / Unnamed Rd 3

2027 Reference - PM Peak


Project No.: 80108

Checked By: MM

Jan-2025

Reviewed By: FM

Jan-2025



NOTES : (GEOMETRIC INPUT DATA)

- W = MAJOR ROAD WIDTH
- W_{cr} = CENTRAL RESERVE WIDTH
- W_{b-a} = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-a
- W_{b-c} = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-c
- W_{c-b} = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM c-b
- V_l b-a = VISIBILITY TO THE LEFT FOR VEHICLES WAITING IN STREAM b-a
- V_r b-a = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-a
- V_r b-c = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-c
- V_r c-b = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM c-b
- D = STREAM-SPECIFIC B-A
- E = STREAM-SPECIFIC B-C
- F = STREAM-SPECIFIC C-B
- Y = (1-0.0345W)

GEOMETRIC DETAILS:

MAJOR ROAD (ARM A)

W = 4.8 (metres)
W_{cr} = 0 (metres)
q_{a-b} = 9 (pcu/hr)
q_{a-c} = 14 (pcu/hr)

MAJOR ROAD (ARM C)

W_{c-b} = 2.1 (metres)
V_r c-b = 38 (metres)
q_{c-a} = 30 (pcu/hr)
q_{c-b} = 52 (pcu/hr)

MINOR ROAD (ARM B)

W_{b-a} = 2.5 (metres)
W_{b-c} = 2.5 (metres)
V_l b-a = 22 (metres)
V_r b-a = 24 (metres)
V_r b-c = 38 (metres)
q_{b-a} = 14 (pcu/hr)
q_{b-c} = 80 (pcu/hr)

GEOMETRIC FACTORS :

D = 0.752
E = 0.826
F = 0.791
Y = 0.834

F for (Q_{b-ac}) = 0.851

THE CAPACITY OF MOVEMENT :

Q_{b-a} = 446 (pcu/hr)
Q_{b-c} = 611 (pcu/hr)
Q_{c-b} = 584 (pcu/hr)
Q_{b-ac} = 579 (pcu/hr)
Q_{c-a} = 1640 (pcu/hr)

TOTAL FLOW = 52 (pcu/hr)

COMPARISON OF DESIGN FLOW TO CAPACITY:

DFC_{b-a} = 0.0314
DFC_{b-c} = 0.1309
DFC_{c-b} = 0.0890
DFC_{b-ac} = 0.1623
(Share Lane)
DFC_{c-a} = 0.0183

CRITICAL DFC = 0.16

8FM CONSULTANCY LIMITED

PRIORITY JUNCTION CALCULATION

INITIALS

DATE

Traffic Impact Assessment for Proposed Temporary Open Storage of Construction Material and Equipment of 3 Years at Various Lots in D.D.129, Lau Fau Shan

Prepared By: FF

Jan-2025

Jn D - Deep Bay Rd / Unnamed Rd 2

2027 Design - AM Peak


Project No.: 80108

Checked By: MM

Jan-2025

Reviewed By: FM

Jan-2025



NOTES : (GEOMETRIC INPUT DATA)

- W = MAJOR ROAD WIDTH
- W cr = CENTRAL RESERVE WIDTH
- W b-a = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-a
- W b-c = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-c
- W c-b = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM c-b
- Vi b-a = VISIBILITY TO THE LEFT FOR VEHICLES WAITING IN STREAM b-a
- Vr b-a = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-a
- Vr b-c = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-c
- Vr c-b = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM c-b
- D = STREAM-SPECIFIC B-A
- E = STREAM-SPECIFIC B-C
- F = STREAM-SPECIFIC C-B
- Y = (1-0.0345W)

GEOMETRIC DETAILS:

GENERAL

W = 3.90 (metres)
 W cr = 0 (metres)

Y = 0.865

MAJOR ROAD (ARM A)

W a-d = 2.0 (metres)
 Vr a-d = 120 (metres)
 q a-b = 20 (pcu/hr)
 q a-c = 50 (pcu/hr)
 q a-d = 2 (pcu/hr)

MAJOR ROAD (ARM C)

W c-b = 2.0 (metres)
 Vr c-b = 60 (metres)
 q c-a = 40 (pcu/hr)
 q c-b = 10 (pcu/hr)
 q c-d = 2 (pcu/hr)

MINOR ROAD (ARM B)

W b-a = 3.3 (metres)
 W b-c = 3.3 (metres)
 Vi b-a = 28 (metres)
 Vr b-a = 28 (metres)
 Vr b-c = 80 (metres)
 q b-a = 11 (pcu/hr)
 q b-c = 11 (pcu/hr)
 q b-d = 4 (pcu/hr)

MINOR ROAD (ARM D)

W d-c = 6.0 (metres)
 W d-a = 6.0 (metres)
 Vi d-c = 22 (metres)
 Vr d-c = 60 (metres)
 Vr d-a = 90 (metres)
 q d-c = 5 (pcu/hr)
 q d-a = 2 (pcu/hr)
 q d-b = 2 (pcu/hr)

GEOMETRIC FACTORS :

X b = 0.818
 X c = 0.799
 Z b = 0.928
 M b = 0.860

X a = 0.845
 X d = 1.066
 Z d = 1.188
 M d = 1.097

PROPORTION OF MINOR STRAIGHT AHEAD TRAFFIC :

r b-a = 0.017378
 ql b-d = 2.034755 (pcu/hr)
 qr b-d = 1.965245 (pcu/hr)

r d-c = 0.008
 ql d-b = 1.0078989 (pcu/hr)
 qr d-b = 0.9921011 (pcu/hr)

CAPACITY OF MOVEMENT :

Q b-a = 486 (pcu/hr)
 Q b-c = 671 (pcu/hr)
 Q c-b = 577 (pcu/hr)
 Ql b-d = 512 (pcu/hr)
 Qr b-d = 487 (pcu/hr)

Q d-c = 633 (pcu/hr)
 Q d-a = 868 (pcu/hr)
 Q a-d = 614 (pcu/hr)
 Ql d-b = 654 (pcu/hr)
 Qr d-b = 636 (pcu/hr)

TOTAL FLOW = 159 (PCU/HR)

COMPARISON OF DESIGN FLOW TO CAPACITY :

DFC b-a = 0.0226
 DFC b-c = 0.0164
 DFC c-b = 0.0173
 DFCI b-d = 0.0040
 DFCr b-d = 0.0040
 DFC d-c = 0.0079
 DFC d-a = 0.0023
 DFC a-d = 0.0033
 DFCI d-b = 0.0015
 DFCr d-b = 0.0016

CRITICAL DFC = 0.02

8FM CONSULTANCY LIMITED

PRIORITY JUNCTION CALCULATION

INITIALS

DATE

Traffic Impact Assessment for Proposed Temporary Open Storage of Construction Material and Equipment of 3 Years at Various Lots in D.D.129, Lau Fau Shan

Prepared By: FF

Jan-2025

Jn E - Unnamed Rd 1 / Unnamed Rd 2

2027 Design - AM Peak


Project No.: 80108

Checked By: MM

Jan-2025

Reviewed By: FM

Jan-2025



NOTES : (GEOMETRIC INPUT DATA)

- W = MAJOR ROAD WIDTH
- W_{cr} = CENTRAL RESERVE WIDTH
- W_{b-a} = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-a
- W_{b-c} = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-c
- W_{c-b} = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM c-b
- V_{l b-a} = VISIBILITY TO THE LEFT FOR VEHICLES WAITING IN STREAM b-a
- V_{r b-a} = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-a
- V_{r b-c} = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-c
- V_{r c-b} = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM c-b
- D = STREAM-SPECIFIC B-A
- E = STREAM-SPECIFIC B-C
- F = STREAM-SPECIFIC C-B
- Y = (1-0.0345W)

GEOMETRIC DETAILS:

MAJOR ROAD (ARM A)

W = 5.2 (metres)
W_{cr} = 0 (metres)
q_{a-b} = 0 (pcu/hr)
q_{a-c} = 58 (pcu/hr)

MAJOR ROAD (ARM C)

W_{c-b} = 2.5 (metres)
V_{r c-b} = 22 (metres)
q_{c-a} = 61 (pcu/hr)
q_{c-b} = 11 (pcu/hr)

MINOR ROAD (ARM B)

W_{b-a} = 2.5 (metres)
W_{b-c} = 2.5 (metres)
V_{l b-a} = 22 (metres)
V_{r b-a} = 24 (metres)
V_{r b-c} = 22 (metres)
q_{b-a} = 18 (pcu/hr)
q_{b-c} = 7 (pcu/hr)

GEOMETRIC FACTORS :

D = 0.752
E = 0.813
F = 0.813
Y = 0.821

F for (Q_{b-ac}) = 0.28

THE CAPACITY OF MOVEMENT :

Q_{b-a} = 446 (pcu/hr)
Q_{b-c} = 592 (pcu/hr)
Q_{c-b} = 592 (pcu/hr)
Q_{b-ac} = 479 (pcu/hr)
Q_{c-a} = 1767 (pcu/hr)
TOTAL FLOW = 72 (pcu/hr)

COMPARISON OF DESIGN FLOW TO CAPACITY:

DFC_{b-a} = 0.0404
DFC_{b-c} = 0.0118
DFC_{c-b} = 0.0186
DFC_{b-ac} = 0.0522
(Share Lane)
DFC_{c-a} = 0.0345

CRITICAL DFC = 0.05

8FM CONSULTANCY LIMITED

PRIORITY JUNCTION CALCULATION

INITIALS

DATE

Traffic Impact Assessment for Proposed Temporary Open Storage of Construction Material and Equipment of 3 Years at Various Lots in D.D.129, Lau Fau Shan

Prepared By: FF

Jan-2025

Jn F - Deep Bay Rd / Unnamed Rd 3

2027 Design - AM Peak


Project No.: 80108

Checked By: MM

Jan-2025

Reviewed By: FM

Jan-2025



NOTES : (GEOMETRIC INPUT DATA)

- W = MAJOR ROAD WIDTH
- W_{cr} = CENTRAL RESERVE WIDTH
- W_{b-a} = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-a
- W_{b-c} = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-c
- W_{c-b} = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM c-b
- V_l b-a = VISIBILITY TO THE LEFT FOR VEHICLES WAITING IN STREAM b-a
- V_r b-a = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-a
- V_r b-c = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-c
- V_r c-b = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM c-b
- D = STREAM-SPECIFIC B-A
- E = STREAM-SPECIFIC B-C
- F = STREAM-SPECIFIC C-B
- Y = (1-0.0345W)

GEOMETRIC DETAILS:

MAJOR ROAD (ARM A)

W =	4.8	(metres)
W _{cr} =	0	(metres)
q _{a-b} =	16	(pcu/hr)
q _{a-c} =	25	(pcu/hr)

MAJOR ROAD (ARM C)

W _{c-b} =	2.1	(metres)
V _r c-b =	38	(metres)
q _{c-a} =	35	(pcu/hr)
q _{c-b} =	84	(pcu/hr)

MINOR ROAD (ARM B)

W _{b-a} =	2.5	(metres)
W _{b-c} =	2.5	(metres)
V _l b-a =	22	(metres)
V _r b-a =	24	(metres)
V _r b-c =	38	(metres)
q _{b-a} =	39	(pcu/hr)
q _{b-c} =	74	(pcu/hr)

GEOMETRIC FACTORS :

D =	0.752
E =	0.826
F =	0.791
Y =	0.834

F for (Q_{b-ac}) = 0.655

THE CAPACITY OF MOVEMENT :

Q _{b-a} =	432	(pcu/hr)
Q _{b-c} =	608	(pcu/hr)
Q _{c-b} =	580	(pcu/hr)
Q _{b-ac} =	533	(pcu/hr)
Q _{c-a} =	1539	(pcu/hr)
TOTAL FLOW =	84	(pcu/hr)

COMPARISON OF DESIGN FLOW TO CAPACITY:

DFC _{b-a} =	0.0903
DFC _{b-c} =	0.1217
DFC _{c-b} =	0.1448
DFC _{b-ac} =	0.2120
(Share Lane)	
DFC _{c-a} =	0.0227

CRITICAL DFC = 0.21

8FM CONSULTANCY LIMITED

PRIORITY JUNCTION CALCULATION

INITIALS

DATE

Traffic Impact Assessment for Proposed Temporary Open Storage of Construction Material and Equipment of 3 Years at Various Lots in D.D.129, Lau Fau Shan

Prepared By: FF

Jan-2025

Jn D - Deep Bay Rd / Unnamed Rd 2

2027 Design - PM Peak


Project No.: 80108

Checked By: MM

Jan-2025

Reviewed By: FM

Jan-2025



NOTES : (GEOMETRIC INPUT DATA)

- W = MAJOR ROAD WIDTH
- W cr = CENTRAL RESERVE WIDTH
- W b-a = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-a
- W b-c = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-c
- W c-b = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM c-b
- VI b-a = VISIBILITY TO THE LEFT FOR VEHICLES WAITING IN STREAM b-a
- Vr b-a = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-a
- Vr b-c = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-c
- Vr c-b = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM c-b
- D = STREAM-SPECIFIC B-A
- E = STREAM-SPECIFIC B-C
- F = STREAM-SPECIFIC C-B
- Y = (1-0.0345W)

GEOMETRIC DETAILS:

GENERAL

W = 3.90 (metres)
W cr = 0 (metres)

Y = 0.865

MAJOR ROAD (ARM A)

W a-d = 2.0 (metres)
Vr a-d = 120 (metres)
q a-b = 13 (pcu/hr)
q a-c = 62 (pcu/hr)
q a-d = 0 (pcu/hr)

MAJOR ROAD (ARM C)

W c-b = 2.0 (metres)
Vr c-b = 60 (metres)
q c-a = 30 (pcu/hr)
q c-b = 12 (pcu/hr)
q c-d = 3 (pcu/hr)

MINOR ROAD (ARM B)

W b-a = 3.3 (metres)
W b-c = 3.3 (metres)
VI b-a = 28 (metres)
Vr b-a = 28 (metres)
Vr b-c = 80 (metres)
q b-a = 18 (pcu/hr)
q b-c = 11 (pcu/hr)
q b-d = 0 (pcu/hr)

MINOR ROAD (ARM D)

W d-c = 6.0 (metres)
W d-a = 6.0 (metres)
VI d-c = 22 (metres)
Vr d-c = 60 (metres)
Vr d-a = 90 (metres)
q d-c = 0 (pcu/hr)
q d-a = 0 (pcu/hr)
q d-b = 0 (pcu/hr)

GEOMETRIC FACTORS :

X b = 0.818
X c = 0.799
Z b = 0.928
M b = 0.860

X a = 0.845
X d = 1.066
Z d = 1.188
M d = 1.097

PROPORTION OF MINOR STRAIGHT AHEAD TRAFFIC :

r b-a = 0.028391
ql b-d = 0 (pcu/hr)
qr b-d = 0 (pcu/hr)

r d-c = 0.000
ql d-b = 0 (pcu/hr)
qr d-b = 0 (pcu/hr)

CAPACITY OF MOVEMENT :

Q b-a = 486 (pcu/hr)
Q b-c = 667 (pcu/hr)
Q c-b = 577 (pcu/hr)
Ql b-d = 511 (pcu/hr)
Qr b-d = 486 (pcu/hr)

Q d-c = 634 (pcu/hr)
Q d-a = 873 (pcu/hr)
Q a-d = 616 (pcu/hr)
Ql d-b = 656 (pcu/hr)
Qr d-b = 638 (pcu/hr)

TOTAL FLOW = 149 (PCU/HR)

COMPARISON OF DESIGN FLOW TO CAPACITY :

DFC b-a = 0.0370
DFC b-c = 0.0165
DFC c-b = 0.0208
DFCI b-d = 0.0000
DFCr b-d = 0.0000
DFC d-c = 0.0000
DFC d-a = 0.0000
DFC a-d = 0.0000
DFCI d-b = 0.0000
DFCr d-b = 0.0000

CRITICAL DFC = 0.04

8FM CONSULTANCY LIMITED

PRIORITY JUNCTION CALCULATION

INITIALS

DATE

Traffic Impact Assessment for Proposed Temporary Open Storage of Construction Material and Equipment of 3 Years at Various Lots in D.D.129, Lau Fau Shan

Prepared By: FF

Jan-2025

Jn E - Unnamed Rd 1 / Unnamed Rd 2

2027 Design - PM Peak


Project No.: 80108

Checked By: MM

Jan-2025

Reviewed By: FM

Jan-2025



NOTES : (GEOMETRIC INPUT DATA)

- W = MAJOR ROAD WIDTH
- W cr = CENTRAL RESERVE WIDTH
- W b-a = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-a
- W b-c = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-c
- W c-b = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM c-b
- Vl b-a = VISIBILITY TO THE LEFT FOR VEHICLES WAITING IN STREAM b-a
- Vr b-a = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-a
- Vr b-c = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-c
- Vr c-b = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM c-b
- D = STREAM-SPECIFIC B-A
- E = STREAM-SPECIFIC B-C
- F = STREAM-SPECIFIC C-B
- Y = (1-0.0345W)

GEOMETRIC DETAILS:

MAJOR ROAD (ARM A)

W = 5.2 (metres)
 W cr = 0 (metres)
 q a-b = 0 (pcu/hr)
 q a-c = 49 (pcu/hr)

MAJOR ROAD (ARM C)

W c-b = 2.5 (metres)
 Vr c-b = 22 (metres)
 q c-a = 67 (pcu/hr)
 q c-b = 23 (pcu/hr)

MINOR ROAD (ARM B)

W b-a = 2.5 (metres)
 W b-c = 2.5 (metres)
 Vl b-a = 22 (metres)
 Vr b-a = 24 (metres)
 Vr b-c = 22 (metres)
 q b-a = 46 (pcu/hr)
 q b-c = 4 (pcu/hr)

GEOMETRIC FACTORS :

D = 0.752
 E = 0.813
 F = 0.813
 Y = 0.821

F for (Qb-ac) = 0.08

THE CAPACITY OF MOVEMENT :

Q b-a = 444 (pcu/hr)
 Q b-c = 594 (pcu/hr)
 Q c-b = 594 (pcu/hr)
 Q b-ac = 453 (pcu/hr)
 Q c-a = 1730 (pcu/hr)

TOTAL FLOW = 90 (pcu/hr)

COMPARISON OF DESIGN FLOW TO CAPACITY:

DFC b-a = 0.1036
 DFC b-c = 0.0067
 DFC c-b = 0.0387
 DFC b-ac = 0.1103
 (Share Lane)
 DFC c-a = 0.0387

CRITICAL DFC = 0.11

8FM CONSULTANCY LIMITED

PRIORITY JUNCTION CALCULATION

INITIALS

DATE

Traffic Impact Assessment for Proposed Temporary Open Storage of Construction Material and Equipment of 3 Years at Various Lots in D.D.129, Lau Fau Shan

Prepared By: FF

Jan-2025

Jn F - Deep Bay Rd / Unnamed Rd 3

2027 Design - PM Peak


Project No.: 80108

Checked By: MM

Jan-2025

Reviewed By: FM

Jan-2025



NOTES : (GEOMETRIC INPUT DATA)

- W = MAJOR ROAD WIDTH
- W_{cr} = CENTRAL RESERVE WIDTH
- W_{b-a} = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-a
- W_{b-c} = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-c
- W_{c-b} = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM c-b
- V_l b-a = VISIBILITY TO THE LEFT FOR VEHICLES WAITING IN STREAM b-a
- V_r b-a = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-a
- V_r b-c = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-c
- V_r c-b = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM c-b
- D = STREAM-SPECIFIC B-A
- E = STREAM-SPECIFIC B-C
- F = STREAM-SPECIFIC C-B
- Y = (1-0.0345W)

GEOMETRIC DETAILS:

MAJOR ROAD (ARM A)

W = 4.8 (metres)
W_{cr} = 0 (metres)
q_{a-b} = 25 (pcu/hr)
q_{a-c} = 14 (pcu/hr)

MAJOR ROAD (ARM C)

W_{c-b} = 2.1 (metres)
V_r c-b = 38 (metres)
q_{c-a} = 30 (pcu/hr)
q_{c-b} = 52 (pcu/hr)

MINOR ROAD (ARM B)

W_{b-a} = 2.5 (metres)
W_{b-c} = 2.5 (metres)
V_l b-a = 22 (metres)
V_r b-a = 24 (metres)
V_r b-c = 38 (metres)
q_{b-a} = 27 (pcu/hr)
q_{b-c} = 80 (pcu/hr)

GEOMETRIC FACTORS :

D = 0.752
E = 0.826
F = 0.791
Y = 0.834

F for (Q_{b-ac}) = 0.748

THE CAPACITY OF MOVEMENT :

Q_{b-a} = 445 (pcu/hr)
Q_{b-c} = 609 (pcu/hr)
Q_{c-b} = 580 (pcu/hr)
Q_{b-ac} = 557 (pcu/hr)
Q_{c-a} = 1639 (pcu/hr)
TOTAL FLOW = 52 (pcu/hr)

COMPARISON OF DESIGN FLOW TO CAPACITY:

DFC_{b-a} = 0.0607
DFC_{b-c} = 0.1314
DFC_{c-b} = 0.0897
DFC_{b-ac} = 0.1920
(Share Lane)
DFC_{c-a} = 0.0183

CRITICAL DFC = 0.19