Annex 2 Estimated Traffic Generation

- 2.1 The ingress/egress of the application site is abutting a local vehicular track leading to Lau Fau Shan Roundabout. (**Figure 1**)
- 2.2 Only 5.5 tonnes light goods vehicle is required to deliver construction materials such as tiles and sanitary wares to and from the application site.
- 2.3 The average and peak trip rates generated from and attracted to the site are shown below.

Type of	Average Traffic	Average Traffic	Traffic	Traffic
vehicle	Generation Rate	Attraction Rate	Generation Rate	Attraction Rate
	(pcu/hr)	(pcu/hr)	at Peak Hours	at Peak Hours
			(pcu/hr)	(pcu/hr)
Light goods vehicle	0.15	0.15	0	0

Note 1: The opening hour of the proposed development is restricted to 9:00 a.m. to 7:00 p.m. from Mondays to Saturdays. No operation will be held on Sundays and public holidays.

- Note 2: The pcu of light goods vehicle is taken as 1.5; and
- Note 3: Morning peak is defined as 7:00a.m. to 9:00a.m. whereas afternoon peak is defined as 5:00p.m. to 7:00p.m.
- 2.4 In association with the proposed use, adequate space for manoeuvring and loading/unloading are available within the application site. By virtue of the fact that the application site is directly linked with Yuen Long Highway via Lau Fau Shan Road and the traffic generated by the proposed development is insignificant, the proposed development being applied would not aggravate the traffic condition in the area. Adjacent warehouse has also been approved by Town Planning Board recently such as A/YL-LFS/457.